

# Safety Data Sheet

Copyright, 2023, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document group:
 30-3729-8
 Version number:
 8.00

 Revision date:
 26/04/2023
 Supersedes date:
 09/02/2018

Transportation version number:

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (1907/2006), as amended for GB.

# IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

#### 1.1. Product identifier

3M Aerospace Sealant AC-735 B-1/2

#### **Product Identification Numbers**

70-0052-2264-4

7000048365

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Identified uses

Sealant.

#### 1.3. Details of the supplier of the safety data sheet

Address: 3M United Kingdom PLC, 3M Centre, Cain Road, Bracknell, Berkshire, RG12 8HT.

**Telephone:** +44 (0)1344 858 000 **E Mail:** tox.uk@mmm.com

Website: www.3M.com/uk

#### 1.4. Emergency telephone number

+44 (0)1344 858 000

This product is a kit or a multipart product which consists of multiple, independently packaged components. A Safety Data Sheet for each of these components is included. Please do not separate the component Safety Data Sheets from this cover page. The document numbers of the MSDSs for components of this product are:

30-3086-3, 30-3363-6

# TRANSPORTATION INFORMATION

Refer to section 14 of the kit components for transport information.

# KIT LABEL

#### 2.1. Classification of the substance or mixture

The retained CLP Regulation (EU) No 1272/2008 as amended for Great Britain

#### **CLASSIFICATION:**

Acute Toxicity, Category 4 - Acute Tox. 4; H302

Skin Corrosion/Irritation, Category 2 - Skin Irrit. 2; H315

Serious Eye Damage/Eye Irritation, Category 2 - Eye Irrit. 2; H319

Reproductive Toxicity, Category 1A - Repr. 1A; H360D

Specific Target Organ Toxicity-Repeated Exposure, Category 2 - STOT RE 2; H373 Hazardous to the Aquatic Environment (Acute), Category 1 - Aquatic Acute 1; H400 Hazardous to the Aquatic Environment (Chronic), Category 1 - Aquatic Chronic 1; H410

For full text of H phrases, see Section 16.

#### 2.2. Label elements

The retained CLP Regulation (EU) No 1272/2008 as amended for Great Britain

# SIGNAL WORD

DANGER.

#### **Symbols**

GHS07 (Exclamation mark) |GHS08 (Health Hazard) |GHS09 (Environment) |

#### **Pictograms**







#### **Contains:**

manganese dioxide; Titanium dioxide; bis-[4-(2,3-epoxipropoxi)phenyl]propane; Calcium carbonate; Propane, 1,2,3-trichloro-, polymer with 1,1'-[methylenebis(oxy)]bis[2- chloroethane] and sodium sulfide (Na2(Sx)), reduced; lead powder; [particle diameter < 1 mm]; trizinc bis(orthophosphate); Formaldehyde, oligomeric reaction products with phenol

#### **HAZARD STATEMENTS:**

H302 Harmful if swallowed.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H360D May damage the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure:

nervous system |

H410 Very toxic to aquatic life with long lasting effects.

#### PRECAUTIONARY STATEMENTS

# **Prevention:**

P201 Obtain special instructions before use.

P260A Do not breathe vapours.

P273 Avoid release to the environment.

P280F Wear respiratory protection.

**Response:** 

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P308 + P313 IF exposed or concerned: Get medical advice/attention.

# For containers not exceeding 125 ml the following Hazard and Precautionary statements may be used:

<=125 ml Hazard statements

H360D May damage the unborn child.

# <=125 ml Precautionary statements

**Prevention:** 

P201 Obtain special instructions before use.

P280F Wear respiratory protection.

**Response:** 

P308 + P313 IF exposed or concerned: Get medical advice/attention.

#### SUPPLEMENTAL INFORMATION:

**Supplemental Hazard Statements:** 

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or

mist.

.

EUH208 Contains Formaldehyde, oligomeric reaction products with phenol. | bis-[4-(2,3-

epoxipropoxi)phenyl]propane.May produce an allergic reaction.

#### **Supplemental Precautionary Statements:**

Restricted to professional users.

Refer to Safety Data Sheet for component % unknown values (www.3M.com/msds).

#### **Revision information:**

GB Kit Information: CLP Percent Unknown information was added.

GB Label: CLP Ingredients - kit components information was added.

Label: CLP Percent Unknown - Kit information was deleted.

Kit: Component document group number(s) information was modified.

Kit Information: Contains statement for sensitisers information was added.

Kit Information: Contains statement for sensitisers information was deleted.

Section 2: <125ml Precautionary - Prevention information was modified.

Label: CLP Classification information was modified.

Label: CLP Precautionary - Disposal information was deleted.

Label: CLP Precautionary - Prevention information was modified.

Label: CLP Supplemental Hazard Statements information was added.

Label: CLP Supplemental Precautionary Statements information was deleted.

Section 02: SDS Elements: CLP Supplemental Precautionary Statements information was added.



# Safety Data Sheet

Copyright, 2023, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document group:
 30-3363-6
 Version number:
 10.01

 Revision date:
 28/08/2023
 Supersedes date:
 19/04/2023

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (1907/2006), as amended for GB.

# **SECTION 1: Identification of the substance/mixture and of the company/undertaking**

#### 1.1. Product identifier

3M Aerospace Sealant AC-735 B-1/2 and B-2 Base

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### **Identified uses**

Sealant.

#### 1.3. Details of the supplier of the safety data sheet

**Address:** 3M United Kingdom PLC, 3M Centre, Cain Road, Bracknell, Berkshire, RG12 8HT.

**Telephone:** +44 (0)1344 858 000 **E Mail:** tox.uk@mmm.com **Website:** www.3M.com/uk

#### 1.4. Emergency telephone number

+44 (0)1344 858 000

# **SECTION 2: Hazard identification**

# 2.1. Classification of the substance or mixture

The retained CLP Regulation (EU) No 1272/2008 as amended for Great Britain

The health and environmental classifications of this material have been derived using the calculation method, except in cases where test data are available or the physical form impacts classification. Classification(s) based on test data or physical form are noted below, if applicable.

The carcinogenicity classification for titanium dioxide is not applicable based on physical form (material is not a powder).

#### **CLASSIFICATION:**

Hazardous to the Aquatic Environment (Chronic), Category 2 - Aquatic Chronic 2; H411

For full text of H phrases, see Section 16.

# 2.2. Label elements

# The retained CLP Regulation (EU) No 1272/2008 as amended for Great Britain

# **Symbols**

GHS09 (Environment) |

#### **Pictograms**



Ingredient	CAS Nbr	EC No.	% by Wt
Propane, 1,2,3-trichloro-, polymer with 1,1'- [methylenebis(oxy)]bis[2- chloroethane] and sodium sulfide (Na2(Sx)), reduced	68611-50-7		70 - 80
Calcium carbonate	471-34-1	207-439-9	10 - 20
bis-[4-(2,3-epoxipropoxi)phenyl]propane	1675-54-3	216-823-5	< 1
Formaldehyde, oligomeric reaction products with phenol	9003-35-4	500-005-2	< 1
Titanium dioxide	13463-67-7	236-675-5	<= 1
trizinc bis(orthophosphate)	7779-90-0	231-944-3	< 1

#### **HAZARD STATEMENTS:**

H411 Toxic to aquatic life with long lasting effects.

# For containers not exceeding 125 ml the following Hazard and Precautionary statements may be used:

No hazard statements are required for containers <=125 mL.

No precautionary statements are required for containers <=125 mL.

#### SUPPLEMENTAL INFORMATION:

## **Supplemental Hazard Statements:**

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe

spray or mist.

EUH208 Contains Formaldehyde, oligomeric reaction products with phenol. | bis-[4-(2,3-

epoxipropoxi)phenyl]propane. May produce an allergic reaction.

Contains 75% of components with unknown hazards to the aquatic environment.

# 2.3. Other hazards

None known.

This material does not contain any substances that are assessed to be a PBT or vPvB

# **SECTION 3: Composition/information on ingredients**

## 3.1. Substances

Not applicable

#### 3.2. Mixtures

Ingredient	Identifier(s)	%	Classification according to Regulation (EC) No. 1272/2008 [CLP], as amended for GB
Propane, 1,2,3-trichloro-, polymer with 1,1'-[methylenebis(oxy)]bis[2-chloroethane] and sodium sulfide (Na2(Sx)), reduced	(CAS-No.) 68611-50-7	70 - 80	Substance not classified as hazardous
Calcium carbonate	(CAS-No.) 471-34-1 (EC-No.) 207-439-9	10 - 20	Substance with a national occupational exposure limit
Formaldehyde, oligomeric reaction products with phenol	(CAS-No.) 9003-35-4 (EC-No.) 500-005-2	< 1	Skin Sens. 1, H317
bis-[4-(2,3-epoxipropoxi)phenyl]propane	(CAS-No.) 1675-54-3 (EC-No.) 216-823-5	< 1	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411
trizinc bis(orthophosphate)	(CAS-No.) 7779-90-0 (EC-No.) 231-944-3	< 1	Aquatic Acute 1, H400,M=10 Aquatic Chronic 1, H410,M=10
Titanium dioxide	(CAS-No.) 13463-67-7 (EC-No.) 236-675-5	<= 1	Carc. 2, H351 (inhalation)

Please see section 16 for the full text of any H statements referred to in this section

# **Specific Concentration Limits**

Ingredient	Identifier(s)	Specific Concentration Limits
	[`	(C >= 5%) Skin Irrit. 2, H315 (C >= 5%) Eye Irrit. 2, H319

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

# **SECTION 4: First aid measures**

# 4.1. Description of first aid measures

#### Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

#### Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

## Eye contact

If exposed, flush eyes with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms develop, get medical attention.

#### If swallowed

Rinse mouth. If you feel unwell, get medical attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

No critical symptoms or effects. See Section 11.1, information on toxicological effects.

## 4.3. Indication of any immediate medical attention and special treatment required

Not applicable

# **SECTION 5: Fire-fighting measures**

#### 5.1. Extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

#### 5.2. Special hazards arising from the substance or mixture

None inherent in this product.

## **Hazardous Decomposition or By-Products**

SubstanceConditionformaldehydeDuring combustion.Carbon monoxideDuring combustion.Carbon dioxide.During combustion.Hydrogen ChlorideDuring combustion.

#### 5.3. Advice for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

# **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

#### 6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

#### 6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible.

#### 6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

# **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

Avoid breathing dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse.

#### 7.2. Conditions for safe storage including any incompatibilities

Store away from acids. Store away from strong bases.

#### 7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

# **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

#### Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	<b>Additional comments</b>
Titanium dioxide	13463-67-7	UK HSC	TWA(respirable):4 mg/m3;TWA(Inhalable):10 mg/m3	
DUST, INERT OR NUISANCE	471-34-1	UK HSC	TWA(as respirable dust):4 mg/m3;TWA(as inhalable dust):10 mg/m3	
Limestone	471-34-1	UK HSC	TWA(respirable):4 mg/m3;TWA(as respirable dust):4 mg/m3;TWA(Inhalable):10 mg/m3;TWA(as inhalable dust):10 mg/m3	

UK HSC: UK Health and Safety Commission

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

#### **Biological limit values**

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

# 8.2. Exposure controls

#### 8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

# 8.2.2. Personal protective equipment (PPE)

# **Eye/face protection**

None required.

# Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended:

MaterialThickness (mm)Breakthrough TimePolymer laminateNo data availableNo data available

Applicable Norms/Standards
Use gloves tested to EN 374

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

#### Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

Applicable Norms/Standards

Use a respirator conforming to EN 140 or EN 136: filter types A & P

# **SECTION 9: Physical and chemical properties**

9.1. Information on basic physical and chemical properties

Physical stateLiquid.Specific Physical Form:PasteColourWhiteOdorSulfuric

Odour thresholdNo data available.Melting point/freezing pointNot applicable.Boiling point/boiling rangeNot applicable.Flammability (solid, gas)Not applicable.Flammable Limits(LEL)No data available.Flammable Limits(UEL)No data available.

Flash point >=93.3 °C [Test Method:Closed Cup]

Autoignition temperature

No data available.

No data available.

No data available.

Decomposition temperature

No data available.

pH substance/mixture is non-soluble (in water)

Kinematic Viscosity No data available.

Water solubility Nil

Solubility- non-waterNo data available.Partition coefficient: n-octanol/waterNo data available.Vapour pressureNo data available.

**Density** 1.1 g/ml

Relative density

1.1 [Ref Std: WATER=1]

**Relative Vapour Density**No data available.

#### 9.2. Other information

9.2.2 Other safety characteristics

EU Volatile Organic CompoundsNo data available.Evaporation rateNo data available.Molecular weightNot applicable.

# **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

This material is considered to be non reactive under normal use conditions

#### 10.2 Chemical stability

Stable.

#### 10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

## 10.4 Conditions to avoid

None known.

#### 10.5 Incompatible materials

Strong bases.

Reducing agents.

Strong acids.

# 10.6 Hazardous decomposition products

#### **Substance**

Condition

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

# **SECTION 11: Toxicological information**

The information below may not agree with the material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from 3M assessments.

11.1. Information on hazard classes as defined in the retained CLP Regulation (EU) No 1272/2008, as amended for Great Britain.

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

## Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

#### Skin contact

Contact with the skin during product use is not expected to result in significant irritation. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

#### **Eve contact**

Contact with the eyes during product use is not expected to result in significant irritation.

## Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.

#### **Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

**Acute Toxicity** 

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Propane, 1,2,3-trichloro-, polymer with 1,1'- [methylenebis(oxy)]bis[2- chloroethane] and sodium sulfide (Na2(Sx)), reduced	Dermal	Rat	LD50 > 7,800 mg/kg
Propane, 1,2,3-trichloro-, polymer with 1,1'- [methylenebis(oxy)]bis[2- chloroethane] and sodium sulfide (Na2(Sx)), reduced	Ingestion	Rat	LD50 > 5,000 mg/kg
Calcium carbonate	Dermal	Rat	LD50 > 2,000 mg/kg
Calcium carbonate	Inhalation- Dust/Mist (4 hours)	Rat	LC50 3 mg/l
Calcium carbonate	Ingestion	Rat	LD50 6,450 mg/kg
Titanium dioxide	Dermal	Rabbit	LD50 > 10,000 mg/kg
Titanium dioxide	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 6.82 mg/l
Titanium dioxide	Ingestion	Rat	LD50 > 10,000 mg/kg
trizinc bis(orthophosphate)	Dermal		LD50 estimated to be > 5,000 mg/kg
trizinc bis(orthophosphate)	Ingestion	Rat	LD50 > 5,000 mg/kg
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Dermal	Rat	LD50 > 1,600 mg/kg
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Ingestion	Rat	LD50 > 1,000 mg/kg
Formaldehyde, oligomeric reaction products with phenol	Dermal	Rat	LD50 > 2,000 mg/kg
Formaldehyde, oligomeric reaction products with phenol	Ingestion	Rat	LD50 > 2,900 mg/kg

ATE = acute toxicity estimate

# Skin Corrosion/Irritation

Name	Species	Value
Propane, 1,2,3-trichloro-, polymer with 1,1'-[methylenebis(oxy)]bis[2-chloroethane] and sodium sulfide (Na2(Sx)), reduced	Rabbit	No significant irritation
Calcium carbonate	Rabbit	No significant irritation
Titanium dioxide	Rabbit	No significant irritation
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Rabbit	Mild irritant
Formaldehyde, oligomeric reaction products with phenol	Human	Mild irritant
	and	
	animal	

**Serious Eye Damage/Irritation** 

Name	Species	Value
Propane, 1,2,3-trichloro-, polymer with 1,1'-[methylenebis(oxy)]bis[2-	Rabbit	No significant irritation
chloroethane] and sodium sulfide (Na2(Sx)), reduced		
Calcium carbonate	Rabbit	No significant irritation
Titanium dioxide	Rabbit	No significant irritation
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Rabbit	Moderate irritant
Formaldehyde, oligomeric reaction products with phenol	Human	Moderate irritant
	and	
	animal	

# **Skin Sensitisation**

Name	Species	Value
Propane, 1,2,3-trichloro-, polymer with 1,1'-[methylenebis(oxy)]bis[2-chloroethane] and sodium sulfide (Na2(Sx)), reduced		Not classified
Titanium dioxide	Human	Not classified
	and	
	animal	
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Human	Sensitising
	and	
	animal	

# 3M Aerospace Sealant AC-735 B-1/2 and B-2 Base

Formaldehyde, oligomeric reaction products with phenol	Human	Sensitising
	and	
	animal	

**Respiratory Sensitisation** 

Name	Species	Value
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Human	Not classified
Formaldehyde, oligomeric reaction products with phenol	Human	Not classified

**Germ Cell Mutagenicity** 

Name	Route	Value
Titanium dioxide	In Vitro	Not mutagenic
Titanium dioxide	In vivo	Not mutagenic
bis-[4-(2,3-epoxipropoxi)phenyl]propane	In vivo	Not mutagenic
bis-[4-(2,3-epoxipropoxi)phenyl]propane	In Vitro	Some positive data exist, but the data are not
		sufficient for classification

Carcinogenicity

Name	Route	Species	Value
Titanium dioxide	Ingestion	Multiple	Not carcinogenic
		animal	
		species	
Titanium dioxide	Inhalation	Rat	Carcinogenic.
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Dermal	Mouse	Some positive data exist, but the data are not
			sufficient for classification

# **Reproductive Toxicity**

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
Calcium carbonate	Ingestion	Not classified for development	Rat	NOAEL 625 mg/kg/day	premating & during gestation
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Ingestion	Not classified for female reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Ingestion	Not classified for male reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Dermal	Not classified for development	Rabbit	NOAEL 300 mg/kg/day	during organogenesis
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Ingestion	Not classified for development	Rat	NOAEL 750 mg/kg/day	2 generation

# Target Organ(s)

**Specific Target Organ Toxicity - single exposure** 

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Calcium carbonate	Inhalation	respiratory system	Not classified	Rat	NOAEL 0.812 mg/l	90 minutes
Formaldehyde, oligomeric reaction products with phenol	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human and animal	NOAEL Not available	

**Specific Target Organ Toxicity - repeated exposure** 

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Calcium carbonate	Inhalation	respiratory system	Not classified	Human	NOAEL Not available	occupational exposure
Titanium dioxide	Inhalation	respiratory system	Some positive data exist, but the	Rat	LOAEL 0.01	2 years

			data are not sufficient for classification		mg/l	
Titanium dioxide	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not available	occupational exposure
bis-[4-(2,3- epoxipropoxi)phenyl]prop ane	Dermal	liver	Not classified	Rat	NOAEL 1,000 mg/kg/day	2 years
bis-[4-(2,3- epoxipropoxi)phenyl]prop ane	Dermal	nervous system	Not classified	Rat	NOAEL 1,000 mg/kg/day	13 weeks
bis-[4-(2,3- epoxipropoxi)phenyl]prop ane	Ingestion	auditory system   heart   endocrine system   hematopoietic system   liver   eyes   kidney and/or bladder	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
Formaldehyde, oligomeric reaction products with phenol	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure

#### **Aspiration Hazard**

For the component/components, either no data is currently available or the data is not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

#### 11.2. Information on other hazards

This material does not contain any substances that are assessed to be an endocrine disruptor for human health.

# **SECTION 12: Ecological information**

The information below may not agree with the material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

# 12.1. Toxicity

No product test data available.

Material	CAS#	Organism	Type	Exposure	Test endpoint	Test result
Propane, 1,2,3- trichloro-, polymer with 1,1'- [methylenebis(oxy)]bis[2- chloroethane] and sodium sulfide (Na2(Sx)), reduced		N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Calcium carbonate	471-34-1	Green algae	Experimental	72 hours	EC50	>100 mg/l
Calcium carbonate	471-34-1	Rainbow trout	Experimental	96 hours	LC50	>100 mg/l
Calcium carbonate	471-34-1	Water flea	Experimental	48 hours	EC50	>100 mg/l
Calcium carbonate	471-34-1	Green algae	Experimental	72 hours	EC10	100 mg/l
bis-[4-(2,3- epoxipropoxi)phen yl]propane	1675-54-3	Activated sludge	Analogous Compound	3 hours	IC50	>100 mg/l
bis-[4-(2,3- epoxipropoxi)phen	1675-54-3	Rainbow trout	Estimated	96 hours	LC50	2 mg/l

yl]propane						
bis-[4-(2,3- epoxipropoxi)phen yl]propane	1675-54-3	Water flea	Estimated	48 hours	EC50	1.8 mg/l
bis-[4-(2,3- epoxipropoxi)phen yl]propane	1675-54-3	Green algae	Experimental	72 hours	ErC50	>11 mg/l
bis-[4-(2,3- epoxipropoxi)phen yl]propane	1675-54-3	Green algae	Experimental	72 hours	NOEC	4.2 mg/l
bis-[4-(2,3- epoxipropoxi)phen yl]propane	1675-54-3	Water flea	Experimental	21 days	NOEC	0.3 mg/l
Formaldehyde, oligomeric reaction products with phenol	9003-35-4	N/A	Data not available or insufficient for classification	N/A	N/A	n/a
Titanium dioxide	13463-67-7	Activated sludge	Experimental	3 hours	NOEC	>=1,000 mg/l
Titanium dioxide	13463-67-7	Diatom	Experimental	72 hours	EC50	>10,000 mg/l
Titanium dioxide	13463-67-7	Fathead minnow	Experimental	96 hours	LC50	>100 mg/l
Titanium dioxide	13463-67-7	Water flea	Experimental	48 hours	EC50	>100 mg/l
Titanium dioxide	13463-67-7	Diatom	Experimental	72 hours	NOEC	5,600 mg/l
trizinc bis(orthophosphate	7779-90-0	Activated sludge	Estimated	3 hours	EC50	10 mg/l
trizinc bis(orthophosphate	7779-90-0	Green algae	Estimated	72 hours	EC50	0.083 mg/l
trizinc bis(orthophosphate	7779-90-0	Invertebrate	Estimated	48 hours	EC50	0.08 mg/l
trizinc bis(orthophosphate )	7779-90-0	Rainbow trout	Estimated	96 hours	LC50	0.33 mg/l
trizinc bis(orthophosphate )	7779-90-0	Water flea	Estimated	48 hours	EC50	0.12 mg/l
trizinc bis(orthophosphate )	7779-90-0	Diatom	Estimated	72 hours	EC50	0.04 mg/l
trizinc bis(orthophosphate )	7779-90-0	Green algae	Estimated	72 hours	NOEC	0.01 mg/l
trizinc bis(orthophosphate )	7779-90-0	Water flea	Estimated	7 days	NOEC	0.026 mg/l

# 12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Propane, 1,2,3- trichloro-, polymer with 1,1'- [methylenebis(oxy)]bis[2- chloroethane] and sodium sulfide (Na2(Sx)), reduced		Data not availblinsufficient	N/A	N/A	N/A	N/A
Calcium carbonate	471-34-1	Data not availbl- insufficient	N/A	N/A	N/A	N/A
bis-[4-(2,3-	1675-54-3	Experimental	28 days	BOD	5 %BOD/COD	OECD 301F - Manometric

\_\_\_\_

epoxipropoxi)phen yl]propane		Biodegradation				respirometry
bis-[4-(2,3- epoxipropoxi)phen yl]propane	1675-54-3	Experimental Hydrolysis		Hydrolytic half-life (pH 7)	117 hours (t 1/2)	OECD 111 Hydrolysis func of pH
Formaldehyde, oligomeric reaction products with phenol	9003-35-4	Estimated Biodegradation	28 days	BOD	3 %BOD/ThOD	
Titanium dioxide	13463-67-7	Data not availbl- insufficient	N/A	N/A	N/A	N/A
trizinc bis(orthophosphate )	7779-90-0	Data not availbl- insufficient	N/A	N/A	N/A	N/A

# 12.3 : Bioaccumulative potential

Material	Cas No.	Test type	Duration	Study Type	Test result	Protocol
Propane, 1,2,3- trichloro-, polymer with 1,1'- [methylenebis(oxy)]bis[2- chloroethane] and sodium sulfide (Na2(Sx)), reduced		Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Calcium carbonate	471-34-1	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
bis-[4-(2,3- epoxipropoxi)phen yl]propane	1675-54-3	Experimental Bioconcentration		Log Kow	3.242	OECD 117 log Kow HPLC method
Formaldehyde, oligomeric reaction products with phenol	9003-35-4	Estimated Bioconcentration		Bioaccumulation factor	2.57	
Titanium dioxide	13463-67-7	Experimental BCF - Fish	42 days	Bioaccumulation factor	9.6	

# 12.4. Mobility in soil

Material	Cas No.	Test type	Study Type	Test result	Protocol
bis-[4-(2,3- epoxipropoxi)pheny l]propane		Modeled Mobility in Soil	Koc	450 l/kg	Episuite <sup>™</sup>
Formaldehyde, oligomeric reaction products with phenol		Experimental Mobility in Soil	Koc	637 l/kg	OECD 121 Estim. of Koc by HPLC

# 12.5. Results of the PBT and vPvB assessment

This material does not contain any substances that are assessed to be a PBT or vPvB

# 12.6. Other adverse effects

This material does not contain any substances that are assessed to be an endocrine disruptor for environmental effects

# **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

# EU waste code (product as sold)

08 04 09\* Waste adhesives and sealants containing organic solvents or other dangerous substances

# **SECTION 14: Transportation information**

	Ground Transport (ADR)	Air Transport (IATA)	Marine Transport (IMDG)
14.1 UN number	UN3082	UN3082	UN3082
14.2 UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.(ZINC PHOSPHATE; ZINC OXIDE)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.(ZINC PHOSPHATE; ZINC OXIDE)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.(ZINC PHOSPHATE; ZINC OXIDE)
14.3 Transport hazard class(es)	9	9	9
14.4 Packing group	Ш	III	III
14.5 Environmental hazards	Environmentally Hazardous	Not applicable	Marine Pollutant
14.6 Special precautions for user	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.
14.7 Transport in bulk according to Annex II of Marpol 73/78 and IBC Code	No data available.	No data available.	No data available.
Control Temperature	No data available.	No data available.	No data available.
Emergency Temperature	No data available.	No data available.	No data available.
ADR Classification Code	M6	Not applicable.	Not applicable.
IMDG Segregation Code	Not applicable.	Not applicable.	NONE

Please contact the address or phone number listed on the first page of the SDS for additional information on the transport/shipment of the material by rail (RID) or inland waterways (ADN).

\_\_\_\_\_

# **SECTION 15: Regulatory information**

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

# Carcinogenicity

Ingredient	CAS Nbr	Classification	Regulation
bis-[4-(2,3-epoxipropoxi)phenyl]propane	1675-54-3	Gr. 3: Not classifiable	International Agency
Titanium dioxide	13463-67-7	Grp. 2B: Possible human carc.	for Research on Cancer International Agency for Research on Cancer

# Restrictions on the manufacture, placing on the market and use:

The following substance(s) contained in this product is/are subject to Annex XVII of regulation (EC) 1907/2006, as amended for GB, with regard to restrictions on the manufacture, placing on the market and use when present in certain dangerous conditions. Users of this product are required to comply with the restrictions placed upon it by the aforementioned provision.

bis-[4-(2,3-epoxipropoxi)phenyl]propane 1675-54-3

#### Global inventory status

Contact 3M for more information. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

#### COMAH Regulation, SI 2015/483

Seveso hazard categories, Annex 1, Part 1

Hazard Categories	Qualifying quantity (tonnes) for the application of		
	Lower-tier requirements	Upper-tier requirements	
E2 Hazardous to the Aquatic	200	500	
environment			

Seveso named dangerous substances, Annex 1, Part 2

Dangerous Substances	Identifier(s)	Qualifying quantity (tonnes) for the application of		
		Lower-tier requirements	Upper-tier requirements	
trizinc bis(orthophosphate)	7779-90-0	100	200	

# Regulation (EU) No 649/2012, as amended for GB

No chemicals listed

#### 15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out for this substance/mixture in accordance with Regulation (EC) No 1907/2006, as amended for GB.

ı	$\alpha$		$\sim$	T 4		$\sim$		• 4	•	4 •
ı			 		<i>_</i> •	1 14	$\alpha \alpha \mathbf{w}$	1101	forma	tion
ı		1.4								

#### List of relevant H statements

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H351i	Suspected of causing cancer by inhalation.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

#### **Revision information:**

GB Section 02: CLP Ingredient table information was added.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into the European Union, you are responsible for all regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration.

#### 3M SDSs for Great Britain are available at www.3M.com/uk

For Northern Ireland documents, please contact your 3M representative to obtain a copy.



# Safety Data Sheet

Copyright, 2023, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document group:
 30-3086-3
 Version number:
 11.01

 Revision date:
 20/07/2023
 Supersedes date:
 21/06/2023

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (1907/2006), as amended for GB.

# **SECTION 1: Identification of the substance/mixture and of the company/undertaking**

#### 1.1. Product identifier

3M Aerospace Sealant AC-735 B-1/2 Catalyst

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### **Identified uses**

Hardener

#### 1.3. Details of the supplier of the safety data sheet

Address: 3M United Kingdom PLC, 3M Centre, Cain Road, Bracknell, Berkshire, RG12 8HT.

**Telephone:** +44 (0)1344 858 000 **E Mail:** tox.uk@mmm.com **Website:** www.3M.com/uk

#### 1.4. Emergency telephone number

+44 (0)1344 858 000

# **SECTION 2: Hazard identification**

# 2.1. Classification of the substance or mixture

The retained CLP Regulation (EU) No 1272/2008 as amended for Great Britain

The health and environmental classifications of this material have been derived using the calculation method, except in cases where test data are available or the physical form impacts classification. Classification(s) based on test data or physical form are noted below, if applicable.

# **CLASSIFICATION:**

Acute Toxicity, Category 4 - Acute Tox. 4; H302

Skin Corrosion/Irritation, Category 2 - Skin Irrit. 2; H315

Serious Eye Damage/Eye Irritation, Category 2 - Eye Irrit. 2; H319

Reproductive Toxicity, Category 1A - Repr. 1A; H360D

Specific Target Organ Toxicity-Repeated Exposure, Category 2 - STOT RE 2; H373

Hazardous to the Aquatic Environment (Acute), Category 1 - Aquatic Acute 1; H400

Hazardous to the Aquatic Environment (Chronic), Category 1 - Aquatic Chronic 1; H410

For full text of H phrases, see Section 16.

#### 2.2. Label elements

# The retained CLP Regulation (EU) No 1272/2008 as amended for Great Britain

#### SIGNAL WORD

DANGER.

#### **Symbols**

GHS07 (Exclamation mark) |GHS08 (Health Hazard) |GHS09 (Environment) |

#### **Pictograms**







Ingredient	CAS Nbr	EC No.	% by Wt
manganese dioxide	1313-13-9	215-202-6	30 - 45
lead powder; [particle diameter < 1 mm]	7439-92-1	231-100-4	< 0.1

#### **HAZARD STATEMENTS:**

H302 Harmful if swallowed.
 H315 Causes skin irritation.
 H319 Causes serious eye irritation.
 H360D May damage the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure: nervous system.

H410 Very toxic to aquatic life with long lasting effects.

# PRECAUTIONARY STATEMENTS

**Prevention:** 

P201 Obtain special instructions before use.

P260A Do not breathe vapours.

P273 Avoid release to the environment.
P280F Wear respiratory protection.

**Response:** 

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P308 + P313 IF exposed or concerned: Get medical advice/attention.

# For containers not exceeding 125 ml the following Hazard and Precautionary statements may be used:

<=125 ml Hazard statements

H360D May damage the unborn child.

# <=125 ml Precautionary statements

# 3M Aerospace Sealant AC-735 B-1/2 Catalyst

**Prevention:** 

P201 Obtain special instructions before use.

P280F Wear respiratory protection.

**Response:** 

P308 + P313 IF exposed or concerned: Get medical advice/attention.

#### SUPPLEMENTAL INFORMATION:

# **Supplemental Precautionary Statements:**

Restricted to professional users.

12% of the mixture consists of components of unknown acute oral toxicity.

Contains 51% of components with unknown hazards to the aquatic environment.

#### 2.3. Other hazards

Contains a substance that meets the criteria for vPvB according to Regulation (EC) No 1907/2006, Annex XIII, as amended by UK REACH Regulations SI 2019/758

# **SECTION 3: Composition/information on ingredients**

#### 3.1. Substances

Not applicable

#### 3.2. Mixtures

Ingredient	Identifier(s)	0/0	Classification according to Regulation (EC) No. 1272/2008 [CLP], as amended for GB
manganese dioxide	(CAS-No.) 1313-13-9 (EC-No.) 215-202-6	30 - 45	Acute Tox. 4, H332 Acute Tox. 4, H302 EUH031 STOT RE 2, H373
Hydrogenated terphenyl	(CAS-No.) 61788-32-7 (EC-No.) 262-967-7	30 - 40	Aquatic Chronic 2, H411
Polyphenyls, quater- and higher, partially hydrogenated	(CAS-No.) 68956-74-1 (EC-No.) 273-316-1	< 10	Substance not classified as hazardous
Natural Amorphous compounds	Trade Secret	< 5	Substance not classified as hazardous
Water	(CAS-No.) 7732-18-5 (EC-No.) 231-791-2	1 - 5	Substance not classified as hazardous
Bis(piperidinothiocarbonyl) hexasulphide	(CAS-No.) 971-15-3 (EC-No.) 213-537-2	1 - 5	Substance not classified as hazardous
Terphenyl	(CAS-No.) 26140-60-3 (EC-No.) 247-477-3	1 - 5	Aquatic Acute 1, H400,M=10 Aquatic Chronic 1, H410,M=10
ferbam (ISO)	(CAS-No.) 14484-64-1 (EC-No.) 238-484-2	0.1 - 1	Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335

			Aquatic Acute 1, H400,M=10 Aquatic Chronic 1, H410,M=100 Acute Tox. 2, H330
sodium hydroxide	(CAS-No.) 1310-73-2 (EC-No.) 215-185-5	0.1 - 1	Skin Corr. 1A, H314 Eye Dam. 1, H318 Met. Corr. 1, H290
lead powder; [particle diameter < 1 mm]	(CAS-No.) 7439-92-1 (EC-No.) 231-100-4	< 0.1	Repr. 1A, H360FD Lact., H362 STOT SE 2, H371 STOT RE 2, H373 Aquatic Acute 1, H400,M=1 Aquatic Chronic 1, H410,M=10

Please see section 16 for the full text of any H statements referred to in this section

# **Specific Concentration Limits**

Ingredient	Identifier(s)	Specific Concentration Limits
lead powder; [particle diameter < 1 mm]	(CAS-No.) 7439-92-1 (EC-No.) 231-100-4	(C >= 0.03%) Repr. 1A, H360D
sodium hydroxide	(CAS-No.) 1310-73-2 (EC-No.) 215-185-5	(C >= 5%) Skin Corr. 1A, H314 (2% =< C < 5%) Skin Corr. 1B, H314 (0.5% =< C < 2%) Skin Irrit. 2, H315 (C >= 2%) Eye Dam. 1, H318 (0.5% =< C < 2%) Eye Irrit. 2, H319

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

# **SECTION 4: First aid measures**

## 4.1. Description of first aid measures

#### Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

#### Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

#### **Eve contact**

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

## If swallowed

Rinse mouth. If you feel unwell, get medical attention.

# 4.2. Most important symptoms and effects, both acute and delayed

The most important symptoms and effects based on the GB CLP classification include:

Irritation to the skin (localized redness, swelling, itching, and dryness). Serious irritation to the eyes (significant redness, swelling, pain, tearing, and impaired vision). Harmful if swallowed. Target organ effects. See Section 11 for additional details.

# 4.3. Indication of any immediate medical attention and special treatment required

Not applicable

# **SECTION 5: Fire-fighting measures**

#### 5.1. Extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

# 5.2. Special hazards arising from the substance or mixture

None inherent in this product.

## **Hazardous Decomposition or By-Products**

<u>Substance</u>	<u>Condition</u>
Carbon monoxide	During combustion.
Carbon dioxide.	During combustion.
Oxides of nitrogen.	During combustion.
Oxides of Lead	During combustion.
Oxides of sulphur.	During combustion.

#### 5.3. Advice for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

# **SECTION 6: Accidental release measures**

# 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

#### 6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

#### 6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible.

#### 6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

# **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Avoid contact during pregnancy/while nursing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment.

#### 7.2. Conditions for safe storage including any incompatibilities

Store away from heat. Store away from acids.

# 7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

# **SECTION 8: Exposure controls/personal protection**

### 8.1 Control parameters

#### Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient sodium hydroxide	CAS Nbr 1310-73-2	Agency UK HSC	Limit type STEL:2 mg/m3	Additional comments
Manganese, inorganic compounds		UK HSC	TWA(as Mn, respirable	
			fraction):0.05 mg/m3;TWA(as	
Terphenyl	26140-60-3	UK HSC	Mn):0.5 mg/m3 STEL:4.8 mg/m3(0.5 ppm)	
Hydrogenated terphenyl	61788-32-7	UK HSC	TWA:19 mg/m3(2 ppm);STEL:48 mg/m3(5 ppm)	
lead powder; [particle diameter < 1 mm]	7439-92-1	UK HSC	TWA(as Pb):0.15 mg/m3	

UK HSC: UK Health and Safety Commission

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

# **Biological limit values**

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

#### 8.2. Exposure controls

#### 8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

#### 8.2.2. Personal protective equipment (PPE)

## Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect vented goggles.

Applicable Norms/Standards

Use eye protection conforming to EN 166

#### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended:

Material	Thickness (mm)	Breakthrough Time
Butyl rubber.	0.5	=>8 hours

## 3M Aerospace Sealant AC-735 B-1/2 Catalyst

Neoprene. 0.5 =>8 hours
Nitrile rubber. 0.35 =>8 hours

The glove data presented are based on the substance driving dermal toxicity and the conditions present at the time of testing. Breakthrough time may be altered when the glove is subjected to use conditions that place additional stress on the glove.

Applicable Norms/Standards
Use gloves tested to EN 374

#### Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

Applicable Norms/Standards

Use a respirator conforming to EN 140 or EN 136: filter types A & P

# **SECTION 9: Physical and chemical properties**

9.1. Information on basic physical and chemical properties

Physical state Liquid. Colour Dark Brown Odor Slight Odor Odour threshold No data available. Melting point/freezing point Not applicable. Boiling point/boiling range No data available. Flammability (solid, gas) Not applicable. Flammable Limits(LEL) No data available. Flammable Limits(UEL) No data available.

Flash point >=93.3 °C [Test Method:Closed Cup]

Autoignition temperatureNo data available.Decomposition temperatureNo data available.

pH substance/mixture is non-soluble (in water)

Kinematic Viscosity No data available.

Water solubility Nil

Solubility- non-waterNo data available.Partition coefficient: n-octanol/waterNot applicable.Vapour pressureNo data available.Density1.58 g/ml

**Relative density** 1.58 [Ref Std:WATER=1] **Relative Vapour Density** >=1 [Ref Std:AIR=1]

#### 9.2. Other information

9.2.2 Other safety characteristics

EU Volatile Organic Compounds

Evaporation rate

Molecular weight

No data available.

Not applicable.

# **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

This material is considered to be non reactive under normal use conditions

#### 10.2 Chemical stability

Stable.

#### 10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

#### 10.4 Conditions to avoid

Heat.

#### 10.5 Incompatible materials

Reducing agents.

Strong acids.

# 10.6 Hazardous decomposition products

**Substance** 

Condition

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

# **SECTION 11: Toxicological information**

The information below may not agree with the material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from 3M assessments.

11.1. Information on hazard classes as defined in the retained CLP Regulation (EU) No 1272/2008, as amended for Great Britain.

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

#### Skin contact

Skin Irritation: Signs/symptoms may include localised redness, swelling, itching, dryness, cracking, blistering, and pain.

#### Eye contact

Severe eye irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

#### **Ingestion**

May be harmful if swallowed.

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea. May cause additional health effects (see below).

#### **Additional Health Effects:**

Prolonged or repeated exposure may cause target organ effects:

Neurological effects: Signs/symptoms may include personality changes, lack of coordination, sensory loss, tingling or numbness of the extremities, weakness, tremors, and changes in blood pressure and heart rate. Respiratory effects: Signs/symptoms may include cough, shortness of breath, chest tightness, wheezing, increased heart rate, bluish coloured skin (cyanosis), sputum production, changes in lung function tests, and respiratory failure.

# Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which may interfere with lactation or be harmful to breastfed children.

# **Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

**Acute Toxicity** 

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE >2,000 - =5,000 mg/kg
manganese dioxide	Dermal	Rat	LD50 2,000 mg/kg
manganese dioxide	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 1.5 mg/l
manganese dioxide	Ingestion	Rat	LD50 > 2,197 mg/kg
Hydrogenated terphenyl	Dermal	Rabbit	LD50 > 2,000 mg/kg
Hydrogenated terphenyl	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 4.7 mg/l
Hydrogenated terphenyl	Ingestion	Rat	LD50 > 10,000 mg/kg
Bis(piperidinothiocarbonyl) hexasulphide	Ingestion	Rat	LD50 > 5,000 mg/kg
Terphenyl	Dermal	Rabbit	LD50 > 5,000 mg/kg
Terphenyl	Inhalation- Dust/Mist (4 hours)	Rat	LD50 > 3.8 mg/l
Terphenyl	Ingestion	Rat	LD50 2,304 mg/kg
ferbam (ISO)	Dermal	Rabbit	LD50 > 4,000 mg/kg
ferbam (ISO)	Inhalation- Dust/Mist (4 hours)	Rat	LC50 0.4 mg/l
ferbam (ISO)	Ingestion	Rat	LD50 1,130 mg/kg
lead powder; [particle diameter < 1 mm]	Dermal		LD50 estimated to be 2,000 - 5,000 mg/kg

ATE = acute toxicity estimate

# Skin Corrosion/Irritation

Name		Value
manganese dioxide	Rabbit	No significant irritation
Hydrogenated terphenyl	Rabbit	No significant irritation
Terphenyl	Rabbit	No significant irritation
sodium hydroxide	Rabbit	Corrosive
ferbam (ISO)	Rabbit	No significant irritation
lead powder; [particle diameter < 1 mm]	similar	No significant irritation
	compoun	
	ds	

Serious Eye Damage/Irritation

Name	Species	Value
manganese dioxide	Rabbit	Mild irritant
Hydrogenated terphenyl	Rabbit	No significant irritation
Terphenyl	Rabbit	No significant irritation
sodium hydroxide	Rabbit	Corrosive
ferbam (ISO)	Rabbit	Severe irritant

\_\_\_\_

# 3M Aerospace Sealant AC-735 B-1/2 Catalyst

lead powder; [particle diameter < 1 mm]	similar	Mild irritant
	compoun	
	ds	

# **Skin Sensitisation**

Name	Species	Value
manganese dioxide	Mouse	Not classified
Hydrogenated terphenyl	Human	Not classified
sodium hydroxide	Human	Not classified
ferbam (ISO)	Guinea	Not classified
	pig	

# **Respiratory Sensitisation**

For the component/components, either no data is currently available or the data is not sufficient for classification.

**Germ Cell Mutagenicity** 

Name	Route	Value		
manganese dioxide	In Vitro	Some positive data exist, but the data are not sufficient for classification		
manganese dioxide	In vivo	Some positive data exist, but the data are not sufficient for classification		
Hydrogenated terphenyl	In Vitro	Not mutagenic		
Hydrogenated terphenyl	In vivo	Not mutagenic		
Bis(piperidinothiocarbonyl) hexasulphide	In Vitro	Not mutagenic		
Terphenyl	In Vitro	Not mutagenic		
Terphenyl	In vivo	Not mutagenic		
sodium hydroxide	In Vitro	Not mutagenic		
lead powder; [particle diameter < 1 mm]	In vivo	Some positive data exist, but the data are not sufficient for classification		

Carcinogenicity

Name	Route	Species	Value
ferbam (ISO)	Ingestion	Rat	Not carcinogenic
lead powder; [particle diameter < 1 mm]	Not	official	Carcinogenic.
	specified.	classifica	
		tion	

# Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
manganese dioxide	Inhalation	Not classified for female reproduction	Rat	NOAEL 20 mg/m³	2 generation
manganese dioxide	Inhalation	Not classified for male reproduction	Rabbit	LOAEL 250 mg/kg	1 days
manganese dioxide	Ingestion	Not classified for development	Rat	LOAEL 354 mg/kg/day	premating into lactation
manganese dioxide	Inhalation	Not classified for development	Rat	LOAEL 61 mg/m³	gestation into lactation
Hydrogenated terphenyl	Ingestion	Not classified for female reproduction	Rat	NOAEL 81 mg/kg/day	2 generation
Hydrogenated terphenyl	Ingestion	Not classified for male reproduction	Rat	NOAEL 62 mg/kg/day	2 generation
Hydrogenated terphenyl	Ingestion	Not classified for development	Rat	NOAEL 500 mg/kg/day	during organogenesis
ferbam (ISO)	Ingestion	Not classified for female reproduction	Rat	NOAEL 25 mg/kg/day	3 generation
ferbam (ISO)	Ingestion	Not classified for male reproduction	Rat	NOAEL 25 mg/kg/day	3 generation
ferbam (ISO)	Ingestion	Not classified for development	Rat	NOAEL 11	during

D 10 C 16

				mg/kg/day	organogenesis
lead powder; [particle diameter < 1 mm]	Not	Toxic to female reproduction	Human	LOAEL 10	
	specified.			ug/dl blood	
lead powder; [particle diameter < 1 mm]	Not	Toxic to male reproduction	Human	LOAEL 37	
	specified.	-		ug/dl blood	
lead powder; [particle diameter < 1 mm]	Not	Toxic to development	Human	NOAEL Not	
	specified.	-		available	

# Lactation

Name	Route Species Value			
ferbam (ISO)	Ingestion	Rat	Causes effects on or via lactation	

# Target Organ(s)

Specific Target Organ Toxicity - single exposure

Specific Turget Organ	seeme raiget organ roateity single exposure							
Name	Route	Target Organ(s)	Value	Species	Test result	Exposure		
						Duration		
sodium hydroxide	Inhalation	respiratory irritation	May cause respiratory irritation	Human	NOAEL Not			
					available			
lead powder; [particle	Ingestion	nervous system	May cause damage to organs	Human	LOAEL 90	poisoning		
diameter < 1 mm]		-			ug/dl blood	and/or abuse		
lead powder; [particle	Ingestion	heart	Not classified	Human	NOAEL Not	poisoning		
diameter < 1 mm]	_				available	and/or abuse		

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
manganese dioxide	Inhalation	respiratory system	Causes damage to organs through prolonged or repeated exposure	Monkey	LOAEL 1.1 mg/m³	10 months
manganese dioxide	Inhalation	nervous system	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure
Hydrogenated terphenyl	Dermal	skin	Not classified	Rabbit	NOAEL 500 mg/kg/day	3 weeks
Hydrogenated terphenyl	Dermal	hematopoietic system	Not classified	Rabbit	NOAEL 2,000 mg/kg/day	3 weeks
Hydrogenated terphenyl	Inhalation	liver   hematopoietic system   eyes	Not classified	Rat	NOAEL 0.5 mg/l	13 weeks
Hydrogenated terphenyl	Ingestion	hematopoietic system   kidney and/or bladder   liver   eyes   respiratory system	Not classified	Rat	NOAEL 120 mg/kg/day	14 weeks
lead powder; [particle diameter < 1 mm]	Inhalation	kidney and/or bladder	May cause damage to organs though prolonged or repeated exposure	Human	LOAEL 60 ug/dl blood	occupational exposure
lead powder; [particle diameter < 1 mm]	Inhalation	hematopoietic system	May cause damage to organs though prolonged or repeated exposure	Human	LOAEL 50 ug/dl blood	occupational exposure
lead powder; [particle diameter < 1 mm]	Inhalation	nervous system	May cause damage to organs though prolonged or repeated exposure	Human	LOAEL 40 ug/dl blood	occupational exposure
lead powder; [particle diameter < 1 mm]	Inhalation	gastrointestinal tract	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure
lead powder; [particle diameter < 1 mm]	Inhalation	heart   endocrine system   immune system   vascular system	Not classified	Human	NOAEL Not available	occupational exposure
lead powder; [particle diameter < 1 mm]	Ingestion	bone, teeth, nails, and/or hair	May cause damage to organs though prolonged or repeated exposure	Rat	LOAEL 20 ug/dl blood	3 months
lead powder; [particle diameter < 1 mm]	Ingestion	eyes	May cause damage to organs though prolonged or repeated	Rat	LOAEL 0.5 mg/kg/day	20 days

			exposure			
lead powder; [particle diameter < 1 mm]	Ingestion	hematopoietic system   kidney and/or bladder	May cause damage to organs though prolonged or repeated exposure	Human	LOAEL 40 ug/dl blood	environmenta l exposure
lead powder; [particle diameter < 1 mm]	Ingestion	nervous system	May cause damage to organs though prolonged or repeated exposure	Human	LOAEL 11 ug/dl blood	environmenta l exposure
lead powder; [particle diameter < 1 mm]	Ingestion	auditory system   heart   endocrine system   vascular system	Not classified	Human	NOAEL Not available	environmenta 1 exposure

#### **Aspiration Hazard**

For the component/components, either no data is currently available or the data is not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

# 11.2. Information on other hazards

This material does not contain any substances that are assessed to be an endocrine disruptor for human health.

# **SECTION 12: Ecological information**

The information below may not agree with the material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

# 12.1. Toxicity

No product test data available.

Material	CAS#	Organism	Type	Exposure	Test endpoint	Test result
manganese dioxide	1313-13-9	Rainbow trout	Endpoint not reached	96 hours	LC50	>100 mg/l
manganese dioxide	1313-13-9	Green algae	Experimental	72 hours	EC50	>100 mg/l
manganese dioxide	1313-13-9	Water flea	Experimental	48 hours	EC50	>100 mg/l
manganese dioxide	1313-13-9	Green algae	Experimental	72 hours	EC10	100 mg/l
manganese dioxide	1313-13-9	Water flea	Experimental	8 days	NOEC	100 mg/l
Hydrogenated terphenyl	61788-32-7	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Hydrogenated terphenyl	61788-32-7	Activated sludge	Experimental	3 hours	NOEC	103 mg/l
Polyphenyls, quater- and higher, partially hydrogenated	68956-74-1	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Bis(piperidinothioc arbonyl) hexasulphide	971-15-3	Green algae	Experimental	72 hours	EC50	>100 mg/l
Bis(piperidinothioc arbonyl) hexasulphide	971-15-3	Green algae	Experimental	72 hours	NOEC	100 mg/l
Terphenyl	26140-60-3	Water flea	Estimated	48 hours	EC50	0.022 mg/l
Terphenyl	26140-60-3	Green algae	Experimental	72 hours	EC50	0.102 mg/l

Terphenyl	26140-60-3	Rainbow trout	Experimental	96 hours	LC50	27 mg/l
Terphenyl	26140-60-3	Fathead minnow	Experimental	34 days	NOEC	0.064 mg/l
Terphenyl	26140-60-3	Green algae	Experimental	72 hours	NOEC	0.003 mg/l
Terphenyl	26140-60-3	Water flea	Experimental	21 days	NOEC	0.005 mg/l
ferbam (ISO)	14484-64-1	Green algae	Experimental	96 hours	ErC50	2.4 mg/l
ferbam (ISO)	14484-64-1	Guppy	Experimental	96 hours	LC50	0.09 mg/l
ferbam (ISO)	14484-64-1	Water flea	Experimental	48 hours	LC50	0.09 mg/l
ferbam (ISO)	14484-64-1	Rainbow trout	Experimental	60 days	NOEC	0.00056 mg/l
sodium hydroxide	1310-73-2	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
lead powder; [particle diameter < 1 mm]	7439-92-1	Fathead minnow	Analogous Compound	96 hours	LC50	0.0408 mg/l
lead powder; [particle diameter < 1 mm]	7439-92-1	Green algae	Analogous Compound	72 hours	ErC50	0.0205 mg/l
lead powder; [particle diameter < 1 mm]	7439-92-1	Water flea	Analogous Compound	48 hours	EC50	0.026 mg/l
lead powder; [particle diameter < 1 mm]	7439-92-1	N/A	Analogous Compound	30 days	EC10	0.0017 mg/l
lead powder; [particle diameter < 1 mm]	7439-92-1	Green algae	Analogous Compound	72 hours	ErC10	0.0061 mg/l
lead powder; [particle diameter < 1 mm]	7439-92-1	Rainbow trout	Analogous Compound	578 days	NOEC	0.003 mg/l
lead powder; [particle diameter < 1 mm]	7439-92-1	Activated sludge	Analogous Compound	24 hours	EC50	9 mg/l

# 12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
manganese dioxide	1313-13-9	Data not availbl- insufficient	N/A	N/A	N/A	N/A
Hydrogenated terphenyl	61788-32-7	Experimental Biodegradation	35 days	CO2 evolution	1 %CO2 evolution/THCO2 evolution	OECD 301B - Modified sturm or CO2
Hydrogenated terphenyl	61788-32-7	Experimental Photolysis		Photolytic half- life(in water)	86 days (t 1/2)	
Hydrogenated terphenyl	61788-32-7	Experimental Soil Metabolism Aerobic		Half-life (t 1/2)	202 days (t 1/2)	
Polyphenyls, quater- and higher, partially hydrogenated	68956-74-1	Data not availblinsufficient	N/A	N/A	N/A	N/A
Bis(piperidinothioc arbonyl) hexasulphide	971-15-3	Experimental Biodegradation	28 days	BOD	0 %BOD/ThOD	OECD 301F - Manometric respirometry
Terphenyl	26140-60-3	Experimental Biodegradation	14 days	BOD	0.5 %BOD/ThOD	OECD 301C - MITI test (I)
ferbam (ISO)	14484-64-1	Analogous Compound Biodegradation	14 days	BOD	0 %BOD/ThOD	OECD 301C - MITI test (I)

# 3M Aerospace Sealant AC-735 B-1/2 Catalyst

ferbam (ISO)	14484-64-1	Experimental		Hydrolytic half-life	≤31 minutes (t 1/2)	
		Hydrolysis				
sodium hydroxide	1310-73-2	Data not availbl-	N/A	N/A	N/A	N/A
		insufficient				
lead powder;	7439-92-1	Data not availbl-	N/A	N/A	N/A	N/A
[particle diameter <		insufficient				
1 mm]						

# 12.3 : Bioaccumulative potential

Material	Cas No.	Test type	Duration	Study Type	Test result	Protocol
manganese dioxide	1313-13-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Hydrogenated terphenyl	61788-32-7	Analogous Compound BCF - Fish	42 days	Bioaccumulation factor	5200	similar to OECD 305
Hydrogenated terphenyl	61788-32-7	Experimental Bioconcentration		Log Kow	>5.3	OECD 117 log Kow HPLC method
Polyphenyls, quater- and higher, partially hydrogenated	68956-74-1	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Bis(piperidinothioc arbonyl) hexasulphide	971-15-3	Estimated Bioconcentration		Bioaccumulation factor	2.8	
Terphenyl	26140-60-3	Estimated BCF - Fish	60 days	Bioaccumulation factor	2300	OECD305-Bioconcentration
ferbam (ISO)	14484-64-1	Experimental Bioconcentration		Log Kow	-1.597	OECD 107 log Kow shke flsk mtd
sodium hydroxide	1310-73-2	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
lead powder; [particle diameter < 1 mm]	7439-92-1	Experimental BCF - Other		Bioaccumulation factor	1322	

# 12.4. Mobility in soil

Material	Cas No.	Test type	Study Type	Test result	Protocol
Hydrogenated	61788-32-7	Experimental	Koc	≥8400 l/kg	OECD 121 Estim. of Koc by
terphenyl		Mobility in Soil		_	HPLC
Bis(piperidinothioc	971-15-3	Modeled Mobility	Koc	37,000 l/kg	Episuite <sup>TM</sup>
arbonyl)		in Soil			
hexasulphide					

# 12.5. Results of the PBT and vPvB assessment

Ingredient	CAS Nbr	PBT/vPvB status
Hydrogenated terphenyl	61788-32-7	Meets UK REACH vPvB criteria

# 12.6. Other adverse effects

This material does not contain any substances that are assessed to be an endocrine disruptor for environmental effects

# **SECTION 13: Disposal considerations**

# 13.1 Waste treatment methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. Empty

drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

# EU waste code (product as sold)

08 04 09\* Waste adhesives and sealants containing organic solvents or other dangerous substances

# **SECTION 14: Transportation information**

	Ground Transport (ADR)	Air Transport (IATA)	Marine Transport (IMDG)
14.1 UN number	UN3082	UN3082	UN3082
14.2 UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.(FERBAM; TERPHENYL)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.(FERBAM; TERPHENYL)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.(FERBAM; TERPHENYL)
14.3 Transport hazard class(es)	9	9	9
14.4 Packing group	III	III	III
14.5 Environmental hazards	Environmentally Hazardous	Not applicable	Marine Pollutant
14.6 Special precautions for user	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.
14.7 Transport in bulk according to Annex II of Marpol 73/78 and IBC Code	No data available.	No data available.	No data available.
Control Temperature	No data available.	No data available.	No data available.
Emergency Temperature	No data available.	No data available.	No data available.
ADR Classification Code	M6	Not applicable.	Not applicable.
IMDG Segregation Code	Not applicable.	Not applicable.	NONE

Please contact the address or phone number listed on the first page of the SDS for additional information on the transport/shipment of the material by rail (RID) or inland waterways (ADN).

# **SECTION 15: Regulatory information**

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

# Carcinogenicity

<u>Ingredient</u>	CAS Nbr	<b>Classification</b>	Regulation
ferbam (ISO)	14484-64-1	Gr. 3: Not classifiable	International Agency
			for Research on Cancer
lead powder; [particle diameter < 1 mm]	7439-92-1	Grp. 2B: Possible human carc.	International Agency for Research on Cancer

# Restrictions on the manufacture, placing on the market and use:

The following substance(s) contained in this product is/are subject to Annex XVII of regulation (EC) 1907/2006, as amended for GB, with regard to restrictions on the manufacture, placing on the market and use when present in certain dangerous conditions. Users of this product are required to comply with the restrictions placed upon it by the aforementioned provision.

<u>Ingredient</u>	CAS Nbr
lead powder; [particle diameter < 1 mm]	7439-92-1

Restriction status: listed in UK REACH Annex XVII

Restricted uses: See Annex XVII to Regulation (EC) No 1907/2006 as amended for Great Britain for Conditions of Restriction

#### Authorisation status under UK REACH:

The following substance/s contained in this product might be or is/are subject to authorisation in accordance with UK REACH:

<u>Ingredient</u>	<u>CAS Nbr</u>
Hydrogenated terphenyl	61788-32-7
lead powder; [particle diameter < 1 mm]	7439-92-1

Authorisation status: listed in the UK REACH Candidate List of Substances of Very High Concern for Authorisation **Global inventory status** 

Contact 3M for more information. The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

## COMAH Regulation, SI 2015/483

# 3M Aerospace Sealant AC-735 B-1/2 Catalyst

Seveso hazard categories, Annex 1, Part 1

Hazard Categories	Qualifying quantity (tonnes) for the application of		
	Lower-tier requirements	Upper-tier requirements	
E1 Hazardous to the Aquatic environment	100	200	

Seveso named dangerous substances, Annex 1, Part 2

Dangerous Substances	Identifier(s)	Qualifying quantity (tonnes) for the application of	
		Lower-tier requirements	Upper-tier requirements
ferbam (ISO)	14484-64-1	100	200
lead powder; [particle diameter < 1 mm]	7439-92-1	100	200

# Regulation (EU) No 649/2012, as amended for GB

Chemical	Identifier(s)	Annex I
ferbam (ISO)	14484-64-1	Part 1 and Part 2
lead powder; [particle diameter < 1 mm]	7439-92-1	Part 1

# 15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out for this substance/mixture in accordance with Regulation (EC) No 1907/2006, as amended for GB.

# **SECTION 16: Other information**

# List of relevant H statements

EUH031	Contact with acid liberates toxic gas.
H290	May be corrosive to metals.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H360D	May damage the unborn child.
H360FD	May damage fertility. May damage the unborn child.
H362	May cause harm to breast-fed children.
H371	May cause damage to organs.
H373	May cause damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure: nervous system.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

# **Revision information:**

No revision information

#### 3M Aerospace Sealant AC-735 B-1/2 Catalyst

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into the European Union, you are responsible for all regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration.

#### 3M SDSs for Great Britain are available at www.3M.com/uk

For Northern Ireland documents, please contact your 3M representative to obtain a copy.