



Safety Data Sheet

Copyright, 2023, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

| | | | |
|---------------------------------------|------------|-------------------------|------------|
| Document group: | 09-0182-7 | Version number: | 28.05 |
| Revision date: | 03/11/2023 | Supersedes date: | 09/01/2023 |
| Transportation version number: | | | |

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

3M™ Scotch-Weld™ Epoxy Structural Adhesive DP-760 Off-White

Product Identification Numbers

| | | |
|----------------|----------------|----------------|
| FS-9100-4045-0 | UU-0101-3339-3 | UU-0101-3340-1 |
| 7000006834 | 7100200505 | 7100200506 |

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Structural adhesive.

1.3. Details of the supplier of the safety data sheet

| | |
|-------------------|---|
| Address: | 3M Ireland Limited, The Iveagh Building, The Park, Carrickmines, Dublin 18. |
| Telephone: | +353 1 280 3555 |
| E Mail: | tox.uk@mmm.com |

| | |
|-----------------|------------|
| Website: | www.3M.com |
|-----------------|------------|

1.4. Emergency telephone number

Emergency medical information: 8am-10pm (seven days) contact National Poisons Information Centre, Beaumont Hospital, Dublin 9 DOV2NO, Ireland. Telephone Number: +353 (0)1 809 2166

This product is a kit or a multipart product which consists of multiple, independently packaged components. A Safety Data Sheet for each of these components is included. Please do not separate the component Safety Data Sheets from this cover page. The document numbers of the MSDSs for components of this product are:

09-0180-1, 09-0181-9

TRANSPORTATION INFORMATION

Refer to section 14 of the kit components for transport information.

KIT LABEL

2.1. Classification of the substance or mixture CLP REGULATION (EC) No 1272/2008

CLASSIFICATION:

Acute Toxicity, Category 4 - Acute Tox. 4; H302

Skin Corrosion/Irritation, Category 1B - Skin Corr. 1B; H314

Serious Eye Damage/Eye Irritation, Category 1 - Eye Dam. 1; H318

Skin Sensitization, Category 1 - Skin Sens. 1; H317

Germ Cell Mutagenicity, Category 2 - Muta. 2; H341

Hazardous to the Aquatic Environment (Chronic), Category 2 - Aquatic Chronic 2; H411

For full text of H phrases, see Section 16.

2.2. Label elements

CLP REGULATION (EC) No 1272/2008

SIGNAL WORD

DANGER.

Symbols

GHS05 (Corrosion) | GHS07 (Exclamation mark) | GHS08 (Health Hazard) | GHS09 (Environment) |

Pictograms



Contains:

p-(2,3-epoxypropoxy)-N,N-bis(2,3-epoxypropyl)aniline; Amines, polyethylenepoly-, triethylenetetramine fraction; bis-[4-(2,3-epoxypropoxy)phenyl]propane; Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-([2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy]methyl)oxirane.

HAZARD STATEMENTS:

| | |
|------|--|
| H302 | Harmful if swallowed. |
| H314 | Causes severe skin burns and eye damage. |
| H317 | May cause an allergic skin reaction. |
| H341 | Suspected of causing genetic defects. |
| H411 | Toxic to aquatic life with long lasting effects. |

PRECAUTIONARY STATEMENTS

Prevention:

| | |
|-------|---|
| P260A | Do not breathe vapours. |
| P273 | Avoid release to the environment. |
| P280D | Wear protective gloves, protective clothing, and eye/face protection. |

Response:

| | |
|--------------------|--|
| P303 + P361 + P353 | IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or |
|--------------------|--|

P305 + P351 + P338 shower.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a POISON CENTRE or doctor/physician.

For containers not exceeding 125 ml the following Hazard and Precautionary statements may be used:

<=125 ml Hazard statements

H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.
H341 Suspected of causing genetic defects.

<=125 ml Precautionary statements

Prevention:

P260A Do not breathe vapours.
P280D Wear protective gloves, protective clothing, and eye/face protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a POISON CENTRE or doctor/physician.

SUPPLEMENTAL INFORMATION:

Supplemental Hazard Statements:

EUH212 Warning! Hazardous respirable dust may be formed when used. Do not breathe dust.

Refer to Safety Data Sheet for component % unknown values (www.3M.com/msds).

Revision information:

Label: CLP Ingredients - kit components information was modified.
Section 1: Product identification numbers information was modified.
Section 01: SAP Material Numbers information was modified.



Safety Data Sheet

Copyright, 2023, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

| | | | |
|------------------------|------------|-------------------------|------------|
| Document group: | 09-0181-9 | Version number: | 25.03 |
| Revision date: | 21/08/2023 | Supersedes date: | 09/01/2023 |

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

3M™ Scotch-Weld™ Epoxy Structural Adhesive DP-760 Off-White : Part B

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Structural adhesive.

1.3. Details of the supplier of the safety data sheet

Address: 3M Ireland Limited, The Iveagh Building, The Park, Carrickmines, Dublin 18.
Telephone: +353 1 280 3555
E Mail: tox.uk@mmm.com
Website: www.3M.com

1.4. Emergency telephone number

Emergency medical information: 8am-10pm (seven days) contact National Poisons Information Centre, Beaumont Hospital, Dublin 9 DOV2NO, Ireland. Telephone Number: +353 (0)1 809 2166

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

CLP REGULATION (EC) No 1272/2008

The health and environmental classifications of this material have been derived using the calculation method, except in cases where test data are available or the physical form impacts classification. Classification(s) based on test data or physical form are noted below, if applicable.

The carcinogenicity classification for titanium dioxide is not applicable based on physical form (material is not a powder).

CLASSIFICATION:

Acute Toxicity, Category 4 - Acute Tox. 4; H302
Skin Corrosion/Irritation, Category 2 - Skin Irrit. 2; H315
Serious Eye Damage/Eye Irritation, Category 2 - Eye Irrit. 2; H319
Skin Sensitization, Category 1 - Skin Sens. 1; H317
Germ Cell Mutagenicity, Category 2 - Muta. 2; H341
Hazardous to the Aquatic Environment (Chronic), Category 2 - Aquatic Chronic 2; H411

For full text of H phrases, see Section 16.

2.2. Label elements

CLP REGULATION (EC) No 1272/2008

SIGNAL WORD

WARNING.

Symbols

GHS07 (Exclamation mark) |GHS08 (Health Hazard) |GHS09 (Environment) |

Pictograms



Ingredients:

| Ingredient | CAS Nbr | EC No. | % by Wt |
|---|-----------|-----------|---------|
| p-(2,3-epoxypropoxy)-N,N-bis(2,3-epoxypropyl)aniline | 5026-74-4 | 225-716-2 | 30 - 60 |
| Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-(\{2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy\}methyl)oxirane | | 701-263-0 | 7 - 15 |
| bis-[4-(2,3-epoxipropoxy)phenyl]propane | 1675-54-3 | 216-823-5 | 7 - 13 |

HAZARD STATEMENTS:

| | |
|------|--|
| H302 | Harmful if swallowed. |
| H315 | Causes skin irritation. |
| H319 | Causes serious eye irritation. |
| H317 | May cause an allergic skin reaction. |
| H341 | Suspected of causing genetic defects. |
| H411 | Toxic to aquatic life with long lasting effects. |

PRECAUTIONARY STATEMENTS

Prevention:

| | |
|-------|-----------------------------------|
| P273 | Avoid release to the environment. |
| P280E | Wear protective gloves. |

Response:

| | |
|--------------------|--|
| P305 + P351 + P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| P333 + P313 | If skin irritation or rash occurs: Get medical advice/attention. |
| P391 | Collect spillage. |

For containers not exceeding 125 ml the following Hazard and Precautionary statements may be used:

<=125 ml Hazard statements

| | |
|------|--------------------------------------|
| H317 | May cause an allergic skin reaction. |
|------|--------------------------------------|

H341 Suspected of causing genetic defects.

<=125 ml Precautionary statements

Prevention:

P280E Wear protective gloves.

Response:

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

SUPPLEMENTAL INFORMATION:

Supplemental Hazard Statements:

EUH212 Warning! Hazardous respirable dust may be formed when used. Do not breathe dust.

15% of the mixture consists of components of unknown acute oral toxicity.

Contains 19% of components with unknown hazards to the aquatic environment.

2.3. Other hazards

None known.

This material does not contain any substances that are assessed to be a PBT or vPvB

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

| Ingredient | Identifier(s) | % | Classification according to Regulation (EC) No. 1272/2008 [CLP] |
|---|---|-----------|---|
| p-(2,3-epoxypropoxy)-N,N-bis(2,3-epoxypropyl)aniline | (CAS-No.) 5026-74-4 (EC-No.) 225-716-2 | 30 - 60 | Aquatic Chronic 2, H411 Acute Tox. 4, H302 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Muta. 2, H341 |
| [3-(2,3-epoxypropoxy)propyl]trimethoxysilane | (CAS-No.) 2530-83-8 (EC-No.) 219-784-2 (REACH-No.) 01-2119513212-58 | 0.5 - 1.5 | Eye Dam. 1, H318 Aquatic Chronic 3, H412 |
| Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-(\{2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy\}methyl)oxirane | (EC-No.) 701-263-0 | 7 - 15 | Skin Irrit. 2, H315 Skin Sens. 1A, H317 Aquatic Acute 1, H400,M=1 Aquatic Chronic 1, H410,M=1 |
| bis-[4-(2,3-epoxipropoxy)phenyl]propane | (CAS-No.) 1675-54-3 (EC-No.) 216-823-5 (REACH-No.) 01-2119456619-26 | 7 - 13 | Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411 |

3M™ Scotch-Weld™ Epoxy Structural Adhesive DP-760 Off-White : Part B

| | | | |
|---|--|-------|---|
| Acrylic copolymer | Trade Secret | < 8 | Substance not classified as hazardous |
| Vinyl-Acrylic copolymer | Trade Secret | < 8 | Substance not classified as hazardous |
| Silica, vitreous | (CAS-No.) 60676-86-0 (EC-No.) 262-373-8 | 3 - 8 | Substance with a national occupational exposure limit |
| Siloxanes and Silicones, di-Me, reaction products with silica | (CAS-No.) 67762-90-7 | 1 - 5 | Substance with a national occupational exposure limit |
| Titanium dioxide | (CAS-No.) 13463-67-7 (EC-No.) 236-675-5 (REACH-No.) 01-2119489379-17 | 1 - 3 | Carc. 2, H351 (inhalation) |

Any entry in the Identifier(s) column that begins with the numbers 6, 7, 8, or 9 are a Provisional List Number provided by ECHA pending publication of the official EC Inventory Number for the substance.

Please see section 16 for the full text of any H statements referred to in this section

Specific Concentration Limits

| Ingredient | Identifier(s) | Specific Concentration Limits |
|---|---|---|
| bis-[4-(2,3-epoxipropoxy)phenyl]propane | (CAS-No.) 1675-54-3 (EC-No.) 216-823-5 (REACH-No.) 01-2119456619-26 | (C >= 5%) Skin Irrit. 2, H315 (C >= 5%) Eye Irrit. 2, H319 |

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

SECTION 4: First aid measures**4.1. Description of first aid measures****Inhalation**

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye contact

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

The most important symptoms and effects based on the CLP classification include:

Irritation to the skin (localized redness, swelling, itching, and dryness). Allergic skin reaction (redness, swelling, blistering, and itching). Serious irritation to the eyes (significant redness, swelling, pain, tearing, and impaired vision). Harmful if swallowed.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

| <u>Substance</u> | <u>Condition</u> |
|----------------------------|--------------------|
| Carbon monoxide | During combustion. |
| Carbon dioxide. | During combustion. |
| Irritant vapours or gases. | During combustion. |

5.3. Advice for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible.

6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

SECTION 7: Handling and storage

7.1. Precautions for safe handling

For industrial/occupational use only. Not for consumer sale or use. Do not handle until all safety precautions have been read and understood. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Use personal protective equipment (eg. gloves, respirators...) as required.

7.2. Conditions for safe storage including any incompatibilities

Store away from heat. Store away from acids.

7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

| Ingredient | CAS Nbr | Agency | Limit type | Additional comments |
|------------------|------------|--------------|--|---------------------|
| Titanium dioxide | 13463-67-7 | Ireland OELs | TWA(Total inhalable dust)(8 hours):10 mg/m ³ ;TWA(as respirable dust)(8 hours):4 mg/m ³ | |
| Silica, vitreous | 60676-86-0 | Ireland OELs | TWA(as respirable dust)(8 hours):0.08 mg/m ³ | |
| Silicon dioxide | 67762-90-7 | Ireland OELs | TWA(Total inhalable dust)(8 hours):6 mg/m ³ ;TWA(as respirable dust)(8 hours):2.4 mg/m ³ | |

Ireland OELs : Ireland. OELs
TWA: Time-Weighted-Average
STEL: Short Term Exposure Limit
CEIL: Ceiling

Biological limit values

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

Derived no effect level (DNEL)

| Ingredient | Degradation Product | Population | Human exposure pattern | DNEL |
|---|---------------------|------------|--|------------------------|
| bis-[4-(2,3-epoxipropoxy)phenyl]propane | | Worker | Dermal, Long-term exposure (8 hours), Systemic effects | 8.3 mg/kg bw/d |
| bis-[4-(2,3-epoxipropoxy)phenyl]propane | | Worker | Dermal, Short-term exposure, Systemic effects | 8.3 mg/kg bw/d |
| bis-[4-(2,3-epoxipropoxy)phenyl]propane | | Worker | Inhalation, Long-term exposure (8 hours), Systemic effects | 12.3 mg/m ³ |
| bis-[4-(2,3-epoxipropoxy)phenyl]propane | | Worker | Inhalation, Short-term exposure, Systemic effects | 12.3 mg/m ³ |

Predicted no effect concentrations (PNEC)

| Ingredient | Degradation Product | Compartment | PNEC |
|---|---------------------|--------------------------------|----------------|
| bis-[4-(2,3-epoxipropoxy)phenyl]propane | | Freshwater | 0.003 mg/l |
| bis-[4-(2,3-epoxipropoxy)phenyl]propane | | Freshwater sediments | 0.5 mg/kg d.w. |
| bis-[4-(2,3-epoxipropoxy)phenyl]propane | | Intermittent releases to water | 0.013 mg/l |
| bis-[4-(2,3-epoxipropoxy)phenyl]propane | | Marine water | 0.0003 mg/l |
| bis-[4-(2,3-epoxipropoxy)phenyl]propane | | Marine water sediments | 0.5 mg/kg d.w. |

| | | | |
|---|--|------------------------|---------|
| ne | | | |
| bis-[4-(2,3-epoxipropoxy)phenyl]propane | | Sewage Treatment Plant | 10 mg/l |

Recommended monitoring procedures: Information on recommended monitoring procedures can be obtained from Indust. Inspect./Ministry (IE)

8.2. Exposure controls

In addition, refer to the annex for more information.

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect vented goggles.

Applicable Norms/Standards

Use eye protection conforming to EN 166

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended:

| Material | Thickness (mm) | Breakthrough Time |
|------------------|-----------------------|--------------------------|
| Polymer laminate | No data available | No data available |

Applicable Norms/Standards

Use gloves tested to EN 374

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours

For questions about suitability for a specific application, consult with your respirator manufacturer.

Applicable Norms/Standards

Use a respirator conforming to EN 140 or EN 136: filter type A

8.2.3. Environmental exposure controls

Refer to Annex

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

| | |
|--|--|
| Physical state | Solid. |
| Specific Physical Form: | Paste |
| Colour | Off-White |
| Odor | Epoxy |
| Odour threshold | <i>No data available.</i> |
| Melting point/freezing point | <i>No data available.</i> |
| Boiling point/boiling range | <i>Not applicable.</i> |
| Flammability (solid, gas) | Not classified |
| Flammable Limits(LEL) | <i>Not applicable.</i> |
| Flammable Limits(UEL) | <i>Not applicable.</i> |
| Flash point | ≥ 100 °C [<i>Test Method: Closed Cup</i>] |
| Autoignition temperature | <i>Not applicable.</i> |
| Decomposition temperature | <i>No data available.</i> |
| pH | <i>substance/mixture is non-soluble (in water)</i> |
| Kinematic Viscosity | 826,772 mm ² /sec |
| Water solubility | Negligible |
| Solubility- non-water | <i>No data available.</i> |
| Partition coefficient: n-octanol/water | <i>No data available.</i> |
| Vapour pressure | <i>Not applicable.</i> |
| Density | ≥ 1.23 g/cm ³ |
| Relative density | 1.23 - 1.29 [<i>Ref Std: WATER=1</i>] |
| Relative Vapour Density | <i>Not applicable.</i> |

9.2. Other information**9.2.2 Other safety characteristics**

| | |
|-------------------------------|---------------------------|
| EU Volatile Organic Compounds | <i>No data available.</i> |
| Evaporation rate | <i>Not applicable.</i> |
| Molecular weight | <i>No data available.</i> |
| Percent volatile | 1 % weight |

SECTION 10: Stability and reactivity**10.1 Reactivity**

This material is considered to be non reactive under normal use conditions

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

Heat.

10.5 Incompatible materials

Strong acids.

10.6 Hazardous decomposition products

| <u>Substance</u> | <u>Condition</u> |
|------------------|------------------|
| None known. | |

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from internal hazard assessments.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Skin contact

Skin Irritation: Signs/symptoms may include localised redness, swelling, itching, dryness, cracking, blistering, and pain. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye contact

Severe eye irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

Ingestion

Harmful if swallowed.

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.

Additional Health Effects:

Genotoxicity:

Genotoxicity and Mutagenicity: May interact with genetic material and possibly alter gene expression.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

| Name | Route | Species | Value |
|--|-----------|---------|---|
| Overall product | Dermal | | No data available; calculated ATE >5,000 mg/kg |
| Overall product | Ingestion | | No data available; calculated ATE >300 - =2,000 mg/kg |
| p-(2,3-epoxypropoxy)-N,N-bis(2,3-epoxypropyl)aniline | Dermal | Rabbit | LD50 > 4,000 mg/kg |
| p-(2,3-epoxypropoxy)-N,N-bis(2,3-epoxypropyl)aniline | Ingestion | Rat | LD50 500-5000 mg/kg |
| Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-[2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy]methyl)oxirane | Dermal | Rat | LD50 > 2,000 mg/kg |

3M™ Scotch-Weld™ Epoxy Structural Adhesive DP-760 Off-White : Part B

| | | | |
|---|--------------------------------|--------|---------------------|
| Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-(\{2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy\}methyl)oxirane | Ingestion | Rat | LD50 > 5,000 mg/kg |
| bis-[4-(2,3-epoxypropoxy)phenyl]propane | Dermal | Rat | LD50 > 1,600 mg/kg |
| bis-[4-(2,3-epoxypropoxy)phenyl]propane | Ingestion | Rat | LD50 > 1,000 mg/kg |
| Silica, vitreous | Dermal | Rabbit | LD50 > 5,000 mg/kg |
| Silica, vitreous | Inhalation-Dust/Mist (4 hours) | Rat | LC50 > 0.691 mg/l |
| Silica, vitreous | Ingestion | Rat | LD50 > 5,110 mg/kg |
| Siloxanes and Silicones, di-Me, reaction products with silica | Dermal | Rabbit | LD50 > 5,000 mg/kg |
| Siloxanes and Silicones, di-Me, reaction products with silica | Inhalation-Dust/Mist (4 hours) | Rat | LC50 > 0.691 mg/l |
| Siloxanes and Silicones, di-Me, reaction products with silica | Ingestion | Rat | LD50 > 5,110 mg/kg |
| Titanium dioxide | Dermal | Rabbit | LD50 > 10,000 mg/kg |
| Titanium dioxide | Inhalation-Dust/Mist (4 hours) | Rat | LC50 > 6.82 mg/l |
| Titanium dioxide | Ingestion | Rat | LD50 > 10,000 mg/kg |
| [3-(2,3-epoxypropoxy)propyl]trimethoxysilane | Dermal | Rabbit | LD50 4,000 mg/kg |
| [3-(2,3-epoxypropoxy)propyl]trimethoxysilane | Inhalation-Dust/Mist (4 hours) | Rat | LC50 > 5.3 mg/l |
| [3-(2,3-epoxypropoxy)propyl]trimethoxysilane | Ingestion | Rat | LD50 7,010 mg/kg |

ATE = acute toxicity estimate

Skin Corrosion/Irritation

| Name | Species | Value |
|---|---------|---------------------------|
| p-(2,3-epoxypropoxy)-N,N-bis(2,3-epoxypropyl)aniline | Rabbit | Irritant |
| Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-(\{2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy\}methyl)oxirane | Rabbit | Irritant |
| bis-[4-(2,3-epoxypropoxy)phenyl]propane | Rabbit | Mild irritant |
| Silica, vitreous | Rabbit | No significant irritation |
| Siloxanes and Silicones, di-Me, reaction products with silica | Rabbit | No significant irritation |
| Titanium dioxide | Rabbit | No significant irritation |
| [3-(2,3-epoxypropoxy)propyl]trimethoxysilane | Rabbit | Mild irritant |

Serious Eye Damage/Irritation

| Name | Species | Value |
|---|---------|---------------------------|
| p-(2,3-epoxypropoxy)-N,N-bis(2,3-epoxypropyl)aniline | Rabbit | Severe irritant |
| Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-(\{2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy\}methyl)oxirane | Rabbit | No significant irritation |
| bis-[4-(2,3-epoxypropoxy)phenyl]propane | Rabbit | Moderate irritant |
| Silica, vitreous | Rabbit | No significant irritation |
| Siloxanes and Silicones, di-Me, reaction products with silica | Rabbit | No significant irritation |
| Titanium dioxide | Rabbit | No significant irritation |
| [3-(2,3-epoxypropoxy)propyl]trimethoxysilane | Rabbit | Corrosive |

Skin Sensitisation

| Name | Species | Value |
|---|-------------------------|-------------|
| p-(2,3-epoxypropoxy)-N,N-bis(2,3-epoxypropyl)aniline | Guinea pig | Sensitising |
| Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-(\{2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy\}methyl)oxirane | Multiple animal species | Sensitising |
| bis-[4-(2,3-epoxypropoxy)phenyl]propane | Human | Sensitising |

3M™ Scotch-Weld™ Epoxy Structural Adhesive DP-760 Off-White : Part B

| | | |
|---|------------------|----------------|
| | and animal | |
| Silica, vitreous | Human and animal | Not classified |
| Siloxanes and Silicones, di-Me, reaction products with silica | Human and animal | Not classified |
| Titanium dioxide | Human and animal | Not classified |
| [3-(2,3-epoxypropoxy)propyl]trimethoxysilane | Guinea pig | Not classified |

Respiratory Sensitisation

| Name | Species | Value |
|---|---------|----------------|
| bis-[4-(2,3-epoxypropoxy)phenyl]propane | Human | Not classified |

Germ Cell Mutagenicity

| Name | Route | Value |
|--|----------|--|
| p-(2,3-epoxypropoxy)-N,N-bis(2,3-epoxypropyl)aniline | In Vitro | Some positive data exist, but the data are not sufficient for classification |
| p-(2,3-epoxypropoxy)-N,N-bis(2,3-epoxypropyl)aniline | In vivo | Mutagenic |
| Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-(\{2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy\},methyl)oxirane | In vivo | Not mutagenic |
| Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-(\{2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy\},methyl)oxirane | In Vitro | Some positive data exist, but the data are not sufficient for classification |
| bis-[4-(2,3-epoxypropoxy)phenyl]propane | In vivo | Not mutagenic |
| bis-[4-(2,3-epoxypropoxy)phenyl]propane | In Vitro | Some positive data exist, but the data are not sufficient for classification |
| Silica, vitreous | In Vitro | Not mutagenic |
| Siloxanes and Silicones, di-Me, reaction products with silica | In Vitro | Not mutagenic |
| Titanium dioxide | In Vitro | Not mutagenic |
| Titanium dioxide | In vivo | Not mutagenic |
| [3-(2,3-epoxypropoxy)propyl]trimethoxysilane | In vivo | Not mutagenic |
| [3-(2,3-epoxypropoxy)propyl]trimethoxysilane | In Vitro | Some positive data exist, but the data are not sufficient for classification |

Carcinogenicity

| Name | Route | Species | Value |
|---|----------------|-------------------------|--|
| bis-[4-(2,3-epoxypropoxy)phenyl]propane | Dermal | Mouse | Some positive data exist, but the data are not sufficient for classification |
| Silica, vitreous | Not specified. | Mouse | Some positive data exist, but the data are not sufficient for classification |
| Siloxanes and Silicones, di-Me, reaction products with silica | Not specified. | Mouse | Some positive data exist, but the data are not sufficient for classification |
| Titanium dioxide | Ingestion | Multiple animal species | Not carcinogenic |
| Titanium dioxide | Inhalation | Rat | Carcinogenic. |
| [3-(2,3-epoxypropoxy)propyl]trimethoxysilane | Dermal | Mouse | Not carcinogenic |

Reproductive Toxicity

Reproductive and/or Developmental Effects

| Name | Route | Value | Species | Test result | Exposure Duration |
|---|-----------|--|---------|---------------------|-------------------|
| bis-[4-(2,3-epoxypropoxy)phenyl]propane | Ingestion | Not classified for female reproduction | Rat | NOAEL 750 mg/kg/day | 2 generation |

3M™ Scotch-Weld™ Epoxy Structural Adhesive DP-760 Off-White : Part B

| | | | | | |
|---|------------|--|--------|-----------------------|----------------------|
| bis-[4-(2,3-epoxipropoxy)phenyl]propane | Ingestion | Not classified for male reproduction | Rat | NOAEL 750 mg/kg/day | 2 generation |
| bis-[4-(2,3-epoxipropoxy)phenyl]propane | Dermal | Not classified for development | Rabbit | NOAEL 300 mg/kg/day | during organogenesis |
| bis-[4-(2,3-epoxipropoxy)phenyl]propane | Ingestion | Not classified for development | Rat | NOAEL 750 mg/kg/day | 2 generation |
| Silica, vitreous | Ingestion | Not classified for female reproduction | Rat | NOAEL 509 mg/kg/day | 1 generation |
| Silica, vitreous | Inhalation | Not classified for male reproduction | Rat | NOAEL 497 mg/kg/day | 1 generation |
| Silica, vitreous | Ingestion | Not classified for development | Rat | NOAEL 1,350 mg/kg/day | during organogenesis |
| Siloxanes and Silicones, di-Me, reaction products with silica | Ingestion | Not classified for female reproduction | Rat | NOAEL 509 mg/kg/day | 1 generation |
| Siloxanes and Silicones, di-Me, reaction products with silica | Ingestion | Not classified for male reproduction | Rat | NOAEL 497 mg/kg/day | 1 generation |
| Siloxanes and Silicones, di-Me, reaction products with silica | Ingestion | Not classified for development | Rat | NOAEL 1,350 mg/kg/day | during organogenesis |
| [3-(2,3-epoxypropoxy)propyl]trimethoxysilane | Ingestion | Not classified for female reproduction | Rat | NOAEL 1,000 mg/kg/day | 1 generation |
| [3-(2,3-epoxypropoxy)propyl]trimethoxysilane | Ingestion | Not classified for male reproduction | Rat | NOAEL 1,000 mg/kg/day | 1 generation |
| [3-(2,3-epoxypropoxy)propyl]trimethoxysilane | Ingestion | Not classified for development | Rat | NOAEL 3,000 mg/kg/day | during organogenesis |

Target Organ(s)

Specific Target Organ Toxicity - single exposure

| Name | Route | Target Organ(s) | Value | Species | Test result | Exposure Duration |
|--|------------|------------------------|--|------------------------|---------------------|-------------------|
| Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-(2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy)methyl)oxirane | Inhalation | respiratory irritation | Some positive data exist, but the data are not sufficient for classification | similar health hazards | NOAEL not available | |

Specific Target Organ Toxicity - repeated exposure

| Name | Route | Target Organ(s) | Value | Species | Test result | Exposure Duration |
|--|-----------|---|----------------|---------|-----------------------|-------------------|
| Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-(2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy)methyl)oxirane | Ingestion | heart endocrine system gastrointestinal tract bone, teeth, nails, and/or hair hematopoietic system liver immune system nervous system eyes kidney and/or bladder respiratory system vascular system | Not classified | Rat | NOAEL 250 mg/kg/day | 13 weeks |
| bis-[4-(2,3-epoxipropoxy)phenyl]propane | Dermal | liver | Not classified | Rat | NOAEL 1,000 mg/kg/day | 2 years |
| bis-[4-(2,3-epoxipropoxy)phenyl]propane | Dermal | nervous system | Not classified | Rat | NOAEL 1,000 | 13 weeks |

3M™ Scotch-Weld™ Epoxy Structural Adhesive DP-760 Off-White : Part B

| | | | | | | |
|---|------------|---|--|-------|-----------------------|-----------------------|
| ane | | | | | mg/kg/day | |
| bis-[4-(2,3-epoxypropoxy)phenyl]propane | Ingestion | auditory system heart endocrine system hematopoietic system liver eyes kidney and/or bladder | Not classified | Rat | NOAEL 1,000 mg/kg/day | 28 days |
| Silica, vitreous | Inhalation | respiratory system silicosis | Not classified | Human | NOAEL Not available | occupational exposure |
| Siloxanes and Silicones, di-Me, reaction products with silica | Inhalation | respiratory system silicosis | Not classified | Human | NOAEL Not available | occupational exposure |
| Titanium dioxide | Inhalation | respiratory system | Some positive data exist, but the data are not sufficient for classification | Rat | LOAEL 0.01 mg/l | 2 years |
| Titanium dioxide | Inhalation | pulmonary fibrosis | Not classified | Human | NOAEL Not available | occupational exposure |
| [3-(2,3-epoxypropoxy)propyl]trimethoxysilane | Ingestion | heart endocrine system bone, teeth, nails, and/or hair hematopoietic system liver immune system nervous system kidney and/or bladder respiratory system | Not classified | Rat | NOAEL 1,000 mg/kg/day | 28 days |

Aspiration Hazard

For the component/components, either no data is currently available or the data is not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

11.2. Information on other hazards

This material does not contain any substances that are assessed to be an endocrine disruptor for human health.

SECTION 12: Ecological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

12.1. Toxicity

No product test data available.

| Material | CAS # | Organism | Type | Exposure | Test endpoint | Test result |
|--|-----------|-------------|--------------------|----------|---------------|-------------|
| p-(2,3-epoxypropoxy)-N,N-bis(2,3-epoxypropyl)aniline | 5026-74-4 | Water flea | Analogous Compound | 48 hours | EC50 | 18 mg/l |
| p-(2,3-epoxypropoxy)-N,N-bis(2,3-epoxypropyl)aniline | 5026-74-4 | Bacteria | Experimental | 16 hours | EC50 | >=10 mg/l |
| p-(2,3-epoxypropoxy)-N,N-bis(2,3-epoxypropyl)aniline | 5026-74-4 | Common Carp | Experimental | 96 hours | LC50 | 4.2 mg/l |
| p-(2,3-epoxypropoxy)-N,N-bis(2,3-epoxypropyl)aniline | 5026-74-4 | Green algae | Experimental | 96 hours | ErC50 | 13 mg/l |

3M™ Scotch-Weld™ Epoxy Structural Adhesive DP-760 Off-White : Part B

| | | | | | | |
|---|-----------|------------------|--------------------|----------|-------|-----------|
| p-(2,3-epoxypropoxy)-N,N-bis(2,3-epoxypropyl)aniline | 5026-74-4 | Green algae | Experimental | 96 hours | NOEC | 4.2 mg/l |
| p-(2,3-epoxypropoxy)-N,N-bis(2,3-epoxypropyl)aniline | 5026-74-4 | Water flea | Experimental | 21 days | NOEC | 0.42 mg/l |
| [3-(2,3-epoxypropoxy)propyl]trimethoxysilane | 2530-83-8 | Common Carp | Experimental | 96 hours | LC50 | 55 mg/l |
| [3-(2,3-epoxypropoxy)propyl]trimethoxysilane | 2530-83-8 | Green algae | Experimental | 96 hours | ErC50 | 350 mg/l |
| [3-(2,3-epoxypropoxy)propyl]trimethoxysilane | 2530-83-8 | Invertebrate | Experimental | 48 hours | LC50 | 324 mg/l |
| [3-(2,3-epoxypropoxy)propyl]trimethoxysilane | 2530-83-8 | Green algae | Experimental | 96 hours | NOEC | 130 mg/l |
| [3-(2,3-epoxypropoxy)propyl]trimethoxysilane | 2530-83-8 | Water flea | Experimental | 21 days | NOEC | 100 mg/l |
| [3-(2,3-epoxypropoxy)propyl]trimethoxysilane | 2530-83-8 | Activated sludge | Experimental | 3 hours | EC50 | >100 mg/l |
| Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-(\{2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy\}methyl)oxirane | 701-263-0 | Green algae | Experimental | 72 hours | EC50 | >1.8 mg/l |
| Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-(\{2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy\}methyl)oxirane | 701-263-0 | Rainbow trout | Experimental | 96 hours | LC50 | 0.55 mg/l |
| Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-(\{2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy\}methyl)oxirane | 701-263-0 | Water flea | Experimental | 48 hours | EC50 | 1.6 mg/l |
| Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-(\{2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy\}methyl)oxirane | 701-263-0 | Water flea | Analogous Compound | 21 days | NOEC | 0.3 mg/l |
| Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-(\{2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy\}methyl)oxirane | 701-263-0 | Activated sludge | Analogous Compound | 3 hours | IC50 | >100 mg/l |

3M™ Scotch-Weld™ Epoxy Structural Adhesive DP-760 Off-White : Part B

| | | | | | | |
|---|------------|------------------|---|----------|-------|--------------|
| phenyleneoxymethylene)bis(oxirane) and 2-(\{2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy\}methyl)oxirane | | | | | | |
| bis-[4-(2,3-epoxypropoxy)phenyl]propylene | 1675-54-3 | Activated sludge | Analogous Compound | 3 hours | IC50 | >100 mg/l |
| bis-[4-(2,3-epoxypropoxy)phenyl]propylene | 1675-54-3 | Rainbow trout | Estimated | 96 hours | LC50 | 2 mg/l |
| bis-[4-(2,3-epoxypropoxy)phenyl]propylene | 1675-54-3 | Water flea | Estimated | 48 hours | EC50 | 1.8 mg/l |
| bis-[4-(2,3-epoxypropoxy)phenyl]propylene | 1675-54-3 | Green algae | Experimental | 72 hours | ErC50 | >11 mg/l |
| bis-[4-(2,3-epoxypropoxy)phenyl]propylene | 1675-54-3 | Green algae | Experimental | 72 hours | NOEC | 4.2 mg/l |
| bis-[4-(2,3-epoxypropoxy)phenyl]propylene | 1675-54-3 | Water flea | Experimental | 21 days | NOEC | 0.3 mg/l |
| Silica, vitreous | 60676-86-0 | Common Carp | Experimental | 72 hours | LC50 | >10,000 mg/l |
| Siloxanes and Silicones, di-Me, reaction products with silica | 67762-90-7 | N/A | Data not available or insufficient for classification | N/A | N/A | N/A |
| Titanium dioxide | 13463-67-7 | Activated sludge | Experimental | 3 hours | NOEC | >=1,000 mg/l |
| Titanium dioxide | 13463-67-7 | Diatom | Experimental | 72 hours | EC50 | >10,000 mg/l |
| Titanium dioxide | 13463-67-7 | Fathead minnow | Experimental | 96 hours | LC50 | >100 mg/l |
| Titanium dioxide | 13463-67-7 | Water flea | Experimental | 48 hours | EC50 | >100 mg/l |
| Titanium dioxide | 13463-67-7 | Diatom | Experimental | 72 hours | NOEC | 5,600 mg/l |

12.2. Persistence and degradability

| Material | CAS Nbr | Test type | Duration | Study Type | Test result | Protocol |
|---|-----------|-------------------------------|----------|--------------------------------|-------------------------------------|-----------------------------------|
| p-(2,3-epoxypropoxy)-N,N-bis(2,3-epoxypropyl)aniline | 5026-74-4 | Experimental Biodegradation | 29 days | CO2 evolution | ≤10 %CO2 evolution/THC O2 evolution | OECD 301B - Modified sturm or CO2 |
| p-(2,3-epoxypropoxy)-N,N-bis(2,3-epoxypropyl)aniline | 5026-74-4 | Experimental Hydrolysis | | Hydrolytic half-life (pH 7) | 4.1 days (t 1/2) | OECD 111 Hydrolysis func of pH |
| [3-(2,3-epoxypropoxy)propyl]trimethoxysilane | 2530-83-8 | Experimental Biodegradation | 28 days | Dissolv. Organic Carbon Deplet | 37 %removal of DOC | EC C.4.A. DOC Die-Away Test |
| [3-(2,3-epoxypropoxy)propyl]trimethoxysilane | 2530-83-8 | Experimental Hydrolysis | | Hydrolytic half-life (pH 7) | 6.5 hours (t 1/2) | OECD 111 Hydrolysis func of pH |
| Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-(\{2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy\}methyl)oxirane | 701-263-0 | Experimental Biodegradation | 28 days | BOD | 0 %BOD/ThO D | EC C.4.E Closed Bottle Test |
| Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bi | 701-263-0 | Analogous Compound Hydrolysis | | Hydrolytic half-life (pH 7) | 86 hours (t 1/2) | OECD 111 Hydrolysis func of pH |

| | | | | | | |
|--|------------|------------------------------------|---------|-----------------------------|-------------------------------|-------------------------------------|
| s(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-(\{2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy\}methyl)oxirane | | | | | | |
| bis-[4-(2,3-epoxypropoxy)phenyl]propane | 1675-54-3 | Experimental Biodegradation | 28 days | BOD | 5 %BOD/COD | OECD 301F - Manometric respirometry |
| bis-[4-(2,3-epoxypropoxy)phenyl]propane | 1675-54-3 | Experimental Hydrolysis | | Hydrolytic half-life (pH 7) | 117 hours (t _{1/2}) | OECD 111 Hydrolysis func of pH |
| Silica, vitreous | 60676-86-0 | Data not available or insufficient | N/A | N/A | N/A | N/A |
| Siloxanes and Silicones, di-Me, reaction products with silica | 67762-90-7 | Data not available or insufficient | N/A | N/A | N/A | N/A |
| Titanium dioxide | 13463-67-7 | Data not available or insufficient | N/A | N/A | N/A | N/A |

12.3 : Bioaccumulative potential

| Material | Cas No. | Test type | Duration | Study Type | Test result | Protocol |
|---|------------|---|----------|------------------------|-------------|------------------------------|
| p-(2,3-epoxypropoxy)-N,N-bis(2,3-epoxypropyl)aniline | 5026-74-4 | Modeled Bioconcentration | | Log Kow | 0.87 | Episuite™ |
| [3-(2,3-epoxypropoxy)propyl]trimethoxysilane | 2530-83-8 | Experimental Bioconcentration | | Log Kow | 0.5 | Episuite™ |
| Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-(\{2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy\}methyl)oxirane | 701-263-0 | Experimental Bioconcentration | | Log Kow | 3.6 | OECD 117 log Kow HPLC method |
| bis-[4-(2,3-epoxypropoxy)phenyl]propane | 1675-54-3 | Experimental Bioconcentration | | Log Kow | 3.242 | OECD 117 log Kow HPLC method |
| Silica, vitreous | 60676-86-0 | Data not available or insufficient for classification | N/A | N/A | N/A | N/A |
| Siloxanes and Silicones, di-Me, reaction products with silica | 67762-90-7 | Data not available or insufficient for classification | N/A | N/A | N/A | N/A |
| Titanium dioxide | 13463-67-7 | Experimental BCF - Fish | 42 days | Bioaccumulation factor | 9.6 | |

12.4. Mobility in soil

| Material | Cas No. | Test type | Study Type | Test result | Protocol |
|---|-----------|-------------------------------|------------|-------------|--------------------------------|
| p-(2,3-epoxypropoxy)-N,N-bis(2,3-epoxypropyl)aniline | 5026-74-4 | Experimental Mobility in Soil | Koc | 84 l/kg | OECD 121 Estim. of Koc by HPLC |
| [3-(2,3-epoxypropoxy)propyl]trimethoxysilane | 2530-83-8 | Modeled Mobility in Soil | Koc | 10 l/kg | Episuite™ |
| Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1- | 701-263-0 | Experimental Mobility in Soil | Koc | 4,460 l/kg | OECD 121 Estim. of Koc by HPLC |

| | | | | | |
|---|-----------|--------------------------|-----|----------|-----------|
| phenyleneoxymethylene)]bis(oxirane) and 2-([4-(oxiran-2-ylmethoxy)benzyl]phenoxy)methyl)oxirane | | | | | |
| bis-[4-(2,3-epoxipropoxy)phenyl]propane | 1675-54-3 | Modeled Mobility in Soil | Koc | 450 l/kg | Episuite™ |

12.5. Results of the PBT and vPvB assessment

This material does not contain any substances that are assessed to be a PBT or vPvB

12.6. Endocrine disrupting properties

This material does not contain any substances that are assessed to be an endocrine disruptor for environmental effects

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

EU waste code (product as sold)

08 04 09* Waste adhesives and sealants containing organic solvents or other dangerous substances

SECTION 14: Transportation information

| | Ground Transport (ADR) | Air Transport (IATA) | Marine Transport (IMDG) |
|-------------------------------------|---|---|---|
| 14.1 UN number or ID number | UN3077 | UN3077 | UN3077 |
| 14.2 UN proper shipping name | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.(TRIGYLCIDYL-P-AMINOPHENOL) | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.(TRIGYLCIDYL-P-AMINOPHENOL) | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.(TRIGYLCIDYL-P-AMINOPHENOL) |

| | | | |
|---|--|--|--|
| 14.3 Transport hazard class(es) | 9 | 9 | 9 |
| 14.4 Packing group | III | III | III |
| 14.5 Environmental hazards | Environmentally Hazardous | Not applicable | Marine Pollutant |
| 14.6 Special precautions for user | Please refer to the other sections of the SDS for further information. | Please refer to the other sections of the SDS for further information. | Please refer to the other sections of the SDS for further information. |
| 14.7 Marine Transport in bulk according to IMO instruments | No data available. | No data available. | No data available. |
| Control Temperature | No data available. | No data available. | No data available. |
| Emergency Temperature | No data available. | No data available. | No data available. |
| ADR Classification Code | M7 | Not applicable. | Not applicable. |
| IMDG Segregation Code | Not applicable. | Not applicable. | NONE |

Please contact the address or phone number listed on the first page of the SDS for additional information on the transport/shipment of the material by rail (RID) or inland waterways (ADN).

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Carcinogenicity

| <u>Ingredient</u> | <u>CAS Nbr</u> | <u>Classification</u> | <u>Regulation</u> |
|---|-----------------------|-------------------------------|---|
| bis-[4-(2,3-epoxipropoxy)phenyl]propane | 1675-54-3 | Gr. 3: Not classifiable | International Agency for Research on Cancer |
| Titanium dioxide | 13463-67-7 | Grp. 2B: Possible human carc. | International Agency for Research on Cancer |

Restrictions on the manufacture, placing on the market and use:

The following substance(s) contained in this product is/are subject through Annex XVII of REACH regulation to restrictions on the manufacture, placing on the market and use when present in certain dangerous substances, mixtures and articles. Users of this product are required to comply with the restrictions placed upon it by the aforementioned provision.

| <u>Ingredient</u> | <u>CAS Nbr</u> |
|---|-----------------------|
| bis-[4-(2,3-epoxipropoxy)phenyl]propane | 1675-54-3 |

Restriction status: listed in REACH Annex XVII

Restricted uses: See Annex XVII to Regulation (EC) No 1907/2006 for Conditions of Restriction

Global inventory status

Contact 3M for more information. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

DIRECTIVE 2012/18/EU

Seveso hazard categories, Annex 1, Part 1

| Hazard Categories | Qualifying quantity (tonnes) for the application of | |
|---|---|-------------------------|
| | Lower-tier requirements | Upper-tier requirements |
| E2 Hazardous to the Aquatic environment | 200 | 500 |

Seveso named dangerous substances, Annex 1, Part 2

None

Regulation (EU) No 649/2012

No chemicals listed

15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out for this mixture. Chemical safety assessments for the contained substances may have been carried out by the registrants of the substances in accordance with Regulation (EC) No 1907/2006, as amended.

SECTION 16: Other information

List of relevant H statements

- H302 Harmful if swallowed.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H341 Suspected of causing genetic defects.
- H351i Suspected of causing cancer by inhalation.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.

Revision information:

- Industrial Use of Adhesives: Section 16: Annex information was modified.
- Section 14 Classification Code – Regulation Data information was modified.
- Section 14 Hazard Class + Sub Risk – Regulation Data information was modified.
- Section 14 Hazardous/Not Hazardous for Transportation information was modified.
- Section 14 Other Dangerous Goods – Regulation Data information was modified.
- Section 14 Packing Group – Regulation Data information was modified.
- Section 14 Proper Shipping Name information was modified.
- Section 14 Segregation – Regulation Data information was modified.
- Section 14 UN Number Column data information was modified.
- Section 14: Transportation classification information was deleted.

Annex

| |
|-----------------|
| 1. Title |
|-----------------|

| | |
|---|---|
| Substance identification | bis-[4-(2,3-epoxipropoxy)phenyl]propane; EC No. 216-823-5; CAS Nbr 1675-54-3; |
| Exposure Scenario Name | Formulation |
| Lifecycle Stage | Formulation or re-packing |
| Contributing activities | PROC 09 -Transfer of substance or mixture into small containers (dedicated filling line, including weighing) ERC 02 -Formulation into mixture |
| Processes, tasks and activities covered | Batch manufacture of a chemical substance or formulation (including polymerisation reactions). |
| 2. Operational conditions and risk management measures | |
| Operating Conditions | Physical state: Liquid. General operating conditions: Duration of use: 8 hours/day; Emission days per year: <= 225 days per year; |
| Risk management measures | Under the operational conditions described above the following risk management measures apply: General risk management measures: Human health: Protective Gloves - Chemical resistant. Refer to Section 8 of the SDS for specific glove material.; Environmental: Waste Water treatment - Incineration; |
| Waste management measures | Do not apply industrial sludge to natural soils; Prevent leaks and prevent soil / water pollution caused by leaks; |
| 3. Prediction of exposure | |
| Prediction of exposure | Human and environmental exposures are not expected to exceed the DNELs and PNECs when the identified risk management measures are adopted. |

| | |
|---|---|
| 1. Title | |
| Substance identification | bis-[4-(2,3-epoxipropoxy)phenyl]propane; EC No. 216-823-5; CAS Nbr 1675-54-3; |
| Exposure Scenario Name | Industrial Use of Adhesives |
| Lifecycle Stage | Use at industrial sites |
| Contributing activities | PROC 08a -Transfer of substance or mixture (charging and discharging) at non-dedicated facilities PROC 13 -Treatment of articles by dipping and pouring ERC 05 -Use at industrial site leading to inclusion into/onto article |
| Processes, tasks and activities covered | Application of product with a roller or brush. Application of product with applicator gun. Application with a wipe. Transfers without dedicated controls, including loading, filling, dumping, bagging. |
| 2. Operational conditions and risk management measures | |
| Operating Conditions | Physical state: Liquid. General operating conditions: Duration of use: 8 hours/day; Emission days per year: 220 days/year; Frequency of exposure at workplace [for one worker]: 5 days/week; |
| Risk management measures | Under the operational conditions described above the following risk management measures apply: General risk management measures: Human health: |

| | |
|----------------------------------|---|
| | Protective Gloves - Chemical resistant. Refer to Section 8 of the SDS for specific glove material; Environmental: None needed; |
| Waste management measures | Do not apply industrial sludge to natural soils; Prevent discharge of undissolved substance to or recover from wastewater; |
| 3. Prediction of exposure | |
| Prediction of exposure | Human and environmental exposures are not expected to exceed the DNELs and PNECs when the identified risk management measures are adopted. |

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into the European Union, you are responsible for all regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration.

3M Ireland MSDSs are available at www.3M.com



Safety Data Sheet

Copyright, 2023, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

| | | | |
|------------------------|------------|-------------------------|------------|
| Document group: | 09-0180-1 | Version number: | 26.00 |
| Revision date: | 06/03/2023 | Supersedes date: | 20/12/2022 |

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

3M™ Scotch-Weld™ Epoxy Structural Adhesive DP-760 Off-White : Part A

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Structural adhesive.

1.3. Details of the supplier of the safety data sheet

Address: 3M Ireland Limited, The Iveagh Building, The Park, Carrickmines, Dublin 18.
Telephone: +353 1 280 3555
E Mail: tox.uk@mmm.com
Website: www.3M.com

1.4. Emergency telephone number

Emergency medical information: 8am-10pm (seven days) contact National Poisons Information Centre, Beaumont Hospital, Dublin 9 DOV2NO, Ireland. Telephone Number: +353 (0)1 809 2166

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

CLP REGULATION (EC) No 1272/2008

The health and environmental classifications of this material have been derived using the calculation method, except in cases where test data are available or the physical form impacts classification. Classification(s) based on test data or physical form are noted below, if applicable.

The carcinogenicity classification for titanium dioxide is not applicable based on physical form (material is not a powder).

CLASSIFICATION:

Acute Toxicity, Category 4 - Acute Tox. 4; H302

Acute Toxicity, Category 4 - Acute Tox. 4; H312

Skin Corrosion/Irritation, Category 1B - Skin Corr. 1B; H314

Serious Eye Damage/Eye Irritation, Category 1 - Eye Dam. 1; H318

Skin Sensitization, Category 1 - Skin Sens. 1; H317

Hazardous to the Aquatic Environment (Chronic), Category 2 - Aquatic Chronic 2; H411

For full text of H phrases, see Section 16.

2.2. Label elements

CLP REGULATION (EC) No 1272/2008

SIGNAL WORD

DANGER.

Symbols

GHS05 (Corrosion) |GHS07 (Exclamation mark) |GHS09 (Environment) |

Pictograms



Ingredients:

| Ingredient | CAS Nbr | EC No. | % by Wt |
|--|------------|-----------|---------|
| Amines, polyethylenepoly-, triethylenetetramine fraction | 90640-67-8 | 292-588-2 | 40 - 50 |

HAZARD STATEMENTS:

| | |
|-------------|--|
| H302 + H312 | Harmful if swallowed or in contact with skin. |
| H314 | Causes severe skin burns and eye damage. |
| H317 | May cause an allergic skin reaction. |
| H411 | Toxic to aquatic life with long lasting effects. |

PRECAUTIONARY STATEMENTS

Prevention:

| | |
|-------|---|
| P260F | Do not breathe fumes. |
| P273 | Avoid release to the environment. |
| P280D | Wear protective gloves, protective clothing, and eye/face protection. |

Response:

| | |
|--------------------|--|
| P303 + P361 + P353 | IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. |
| P305 + P351 + P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| P310 | Immediately call a POISON CENTRE or doctor/physician. |

For containers not exceeding 125 ml the following Hazard and Precautionary statements may be used:

<=125 ml Hazard statements

| | |
|------|--|
| H314 | Causes severe skin burns and eye damage. |
| H317 | May cause an allergic skin reaction. |

<=125 ml Precautionary statements

Prevention:

| | |
|-------|---|
| P260F | Do not breathe fumes. |
| P280D | Wear protective gloves, protective clothing, and eye/face protection. |

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
 P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P310 Immediately call a POISON CENTRE or doctor/physician.

SUPPLEMENTAL INFORMATION:

Supplemental Hazard Statements:

EUH212 Warning! Hazardous respirable dust may be formed when used. Do not breathe dust.

50% of the mixture consists of components of unknown acute oral toxicity.
 50% of the mixture consists of components of unknown acute dermal toxicity.

Contains 52% of components with unknown hazards to the aquatic environment.

2.3. Other hazards

Persons previously sensitised to amines may develop a cross-sensitisation reaction to certain other amines.
 This material does not contain any substances that are assessed to be a PBT or vPvB

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

| Ingredient | Identifier(s) | % | Classification according to Regulation (EC) No. 1272/2008 [CLP] |
|---|--|---------|--|
| Amine terminated adduct | None | 40 - 50 | Substance not classified as hazardous |
| Amines, polyethylenepoly-, triethylenetetramine fraction | (CAS-No.) 90640-67-8 (EC-No.) 292-588-2 | 40 - 50 | Aquatic Chronic 3, H412 Acute Tox. 4, H312 Acute Tox. 4, H302 Skin Corr. 1B, H314 Skin Sens. 1, H317 |
| Reaction mass of 12-hydroxy-N-[2-[(1-oxodecyl)amino]alkyl]octadecanamide, 12-hydroxy-N-[2-[(1-oxooctyl)amino]alkyl]octadecanamide and N,N'-1,2-alkandiyldis[12-hydroxyoctadecanamide] | (EC-No.) ELINCS 484-050-2 (REACH-No.) 01-0000020228-74 | < 1.5 | Aquatic Acute 1, H400,M=10 Aquatic Chronic 1, H410,M=10 |
| Octadecanoic acid, 12-hydroxy-, reaction products with decanoic acid and ethylenediamine | (EC-No.) 907-495-0 | < 1.5 | Substance not classified as hazardous |
| Oxide glass chemicals | (CAS-No.) 65997-17-3 (EC-No.) 266-046-0 | 5 - 10 | Substance with a national occupational exposure limit |
| Titanium dioxide | (CAS-No.) 13463-67-7 (EC-No.) 236-675-5 (REACH-No.) 01-2119489379-17 | 1 - 3 | Carc. 2, H351 (inhalation) |

| | | | |
|---|----------------------|-------|---|
| Siloxanes and Silicones, di-Me, reaction products with silica | (CAS-No.) 67762-90-7 | 1 - 3 | Substance with a national occupational exposure limit |
|---|----------------------|-------|---|

Any entry in the Identifier(s) column that begins with the numbers 6, 7, 8, or 9 are a Provisional List Number provided by ECHA pending publication of the official EC Inventory Number for the substance.
Please see section 16 for the full text of any H statements referred to in this section

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Immediately flush with large amounts of water for at least 15 minutes. Remove contaminated clothing. Get immediate medical attention. Wash clothing before reuse.

Eye contact

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

If swallowed

Rinse mouth. Do not induce vomiting. Get immediate medical attention.

4.2. Most important symptoms and effects, both acute and delayed

The most important symptoms and effects based on the CLP classification include:

Skin burns (localized redness, swelling, itching, intense pain, blistering, and tissue destruction). Allergic skin reaction (redness, swelling, blistering, and itching). Harmful in contact with skin. Serious damage to the eyes (corneal cloudiness, severe pain, tearing, ulcerations, and significantly impaired or loss of vision). Harmful if swallowed.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

In case of fire: Use a carbon dioxide or dry chemical extinguisher to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

Substance

Aldehydes.
Amine compounds.
Carbon monoxide
Carbon dioxide.
Hydrogen Chloride
Oxides of nitrogen.

Condition

During combustion.
During combustion.
During combustion.
During combustion.
During combustion.
During combustion.

5.3. Advice for fire-fighters

When fire fighting conditions are severe and total thermal decomposition of the product is possible, wear full protective

clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, tunic and trousers (leggings), bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible.

6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

SECTION 7: Handling and storage

7.1. Precautions for safe handling

For industrial/occupational use only. Not for consumer sale or use. Do not use in a confined area with minimal air exchange. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage including any incompatibilities

Keep container tightly closed to prevent contamination with water or air. If contamination is suspected, do not reseal container. Store away from heat. Store away from acids. Store away from strong bases.

7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

| Ingredient | CAS Nbr | Agency | Limit type | Additional comments |
|---|----------------|-------------------------|---|----------------------------|
| Titanium dioxide | 13463-67-7 | Ireland OELs | TWA(Total inhalable dust)(8 hours):10 mg/m ³ ;TWA(as respirable dust)(8 hours):4 mg/m ³ | |
| Mineral wool, with the exception of those specified elsewhere in this Annex | 65997-17-3 | Ireland OELs | TWA(8 hours):5 mg/m ³ (2 fiber/cc) | |
| Oxide glass chemicals | 65997-17-3 | Manufacturer determined | TWA(as non-fibrous, respirable)(8 hours):3 mg/m ³ ;TWA(as non-fibrous, inhalable fraction)(8 hours):10 | |

| | | | |
|-----------------|------------|--------------|--|
| Silicon dioxide | 67762-90-7 | Ireland OELs | mg/m3 TWA(Total inhalable dust)(8 hours):6 mg/m3;TWA(as respirable dust)(8 hours):2.4 mg/m3 |
|-----------------|------------|--------------|--|

Ireland OELs : Ireland. OELs
TWA: Time-Weighted-Average
STEL: Short Term Exposure Limit
CEIL: Ceiling

Biological limit values

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

Recommended monitoring procedures:Information on recommended monitoring procedures can be obtained from Indust. Inspect./Ministry (IE)

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Full face shield.

Indirect vented goggles.

Applicable Norms/Standards

Use eye/face protection conforming to EN 166

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended:

| Material | Thickness (mm) | Breakthrough Time |
|-----------------|----------------|-------------------|
| Butyl rubber. | 0.5 | =>8 hours |
| Fluoroelastomer | 0.4 | =>8 hours |
| Neoprene. | 0.5 | =>8 hours |

The glove data presented are based on the substance driving dermal toxicity and the conditions present at the time of testing. Breakthrough time may be altered when the glove is subjected to use conditions that place additional stress on the glove.

Applicable Norms/Standards

Use gloves tested to EN 374

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron – Butyl rubber Neoprene apron.

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

Applicable Norms/Standards

Use a respirator conforming to EN 140 or EN 136: filter types A & P

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|--|--|
| Physical state | Solid. |
| Specific Physical Form: | Paste |
| Colour | Off-White |
| Odor | Amine |
| Odour threshold | <i>No data available.</i> |
| Melting point/freezing point | <i>Not applicable.</i> |
| Boiling point/boiling range | <i>Not applicable.</i> |
| Flammability (solid, gas) | Not classified |
| Flammable Limits(LEL) | <i>No data available.</i> |
| Flammable Limits(UEL) | <i>No data available.</i> |
| Flash point | ≥ 100 °C [<i>Test Method: Closed Cup</i>] |
| Autoignition temperature | <i>Not applicable.</i> |
| Decomposition temperature | <i>No data available.</i> |
| pH | <i>substance/mixture is non-soluble (in water)</i> |
| Kinematic Viscosity | <i>No data available.</i> |
| Water solubility | <i>No data available.</i> |
| Solubility- non-water | <i>No data available.</i> |
| Partition coefficient: n-octanol/water | <i>No data available.</i> |
| Vapour pressure | <i>Not applicable.</i> |
| Density | 0.79 - 0.85 g/ml |
| Relative density | 0.79 - 0.85 [<i>Ref Std: WATER=1</i>] |
| Relative Vapour Density | <i>Not applicable.</i> |

9.2. Other information

9.2.2 Other safety characteristics

| | |
|-------------------------------|---------------------------|
| EU Volatile Organic Compounds | <i>No data available.</i> |
| Evaporation rate | <i>No data available.</i> |
| Molecular weight | <i>No data available.</i> |
| Percent volatile | 1 % weight |

SECTION 10: Stability and reactivity

10.1 Reactivity

This material is considered to be non reactive under normal use conditions

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

Heat.

10.5 Incompatible materials

Strong bases.

Water

10.6 Hazardous decomposition products

| <u>Substance</u> | <u>Condition</u> |
|------------------|------------------|
| None known. | |

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from internal hazard assessments.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Skin contact

Harmful in contact with skin. Corrosive (skin burns): Signs/symptoms may include localised redness, swelling, itching, intense pain, blistering, ulceration, and tissue destruction. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching. May cause additional health effects (see below).

Eye contact

Corrosive (eye burns): Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision.

Ingestion

Harmful if swallowed.

Gastrointestinal corrosion: Signs/symptoms may include severe mouth, throat and abdominal pain, nausea, vomiting, and diarrhea; blood in the faeces and/or vomitus may also be seen. May cause additional health effects (see below).

Additional information:

Persons previously sensitised to amines may develop a cross-sensitisation reaction to certain other amines.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

| Name | Route | Species | Value |
|---|--------------------------------|---------|---|
| Overall product | Dermal | | No data available; calculated ATE >1,000 - =2,000 mg/kg |
| Overall product | Ingestion | | No data available; calculated ATE >300 - =2,000 mg/kg |
| Amines, polyethylenepoly-, triethylenetetramine fraction | Dermal | Rabbit | LD50 1,465 mg/kg |
| Amines, polyethylenepoly-, triethylenetetramine fraction | Ingestion | Rat | LD50 1,591 mg/kg |
| Oxide glass chemicals | Dermal | | LD50 estimated to be > 5,000 mg/kg |
| Oxide glass chemicals | Ingestion | | LD50 estimated to be 2,000 - 5,000 mg/kg |
| Siloxanes and Silicones, di-Me, reaction products with silica | Dermal | Rabbit | LD50 > 5,000 mg/kg |
| Titanium dioxide | Dermal | Rabbit | LD50 > 10,000 mg/kg |
| Siloxanes and Silicones, di-Me, reaction products with silica | Inhalation-Dust/Mist (4 hours) | Rat | LC50 > 0.691 mg/l |
| Siloxanes and Silicones, di-Me, reaction products with silica | Ingestion | Rat | LD50 > 5,110 mg/kg |
| Titanium dioxide | Inhalation-Dust/Mist (4 hours) | Rat | LC50 > 6.82 mg/l |
| Titanium dioxide | Ingestion | Rat | LD50 > 10,000 mg/kg |
| Octadecanoic acid, 12-hydroxy-, reaction products with decanoic acid and ethylenediamine | Dermal | Rat | LD50 > 2,000 mg/kg |
| Octadecanoic acid, 12-hydroxy-, reaction products with decanoic acid and ethylenediamine | Inhalation-Dust/Mist (4 hours) | Rat | LC50 > 5.1 mg/l |
| Octadecanoic acid, 12-hydroxy-, reaction products with decanoic acid and ethylenediamine | Ingestion | Rat | LD50 > 2,000 mg/kg |
| Reaction mass of 12-hydroxy-N-[2-[(1-oxodecyl)amino]alkyl]octadecanamide, 12-hydroxy-N-[2-[(1-oxooctyl)amino]alkyl]octadecanamide and N,N'-1,2-alkandiylbis[12-hydroxyoctadecanamide] | Dermal | Rat | LD50 > 2,000 |
| Reaction mass of 12-hydroxy-N-[2-[(1-oxodecyl)amino]alkyl]octadecanamide, 12-hydroxy-N-[2-[(1-oxooctyl)amino]alkyl]octadecanamide and N,N'-1,2-alkandiylbis[12-hydroxyoctadecanamide] | Inhalation-Dust/Mist (4 hours) | Rat | LC50 > 6.3 |
| Reaction mass of 12-hydroxy-N-[2-[(1-oxodecyl)amino]alkyl]octadecanamide, 12-hydroxy-N-[2-[(1-oxooctyl)amino]alkyl]octadecanamide and N,N'-1,2-alkandiylbis[12-hydroxyoctadecanamide] | Ingestion | Rat | LD50 > 2,000 |

ATE = acute toxicity estimate

Skin Corrosion/Irritation

| Name | Species | Value |
|---|------------------------|---------------------------|
| Amines, polyethylenepoly-, triethylenetetramine fraction | Rabbit | Corrosive |
| Oxide glass chemicals | Professional judgement | No significant irritation |
| Siloxanes and Silicones, di-Me, reaction products with silica | Rabbit | No significant irritation |
| Titanium dioxide | Rabbit | No significant irritation |
| Octadecanoic acid, 12-hydroxy-, reaction products with decanoic acid and ethylenediamine | Rabbit | No significant irritation |
| Reaction mass of 12-hydroxy-N-[2-[(1-oxodecyl)amino]alkyl]octadecanamide, 12-hydroxy-N-[2-[(1-oxooctyl)amino]alkyl]octadecanamide and N,N'-1,2-alkandiylbis[12-hydroxyoctadecanamide] | Rabbit | No significant irritation |

Serious Eye Damage/Irritation

| Name | Species | Value |
|--|------------------------|---------------------------|
| Amines, polyethylenepoly-, triethylenetetramine fraction | Rabbit | Corrosive |
| Oxide glass chemicals | Professional judgement | No significant irritation |

3M™ Scotch-Weld™ Epoxy Structural Adhesive DP-760 Off-White : Part A

| | t | |
|--|--------|---------------------------|
| Siloxanes and Silicones, di-Me, reaction products with silica | Rabbit | No significant irritation |
| Titanium dioxide | Rabbit | No significant irritation |
| Octadecanoic acid, 12-hydroxy-, reaction products with decanoic acid and ethylenediamine | Rabbit | No significant irritation |
| Reaction mass of 12-hydroxy-N-[2-[(1-oxodecyl)amino]alkyl]octadecanamide, 12-hydroxy-N-[2-[(1-oxooctyl)amino]alkyl]octadecanamide and N,N'-1,2-alkandylbis[12-hydroxyoctadecanamide] | Rabbit | Mild irritant |

Skin Sensitisation

| Name | Species | Value |
|--|------------------|----------------|
| Amines, polyethylenepoly-, triethylenetetramine fraction | Guinea pig | Sensitising |
| Siloxanes and Silicones, di-Me, reaction products with silica | Human and animal | Not classified |
| Titanium dioxide | Human and animal | Not classified |
| Octadecanoic acid, 12-hydroxy-, reaction products with decanoic acid and ethylenediamine | Mouse | Not classified |
| Reaction mass of 12-hydroxy-N-[2-[(1-oxodecyl)amino]alkyl]octadecanamide, 12-hydroxy-N-[2-[(1-oxooctyl)amino]alkyl]octadecanamide and N,N'-1,2-alkandylbis[12-hydroxyoctadecanamide] | Mouse | Not classified |

Respiratory Sensitisation

For the component/components, either no data is currently available or the data is not sufficient for classification.

Germ Cell Mutagenicity

| Name | Route | Value |
|--|----------|--|
| Amines, polyethylenepoly-, triethylenetetramine fraction | In vivo | Not mutagenic |
| Amines, polyethylenepoly-, triethylenetetramine fraction | In Vitro | Some positive data exist, but the data are not sufficient for classification |
| Oxide glass chemicals | In Vitro | Some positive data exist, but the data are not sufficient for classification |
| Siloxanes and Silicones, di-Me, reaction products with silica | In Vitro | Not mutagenic |
| Titanium dioxide | In Vitro | Not mutagenic |
| Titanium dioxide | In vivo | Not mutagenic |
| Octadecanoic acid, 12-hydroxy-, reaction products with decanoic acid and ethylenediamine | In Vitro | Not mutagenic |
| Reaction mass of 12-hydroxy-N-[2-[(1-oxodecyl)amino]alkyl]octadecanamide, 12-hydroxy-N-[2-[(1-oxooctyl)amino]alkyl]octadecanamide and N,N'-1,2-alkandylbis[12-hydroxyoctadecanamide] | In Vitro | Not mutagenic |

Carcinogenicity

| Name | Route | Species | Value |
|---|----------------|-------------------------|--|
| Amines, polyethylenepoly-, triethylenetetramine fraction | Dermal | Mouse | Not carcinogenic |
| Oxide glass chemicals | Inhalation | Multiple animal species | Some positive data exist, but the data are not sufficient for classification |
| Siloxanes and Silicones, di-Me, reaction products with silica | Not specified. | Mouse | Some positive data exist, but the data are not sufficient for classification |
| Titanium dioxide | Ingestion | Multiple animal species | Not carcinogenic |
| Titanium dioxide | Inhalation | Rat | Carcinogenic. |

Reproductive Toxicity
Reproductive and/or Developmental Effects

| Name | Route | Value | Species | Test result | Exposure |
|------|-------|-------|---------|-------------|----------|
|------|-------|-------|---------|-------------|----------|

3M™ Scotch-Weld™ Epoxy Structural Adhesive DP-760 Off-White : Part A

| | | | | | Duration |
|---|-----------|--|-----|-----------------------|----------------------------|
| Amines, polyethylenepoly-, triethylenetetramine fraction | Ingestion | Not classified for development | Rat | NOAEL 750 mg/kg/day | during organogenesis |
| Siloxanes and Silicones, di-Me, reaction products with silica | Ingestion | Not classified for female reproduction | Rat | NOAEL 509 mg/kg/day | 1 generation |
| Siloxanes and Silicones, di-Me, reaction products with silica | Ingestion | Not classified for male reproduction | Rat | NOAEL 497 mg/kg/day | 1 generation |
| Siloxanes and Silicones, di-Me, reaction products with silica | Ingestion | Not classified for development | Rat | NOAEL 1,350 mg/kg/day | during organogenesis |
| Reaction mass of 12-hydroxy-N-[2-[(1-oxodecyl)amino]alkyl]octadecanamide, 12-hydroxy-N-[2-[(1-oxooctyl)amino]alkyl]octadecanamide and N,N'-1,2-alkandiylbis[12-hydroxyoctadecanamide] | Ingestion | Not classified for female reproduction | Rat | NOAEL 1,000 mg/kg/day | prematuring into lactation |
| Reaction mass of 12-hydroxy-N-[2-[(1-oxodecyl)amino]alkyl]octadecanamide, 12-hydroxy-N-[2-[(1-oxooctyl)amino]alkyl]octadecanamide and N,N'-1,2-alkandiylbis[12-hydroxyoctadecanamide] | Ingestion | Not classified for male reproduction | Rat | NOAEL 1,000 mg/kg/day | 28 days |
| Reaction mass of 12-hydroxy-N-[2-[(1-oxodecyl)amino]alkyl]octadecanamide, 12-hydroxy-N-[2-[(1-oxooctyl)amino]alkyl]octadecanamide and N,N'-1,2-alkandiylbis[12-hydroxyoctadecanamide] | Ingestion | Not classified for development | Rat | NOAEL 1,000 mg/kg/day | prematuring into lactation |

Target Organ(s)

Specific Target Organ Toxicity - single exposure

| Name | Route | Target Organ(s) | Value | Species | Test result | Exposure Duration |
|--|------------|------------------------|--|------------------------|---------------------|-------------------|
| Amines, polyethylenepoly-, triethylenetetramine fraction | Inhalation | respiratory irritation | Some positive data exist, but the data are not sufficient for classification | similar health hazards | NOAEL Not available | |

Specific Target Organ Toxicity - repeated exposure

| Name | Route | Target Organ(s) | Value | Species | Test result | Exposure Duration |
|---|------------|--------------------------------|--|---------|---------------------|-----------------------|
| Oxide glass chemicals | Inhalation | respiratory system | Not classified | Human | NOAEL not available | occupational exposure |
| Siloxanes and Silicones, di-Me, reaction products with silica | Inhalation | respiratory system silicosis | Not classified | Human | NOAEL Not available | occupational exposure |
| Titanium dioxide | Inhalation | respiratory system | Some positive data exist, but the data are not sufficient for classification | Rat | LOAEL 0.01 mg/l | 2 years |
| Titanium dioxide | Inhalation | pulmonary fibrosis | Not classified | Human | NOAEL Not available | occupational exposure |

Aspiration Hazard

For the component/components, either no data is currently available or the data is not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

11.2. Information on other hazards

This material does not contain any substances that are assessed to be an endocrine disruptor for human health.

SECTION 12: Ecological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

12.1. Toxicity

No product test data available.

| Material | CAS # | Organism | Type | Exposure | Test endpoint | Test result |
|--|------------|------------------|--------------|----------|---------------|-------------------------|
| Amines, polyethylenepoly-, triethylenetetramine fraction | 90640-67-8 | Fathead minnow | Experimental | 96 hours | LC50 | 330 mg/l |
| Amines, polyethylenepoly-, triethylenetetramine fraction | 90640-67-8 | Green algae | Experimental | 72 hours | ErC50 | 20 mg/l |
| Amines, polyethylenepoly-, triethylenetetramine fraction | 90640-67-8 | Water flea | Experimental | 48 hours | EC50 | 31.1 mg/l |
| Amines, polyethylenepoly-, triethylenetetramine fraction | 90640-67-8 | Green algae | Experimental | 72 hours | ErC10 | 1.34 mg/l |
| Amines, polyethylenepoly-, triethylenetetramine fraction | 90640-67-8 | Water flea | Experimental | 21 days | EC10 | 1.9 mg/l |
| Amines, polyethylenepoly-, triethylenetetramine fraction | 90640-67-8 | Bacteria | Experimental | 2 hours | EC50 | 15.7 mg/l |
| Amines, polyethylenepoly-, triethylenetetramine fraction | 90640-67-8 | Redworm | Experimental | 56 days | EC10 | 31.1 mg/kg (Dry Weight) |
| Amines, polyethylenepoly-, triethylenetetramine fraction | 90640-67-8 | Soil microbes | Experimental | 28 days | EC50 | >100 mg/kg (Dry Weight) |
| Octadecanoic acid, 12-hydroxy-, reaction products with decanoic acid and ethylenediamine | 907-495-0 | Activated sludge | Experimental | 3 hours | EC50 | >1,000 mg/l |
| Octadecanoic acid, 12-hydroxy-, reaction products with decanoic acid and ethylenediamine | 907-495-0 | Green algae | Experimental | 72 hours | ErC50 | 43.2 mg/l |
| Octadecanoic acid, 12-hydroxy-, reaction products with decanoic acid and ethylenediamine | 907-495-0 | Rainbow trout | Experimental | 96 hours | LC50 | >=100 mg/l |
| Octadecanoic acid, 12-hydroxy-, reaction products with decanoic acid and ethylenediamine | 907-495-0 | Water flea | Experimental | 48 hours | EC50 | 94.9 mg/l |
| Octadecanoic acid, 12-hydroxy-, reaction products with decanoic | 907-495-0 | Green algae | Experimental | 72 hours | NOEC | 20.7 mg/l |

3M™ Scotch-Weld™ Epoxy Structural Adhesive DP-760 Off-White : Part A

| | | | | | | |
|--|-----------|------------------|----------------------|----------|--------------------------------|------------|
| acid and ethylenediamine | | | | | | |
| Octadecanoic acid, 12-hydroxy-, reaction products with decanoic acid and ethylenediamine | 907-495-0 | Water flea | Experimental | 21 days | NOEL | >=20 mg/l |
| Reaction mass of 12-hydroxy-N-[2-[(1-oxodecyl)amino]alkyl]octadecanamide, 12-hydroxy-N-[2-[(1-oxooctyl)amino]alkyl]octadecanamide and N,N'-1,2-alkandiylobis[12-hydroxyoctadecanamide] | 484-050-2 | Water flea | Endpoint not reached | 48 hours | EC50 | >100 mg/l |
| Reaction mass of 12-hydroxy-N-[2-[(1-oxodecyl)amino]alkyl]octadecanamide, 12-hydroxy-N-[2-[(1-oxooctyl)amino]alkyl]octadecanamide and N,N'-1,2-alkandiylobis[12-hydroxyoctadecanamide] | 484-050-2 | Activated sludge | Experimental | 3 hours | EC50 | >100 mg/l |
| Reaction mass of 12-hydroxy-N-[2-[(1-oxodecyl)amino]alkyl]octadecanamide, 12-hydroxy-N-[2-[(1-oxooctyl)amino]alkyl]octadecanamide and N,N'-1,2-alkandiylobis[12-hydroxyoctadecanamide] | 484-050-2 | Common Carp | Experimental | 96 hours | No tox obs at lmt of water sol | >100 mg/l |
| Reaction mass of 12-hydroxy-N-[2-[(1-oxodecyl)amino]alkyl]octadecanamide, 12-hydroxy-N-[2-[(1-oxooctyl)amino]alkyl]octadecanamide and N,N'-1,2-alkandiylobis[12-hydroxyoctadecanamide] | 484-050-2 | Green algae | Experimental | 72 hours | EC50 | 0.025 mg/l |
| Reaction mass of 12-hydroxy-N-[2-[(1-oxodecyl)amino]alkyl]octadecanamide, 12-hydroxy-N-[2-[(1-oxooctyl)amino]alkyl]octadecanamide and N,N'-1,2-alkandiylobis[12-hydroxyoctadecanamide] | 484-050-2 | Water flea | Endpoint not reached | 21 days | NOEC | >100 mg/l |
| Reaction mass of 12-hydroxy-N-[2-[(1-oxodecyl)amino]alkyl]octadecanamide, 12-hydroxy-N-[2-[(1-oxooctyl)amino]alkyl]octadecanamide and | 484-050-2 | Green algae | Experimental | 72 hours | NOEC | 0.007 mg/l |

3M™ Scotch-Weld™ Epoxy Structural Adhesive DP-760 Off-White : Part A

| | | | | | | |
|---|------------|------------------|---|----------|------|--------------|
| N,N'-1,2-alkandylbis[12-hydroxyoctadecanamide] | | | | | | |
| Oxide glass chemicals | 65997-17-3 | Green algae | Experimental | 72 hours | EC50 | >1,000 mg/l |
| Oxide glass chemicals | 65997-17-3 | Water flea | Experimental | 72 hours | EC50 | >1,000 mg/l |
| Oxide glass chemicals | 65997-17-3 | Zebra Fish | Experimental | 96 hours | LC50 | >1,000 mg/l |
| Oxide glass chemicals | 65997-17-3 | Green algae | Experimental | 72 hours | NOEC | >=1,000 mg/l |
| Siloxanes and Silicones, di-Me, reaction products with silica | 67762-90-7 | N/A | Data not available or insufficient for classification | N/A | N/A | N/A |
| Titanium dioxide | 13463-67-7 | Activated sludge | Experimental | 3 hours | NOEC | >=1,000 mg/l |
| Titanium dioxide | 13463-67-7 | Diatom | Experimental | 72 hours | EC50 | >10,000 mg/l |
| Titanium dioxide | 13463-67-7 | Fathead minnow | Experimental | 96 hours | LC50 | >100 mg/l |
| Titanium dioxide | 13463-67-7 | Water flea | Experimental | 48 hours | EC50 | >100 mg/l |
| Titanium dioxide | 13463-67-7 | Diatom | Experimental | 72 hours | NOEC | 5,600 mg/l |

12.2. Persistence and degradability

| Material | CAS Nbr | Test type | Duration | Study Type | Test result | Protocol |
|--|------------|--|----------|--------------------------------|----------------------------------|-----------------------------------|
| Amines, polyethylenepoly-, triethylenetetramine fraction | 90640-67-8 | Experimental Aquatic Inherent Biodegrad. | 84 days | Dissolv. Organic Carbon Deplet | 20 %removal of DOC | OECD 302A - Modified SCAS Test |
| Octadecanoic acid, 12-hydroxy-, reaction products with decanoic acid and ethylenediamine | 907-495-0 | Experimental Biodegradation | 28 days | BOD | 14 %BOD/ThOD | OECD 301D - Closed bottle test |
| Reaction mass of 12-hydroxy-N-[2-[(1-oxodecyl)amino]alkyl]octadecanamide, 12-hydroxy-N-[2-[(1-oxooctyl)amino]alkyl]octadecanamide and N,N'-1,2-alkandylbis[12-hydroxyoctadecanamide] | 484-050-2 | Experimental Biodegradation | 28 days | CO2 evolution | 7 %CO2 evolution/THCO2 evolution | OECD 301B - Modified sturm or CO2 |
| Oxide glass chemicals | 65997-17-3 | Data not available or insufficient | N/A | N/A | N/A | N/A |
| Siloxanes and Silicones, di-Me, reaction products with silica | 67762-90-7 | Data not available or insufficient | N/A | N/A | N/A | N/A |
| Titanium dioxide | 13463-67-7 | Data not available or insufficient | N/A | N/A | N/A | N/A |

12.3 : Bioaccumulative potential

| Material | Cas No. | Test type | Duration | Study Type | Test result | Protocol |
|--|------------|---|----------|------------|-------------|----------|
| Amines, polyethylenepoly-, triethylenetetramine fraction | 90640-67-8 | Experimental Bioconcentration | | Log Kow | <-2.0 | |
| Octadecanoic acid, 12-hydroxy-, reaction products with decanoic acid and ethylenediamine | 907-495-0 | Data not available or insufficient for classification | N/A | N/A | N/A | N/A |
| Reaction mass of 12-hydroxy-N-[2-[(1- | 484-050-2 | Data not available or insufficient for | N/A | N/A | N/A | N/A |

| | | | | | | |
|--|------------|---|---------|------------------------|-----|-----|
| oxodecyl)amino]alkyl]octadecanamide, 12-hydroxy-N-[2-[(1-oxooctyl)amino]alkyl]octadecanamide and N,N'-1,2-alkandiylbis[12-hydroxyoctadecanamide] | | classification | | | | |
| Oxide glass chemicals | 65997-17-3 | Data not available or insufficient for classification | N/A | N/A | N/A | N/A |
| Siloxanes and Silicones, di-Me, reaction products with silica | 67762-90-7 | Data not available or insufficient for classification | N/A | N/A | N/A | N/A |
| Titanium dioxide | 13463-67-7 | Experimental BCF - Fish | 42 days | Bioaccumulation factor | 9.6 | |

12.4. Mobility in soil

| Material | Cas No. | Test type | Study Type | Test result | Protocol |
|---|------------|-------------------------------|------------|----------------|--------------------------------|
| Amines, polyethylenepoly-, triethylenetetramine fraction | 90640-67-8 | Experimental Mobility in Soil | Koc | 1600-5000 l/kg | |
| Reaction mass of 12-hydroxy-N-[2-[(1-oxodecyl)amino]alkyl]octadecanamide, 12-hydroxy-N-[2-[(1-oxooctyl)amino]alkyl]octadecanamide and N,N'-1,2-alkandiylbis[12-hydroxyoctadecanamide] | 484-050-2 | Experimental Mobility in Soil | Koc | >430000 l/kg | OECD 121 Estim. of Koc by HPLC |

12.5. Results of the PBT and vPvB assessment

This material does not contain any substances that are assessed to be a PBT or vPvB

12.6. Endocrine disrupting properties

This material does not contain any substances that are assessed to be an endocrine disruptor for environmental effects

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Combustion products will include halogen acid (HCl/HF/HBr). Facility must be capable of handling halogenated materials. If no other disposal options are available, waste product that has been completely cured or polymerised may be placed in a landfill properly designed for industrial waste. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC

and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

EU waste code (product as sold)

- 08 04 09* Waste adhesives and sealants containing organic solvents or other dangerous substances
- 20 01 27* Paint, inks, adhesives and resins containing dangerous substances

SECTION 14: Transportation information

| | Ground Transport (ADR) | Air Transport (IATA) | Marine Transport (IMDG) |
|---|--|--|--|
| 14.1 UN number or ID number | UN3259 | UN3259 | UN3259 |
| 14.2 UN proper shipping name | AMINES, SOLID, CORROSIVE, N.O.S.(TRIETHYLENETETRAMINE) | AMINES, SOLID, CORROSIVE, N.O.S.(TRIETHYLENETETRAMINE) | AMINES, SOLID, CORROSIVE, N.O.S.(TRIETHYLENETETRAMINE; EPOXY RESIN) |
| 14.3 Transport hazard class(es) | 8 | 8 | 8 |
| 14.4 Packing group | II | II | II |
| 14.5 Environmental hazards | Environmentally Hazardous | Not applicable | Marine Pollutant |
| 14.6 Special precautions for user | Please refer to the other sections of the SDS for further information. | Please refer to the other sections of the SDS for further information. | Please refer to the other sections of the SDS for further information. |
| 14.7 Marine Transport in bulk according to IMO instruments | No data available. | No data available. | No data available. |
| Control Temperature | No data available. | No data available. | No data available. |
| Emergency Temperature | No data available. | No data available. | No data available. |
| ADR Classification Code | C8 | Not applicable. | Not applicable. |
| IMDG Segregation Code | Not applicable. | Not applicable. | 18 - ALKALIS |

Please contact the address or phone number listed on the first page of the SDS for additional information on the transport/shipment of the material by rail (RID) or inland waterways (ADN).

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Carcinogenicity

Ingredient

Titanium dioxide

CAS Nbr

13463-67-7

Classification

Grp. 2B: Possible human
carc.

Regulation

International Agency
for Research on Cancer

Global inventory status

Contact 3M for more information.

DIRECTIVE 2012/18/EU

Seveso hazard categories, Annex 1, Part 1

| Hazard Categories | Qualifying quantity (tonnes) for the application of | |
|---|---|-------------------------|
| | Lower-tier requirements | Upper-tier requirements |
| E2 Hazardous to the Aquatic environment | 200 | 500 |

Seveso named dangerous substances, Annex 1, Part 2

None

Regulation (EU) No 649/2012

No chemicals listed

15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out for this mixture. Chemical safety assessments for the contained substances may have been carried out by the registrants of the substances in accordance with Regulation (EC) No 1907/2006, as amended.

SECTION 16: Other information

List of relevant H statements

| | |
|-------------|---|
| H302 | Harmful if swallowed. |
| H302 + H312 | Harmful if swallowed or in contact with skin. |
| H312 | Harmful in contact with skin. |
| H314 | Causes severe skin burns and eye damage. |
| H317 | May cause an allergic skin reaction. |
| H351i | Suspected of causing cancer by inhalation. |
| H400 | Very toxic to aquatic life. |
| H410 | Very toxic to aquatic life with long lasting effects. |
| H411 | Toxic to aquatic life with long lasting effects. |
| H412 | Harmful to aquatic life with long lasting effects. |

Revision information:

Section 2: <125ml Precautionary - Prevention information was modified.

CLP: Ingredient table information was modified.

Label: CLP Classification information was modified.

Label: CLP Percent Unknown information was added.

Label: CLP Percent Unknown information was modified.

Label: CLP Precautionary - Prevention information was modified.

Section 3: Composition/ Information of ingredients table information was modified.

Section 03: SCL table information was deleted.

Section 04: First Aid - Symptoms and Effects (CLP) information was modified.
Section 7: Precautions safe handling information information was modified.
Section 8: glove data value information was added.
Section 8: glove data value information was modified.
Section 8: Occupational exposure limit table information was modified.
Section 8: Skin protection - protective clothing information information was modified.
Section 11: Acute Toxicity table information was modified.
Section 11: Carcinogenicity Table information was modified.
Section 11: Germ Cell Mutagenicity Table information was modified.
Section 11: Health Effects - Ingestion information information was modified.
Section 11: Health Effects - Inhalation information information was modified.
Section 11: Health Effects - Skin information information was modified.
Lactation Table information was deleted.
Section 11: Reproductive Toxicity Table information was modified.
Section 11: Reproductive/developmental effects information information was deleted.
Section 11: Respiratory Sensitization Table information was deleted.
Section 11: Respiratory Sensitization text information was added.
Section 11: Serious Eye Damage/Irritation Table information was modified.
Section 11: Skin Corrosion/Irritation Table information was modified.
Section 11: Skin Sensitization Table information was modified.
Section 11: Target Organs - Repeated Table information was modified.
Section 11: Target Organs - Single Table information was modified.
Section 12: Component ecotoxicity information information was modified.
Section 12: Mobility in soil information information was modified.
Section 12: Persistence and Degradability information information was modified.
Section 12: Biocumulative potential information information was modified.
Section 15: Carcinogenicity information information was modified.
Section 15: Restrictions on manufacture ingredients information information was deleted.
Two-column table displaying the unique list of H Codes and statements (std phrases) for all components of the given material.
information was modified.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into the European Union, you are responsible for all regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration.

3M Ireland MSDSs are available at www.3M.com