

Safety Data Sheet

Copyright,2023, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	28-8085-4	Version number:	11.02
Revision date:	08/05/2023	Supersedes date:	05/05/2023

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

3M[™] Scotch-Weld[™] Acrylic Structural Plastic Adhesive DP-8005 (Part A)

Product Identification Numbers FS-9100-3812-4

7000080039

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Structural adhesive.

1.3. Details of the supplier of the safety data sheet

Address:3M Ireland Limited, The Iveagh Building, The Park, Carrickmines, Dublin 18.Telephone:+353 1 280 3555E Mail:tox.uk@mmm.comWebsite:www.3M.com

1.4. Emergency telephone number

Emergency medical information: 8am-10pm (seven days) contact National Poisons Information Centre, Beaumont Hospital, Dublin 9 DOV2NO, Ireland. Telephone Number: +353 (0)1 809 2166

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture CLP REGULATION (EC) No 1272/2008

The health and environmental classifications of this material have been derived using the calculation method, except in cases where test data are available or the physical form impacts classification. Classification(s) based on test data or physical form are noted below, if applicable.

CLASSIFICATION:

Serious Eye Damage/Eye Irritation, Category 1 - Eye Dam. 1; H318 Respiratory Sensitization, Category 1 - Resp. Sens. 1; H334 Skin Sensitization, Category 1 - Skin Sens. 1; H317 Germ Cell Mutagenicity, Category 2 - Muta. 2; H341 Hazardous to the Aquatic Environment (Chronic), Category 2 - Aquatic Chronic 2; H411

For full text of H phrases, see Section 16.

2.2. Label elements CLP REGULATION (EC) No 1272/2008

SIGNAL WORD

DANGER.

Symbols

GHS05 (Corrosion) |GHS08 (Health Hazard) |GHS09 (Environment) |

Pictograms



Ingredients: Ingredient	CAS Nbr	EC No.	% by Wt
2-ethyl-2-[[3-(2-methylaziridin-1- yl)propionyl]methyl]propane-1,3-diyl bis(2- methylaziridine-1-propionate)	64265-57-2	264-763-3	20 - 40
Boron, hexaethyl[mu-(1,6-hexanediamine- kN1:kN6)]di-	223674-50-8	426-100-8	5 - 20

HAZARD STATEMENTS:

H318	Causes serious eye damage.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H317	May cause an allergic skin reaction.
H341	Suspected of causing genetic defects.

H411 Toxic to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENTS

Prevention: P261A P280B	Avoid breathing vapours. Wear protective gloves and eye/face protection.
Response:	
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTRE or doctor/physician.
P342 + P311	If experiencing respiratory symptoms: Call a POISON CENTRE or doctor/physician.

For containers not exceeding 125 ml the following Hazard and Precautionary statements may be used:

<=125 ml Hazard statements	
H318	Causes serious eye damage.

H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H317	May cause an allergic skin reaction.
H341	Suspected of causing genetic defects.

<=125 ml Precautionary statements

Prevention:	
P261A	Avoid breathing vapours.
P280B	Wear protective gloves and eye/face protection.
Response:	
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTRE or doctor/physician.
P342 + P311	If experiencing respiratory symptoms: Call a POISON CENTRE or doctor/physician.

44% of the mixture consists of components of unknown acute oral toxicity.

Contains 100% of components with unknown hazards to the aquatic environment.

Notes on labelling

Polyfunctional aziridine is classified as Acute Tox. 2 (H330) based on dust/mist (aerosol) data.

When incorporated into this product, this substance cannot become aerosolized.

Based on available toxicology data and this substance's very low vapour pressure, the saturated vapour of polyfunctional aziridine is not expected to be acutely toxic. Therefore, the classification is not applicable for this material when used as intended.

2.3. Other hazards

None known. This material does not contain any substances that are assessed to be a PBT or vPvB

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Ingredient	Identifier(s)	%	Classification according to Regulation
			(EC) No. 1272/2008 [CLP]
Polyester plasticizer	Trade Secret	40 - 60	Substance not classified as hazardous
2-ethyl-2-[[3-(2-methylaziridin-1-	(CAS-No.) 64265-57-2	20 - 40	Acute Tox. 2, H330
yl)propionyl]methyl]propane-1,3-diyl	(EC-No.) 264-763-3		Eye Dam. 1, H318
bis(2-methylaziridine-1-propionate)			Resp. Sens. 1, H334
			Skin Sens. 1, H317
			Muta. 2, H341
			Aquatic Chronic 2, H411
Boron, hexaethyl[mu-(1,6-	(CAS-No.) 223674-50-8	5 - 20	Acute Tox. 4, H302
hexanediamine-kN1:kN6)]di-	(EC-No.) ELINCS 426-		Eye Irrit. 2, H319
	100-8		Skin Sens. 1, H317
Siloxanes and Silicones, di-Me, reaction	(CAS-No.) 67762-90-7	0.5 - 1.5	Substance with a national occupational

products with silica			exposure limit
	(CAS-No.) 13463-67-7 (EC-No.) 236-675-5 (REACH-No.) 01- 2119489379-17	0.1 - 0.5	Carc. 2, H351 (inhalation)

Please see section 16 for the full text of any H statements referred to in this section

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye contact

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

The most important symptoms and effects based on the CLP classification include: Allergic respiratory reaction (difficulty breathing, wheezing, cough, and tightness of chest). Allergic skin reaction (redness, swelling, blistering, and itching). Serious damage to the eyes (corneal cloudiness, severe pain, tearing, ulcerations, and significantly impaired or loss of vision).

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products

<u>Substance</u>	<u>Condition</u>
Aldehydes.	During combustion.
Carbon monoxide	During combustion.
Carbon dioxide.	During combustion.
Irritant vapours or gases.	During combustion.
Oxides of nitrogen.	During combustion.

5.3. Advice for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as possible.

6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

SECTION 7: Handling and storage

7.1. Precautions for safe handling

For industrial/occupational use only. Not for consumer sale or use. Do not use in a confined area with minimal air exchange. Do not handle until all safety precautions have been read and understood. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (eg. gloves, respirators...) as required.

7.2. Conditions for safe storage including any incompatibilities

Store away from heat. Store away from acids. Store away from strong bases. Store away from oxidising agents. Store away from amines.

7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
Titanium dioxide	13463-67-7	Ireland OELs	TWA(Total inhalable dust)(8	
			hours):10 mg/m3;TWA(as	

Silicon dioxide

67762-90-7 Ireland OELs

respirable dust)(8 hours):4 mg/m3 TWA(Total inhalable dust)(8 hours):6 mg/m3;TWA(as respirable dust)(8 hours):2.4 mg/m3

Ireland OELs : Ireland. OELs TWA: Time-Weighted-Average STEL: Short Term Exposure Limit CEIL: Ceiling

Biological limit values

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

Recommended monitoring procedures:Information on recommended monitoring procedures can be obtained from Indust. Inspect./Ministry (IE)

8.2. Exposure controls

8.2.1. Engineering controls

Provide appropriate local exhaust ventilation for cutting, grinding, sanding or machining. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended: Full face shield. Indirect vented goggles.

Applicable Norms/Standards Use eye/face protection conforming to EN 166

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended:

Material Polymer laminate Thickness (mm) No data available **Breakthrough Time** No data available

Applicable Norms/Standards Use gloves tested to EN 374

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

Applicable Norms/Standards

Use a respirator conforming to EN 140 or EN 136: filter types A & P

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid.
Specific Physical Form:	Paste
Colour	White
Odor	Mild Odor
Odour threshold	No data available.
Melting point/freezing point	No data available.
Boiling point/boiling range	>=181 °C [Details:758 mmHg]
Flammability (solid, gas)	Not applicable.
Flammable Limits(LEL)	Not applicable.
Flammable Limits(UEL)	Not applicable.
Flash point	>=93.3 °C [<i>Test Method</i> :Closed Cup]
Autoignition temperature	No data available.
Decomposition temperature	No data available.
рН	substance/mixture is non-soluble (in water)
Kinematic Viscosity	33,333 mm ² /sec
Water solubility	Slight (less than 10%)
Solubility- non-water	No data available.
Partition coefficient: n-octanol/water	No data available.
Vapour pressure	No data available.
Density	1.05 - 1.09 g/ml
Relative density	1.05 - 1.09 [<i>Ref Std</i> :WATER=1]
Relative Vapour Density	No data available.

9.2. Other information

9.2.2 Other safety characteristics EU Volatile Organic Compounds Evaporation rate

No data available. Not applicable.

. .

SECTION 10: Stability and reactivity

10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

Heat.

10.5 Incompatible materials

Strong acids. Strong bases. Strong oxidising agents. Amines.

10.6 Hazardous decomposition products

Substance None known. **Condition**

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from internal hazard assessments.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. Allergic respiratory reaction: Signs/symptoms may include difficulty breathing, wheezing, cough, and tightness of chest. May cause additional health effects (see below).

Skin contact

Mild Skin Irritation: Signs/symptoms may include localised redness, swelling, itching, and dryness. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye contact

Corrosive (eye burns): Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision. Vapours released during curing may cause eye irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Ingestion

Harmful if swallowed.

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.

Additional Health Effects:

Genotoxicity:

Genotoxicity and Mutagenicity: May interact with genetic material and possibly alter gene expression.

Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or

the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE >300 - =2,000 mg/kg
2-ethyl-2-[[3-(2-methylaziridin-1-yl)propionyl]methyl]propane- 1,3-diyl bis(2-methylaziridine-1-propionate)	Dermal	Rabbit	LD50 > 3,000 mg/kg
2-ethyl-2-[[3-(2-methylaziridin-1-yl)propionyl]methyl]propane- 1,3-diyl bis(2-methylaziridine-1-propionate)	Inhalation- Dust/Mist (4 hours)	Rat	LC50 0.252 mg/l
2-ethyl-2-[[3-(2-methylaziridin-1-yl)propionyl]methyl]propane- 1,3-diyl bis(2-methylaziridine-1-propionate)	Ingestion	Rat	LD50 3,038 mg/kg
Boron, hexaethyl[mu-(1,6-hexanediamine-kN1:kN6)]di-	Ingestion	Rat	LD50 693 mg/kg
Siloxanes and Silicones, di-Me, reaction products with silica	Dermal	Rabbit	LD50 > 5,000 mg/kg
Siloxanes and Silicones, di-Me, reaction products with silica	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Siloxanes and Silicones, di-Me, reaction products with silica	Ingestion	Rat	LD50 > 5,110 mg/kg
Titanium dioxide	Dermal	Rabbit	LD50 > 10,000 mg/kg
Titanium dioxide	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 6.82 mg/l
Titanium dioxide	Ingestion	Rat	LD50 > 10,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
2-ethyl-2-[[3-(2-methylaziridin-1-yl)propionyl]methyl]propane-1,3-diyl bis(2- methylaziridine-1-propionate)	Rabbit	Mild irritant
Boron, hexaethyl[mu-(1,6-hexanediamine-kN1:kN6)]di-	Rabbit	No significant irritation
Siloxanes and Silicones, di-Me, reaction products with silica	Rabbit	No significant irritation
Titanium dioxide	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
2-ethyl-2-[[3-(2-methylaziridin-1-yl)propionyl]methyl]propane-1,3-diyl bis(2-methylaziridine-1-propionate)	Rabbit	Corrosive
Boron, hexaethyl[mu-(1,6-hexanediamine-kN1:kN6)]di-	Professio nal judgemen t	Severe irritant
Siloxanes and Silicones, di-Me, reaction products with silica	Rabbit	No significant irritation
Titanium dioxide	Rabbit	No significant irritation

Skin Sensitisation

Name	Species	Value
2-ethyl-2-[[3-(2-methylaziridin-1-yl)propionyl]methyl]propane-1,3-diyl bis(2-	Human	Sensitising
methylaziridine-1-propionate)	and	
	animal	
Boron, hexaethyl[mu-(1,6-hexanediamine-kN1:kN6)]di-	Guinea	Sensitising
	pig	
Siloxanes and Silicones, di-Me, reaction products with silica	Human	Not classified
	and	
	animal	
Titanium dioxide	Human	Not classified
	and	
	animal	

Respiratory Sensitisation

Name	Species	Value
2-ethyl-2-[[3-(2-methylaziridin-1-yl)propionyl]methyl]propane-1,3-diyl bis(2-methylaziridine-1-propionate)	Human	Sensitising

Germ Cell Mutagenicity

Name	Route	Value
2-ethyl-2-[[3-(2-methylaziridin-1-yl)propionyl]methyl]propane-1,3-diyl bis(2- methylaziridine-1-propionate)	In vivo	Mutagenic
Boron, hexaethyl[mu-(1,6-hexanediamine-kN1:kN6)]di-	In Vitro	Not mutagenic
Siloxanes and Silicones, di-Me, reaction products with silica	In Vitro	Not mutagenic
Titanium dioxide	In Vitro	Not mutagenic
Titanium dioxide	In vivo	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
Siloxanes and Silicones, di-Me, reaction products with silica	Not	Mouse	Some positive data exist, but the data are not
	specified.		sufficient for classification
Titanium dioxide	Ingestion	Multiple	Not carcinogenic
		animal	
		species	
Titanium dioxide	Inhalation	Rat	Carcinogenic.

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
Siloxanes and Silicones, di-Me, reaction products with silica	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Siloxanes and Silicones, di-Me, reaction products with silica	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Siloxanes and Silicones, di-Me, reaction products with silica	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure
						Duration
2-ethyl-2-[[3-(2- methylaziridin-1- yl)propionyl]methyl]propa ne-1,3-diyl bis(2- methylaziridine-1- propionate)	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL Not available	4 hours

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Siloxanes and Silicones, di-Me, reaction products with silica	Inhalation	respiratory system silicosis	Not classified	Human	NOAEL Not available	occupational exposure
Titanium dioxide	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 0.01 mg/l	2 years
Titanium dioxide	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not available	occupational exposure

Aspiration Hazard

For the component/components, either no data is currently available or the data is not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

11.2. Information on other hazards

This material does not contain any substances that are assessed to be an endocrine disruptor for human health.

SECTION 12: Ecological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

12.1. Toxicity

No product test data available.

Material	CAS #	Organism	Туре	Exposure	Test endpoint	Test result
2-ethyl-2-[[3-(2- methylaziridin-1- yl)propionyl]methyl]pr opane-1,3-diyl bis(2- methylaziridine-1- propionate)	64265-57-2	Algae or other aquatic plants	Experimental	72 hours	EC50	3.8 mg/l
2-ethyl-2-[[3-(2- methylaziridin-1- yl)propionyl]methyl]pr opane-1,3-diyl bis(2- methylaziridine-1- propionate)	64265-57-2	Fish	Experimental	96 hours	LC50	2.35 mg/l
2-ethyl-2-[[3-(2- methylaziridin-1- yl)propionyl]methyl]pr opane-1,3-diyl bis(2- methylaziridine-1- propionate)	64265-57-2	Invertebrate	Experimental	48 hours	EC50	6.96 mg/l
Boron, hexaethyl[mu- (1,6-hexanediamine- kN1:kN6)]di-	223674-50-8	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Titanium dioxide	13463-67-7	Activated sludge	Experimental	3 hours	NOEC	>=1,000 mg/l
Titanium dioxide	13463-67-7	Diatom	Experimental	72 hours	EC50	>10,000 mg/l
Titanium dioxide	13463-67-7	Fathead minnow	Experimental	96 hours	LC50	>100 mg/l
Titanium dioxide	13463-67-7	Water flea	Experimental	48 hours	EC50	>100 mg/l
Titanium dioxide	13463-67-7	Diatom	Experimental	72 hours	NOEC	5,600 mg/l

12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
2-ethyl-2-[[3-(2-	64265-57-2	Experimental	28 days	CO2 evolution	<60 %CO2	OECD 301B - Modified
methylaziridin-1-		Biodegradation			evolution/THC	sturm or CO2

yl)propionyl]methyl]propan e-1,3-diyl bis(2- methylaziridine-1- propionate)					O2 evolution	
Boron, hexaethyl[mu-(1,6- hexanediamine- kN1:kN6)]di-	223674-50-8	Experimental Biodegradation	28 days		44 %CO2 evolution/THC O2 evolution	EC C.4.C. CO2 Evolution Test
Siloxanes and Silicones, di- Me, reaction products with silica	67762-90-7	Data not availbl- insufficient	N/A	N/A	N/A	N/A
Titanium dioxide	13463-67-7	Data not availbl- insufficient	N/A	N/A	N/A	N/A

12.3 : Bioaccumulative potential

Material	Cas No.	Test type	Duration	Study Type	Test result	Protocol
2-ethyl-2-[[3-(2- methylaziridin-1- yl)propionyl]methyl]propa ne-1,3-diyl bis(2- methylaziridine-1- propionate)	64265-57-2	Modeled Bioconcentration		Log Kow	0.5	ACD/Labs ChemSketch™
Boron, hexaethyl[mu-(1,6- hexanediamine- kN1:kN6)]di-	223674-50-8	Experimental Bioconcentration		Log Kow	>5.99	EC A.8 Partition Coefficient
Siloxanes and Silicones, di- Me, reaction products with silica	67762-90-7	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Titanium dioxide	13463-67-7	Experimental BCF - Fish	42 days	Bioaccumulation factor	9.6	

12.4. Mobility in soil

Material	Cas No.	Test type	Study Type	Test result	Protocol
2-ethyl-2-[[3-(2- methylaziridin-1- yl)propionyl]methyl]propa ne-1,3-diyl bis(2- methylaziridine-1- propionate)	64265-57-2	Modeled Mobility in Soil	Кос	19,000 l/kg	Episuite™

12.5. Results of the PBT and vPvB assessment

This material does not contain any substances that are assessed to be a PBT or vPvB

12.6. Endocrine disrupting properties

This material does not contain any substances that are assessed to be an endocrine disruptor for environmental effects

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. If no other disposal options are available, waste product that has been completely cured or

polymerised may be placed in a landfill properly designed for industrial waste. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

EU waste code (product as sold)

- 08 04 09*
- Waste adhesives and sealants containing organic solvents or other dangerous substances
- 20 01 27* Paint, inks, adhesives and resins containing dangerous substances

	Ground Transport (ADR)	Air Transport (IATA)	Marine Transport (IMDG)
14.1 UN number or ID number	UN3082	UN3082	UN3082
14.2 UN proper shipping name	SUBSTANCE, LIQUID,	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.(POLYFUNCTIONAL AZIRIDINE)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.(POLYFUNCTIONAL AZIRIDINE)
14.3 Transport hazard class(es)	9	9	9
14.4 Packing group	III	III	III
14.5 Environmental hazards	Environmentally Hazardous	Not applicable	Marine Pollutant
14.6 Special precautions for user	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.
14.7 Marine Transport in bulk according to IMO instruments	No data available.	No data available.	No data available.
Control Temperature	No data available.	No data available.	No data available.
Emergency Temperature	No data available.	No data available.	No data available.
ADR Classification Code	M6	Not applicable.	Not applicable.

SECTION 14: Transportation information

IMDG Segregation Code	Not applicable.	Not applicable.	NONE

Please contact the address or phone number listed on the first page of the SDS for additional information on the transport/shipment of the material by rail (RID) or inland waterways (ADN).

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Carcino	genic	eity
-		

Ingredient Titanium dioxide

CAC NI		
<u>CAS Nbr</u>	<u>Classification</u>	<u>Regulation</u>
13463-67-7	Grp. 2B: Possible human	International Agency
	carc.	for Research on Cancer

Global inventory status

Contact 3M for more information.

DIRECTIVE 2012/18/EU

Seveso hazard categories, Annex 1, Part 1

Hazard Categories	Qualifying quantity (tonnes) for the application of	
	Lower-tier requirements	Upper-tier requirements
E2 Hazardous to the Aquatic	200	500
environment		

Seveso named dangerous substances, Annex 1, Part 2 None

Regulation (EU) No 649/2012

No chemicals listed

15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out for this substance/mixture in accordance with Regulation (EC) No 1907/2006, as amended.

SECTION 16: Other information

List of relevant H statements

H302	Harmful if swallowed.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H341	Suspected of causing genetic defects.
H351i	Suspected of causing cancer by inhalation.
H411	Toxic to aquatic life with long lasting effects.

Revision information:

No revision information

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into the European Union, you are responsible for all regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration.

3M Ireland MSDSs are available at www.3M.com