



Safety Data Sheet

Copyright, 2023, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	42-7982-4	Version number:	1.00
Revision date:	10/08/2023	Supersedes date:	Initial issue.

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Scotchgard (TM) Fabric Protector

Product Identification Numbers

UU-0115-2621-5

7100282524

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Consumer

1.3. Details of the supplier of the safety data sheet

Address: 3M Ireland Limited, The Iveagh Building, The Park, Carrickmines, Dublin 18.
Telephone: +353 1 280 3555
E Mail: tox.uk@mmm.com
Website: www.3M.com

1.4. Emergency telephone number

Emergency medical information: 8am-10pm (seven days) contact National Poisons Information Centre, Beaumont Hospital, Dublin 9 DOV2NO, Ireland. Telephone Number: +353 (0)1 809 2166

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

CLP REGULATION (EC) No 1272/2008

The health and environmental classifications of this material have been derived using the calculation method, except in cases where test data are available or the physical form impacts classification. Classification(s) based on test data or physical form are noted below, if applicable.

The aspiration hazard classification is not required because the product is an aerosol.

CLASSIFICATION:

Aerosol, Category 1 - Aerosol 1; H222, H229

Skin Corrosion/Irritation, Category 2 - Skin Irrit. 2; H315
 Specific Target Organ Toxicity-Single Exposure, Category 3 - STOT SE 3; H336
 Hazardous to the Aquatic Environment (Chronic), Category 2 - Aquatic Chronic 2; H411

For full text of H phrases, see Section 16.

2.2. Label elements

CLP REGULATION (EC) No 1272/2008

SIGNAL WORD

DANGER.

Symbols

GHS02 (Flame) |GHS07 (Exclamation mark) |GHS09 (Environment) |

Pictograms



Ingredients:

Ingredient	CAS Nbr	EC No.	% by Wt
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics		927-510-4	50 - 70

HAZARD STATEMENTS:

H222	Extremely flammable aerosol.
H229	Pressurised container: may burst if heated.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENTS

General:

P102 Keep out of reach of children.

Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P211 Do not spray on an open flame or other ignition source.
 P251 Do not pierce or burn, even after use.

Storage:

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Disposal:

P501 Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

Contains 2% of components with unknown hazards to the aquatic environment.

2.3. Other hazards

May displace oxygen and cause rapid suffocation.

This material does not contain any substances that are assessed to be a PBT or vPvB

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Ingredient	Identifier(s)	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	(EC-No.) 927-510-4 (REACH-No.) 01-2119475515-33	50 - 70	Aquatic Chronic 2, H411 Flam. Liq. 2, H225 Asp. Tox. 1, H304 Skin Irrit. 2, H315 STOT SE 3, H336
n-butyl acetate	(CAS-No.) 123-86-4 (EC-No.) 204-658-1 (REACH-No.) 01-2119485493-29	1 - 2.5	Flam. Liq. 3, H226 STOT SE 3, H336 EUH066
propane	(CAS-No.) 74-98-6 (EC-No.) 200-827-9 (REACH-No.) 01-2119486944-21	7 - 15	Flam. Gas 1A, H220 Liquified gas, H280 Nota U
ethyl acetate	(CAS-No.) 141-78-6 (EC-No.) 205-500-4 (REACH-No.) 01-2119475103-46	0.5 - 1.5	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 EUH066
butane	(CAS-No.) 106-97-8 (EC-No.) 203-448-7 (REACH-No.) 01-2119474691-32	7 - 13	Flam. Gas 1A, H220 Liquified gas, H280 Nota C,U
Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	(EC-No.) 920-107-4 (REACH-No.) 01-2119453414-43	5 - 10	Asp. Tox. 1, H304 EUH066

Any entry in the Identifier(s) column that begins with the numbers 6, 7, 8, or 9 are a Provisional List Number provided by ECHA pending publication of the official EC Inventory Number for the substance.

Please see section 16 for the full text of any H statements referred to in this section

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. Get medical attention.

Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye contact

If exposed, flush eyes with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If

signs/symptoms develop, get medical attention.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

The most important symptoms and effects based on the CLP classification include:

Irritation to the skin (localized redness, swelling, itching, and dryness). Central nervous system depression (headache, dizziness, drowsiness, incoordination, nausea, slurred speech, giddiness, and unconsciousness).

4.3. Indication of any immediate medical attention and special treatment required

Exposure may increase myocardial irritability. Do not administer sympathomimetic drugs unless absolutely necessary.

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

Use a fire fighting agent suitable for the surrounding fire.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

5.3. Advice for fire-fighters

No special protective actions for fire-fighters are anticipated.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapours in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

If possible, seal leaking container. Place leaking containers in a well-ventilated area, preferably an operating exhaust hood, or if necessary outdoors on an impermeable surface until appropriate packaging for the leaking container or its contents is available. Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible.

6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Keep out of reach of children. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an

open flame or other ignition source. Do not pierce or burn, even after use. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store away from heat.

7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
butane	106-97-8	Ireland OELs	STEL(15 minutes):1000 ppm	
n-butyl acetate	123-86-4	Ireland OELs	TWA(8 hours):241 mg/m3(50 ppm);TWA(8 hours):50 ppm(241 mg/m3);STEL(15 minutes):723 mg/m3(150 ppm);STEL(15 minutes):150 ppm(723 mg/m3)	
ethyl acetate	141-78-6	Ireland OELs	TWA(8 hours):734 mg/m3(200 ppm);TWA(8 hours):200 ppm(734 mg/m3);STEL(15 minutes):1468 mg/m3(400 ppm);STEL(15 minutes):400 ppm(1468 mg/m3)	

Ireland OELs : Ireland. OELs
 TWA: Time-Weighted-Average
 STEL: Short Term Exposure Limit
 CEIL: Ceiling

Biological limit values

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

Recommended monitoring procedures:Information on recommended monitoring procedures can be obtained from Indust. Inspect./Ministry (IE)

8.2. Exposure controls

8.2.1. Engineering controls

Do not remain in area where available oxygen may be reduced. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face

protection(s) are recommended:

Indirect vented goggles.

Applicable Norms/Standards

Use eye protection conforming to EN 166

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended:

Material	Thickness (mm)	Breakthrough Time
Polymer laminate	No data available	No data available

When only incidental contact is anticipated, alternative glove material(s) may be used. If contact with the glove does occur, remove immediately and replace with a set of new gloves. For incidental contact, gloves made of the following material(s) may be used: Nitrile rubber.

Applicable Norms/Standards

Use gloves tested to EN 374

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

Half facepiece or full facepiece supplied-air respirator

Organic vapour respirators may have short service life.

For questions about suitability for a specific application, consult with your respirator manufacturer.

Applicable Norms/Standards

Use a respirator conforming to EN 140 or EN 136

Use a respirator conforming to EN 140 or EN 136: filter types A & P

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid.
Specific Physical Form:	Aerosol
Colour	Colourless
Odor	No data available.
Odour threshold	No data available.
Melting point/freezing point	No data available.
Boiling point/boiling range	No data available.
Flammability (solid, gas)	Not applicable.
Flammable Limits(LEL)	No data available.
Flammable Limits(UEL)	No data available.
Flash point	No data available.
Autoignition temperature	No data available.
Decomposition temperature	No data available.

pH	<i>substance/mixture is non-soluble (in water)</i>
Kinematic Viscosity	<i>No data available.</i>
Water solubility	<i>No data available.</i>
Solubility- non-water	<i>No data available.</i>
Partition coefficient: n-octanol/water	<i>No data available.</i>
Vapour pressure	≥ 300 kPa
Density	<i>No data available.</i>
Relative density	0.709 [$@ 20$ °C] [Ref Std:WATER=1]
Relative Vapour Density	<i>No data available.</i>

9.2. Other information

9.2.2 Other safety characteristics

EU Volatile Organic Compounds	<i>No data available.</i>
Evaporation rate	<i>No data available.</i>
Percent volatile	<i>No data available.</i>

SECTION 10: Stability and reactivity

10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

Heat.
Sparks and/or flames.

10.5 Incompatible materials

Not determined

10.6 Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
Carbon monoxide	At elevated temperatures.
Carbon dioxide.	At elevated temperatures.

SECTION 11: Toxicological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from internal hazard assessments.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

Simple asphyxiation: Signs/symptoms may include increased heart rate, rapid respirations, drowsiness, headache, incoordination, altered judgement, nausea, vomiting, lethargy, seizures, coma, and may be fatal. Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

Skin contact

Skin Irritation: Signs/symptoms may include localised redness, swelling, itching, dryness, cracking, blistering, and pain.

Eye contact

Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.

Additional Health Effects:

Single exposure may cause target organ effects:

Central nervous system (CNS) depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness. Respiratory effects: Signs/symptoms may include cough, shortness of breath, chest tightness, wheezing, increased heart rate, bluish coloured skin (cyanosis), sputum production, changes in lung function tests, and respiratory failure. Single exposure, above recommended guidelines, may cause: Cardiac Sensitization: Signs/symptoms may include irregular heartbeat (arrhythmia), faintness, chest pain, and may be fatal.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Inhalation-Dust/Mist(4 hr)		No data available; calculated ATE >12.5 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	Dermal	Rabbit	LD50 > 2,920 mg/kg
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	Dermal	Rat	LD50 > 2,000 mg/kg
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	Inhalation-Vapour (4 hours)	Rat	LC50 > 23.3 mg/l
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	Inhalation-Vapour (4 hours)	Rat	LC50 > 5.61 mg/l
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	Ingestion	Rat	LD50 > 5,840 mg/kg
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	Ingestion	Rat	LD50 > 5,000 mg/kg
propane	Inhalation-Gas (4 hours)	Rat	LC50 > 200,000 ppm
butane	Inhalation-Gas (4 hours)	Rat	LC50 277,000 ppm
Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	Inhalation-Vapour	Professional judgement	LC50 estimated to be 20 - 50 mg/l
Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	Dermal	Rabbit	LD50 > 5,000 mg/kg
Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	Ingestion	Rat	LD50 > 5,000 mg/kg
n-butyl acetate	Dermal	Rabbit	LD50 > 5,000 mg/kg
n-butyl acetate	Inhalation-Dust/Mist	Rat	LC50 1.4 mg/l

Scotchgard (TM) Fabric Protector

	(4 hours)		
n-butyl acetate	Inhalation-Vapour (4 hours)	Rat	LC50 > 20 mg/l
n-butyl acetate	Ingestion	Rat	LD50 > 8,800 mg/kg
ethyl acetate	Dermal	Rabbit	LD50 > 18,000 mg/kg
ethyl acetate	Inhalation-Vapour (4 hours)	Rat	LC50 70.5 mg/l
ethyl acetate	Ingestion	Rat	LD50 5,620 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	Rabbit	Irritant
propane	Rabbit	Minimal irritation
butane	Professional judgement	No significant irritation
Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	Rabbit	Minimal irritation
n-butyl acetate	Rabbit	Minimal irritation
ethyl acetate	Rabbit	Minimal irritation

Serious Eye Damage/Irritation

Name	Species	Value
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	Rabbit	No significant irritation
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	Rabbit	Mild irritant
propane	Rabbit	Mild irritant
butane	Rabbit	No significant irritation
Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	Rabbit	Mild irritant
n-butyl acetate	Rabbit	Moderate irritant
ethyl acetate	Rabbit	Mild irritant

Skin Sensitisation

Name	Species	Value
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	Guinea pig	Not classified
Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	Guinea pig	Not classified
n-butyl acetate	Multiple animal species	Not classified
ethyl acetate	Guinea pig	Not classified

Respiratory Sensitisation

For the component/components, either no data is currently available or the data is not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	In Vitro	Not mutagenic
propane	In Vitro	Not mutagenic
butane	In Vitro	Not mutagenic
Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	In Vitro	Not mutagenic
Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	In vivo	Not mutagenic
n-butyl acetate	In Vitro	Not mutagenic

Scotchgard (TM) Fabric Protector

ethyl acetate	In Vitro	Not mutagenic
ethyl acetate	In vivo	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	Not specified.	Not available	Not carcinogenic

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	Not specified.	Not classified for female reproduction	Rat	NOAEL Not available	2 generation
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	Not specified.	Not classified for male reproduction	Rat	NOAEL Not available	2 generation
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	Not specified.	Not classified for development	Rat	NOAEL Not available	2 generation
Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	Not specified.	Not classified for female reproduction	Rat	NOAEL Not available	prematuring & during gestation
Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	Not specified.	Not classified for male reproduction	Rat	NOAEL Not available	28 days
Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	Not specified.	Not classified for development	Rat	NOAEL Not available	during gestation
n-butyl acetate	Inhalation	Not classified for female reproduction	Rat	NOAEL 7.1 mg/l	prematuring & during gestation
n-butyl acetate	Inhalation	Not classified for development	Rat	NOAEL 7.1 mg/l	prematuring & during gestation

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	
propane	Inhalation	cardiac sensitisation	Causes damage to organs	Human	NOAEL Not available	
propane	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
propane	Inhalation	respiratory irritation	Not classified	Human	NOAEL Not available	
butane	Inhalation	cardiac sensitisation	Causes damage to organs	Human	NOAEL Not available	
butane	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
butane	Inhalation	heart	Not classified	Dog	NOAEL 5,000 ppm	25 minutes
butane	Inhalation	respiratory irritation	Not classified	Rabbit	NOAEL Not available	

Scotchgard (TM) Fabric Protector

n-butyl acetate	Inhalation	respiratory system	May cause damage to organs	Rat	LOAEL 2.6 mg/l	4 hours
n-butyl acetate	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	not available
n-butyl acetate	Inhalation	respiratory irritation	May cause respiratory irritation	Human	NOAEL Not available	not available
n-butyl acetate	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	
ethyl acetate	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
ethyl acetate	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
ethyl acetate	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
butane	Inhalation	kidney and/or bladder blood	Not classified	Rat	NOAEL 4,489 ppm	90 days
n-butyl acetate	Inhalation	olfactory system	Not classified	Rat	NOAEL 2.4 mg/l	14 weeks
n-butyl acetate	Inhalation	liver kidney and/or bladder	Not classified	Rabbit	NOAEL 7.26 mg/l	13 days
ethyl acetate	Inhalation	endocrine system liver nervous system	Not classified	Rat	NOAEL 0.043 mg/l	90 days
ethyl acetate	Inhalation	hematopoietic system	Not classified	Rabbit	LOAEL 16 mg/l	40 days
ethyl acetate	Ingestion	hematopoietic system liver kidney and/or bladder	Not classified	Rat	NOAEL 3,600 mg/kg/day	90 days

Aspiration Hazard

Name	Value
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	Aspiration hazard
Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

11.2. Information on other hazards

This material does not contain any substances that are assessed to be an endocrine disruptor for human health.

SECTION 12: Ecological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

12.1. Toxicity

No product test data available.

Material	CAS #	Organism	Type	Exposure	Test endpoint	Test result
----------	-------	----------	------	----------	---------------	-------------

Scotchgard (TM) Fabric Protector

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	927-510-4	Green algae	Analogous Compound	72 hours	EL50	29 mg/l
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	927-510-4	Medaka	Analogous Compound	96 hours	LC50	0.561 mg/l
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	927-510-4	Water flea	Analogous Compound	48 hours	EC50	0.4 mg/l
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	927-510-4	Green algae	Estimated	72 hours	EL50	29 mg/l
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	927-510-4	Water flea	Estimated	48 hours	EL50	3 mg/l
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	927-510-4	Rainbow trout	Experimental	96 hours	LL50	>13.4 mg/l
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	927-510-4	Green algae	Analogous Compound	72 hours	NOEL	6.3 mg/l
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	927-510-4	Water flea	Analogous Compound	21 days	NOEC	0.17 mg/l
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	927-510-4	Green algae	Estimated	72 hours	NOEL	6.3 mg/l
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	927-510-4	Water flea	Estimated	21 days	NOEL	1 mg/l
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	927-510-4	Activated sludge	Analogous Compound	15 hours	IC50	29 mg/l
n-butyl acetate	123-86-4	Green algae	Analogous Compound	72 hours	ErC50	397 mg/l
n-butyl acetate	123-86-4	Fathead minnow	Experimental	96 hours	LC50	18 mg/l
n-butyl acetate	123-86-4	Water flea	Experimental	48 hours	EC50	44 mg/l
n-butyl acetate	123-86-4	Green algae	Analogous Compound	72 hours	NOEC	196 mg/l
n-butyl acetate	123-86-4	Water flea	Analogous Compound	21 days	NOEC	23.2 mg/l
n-butyl acetate	123-86-4	Ciliated protozoa	Experimental	40 hours	IC50	356 mg/l
n-butyl acetate	123-86-4	Lettuce	Experimental	14 days	EC50	>1,000 mg/kg (Dry Weight)
ethyl acetate	141-78-6	Bacteria	Experimental	18 hours	EC10	2,900 mg/l
ethyl acetate	141-78-6	Fish	Experimental	96 hours	LC50	212.5 mg/l
ethyl acetate	141-78-6	Invertebrate	Experimental	48 hours	EC50	165 mg/l
ethyl acetate	141-78-6	Green algae	Experimental	72 hours	NOEC	>100 mg/l
ethyl acetate	141-78-6	Water flea	Experimental	21 days	NOEC	2.4 mg/l
propane	74-98-6	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
butane	106-97-8	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	920-107-4	Green algae	Estimated	72 hours	EL50	>1,000 mg/l

Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	920-107-4	Rainbow trout	Estimated	96 hours	LL50	>1,000 mg/l
Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	920-107-4	Water flea	Estimated	48 hours	EL50	>1,000 mg/l
Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	920-107-4	Green algae	Estimated	72 hours	NOEL	1,000 mg/l

12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	927-510-4	Analogous Compound Biodegradation	28 days	BOD	74.4 %BOD/ThOD	OECD 301F - Manometric respirometry
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	927-510-4	Estimated Biodegradation	28 days	BOD	98 %BOD/CO D	OECD 301F - Manometric respirometry
n-butyl acetate	123-86-4	Experimental Biodegradation	28 days	BOD	83 %BOD/ThOD	OECD 301D - Closed bottle test
n-butyl acetate	123-86-4	Experimental Photolysis		Photolytic half-life (in air)	6.3 days (t 1/2)	
n-butyl acetate	123-86-4	Experimental Hydrolysis		Hydrolytic half-life (pH 7)	3.1 years (t 1/2)	
ethyl acetate	141-78-6	Experimental Biodegradation	14 days	BOD	94 %BOD/ThOD	OECD 301C - MITI test (I)
ethyl acetate	141-78-6	Experimental Photolysis		Photolytic half-life (in air)	20.0 days (t 1/2)	
propane	74-98-6	Experimental Photolysis		Photolytic half-life (in air)	27.5 days (t 1/2)	
butane	106-97-8	Experimental Photolysis		Photolytic half-life (in air)	12.3 days (t 1/2)	
Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	920-107-4	Estimated Biodegradation	28 days	BOD	67.6 %BOD/ThOD	OECD 301F - Manometric respirometry

12.3 : Bioaccumulative potential

Material	Cas No.	Test type	Duration	Study Type	Test result	Protocol
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	927-510-4	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	927-510-4	Analogous Compound BCF - Fish	28 days	Bioaccumulation factor	540	OECD305-Bioconcentration
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	927-510-4	Analogous Compound Bioconcentration		Log Kow	4.66	
n-butyl acetate	123-86-4	Experimental Bioconcentration		Log Kow	2.3	OECD 117 log Kow HPLC method
ethyl acetate	141-78-6	Experimental Bioconcentration		Log Kow	0.68	
propane	74-98-6	Experimental Bioconcentration		Log Kow	2.36	
butane	106-97-8	Experimental Bioconcentration		Log Kow	2.89	
Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	920-107-4	Data not available or insufficient for classification	N/A	N/A	N/A	N/A

12.4. Mobility in soil

Material	Cas No.	Test type	Study Type	Test result	Protocol
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	927-510-4	Modeled Mobility in Soil	Koc	≥202 l/kg	Episuite™
n-butyl acetate	123-86-4	Modeled Mobility in Soil	Koc	135 l/kg	Episuite™

12.5. Results of the PBT and vPvB assessment

This material does not contain any substances that are assessed to be a PBT or vPvB

12.6. Endocrine disrupting properties

This material does not contain any substances that are assessed to be an endocrine disruptor for environmental effects

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. Facility must be capable of handling aerosol cans. As a disposal alternative, utilize an acceptable permitted waste disposal facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

EU waste code (product as sold)

16 05 04* Gases in pressure containers (including halons) containing dangerous substances

SECTION 14: Transportation information

	Ground Transport (ADR)	Air Transport (IATA)	Marine Transport (IMDG)
14.1 UN number or ID number	UN1950	UN1950	UN1950
14.2 UN proper shipping name	AEROSOLS	AEROSOLS, FLAMMABLE	AEROSOLS
14.3 Transport hazard class(es)	2.1	2.1	2.1
14.4 Packing group	Not applicable.	Not applicable.	Not applicable.

14.5 Environmental hazards	Not Environmentally Hazardous	Not applicable	Not a Marine Pollutant
14.6 Special precautions for user	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.
14.7 Marine Transport in bulk according to IMO instruments	No data available.	No data available.	No data available.
Control Temperature	No data available.	No data available.	No data available.
Emergency Temperature	No data available.	No data available.	No data available.
ADR Classification Code	5F	Not applicable.	Not applicable.
IMDG Segregation Code	Not applicable.	Not applicable.	NONE

Please contact the address or phone number listed on the first page of the SDS for additional information on the transport/shipment of the material by rail (RID) or inland waterways (ADN).

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status

Contact 3M for more information.

DIRECTIVE 2012/18/EU

Seveso hazard categories, Annex 1, Part 1

Hazard Categories	Qualifying quantity (tonnes) for the application of	
	Lower-tier requirements	Upper-tier requirements
E2 Hazardous to the Aquatic environment	200	500
P3a FLAMMABLE AEROSOLS	150 (net)	500 (net)

Seveso named dangerous substances, Annex 1, Part 2

Dangerous Substances	Identifier(s)	Qualifying quantity (tonnes) for the application of	
		Lower-tier requirements	Upper-tier requirements
butane	106-97-8	10	50
ethyl acetate	141-78-6	10	50
n-butyl acetate	123-86-4	10	50
propane	74-98-6	10	50

Regulation (EU) No 649/2012

No chemicals listed

15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out for this substance/mixture in accordance with Regulation (EC) No 1907/2006, as amended.

SECTION 16: Other information

List of relevant H statements

EUH066	Repeated exposure may cause skin dryness or cracking.
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H229	Pressurised container: may burst if heated.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Revision information:

No revision information

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into the European Union, you are responsible for all regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration.

3M Ireland MSDSs are available at www.3M.com