



Safety Data Sheet

Copyright, 2023, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	11-5752-8	Version number:	11.01
Revision date:	07/07/2023	Supersedes date:	20/06/2023

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

3M™ Finesse-it™ Finishing Material [140]

Product Identification Numbers

UU-0111-1270-1

7100236898

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Automotive.

1.3. Details of the supplier of the safety data sheet

Address: 3M Ireland Limited, The Iveagh Building, The Park, Carrickmines, Dublin 18.
Telephone: +353 1 280 3555
E Mail: tox.uk@mmm.com
Website: www.3M.com

1.4. Emergency telephone number

Emergency medical information: 8am-10pm (seven days) contact National Poisons Information Centre, Beaumont Hospital, Dublin 9 DOV2NO, Ireland. Telephone Number: +353 (0)1 809 2166

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

CLP REGULATION (EC) No 1272/2008

The health and environmental classifications of this material have been derived using the calculation method, except in cases where test data are available or the physical form impacts classification. Classification(s) based on test data or physical form are noted below, if applicable.

The aspiration hazard classification is not required due to the product's viscosity.

CLASSIFICATION:

Specific Target Organ Toxicity-Repeated Exposure, Category 2 - STOT RE 2; H373

For full text of H phrases, see Section 16.

2.2. Label elements

CLP REGULATION (EC) No 1272/2008

SIGNAL WORD

WARNING.

Symbols

GHS08 (Health Hazard) |

Pictograms



Ingredients:

Ingredient	CAS Nbr	EC No.	% by Wt
Hydrocarbons C9-12 N-alkanes, isoalkanes cyclic aromatics (2-25%)		919-446-0	0.5 - 1.5

HAZARD STATEMENTS:

H373 May cause damage to organs through prolonged or repeated exposure: nervous system.

PRECAUTIONARY STATEMENTS

Prevention:

P260A Do not breathe vapours.

3% of the mixture consists of components of unknown acute oral toxicity.

Contains 1% of components with unknown hazards to the aquatic environment.

2.3. Other hazards

None known.

This material does not contain any substances that are assessed to be a PBT or vPvB

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Ingredient	Identifier(s)	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Non-Hazardous Ingredients	Trade Secret	40 - 70	Substance not classified as hazardous
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	(EC-No.) 919-857-5 (REACH-No.) 01-2119463258-33	< 20	Flam. Liq. 3, H226 Asp. Tox. 1, H304 STOT SE 3, H336

			EUH066
White mineral oil (petroleum)	(CAS-No.) 8042-47-5 (EC-No.) 232-455-8	5 - 15	Asp. Tox. 1, H304
Hydrocarbons C9-12 N-alkanes, isoalkanes cyclic aromatics (2-25%)	(EC-No.) 919-446-0	0.5 - 1.5	Aquatic Chronic 2, H411 Flam. Liq. 3, H226 Asp. Tox. 1, H304 STOT SE 3, H336 EUH066 STOT RE 1, H372
Aluminium oxide	(CAS-No.) 1344-28-1 (EC-No.) 215-691-6	1 - 10	Substance with a national occupational exposure limit
Ethylene glycol monoricinoleate	(CAS-No.) 106-17-2 (EC-No.) 203-369-8	1 - 5	Aquatic Acute 1, H400,M=1 Aquatic Chronic 3, H412
morpholine	(CAS-No.) 110-91-8 (EC-No.) 203-815-1	< 0.5	Flam. Liq. 3, H226 Acute Tox. 3, H311 Acute Tox. 4, H332 Acute Tox. 4, H302 Skin Corr. 1B, H314 Eye Dam. 1, H318 Repr. 2, H361f

Any entry in the Identifier(s) column that begins with the numbers 6, 7, 8, or 9 are a Provisional List Number provided by ECHA pending publication of the official EC Inventory Number for the substance.
Please see section 16 for the full text of any H statements referred to in this section

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Wash with soap and water. If signs/symptoms develop, get medical attention.

Eye contact

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

The most important symptoms and effects based on the CLP classification include:
Target organ effects. See Section 11 for additional details.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

5.3. Advice for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapours in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Cover spill area with a fire extinguishing foam that is resistant to polar solvents. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with water. Seal the container. Dispose of collected material as soon as possible.

6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

SECTION 7: Handling and storage

7.1. Precautions for safe handling

For industrial/occupational use only. Not for consumer sale or use. Do not use in a confined area with minimal air exchange. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (eg. gloves, respirators...) as required. Vapours may travel long distances along the ground or floor to an ignition source and flash back.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep cool. Protect from sunlight. Store away from heat. Store away from acids. Store away from oxidising agents.

7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

SECTION 8: Exposure controls/personal protection**8.1 Control parameters****Occupational exposure limits**

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
morpholine	110-91-8	Ireland OELs	TWA(8 hours):36 mg/m ³ (10 ppm);TWA(8 hours):10 ppm(36 mg/m ³);STEL(15 minutes):72 mg/m ³ (20 ppm);STEL(15 minutes):20 ppm(72 mg/m ³)	SKIN
Aluminium oxide	1344-28-1	Ireland OELs	TWA(Total inhalable dust)(8 hours):10 mg/m ³ ;TWA(as respirable dust)(8 hours):4 mg/m ³	
Mineral oils, highly-refined oils	8042-47-5	Ireland OELs	TWA(inhalable fraction)(8 hours):5 mg/m ³	

Ireland OELs : Ireland. OELs

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

Biological limit values

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

Derived no effect level (DNEL)

Ingredient	Degradation Product	Population	Human exposure pattern	DNEL
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics		Worker	Dermal, Long-term exposure (8 hours), Systemic effects	185 mg/kg bw/d
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics		Worker	Inhalation, Long-term exposure (8 hours), Systemic effects	871 mg/m ³

Recommended monitoring procedures:Information on recommended monitoring procedures can be obtained from Indust. Inspect./Ministry (IE)

8.2. Exposure controls

In addition, refer to the annex for more information.

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)**Eye/face protection**

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety glasses with side shields.

Applicable Norms/Standards

Use eye protection conforming to EN 166

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended:

Material	Thickness (mm)	Breakthrough Time
Polymer laminate	No data available	No data available

Applicable Norms/Standards

Use gloves tested to EN 374

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

Applicable Norms/Standards

Use a respirator conforming to EN 140 or EN 136: filter types A & P

8.2.3. Environmental exposure controls

Refer to Annex

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid.
Specific Physical Form:	Creamy, White Liquid
Colour	White
Odor	Little Odor
Odour threshold	<i>No data available.</i>
Melting point/freezing point	<i>No data available.</i>
Boiling point/boiling range	100 °C
Flammability (solid, gas)	Not applicable.
Flammable Limits(LEL)	0.8 %
Flammable Limits(UEL)	6 %
Flash point	64 °C
Autoignition temperature	<i>No data available.</i>
Decomposition temperature	<i>No data available.</i>
pH	8.4 - 9.2
Kinematic Viscosity	10,256 mm ² /sec
Water solubility	Complete
Solubility- non-water	Complete [<i>Details: Complete</i>]
Partition coefficient: n-octanol/water	<i>No data available.</i>

Vapour pressure	<i>No data available.</i>
Density	0.975 - 0.995 g/ml
Relative density	0.975 - 0.995 [Ref Std: WATER=1]
Relative Vapour Density	1 [Ref Std: AIR=1]

9.2. Other information

9.2.2 Other safety characteristics

EU Volatile Organic Compounds	<i>No data available.</i>
Evaporation rate	<i>No data available.</i>
Percent volatile	70 %

SECTION 10: Stability and reactivity

10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

Sparks and/or flames.
Heat.

10.5 Incompatible materials

Alkali and alkaline earth metals.
Strong oxidising agents.

10.6 Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
Hydrocarbons.	Not specified.
Carbon monoxide	Not specified.
Carbon dioxide.	Not specified.

SECTION 11: Toxicological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from internal hazard assessments.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. Dust from cutting, grinding, sanding or machining may cause irritation of the respiratory system: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, nose and throat pain. May cause

additional health effects (see below).

Skin contact

Mild Skin Irritation: Signs/symptoms may include localised redness, swelling, itching, and dryness.

Eye contact

Dust created by cutting, grinding, sanding, or machining may cause eye irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea. May cause additional health effects (see below).

Additional Health Effects:

Prolonged or repeated exposure may cause target organ effects:

Central neuropathy: Signs/symptoms may include irritability, memory impairment, personality changes, sleep disorders, and decreased ability to concentrate.

Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	Inhalation-Vapour	Professional judgement	LC50 estimated to be 20 - 50 mg/l
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	Dermal	Rabbit	LD50 > 5,000 mg/kg
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	Ingestion	Rat	LD50 > 5,000 mg/kg
White mineral oil (petroleum)	Dermal	Rabbit	LD50 > 2,000 mg/kg
White mineral oil (petroleum)	Ingestion	Rat	LD50 > 5,000 mg/kg
Aluminium oxide	Dermal		LD50 estimated to be > 5,000 mg/kg
Aluminium oxide	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 2.3 mg/l
Aluminium oxide	Ingestion	Rat	LD50 > 5,000 mg/kg
Hydrocarbons C9-12 N-alkanes, isoalkanes cyclic aromatics (2-25%)	Dermal	Rat	LD50 > 3,400 mg/kg
Hydrocarbons C9-12 N-alkanes, isoalkanes cyclic aromatics (2-25%)	Inhalation-Vapour (4 hours)	Rat	LC50 > 16.2 mg/l
Hydrocarbons C9-12 N-alkanes, isoalkanes cyclic aromatics (2-25%)	Ingestion	Rat	LD50 > 15,000 mg/kg
morpholine	Dermal	Rabbit	LD50 500 mg/kg
morpholine	Inhalation-Vapour	Rat	LC50 estimated to be 10 - 20 mg/l
morpholine	Ingestion	Rat	LD50 1,680 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
------	---------	-------

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	Rabbit	Mild irritant
White mineral oil (petroleum)	Rabbit	No significant irritation
Aluminium oxide	Rabbit	No significant irritation
Hydrocarbons C9-12 N-alkanes, isoalkanes cyclic aromatics (2-25%)	Rabbit	Minimal irritation
morpholine	Rabbit	Corrosive

Serious Eye Damage/Irritation

Name	Species	Value
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	Rabbit	Mild irritant
White mineral oil (petroleum)	Rabbit	Mild irritant
Aluminium oxide	Rabbit	No significant irritation
Hydrocarbons C9-12 N-alkanes, isoalkanes cyclic aromatics (2-25%)	Rabbit	No significant irritation
morpholine	Rabbit	Corrosive

Skin Sensitisation

Name	Species	Value
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	Guinea pig	Not classified
White mineral oil (petroleum)	Guinea pig	Not classified
Hydrocarbons C9-12 N-alkanes, isoalkanes cyclic aromatics (2-25%)	Guinea pig	Not classified
morpholine	Guinea pig	Not classified

Respiratory Sensitisation

For the component/components, either no data is currently available or the data is not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	In Vitro	Not mutagenic
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	In vivo	Not mutagenic
White mineral oil (petroleum)	In Vitro	Not mutagenic
Aluminium oxide	In Vitro	Not mutagenic
morpholine	In Vitro	Some positive data exist, but the data are not sufficient for classification
morpholine	In vivo	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

Name	Route	Species	Value
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	Not specified.	Not available	Not carcinogenic
White mineral oil (petroleum)	Dermal	Mouse	Not carcinogenic
White mineral oil (petroleum)	Inhalation	Multiple animal species	Not carcinogenic
Aluminium oxide	Inhalation	Rat	Not carcinogenic
morpholine	Ingestion	Multiple animal species	Not carcinogenic
morpholine	Inhalation	Rat	Not carcinogenic

Reproductive Toxicity**Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test result	Exposure
------	-------	-------	---------	-------------	----------

					Duration
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	Not specified.	Not classified for female reproduction	Rat	NOAEL Not available	1 generation
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	Not specified.	Not classified for male reproduction	Rat	NOAEL Not available	28 days
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	Not specified.	Not classified for development	Rat	NOAEL Not available	during gestation
White mineral oil (petroleum)	Ingestion	Not classified for female reproduction	Rat	NOAEL 4,350 mg/kg/day	13 weeks
White mineral oil (petroleum)	Ingestion	Not classified for male reproduction	Rat	NOAEL 4,350 mg/kg/day	13 weeks
White mineral oil (petroleum)	Ingestion	Not classified for development	Rat	NOAEL 4,350 mg/kg/day	during gestation
morpholine	Ingestion	Not classified for development		NA	
morpholine	Ingestion	Toxic to male reproduction	similar compounds	NOAEL 60 mg/kg/day	2 generation

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
Hydrocarbons C9-12 N-alkanes, isoalkanes cyclic aromatics (2-25%)	Inhalation	central nervous system depression	May cause drowsiness or dizziness	similar compounds	NOAEL not available	
Hydrocarbons C9-12 N-alkanes, isoalkanes cyclic aromatics (2-25%)	Ingestion	central nervous system depression	May cause drowsiness or dizziness	similar compounds	NOAEL not available	
morpholine	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
White mineral oil (petroleum)	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 1,381 mg/kg/day	90 days
White mineral oil (petroleum)	Ingestion	liver immune system	Not classified	Rat	NOAEL 1,336 mg/kg/day	90 days
Aluminium oxide	Inhalation	pneumoconiosis	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure
Aluminium oxide	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not available	occupational exposure
Hydrocarbons C9-12 N-alkanes, isoalkanes cyclic aromatics (2-25%)	Inhalation	central nervous system	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL not available	occupational exposure
morpholine	Dermal	liver kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Guinea pig	LOAEL 900 mg/kg/day	13 days
morpholine	Dermal	hematopoietic system	Not classified	Guinea pig	NOAEL 900 mg/kg/day	13 days
morpholine	Inhalation	eyes	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure
morpholine	Inhalation	pulmonary fibrosis	May cause damage to organs though prolonged or repeated	Rat	NOAEL 0.09 mg/l	13 weeks

			exposure			
morpholine	Inhalation	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 64 mg/l	5 days
morpholine	Inhalation	liver	Not classified	Rat	LOAEL 64 mg/l	5 days
morpholine	Inhalation	heart endocrine system	Not classified	Rat	NOAEL 0.9 mg/l	13 weeks
morpholine	Inhalation	gastrointestinal tract nervous system	Not classified	Rat	NOAEL 0.53 mg/l	104 weeks
morpholine	Ingestion	kidney and/or bladder	May cause damage to organs though prolonged or repeated exposure	Rat	LOAEL 160 mg/kg/day	30 days
morpholine	Ingestion	liver respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 160 mg/kg/day	30 days
morpholine	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 800 mg/kg/day	30 days
morpholine	Ingestion	endocrine system	Not classified	Rat	NOAEL 323 mg/kg/day	4 weeks

Aspiration Hazard

Name	Value
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	Aspiration hazard
White mineral oil (petroleum)	Aspiration hazard
Hydrocarbons C9-12 N-alkanes, isoalkanes cyclic aromatics (2-25%)	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

11.2. Information on other hazards

This material does not contain any substances that are assessed to be an endocrine disruptor for human health.

SECTION 12: Ecological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

12.1. Toxicity

No product test data available.

Material	CAS #	Organism	Type	Exposure	Test endpoint	Test result
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	919-857-5	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Hydrocarbons C9-12 N-alkanes, isoalkanes cyclic aromatics (2-25%)	919-446-0	Green algae	Experimental	72 hours	EL50	4.1 mg/l
Hydrocarbons C9-12 N-alkanes, isoalkanes cyclic aromatics (2-25%)	919-446-0	Rainbow trout	Experimental	96 hours	LL50	30 mg/l
Hydrocarbons C9-12 N-alkanes, isoalkanes cyclic aromatics (2-25%)	919-446-0	Water flea	Experimental	48 hours	EL50	22 mg/l

Hydrocarbons C9-12 N-alkanes, isoalkanes cyclic aromatics (2- 25%)	919-446-0	Green algae	Experimental	72 hours	NOEL	0.76 mg/l
Hydrocarbons C9-12 N-alkanes, isoalkanes cyclic aromatics (2- 25%)	919-446-0	Water flea	Experimental	21 days	EL10	0.316 mg/l
White mineral oil (petroleum)	8042-47-5	Water flea	Analogous Compound	48 hours	EL50	>100 mg/l
White mineral oil (petroleum)	8042-47-5	Bluegill	Experimental	96 hours	LL50	>100 mg/l
White mineral oil (petroleum)	8042-47-5	Green algae	Analogous Compound	72 hours	NOEL	100 mg/l
White mineral oil (petroleum)	8042-47-5	Water flea	Analogous Compound	21 days	NOEL	>100 mg/l
Aluminium oxide	1344-28-1	Fish	Experimental	96 hours	LC50	>100 mg/l
Aluminium oxide	1344-28-1	Green algae	Experimental	72 hours	EC50	>100 mg/l
Aluminium oxide	1344-28-1	Water flea	Experimental	48 hours	LC50	>100 mg/l
Aluminium oxide	1344-28-1	Green algae	Experimental	72 hours	NOEC	>100 mg/l
Ethylene glycol monoricinoleate	106-17-2	Green algae	Analogous Compound	72 hours	EC50	0.76 mg/l
Ethylene glycol monoricinoleate	106-17-2	Water flea	Analogous Compound	48 hours	EC50	1.8 mg/l
Ethylene glycol monoricinoleate	106-17-2	Green algae	Analogous Compound	72 hours	NOEC	0.25 mg/l
morpholine	110-91-8	Activated sludge	Experimental	30 minutes	EC20	>1,000 mg/l
morpholine	110-91-8	Fish	Experimental	96 hours	LC50	100 mg/l
morpholine	110-91-8	Green algae	Experimental	96 hours	ErC50	28 mg/l
morpholine	110-91-8	Rainbow trout	Experimental	96 hours	LC50	180 mg/l
morpholine	110-91-8	Water flea	Experimental	48 hours	EC50	45 mg/l
morpholine	110-91-8	Green algae	Experimental	96 hours	NOEC	10 mg/l
morpholine	110-91-8	Water flea	Experimental	21 days	NOEC	5 mg/l

12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Hydrocarbons, C9-C11, n- alkanes, isoalkanes, cyclics, < 2% aromatics	919-857-5	Data not availbl- insufficient	N/A	N/A	N/A	N/A
Hydrocarbons C9-12 N- alkanes, isoalkanes cyclic aromatics (2-25%)	919-446-0	Analogous Compound Biodegradation	28 days	BOD	74.7 %BOD/Th OD	OECD 301F - Manometric respirometry
White mineral oil (petroleum)	8042-47-5	Experimental Biodegradation	28 days	CO2 evolution	0 %CO2 evolution/THC O2 evolution	OECD 301B - Modified sturm or CO2
Aluminium oxide	1344-28-1	Data not availbl- insufficient	N/A	N/A	N/A	N/A
Ethylene glycol monoricinoleate	106-17-2	Analogous Compound Biodegradation	28 days	CO2 evolution	100 %CO2 evolution/THC O2 evolution	OECD 301B - Modified sturm or CO2
morpholine	110-91-8	Experimental Biodegradation	28 days	Dissolv. Organic Carbon Deplet	93 %removal of DOC	OECD 301E - Modif. OECD Screen
morpholine	110-91-8	Experimental Biodegradation	31 days	Dissolv. Organic Carbon Deplet	98 %removal of DOC	OECD 302B Zahn- Wellens/EVPA

12.3 : Bioaccumulative potential

Material	Cas No.	Test type	Duration	Study Type	Test result	Protocol
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	919-857-5	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Hydrocarbons C9-12 N-alkanes, isoalkanes cyclic aromatics (2-25%)	919-446-0	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
White mineral oil (petroleum)	8042-47-5	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Aluminium oxide	1344-28-1	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Ethylene glycol monoricinoleate	106-17-2	Modeled Bioconcentration		Bioaccumulation factor	10	Catalogic™
Ethylene glycol monoricinoleate	106-17-2	Modeled Bioconcentration		Log Kow	5.9	Episuite™
morpholine	110-91-8	Experimental BCF - Fish	42 days	Bioaccumulation factor	<2.8	OECD305-Bioconcentration
morpholine	110-91-8	Experimental Bioconcentration		Log Kow	-2.55	OECD 107 log Kow shke flask mtd

12.4. Mobility in soil

Material	Cas No.	Test type	Study Type	Test result	Protocol
Ethylene glycol monoricinoleate	106-17-2	Modeled Mobility in Soil	Koc	590 l/kg	Episuite™

12.5. Results of the PBT and vPvB assessment

This material does not contain any substances that are assessed to be a PBT or vPvB

12.6. Endocrine disrupting properties

This material does not contain any substances that are assessed to be an endocrine disruptor for environmental effects

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations**13.1 Waste treatment methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. Dispose of waste product in a permitted industrial waste facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

EU waste code (product as sold)

08 01 11* Waste paint and varnish containing organic solvents or other dangerous substances
 120109* Machining emulsions and solutions free of halogens

SECTION 14: Transportation information

Not hazardous for transportation.

	Ground Transport (ADR)	Air Transport (IATA)	Marine Transport (IMDG)
14.1 UN number or ID number	No data available.	No data available.	No data available.
14.2 UN proper shipping name	No data available.	No data available.	No data available.
14.3 Transport hazard class(es)	No data available.	No data available.	No data available.
14.4 Packing group	No data available.	No data available.	No data available.
14.5 Environmental hazards	No data available.	No data available.	No data available.
14.6 Special precautions for user	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.
14.7 Marine Transport in bulk according to IMO instruments	No data available.	No data available.	No data available.
Control Temperature	No data available.	No data available.	No data available.
Emergency Temperature	No data available.	No data available.	No data available.
ADR Classification Code	No data available.	No data available.	No data available.
IMDG Segregation Code	No data available.	No data available.	No data available.

Please contact the address or phone number listed on the first page of the SDS for additional information on the transport/shipment of the material by rail (RID) or inland waterways (ADN).

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****Carcinogenicity**

Ingredient

morpholine

CAS Nbr

110-91-8

Classification

Gr. 3: Not classifiable

RegulationInternational Agency
for Research on Cancer**Global inventory status**

Contact 3M for more information.

DIRECTIVE 2012/18/EU

Seveso hazard categories, Annex 1, Part 1

None

Seveso named dangerous substances, Annex 1, Part 2

Dangerous Substances	Identifier(s)	Qualifying quantity (tonnes) for the application of	
		Lower-tier requirements	Upper-tier requirements
morpholine	110-91-8	10	50

Regulation (EU) No 649/2012

No chemicals listed

15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out for this mixture. Chemical safety assessments for the contained substances may have been carried out by the registrants of the substances in accordance with Regulation (EC) No 1907/2006, as amended.

SECTION 16: Other information**List of relevant H statements**

EUH066	Repeated exposure may cause skin dryness or cracking.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
H361f	Suspected of damaging fertility.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure: nervous system.
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Revision information:

Section 1: Product name information was modified.

Annex**1. Title**

Substance identification	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics; EC No. 919-857-5;
Exposure Scenario Name	Formulation
Lifecycle Stage	Use at industrial sites
Contributing activities	PROC 04 -Chemical production where opportunity for exposure arises PROC 08b -Transfer of substance or mixture (charging and discharging) at dedicated facilities ERC 02 -Formulation into mixture
Processes, tasks and activities covered	Mixing operations (open systems). Transfer of substance/mixture with dedicated engineering controls.
2. Operational conditions and risk management measures	
Operating Conditions	Physical state: Liquid. General operating conditions: Assumes use at not more than 20°C above ambient temperature; Duration of exposure per day at workplace [for one worker]: 8 hours/day;
Risk management measures	Under the operational conditions described above the following risk management measures apply: General risk management measures: Human health: None needed; Environmental: None needed;
Waste management measures	Do not release to waterways or sewers; Incinerate in a permitted hazardous waste incinerator;
3. Prediction of exposure	
Prediction of exposure	Human and environmental exposures are not expected to exceed the DNELs and PNECs when the identified risk management measures are adopted.

1. Title	
Substance identification	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics; EC No. 919-857-5;
Exposure Scenario Name	Industrial Use of Coatings
Lifecycle Stage	Use at industrial sites
Contributing activities	PROC 10 -Roller application or brushing ERC 04 -Use of non-reactive processing aid at industrial site (no inclusion into or onto article)
Processes, tasks and activities covered	Application with a wipe.
2. Operational conditions and risk management measures	
Operating Conditions	Physical state: Liquid. General operating conditions: Assumes use at not more than 20°C above ambient temperature; Duration of exposure per day at workplace [for one worker]: 8 hours/day;
Risk management measures	Under the operational conditions described above the following risk management measures apply: General risk management measures: Human health: None needed; Environmental: None needed;
Waste management measures	Do not release to waterways or sewers; Incinerate in a permitted hazardous waste incinerator;

3. Prediction of exposure	
Prediction of exposure	Human and environmental exposures are not expected to exceed the DNELs and PNECs when the identified risk management measures are adopted.

1. Title	
Substance identification	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics; EC No. 919-857-5;
Exposure Scenario Name	Professional Use of Coatings
Lifecycle Stage	Widespread use by professional workers
Contributing activities	PROC 10 -Roller application or brushing ERC 08a -Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor)
Processes, tasks and activities covered	Application with a wipe.
2. Operational conditions and risk management measures	
Operating Conditions	Physical state: Liquid. General operating conditions: Assumes use at not more than 20°C above ambient temperature; Duration of exposure per day at workplace [for one worker]: 8 hours/day;
Risk management measures	Under the operational conditions described above the following risk management measures apply: General risk management measures: Human health: None needed; Environmental: None needed;
Waste management measures	Do not release to waterways or sewers;
3. Prediction of exposure	
Prediction of exposure	Human and environmental exposures are not expected to exceed the DNELs and PNECs when the identified risk management measures are adopted.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into the European Union, you are responsible for all regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration.

3M Ireland MSDSs are available at www.3M.com