



Safety Data Sheet

Copyright, 2020, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

| | | | |
|---|------------|-------------------------|------------|
| Document group: | 18-9069-8 | Version number: | 9.00 |
| Revision date: | 21/10/2020 | Supersedes date: | 20/02/2019 |
| Transportation version number: 6.00 (01/06/2019) | | | |

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Scotch-Weld EC-9323-150 B/A

Product Identification Numbers

FS-9100-5472-5

7000080441

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Adhesive

1.3. Details of the supplier of the safety data sheet

| | |
|-------------------|---|
| Address: | 3M Ireland Limited, The Iveagh Building, The Park, Carrickmines, Dublin 18. |
| Telephone: | +353 1 280 3555 |
| E Mail: | tox.uk@mmm.com |
| Website: | www.3M.com |

1.4. Emergency telephone number

Emergency medical information: 8am-10pm (seven days) contact National Poisons Information Centre, Beaumont Hospital, Dublin 9 DOV2NO, Ireland. Telephone Number: +353 (0)1 809 2166

This product is a kit or a multipart product which consists of multiple, independently packaged components. A Safety Data Sheet for each of these components is included. Please do not separate the component Safety Data Sheets from this cover page. The document numbers of the MSDSs for components of this product are:

18-5967-7, 11-3739-7

TRANSPORTATION INFORMATION

FS-9100-5472-5

Component 1

ADR/RID: UN3259, AMINES, SOLID, CORROSIVE, N.O.S., LIMITED QUANTITY, (3,3'-OXYBIS(ETHYLENEOXY)BIS(PROPYLAMINE)), 8., II, (E), ADR Classification Code: C8.

IMDG-CODE: UN3259, AMINES, SOLID, CORROSIVE, N.O.S., (3,3'-OXYBIS(ETHYLENEOXY)BIS(PROPYLAMINE)), 8., II, IMDG-Code segregation code: 18 - ALKALIS, LIMITED QUANTITY, EMS: FA, SB.

ICAO/IATA: UN3259, AMINES, SOLID, CORROSIVE, N.O.S., (3,3'-OXYBIS(ETHYLENEOXY)BIS(PROPYLAMINE)), 8., II.

Component 2

ADR/RID: UN3077, NOT RESTRICTED AS PER SPECIAL PROVISION 375, ENVIRONMENTALLY HAZARDOUS SUBSTANCE EXEMPTION, (EPOXY RESIN), III, --.

IMDG-CODE: UN3077, NOT RESTRICTED AS PER IMDG CODE 2.10.2.7, MARINE POLLUTANT EXCEPTION, (EPOXY RESIN), III, IMDG-Code segregation code: NONE, EMS: --.

ICAO/IATA: UN3077, NOT RESTRICTED AS PER SPECIAL PROVISION A197, ENVIRONMENTALLY HAZARDOUS SUBSTANCE EXEMPTION, (EPOXY RESIN), III.

KIT LABEL

2.1. Classification of the substance or mixture

CLP REGULATION (EC) No 1272/2008

CLASSIFICATION:

Serious Eye Damage/Eye Irritation, Category 1 - Eye Dam. 1; H318

Skin Corrosion/Irritation, Category 1B - Skin Corr. 1B; H314

Skin Sensitization, Category 1 - Skin Sens. 1; H317

Hazardous to the Aquatic Environment (Chronic), Category 2 - Aquatic Chronic 2; H411

For full text of H phrases, see Section 16.

2.2. Label elements

CLP REGULATION (EC) No 1272/2008

SIGNAL WORD

DANGER.

Symbols:

GHS05 (Corrosion) | GHS07 (Exclamation mark) | GHS09 (Environment) |

Pictograms



Contains:

bis-[4-(2,3-epoxipropoxy)phenyl]propane; 3,3'-Oxybis(ethyleneoxy)bis(propylamine); 2,4,6-tris(dimethylaminomethyl)phenol

HAZARD STATEMENTS:

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H411 Toxic to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENTS

Prevention:

| | |
|-------|---|
| P260B | Do not breathe dust. |
| P280D | Wear protective gloves, protective clothing, and eye/face protection. |

Response:

| | |
|---------------------|--|
| P303 + P361 + P353A | IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. |
| P305 + P351 + P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| P310 | Immediately call a POISON CENTRE or doctor/physician. |

Disposal:

| | |
|------|--|
| P501 | Dispose of contents/container in accordance with applicable local/regional/national/international regulations. |
|------|--|

Refer to Safety Data Sheet for component % unknown values (www.3M.com/msds).

Revision information:

Label: CLP Ingredients - kit components information was modified.

Section 1: Emergency telephone information was modified.

Label: CLP Precautionary - Prevention information was modified.

Label: CLP Precautionary - Response information was modified.



Safety Data Sheet

Copyright,2023, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

| | | | |
|------------------------|------------|-------------------------|------------|
| Document group: | 18-5967-7 | Version number: | 9.02 |
| Revision date: | 10/03/2023 | Supersedes date: | 28/09/2022 |

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Scotch-Weld(TM) EC-9323-150 B/A: Part B

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Adhesive

1.3. Details of the supplier of the safety data sheet

Address: 3M Ireland Limited, The Iveagh Building, The Park, Carrickmines, Dublin 18.
Telephone: +353 1 280 3555
E Mail: tox.uk@mmm.com
Website: www.3M.com

1.4. Emergency telephone number

Emergency medical information: 8am-10pm (seven days) contact National Poisons Information Centre, Beaumont Hospital, Dublin 9 DOV2NO, Ireland. Telephone Number: +353 (0)1 809 2166

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

CLP REGULATION (EC) No 1272/2008

The health and environmental classifications of this material have been derived using the calculation method, except in cases where test data are available or the physical form impacts classification. Classification(s) based on test data or physical form are noted below, if applicable.

CLASSIFICATION:

Skin Corrosion/Irritation, Category 2 - Skin Irrit. 2; H315
 Serious Eye Damage/Eye Irritation, Category 2 - Eye Irrit. 2; H319
 Skin Sensitization, Category 1 - Skin Sens. 1; H317
 Hazardous to the Aquatic Environment (Chronic), Category 2 - Aquatic Chronic 2; H411

For full text of H phrases, see Section 16.

2.2. Label elements

CLP REGULATION (EC) No 1272/2008

SIGNAL WORD

WARNING.

Symbols

GHS07 (Exclamation mark) | GHS09 (Environment) |

Pictograms



Ingredients:

| Ingredient | CAS Nbr | EC No. | % by Wt |
|---|-----------|-----------|---------|
| bis-[4-(2,3-epoxipropoxy)phenyl]propane | 1675-54-3 | 216-823-5 | 70 - 80 |

HAZARD STATEMENTS:

| | |
|------|--|
| H315 | Causes skin irritation. |
| H319 | Causes serious eye irritation. |
| H317 | May cause an allergic skin reaction. |
| H411 | Toxic to aquatic life with long lasting effects. |

PRECAUTIONARY STATEMENTS

Prevention:

| | |
|-------|-----------------------------------|
| P273 | Avoid release to the environment. |
| P280E | Wear protective gloves. |

Response:

| | |
|--------------------|--|
| P305 + P351 + P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| P333 + P313 | If skin irritation or rash occurs: Get medical advice/attention. |

Disposal:

| | |
|------|--|
| P501 | Dispose of contents/container in accordance with applicable local/regional/national/international regulations. |
|------|--|

16% of the mixture consists of components of unknown acute oral toxicity.

Contains 35% of components with unknown hazards to the aquatic environment.

2.3. Other hazards

None known.

This material does not contain any substances that are assessed to be a PBT or vPvB

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

| Ingredient | Identifier(s) | % | Classification according to Regulation (EC) No. 1272/2008 [CLP] |
|--|---|---------|--|
| bis-[4-(2,3-epoxipropoxy)phenyl]propane | (CAS-No.) 1675-54-3 (EC-No.) 216-823-5 (REACH-No.) 01-2119456619-26 | 70 - 80 | Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411 |
| Acrylic copolymer | Trade Secret | < 20 | Substance not classified as hazardous |
| Styrene, polymer with 1,3-Butadiene, butylacrylate and methyl methacrylate | (CAS-No.) 25101-28-4 | < 20 | Substance not classified as hazardous |
| Calcium carbonate | (CAS-No.) 471-34-1 (EC-No.) 207-439-9 (REACH-No.) 01-2119486795-18 | < 10 | Substance with a national occupational exposure limit |
| Siloxanes and Silicones, di-Me, reaction products with silica | (CAS-No.) 67762-90-7 | < 5 | Substance with a national occupational exposure limit |
| 2,6-Di-tert-butyl-p-cresol | (CAS-No.) 128-37-0 (EC-No.) 204-881-4 (REACH-No.) 01-2119555270-46,01-2119565113-46 | < 1 | Aquatic Chronic 1, H410,M=1 Aquatic Acute 1, H400,M=1 |

Please see section 16 for the full text of any H statements referred to in this section

Specific Concentration Limits

| Ingredient | Identifier(s) | Specific Concentration Limits |
|---|---|---|
| bis-[4-(2,3-epoxipropoxy)phenyl]propane | (CAS-No.) 1675-54-3 (EC-No.) 216-823-5 | (C ≥ 5%) Skin Irrit. 2, H315 (C ≥ 5%) Eye Irrit. 2, H319 |

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye contact

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

No critical symptoms or effects. See Section 11.1, information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

| <u>Substance</u> | <u>Condition</u> |
|------------------|--------------------|
| Aldehydes. | During combustion. |
| Carbon monoxide | During combustion. |
| Carbon dioxide. | During combustion. |

5.3. Advice for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible.

6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid breathing dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.)

7.2. Conditions for safe storage including any incompatibilities

Store away from heat. Store away from acids. Store away from oxidising agents. Store away from amines.

7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

| Ingredient | CAS Nbr | Agency | Limit type | Additional comments |
|----------------------------|----------------|---------------|--|----------------------------|
| 2,6-Di-tert-butyl-p-cresol | 128-37-0 | Ireland OELs | TWA(8 hours):2 mg/m ³ | |
| DUST, INERT OR NUISANCE | 471-34-1 | Ireland OELs | TWA(Total inhalable dust)(8 hours):10 mg/m ³ ;TWA(as respirable dust)(8 hours):4 mg/m ³ | |
| Limestone | 471-34-1 | Ireland OELs | TWA(Total inhalable dust)(8 hours):10 mg/m ³ ;TWA(as respirable dust)(8 hours):4 mg/m ³ | |
| Silicon dioxide | 67762-90-7 | Ireland OELs | TWA(Total inhalable dust)(8 hours):6 mg/m ³ ;TWA(as respirable dust)(8 hours):2.4 mg/m ³ | |

Ireland OELs : Ireland. OELs

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

Biological limit values

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

Derived no effect level (DNEL)

| Ingredient | Degradation Product | Population | Human exposure pattern | DNEL |
|---|----------------------------|-------------------|--|------------------------|
| bis-[4-(2,3-epoxipropoxy)phenyl]propane | | Worker | Dermal, Long-term exposure (8 hours), Systemic effects | 8.3 mg/kg bw/d |
| bis-[4-(2,3-epoxipropoxy)phenyl]propane | | Worker | Dermal, Short-term exposure, Systemic effects | 8.3 mg/kg bw/d |
| bis-[4-(2,3-epoxipropoxy)phenyl]propane | | Worker | Inhalation, Long-term exposure (8 hours), Systemic effects | 12.3 mg/m ³ |
| bis-[4-(2,3-epoxipropoxy)phenyl]propane | | Worker | Inhalation, Short-term exposure, Systemic effects | 12.3 mg/m ³ |

Predicted no effect concentrations (PNEC)

| Ingredient | Degradation Product | Compartment | PNEC |
|---|----------------------------|----------------------|----------------|
| bis-[4-(2,3-epoxipropoxy)phenyl]propane | | Freshwater | 0.003 mg/l |
| bis-[4-(2,3-epoxipropoxy)phenyl]propane | | Freshwater sediments | 0.5 mg/kg d.w. |

| | | | |
|---|--|--------------------------------|----------------|
| bis-[4-(2,3-epoxipropoxy)phenyl]propane | | Intermittent releases to water | 0.013 mg/l |
| bis-[4-(2,3-epoxipropoxy)phenyl]propane | | Marine water | 0.0003 mg/l |
| bis-[4-(2,3-epoxipropoxy)phenyl]propane | | Marine water sediments | 0.5 mg/kg d.w. |
| bis-[4-(2,3-epoxipropoxy)phenyl]propane | | Sewage Treatment Plant | 10 mg/l |

Recommended monitoring procedures: Information on recommended monitoring procedures can be obtained from Indust. Inspect./Ministry (IE)

8.2. Exposure controls

In addition, refer to the annex for more information.

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment. Provide appropriate local exhaust ventilation for cutting, grinding, sanding or machining.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect vented goggles.

Applicable Norms/Standards

Use eye protection conforming to EN 166

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended:

| Material | Thickness (mm) | Breakthrough Time |
|------------------|-------------------|-------------------|
| Polymer laminate | No data available | No data available |

Applicable Norms/Standards

Use gloves tested to EN 374

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

Applicable Norms/Standards

Use a respirator conforming to EN 140 or EN 136: filter types A & P

8.2.3. Environmental exposure controls

Refer to Annex

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|--|---|
| Physical state | Solid. |
| Specific Physical Form: | Viscous. |
| Colour | Off-White |
| Odor | Epoxy |
| Odour threshold | No data available. |
| Melting point/freezing point | Not applicable. |
| Boiling point/boiling range | No data available. |
| Flammability (solid, gas) | Not classified |
| Flammable Limits(LEL) | No data available. |
| Flammable Limits(UEL) | No data available. |
| Flash point | 150 °C |
| Autoignition temperature | No data available. |
| Decomposition temperature | No data available. |
| pH | substance/mixture is non-soluble (in water) |
| Kinematic Viscosity | 1,239,316 mm ² /sec |
| Water solubility | Nil |
| Solubility- non-water | No data available. |
| Partition coefficient: n-octanol/water | No data available. |
| Vapour pressure | No data available. |
| Density | 1.17 g/ml |
| Relative density | 1.16 - 1.2 [Ref Std: WATER=1] |
| Relative Vapour Density | No data available. |

9.2. Other information

9.2.2 Other safety characteristics

| | |
|-------------------------------|--------------------|
| EU Volatile Organic Compounds | No data available. |
| Evaporation rate | No data available. |
| Percent volatile | No data available. |

SECTION 10: Stability and reactivity

10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

Heat.

Heat is generated during cure. Do not cure a mass larger than 50 grams in a confined space to prevent a premature exothermic reaction with production of intense heat and smoke.

Sparks and/or flames.

10.5 Incompatible materials

Amines.

Strong acids.

Strong oxidising agents.

10.6 Hazardous decomposition products

| <u>Substance</u> | <u>Condition</u> |
|------------------|------------------|
| None known. | |

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from internal hazard assessments.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. Vapours from heated material may cause irritation of the respiratory system: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, nose and throat pain.

Skin contact

Mild Skin Irritation: Signs/symptoms may include localised redness, swelling, itching, and dryness.

Prolonged or repeated exposure may cause:

Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye contact

Moderate eye irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision. Vapours from heated material may cause eye irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

| Name | Route | Species | Value |
|--|--------------------------------|---------|--|
| Overall product | Inhalation-Dust/Mist(4 hr) | | No data available; calculated ATE >12.5 mg/l |
| Overall product | Ingestion | | No data available; calculated ATE >5,000 mg/kg |
| bis-[4-(2,3-epoxipropoxy)phenyl]propane | Dermal | Rat | LD50 > 1,600 mg/kg |
| bis-[4-(2,3-epoxipropoxy)phenyl]propane | Ingestion | Rat | LD50 > 1,000 mg/kg |
| Styrene, polymer with 1,3-Butadiene, butylacrylate and methyl methacrylate | Dermal | | LD50 estimated to be > 5,000 mg/kg |
| Styrene, polymer with 1,3-Butadiene, butylacrylate and methyl methacrylate | Ingestion | Rat | LD50 > 5,000 mg/kg |
| Calcium carbonate | Dermal | Rat | LD50 > 2,000 mg/kg |
| Calcium carbonate | Inhalation-Dust/Mist (4 hours) | Rat | LC50 3 mg/l |
| Calcium carbonate | Ingestion | Rat | LD50 6,450 mg/kg |
| Siloxanes and Silicones, di-Me, reaction products with silica | Dermal | Rabbit | LD50 > 5,000 mg/kg |
| Siloxanes and Silicones, di-Me, reaction products with silica | Inhalation-Dust/Mist (4 hours) | Rat | LC50 > 0.691 mg/l |
| Siloxanes and Silicones, di-Me, reaction products with silica | Ingestion | Rat | LD50 > 5,110 mg/kg |
| 2,6-Di-tert-butyl-p-cresol | Dermal | Rat | LD50 > 2,000 mg/kg |
| 2,6-Di-tert-butyl-p-cresol | Ingestion | Rat | LD50 > 2,930 mg/kg |

ATE = acute toxicity estimate

Skin Corrosion/Irritation

| Name | Species | Value |
|---|------------------|---------------------------|
| bis-[4-(2,3-epoxipropoxy)phenyl]propane | Rabbit | Mild irritant |
| Calcium carbonate | Rabbit | No significant irritation |
| Siloxanes and Silicones, di-Me, reaction products with silica | Rabbit | No significant irritation |
| 2,6-Di-tert-butyl-p-cresol | Human and animal | Minimal irritation |

Serious Eye Damage/Irritation

| Name | Species | Value |
|---|---------|---------------------------|
| bis-[4-(2,3-epoxipropoxy)phenyl]propane | Rabbit | Moderate irritant |
| Calcium carbonate | Rabbit | No significant irritation |
| Siloxanes and Silicones, di-Me, reaction products with silica | Rabbit | No significant irritation |
| 2,6-Di-tert-butyl-p-cresol | Rabbit | Mild irritant |

Skin Sensitisation

| Name | Species | Value |
|---|------------------|----------------|
| bis-[4-(2,3-epoxipropoxy)phenyl]propane | Human and animal | Sensitising |
| Siloxanes and Silicones, di-Me, reaction products with silica | Human and animal | Not classified |
| 2,6-Di-tert-butyl-p-cresol | Human | Not classified |

Respiratory Sensitisation

| Name | Species | Value |
|---|---------|----------------|
| bis-[4-(2,3-epoxipropoxy)phenyl]propane | Human | Not classified |

Germ Cell Mutagenicity

| Name | Route | Value |
|---|----------|--|
| bis-[4-(2,3-epoxipropoxy)phenyl]propane | In vivo | Not mutagenic |
| bis-[4-(2,3-epoxipropoxy)phenyl]propane | In Vitro | Some positive data exist, but the data are not sufficient for classification |
| Siloxanes and Silicones, di-Me, reaction products with silica | In Vitro | Not mutagenic |
| 2,6-Di-tert-butyl-p-cresol | In Vitro | Not mutagenic |
| 2,6-Di-tert-butyl-p-cresol | In vivo | Not mutagenic |

Carcinogenicity

| Name | Route | Species | Value |
|---|----------------|-------------------------|--|
| bis-[4-(2,3-epoxipropoxy)phenyl]propane | Dermal | Mouse | Some positive data exist, but the data are not sufficient for classification |
| Siloxanes and Silicones, di-Me, reaction products with silica | Not specified. | Mouse | Some positive data exist, but the data are not sufficient for classification |
| 2,6-Di-tert-butyl-p-cresol | Ingestion | Multiple animal species | Some positive data exist, but the data are not sufficient for classification |

Reproductive Toxicity

Reproductive and/or Developmental Effects

| Name | Route | Value | Species | Test result | Exposure Duration |
|---|-----------|--|---------|-----------------------|------------------------------|
| bis-[4-(2,3-epoxipropoxy)phenyl]propane | Ingestion | Not classified for female reproduction | Rat | NOAEL 750 mg/kg/day | 2 generation |
| bis-[4-(2,3-epoxipropoxy)phenyl]propane | Ingestion | Not classified for male reproduction | Rat | NOAEL 750 mg/kg/day | 2 generation |
| bis-[4-(2,3-epoxipropoxy)phenyl]propane | Dermal | Not classified for development | Rabbit | NOAEL 300 mg/kg/day | during organogenesis |
| bis-[4-(2,3-epoxipropoxy)phenyl]propane | Ingestion | Not classified for development | Rat | NOAEL 750 mg/kg/day | 2 generation |
| Calcium carbonate | Ingestion | Not classified for development | Rat | NOAEL 625 mg/kg/day | premating & during gestation |
| Siloxanes and Silicones, di-Me, reaction products with silica | Ingestion | Not classified for female reproduction | Rat | NOAEL 509 mg/kg/day | 1 generation |
| Siloxanes and Silicones, di-Me, reaction products with silica | Ingestion | Not classified for male reproduction | Rat | NOAEL 497 mg/kg/day | 1 generation |
| Siloxanes and Silicones, di-Me, reaction products with silica | Ingestion | Not classified for development | Rat | NOAEL 1,350 mg/kg/day | during organogenesis |
| 2,6-Di-tert-butyl-p-cresol | Ingestion | Not classified for female reproduction | Rat | NOAEL 500 mg/kg/day | 2 generation |
| 2,6-Di-tert-butyl-p-cresol | Ingestion | Not classified for male reproduction | Rat | NOAEL 500 mg/kg/day | 2 generation |
| 2,6-Di-tert-butyl-p-cresol | Ingestion | Not classified for development | Rat | NOAEL 100 mg/kg/day | 2 generation |

Target Organ(s)

Specific Target Organ Toxicity - single exposure

| Name | Route | Target Organ(s) | Value | Species | Test result | Exposure Duration |
|-------------------|------------|--------------------|----------------|---------|------------------|-------------------|
| Calcium carbonate | Inhalation | respiratory system | Not classified | Rat | NOAEL 0.812 mg/l | 90 minutes |

Specific Target Organ Toxicity - repeated exposure

| Name | Route | Target Organ(s) | Value | Species | Test result | Exposure Duration |
|---|--------|-----------------|----------------|---------|-----------------------|-------------------|
| bis-[4-(2,3-epoxipropoxy)phenyl]propane | Dermal | liver | Not classified | Rat | NOAEL 1,000 mg/kg/day | 2 years |
| bis-[4-(2,3- | Dermal | nervous system | Not classified | Rat | NOAEL | 13 weeks |

| | | | | | | |
|---|------------|--|--|-------|-----------------------|-----------------------|
| epoxipropoxi)phenyl]propane | | | | | 1,000 mg/kg/day | |
| bis-[4-(2,3-epoxipropoxi)phenyl]propane | Ingestion | auditory system heart endocrine system hematopoietic system liver eyes kidney and/or bladder | Not classified | Rat | NOAEL 1,000 mg/kg/day | 28 days |
| Calcium carbonate | Inhalation | respiratory system | Not classified | Human | NOAEL Not available | occupational exposure |
| Siloxanes and Silicones, di-Me, reaction products with silica | Inhalation | respiratory system silicosis | Not classified | Human | NOAEL Not available | occupational exposure |
| 2,6-Di-tert-butyl-p-cresol | Ingestion | liver | Some positive data exist, but the data are not sufficient for classification | Rat | NOAEL 250 mg/kg/day | 28 days |
| 2,6-Di-tert-butyl-p-cresol | Ingestion | kidney and/or bladder | Not classified | Rat | NOAEL 500 mg/kg/day | 2 generation |
| 2,6-Di-tert-butyl-p-cresol | Ingestion | blood | Not classified | Rat | LOAEL 420 mg/kg/day | 40 days |
| 2,6-Di-tert-butyl-p-cresol | Ingestion | endocrine system | Not classified | Rat | NOAEL 25 mg/kg/day | 2 generation |
| 2,6-Di-tert-butyl-p-cresol | Ingestion | heart | Not classified | Mouse | NOAEL 3,480 mg/kg/day | 10 weeks |

Aspiration Hazard

For the component/components, either no data is currently available or the data is not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

11.2. Information on other hazards

This material does not contain any substances that are assessed to be an endocrine disruptor for human health.

SECTION 12: Ecological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

12.1. Toxicity

No product test data available.

| Material | CAS # | Organism | Type | Exposure | Test endpoint | Test result |
|---|-----------|------------------|--------------------|----------|---------------|-------------|
| bis-[4-(2,3-epoxipropoxi)phenyl]propane | 1675-54-3 | Activated sludge | Analogous Compound | 3 hours | IC50 | >100 mg/l |
| bis-[4-(2,3-epoxipropoxi)phenyl]propane | 1675-54-3 | Rainbow trout | Estimated | 96 hours | LC50 | 2 mg/l |
| bis-[4-(2,3-epoxipropoxi)phenyl]propane | 1675-54-3 | Water flea | Estimated | 48 hours | EC50 | 1.8 mg/l |
| bis-[4-(2,3-epoxipropoxi)phenyl]propane | 1675-54-3 | Green algae | Experimental | 72 hours | ErC50 | >11 mg/l |

| | | | | | | |
|--|------------|------------------|---|----------|--------------------------------|--------------|
| bis-[4-(2,3-epoxipropoxy)phenyl]propane | 1675-54-3 | Green algae | Experimental | 72 hours | NOEC | 4.2 mg/l |
| bis-[4-(2,3-epoxipropoxy)phenyl]propane | 1675-54-3 | Water flea | Experimental | 21 days | NOEC | 0.3 mg/l |
| Styrene, polymer with 1,3-Butadiene, butylacrylate and methyl methacrylate | 25101-28-4 | N/A | Data not available or insufficient for classification | N/A | N/A | N/A |
| Calcium carbonate | 471-34-1 | Green algae | Experimental | 72 hours | EC50 | >100 mg/l |
| Calcium carbonate | 471-34-1 | Rainbow trout | Experimental | 96 hours | LC50 | >100 mg/l |
| Calcium carbonate | 471-34-1 | Water flea | Experimental | 48 hours | EC50 | >100 mg/l |
| Calcium carbonate | 471-34-1 | Green algae | Experimental | 72 hours | EC10 | 100 mg/l |
| Siloxanes and Silicones, di-Me, reaction products with silica | 67762-90-7 | N/A | Data not available or insufficient for classification | N/A | N/A | N/A |
| 2,6-Di-tert-butyl-p-cresol | 128-37-0 | Activated sludge | Experimental | 3 hours | EC50 | >10,000 mg/l |
| 2,6-Di-tert-butyl-p-cresol | 128-37-0 | Green algae | Experimental | 72 hours | EC50 | >0.4 mg/l |
| 2,6-Di-tert-butyl-p-cresol | 128-37-0 | Water flea | Experimental | 48 hours | EC50 | 0.48 mg/l |
| 2,6-Di-tert-butyl-p-cresol | 128-37-0 | Zebra Fish | Experimental | 96 hours | No tox obs at lmt of water sol | >100 mg/l |
| 2,6-Di-tert-butyl-p-cresol | 128-37-0 | Green algae | Experimental | 72 hours | EC10 | 0.4 mg/l |
| 2,6-Di-tert-butyl-p-cresol | 128-37-0 | Medaka | Experimental | 42 days | NOEC | 0.053 mg/l |
| 2,6-Di-tert-butyl-p-cresol | 128-37-0 | Water flea | Experimental | 21 days | NOEC | 0.023 mg/l |

12.2. Persistence and degradability

| Material | CAS Nbr | Test type | Duration | Study Type | Test result | Protocol |
|--|------------|-------------------------------|----------|-----------------------------|-------------------|-------------------------------------|
| bis-[4-(2,3-epoxipropoxy)phenyl]propane | 1675-54-3 | Experimental Biodegradation | 28 days | BOD | 5 %BOD/COD | OECD 301F - Manometric respirometry |
| bis-[4-(2,3-epoxipropoxy)phenyl]propane | 1675-54-3 | Experimental Hydrolysis | | Hydrolytic half-life (pH 7) | 117 hours (t 1/2) | OECD 111 Hydrolysis func of pH |
| Styrene, polymer with 1,3-Butadiene, butylacrylate and methyl methacrylate | 25101-28-4 | Data not availbl-insufficient | N/A | N/A | N/A | N/A |
| Calcium carbonate | 471-34-1 | Data not availbl-insufficient | N/A | N/A | N/A | N/A |
| Siloxanes and Silicones, di-Me, reaction products with silica | 67762-90-7 | Data not availbl-insufficient | N/A | N/A | N/A | N/A |
| 2,6-Di-tert-butyl-p-cresol | 128-37-0 | Data not availbl-insufficient | N/A | N/A | N/A | N/A |

12.3 : Bioaccumulative potential

| Material | Cas No. | Test type | Duration | Study Type | Test result | Protocol |
|--|------------|--|----------|------------|-------------|------------------------------|
| bis-[4-(2,3-epoxipropoxy)phenyl]propane | 1675-54-3 | Experimental Bioconcentration | | Log Kow | 3.242 | OECD 117 log Kow HPLC method |
| Styrene, polymer with 1,3-Butadiene, butylacrylate | 25101-28-4 | Data not available or insufficient for | N/A | N/A | N/A | N/A |

| | | | | | | |
|---|------------|---|---------|------------------------|------|--------------------------|
| and methyl methacrylate | | classification | | | | |
| Calcium carbonate | 471-34-1 | Data not available or insufficient for classification | N/A | N/A | N/A | N/A |
| Siloxanes and Silicones, di-Me, reaction products with silica | 67762-90-7 | Data not available or insufficient for classification | N/A | N/A | N/A | N/A |
| 2,6-Di-tert-butyl-p-cresol | 128-37-0 | Experimental BCF - Fish | 56 days | Bioaccumulation factor | 1277 | OECD305-Bioconcentration |

12.4. Mobility in soil

| Material | Cas No. | Test type | Study Type | Test result | Protocol |
|---|-----------|--------------------------|------------|-------------|-----------|
| bis-[4-(2,3-epoxipropoxy)phenyl]propane | 1675-54-3 | Modeled Mobility in Soil | Koc | 450 l/kg | Episuite™ |

12.5. Results of the PBT and vPvB assessment

This material does not contain any substances that are assessed to be a PBT or vPvB

12.6. Endocrine disrupting properties

This material does not contain any substances that are assessed to be an endocrine disruptor for environmental effects

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

EU waste code (product as sold)

08 04 09* Waste adhesives and sealants containing organic solvents or other dangerous substances
20 01 27* Paint, inks, adhesives and resins containing dangerous substances

SECTION 14: Transportation information

| | Ground Transport (ADR) | Air Transport (IATA) | Marine Transport (IMDG) |
|--|------------------------|----------------------|-------------------------|
| | | | |

| | | | |
|---|--|--|--|
| 14.1 UN number or ID number | UN3077 | UN3077 | UN3077 |
| 14.2 UN proper shipping name | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.(EPOXY RESIN) | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.(EPOXY RESIN) | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.(EPOXY RESIN) |
| 14.3 Transport hazard class(es) | 9 | 9 | 9 |
| 14.4 Packing group | III | III | III |
| 14.5 Environmental hazards | Environmentally Hazardous | Not applicable | Marine Pollutant |
| 14.6 Special precautions for user | Please refer to the other sections of the SDS for further information. | Please refer to the other sections of the SDS for further information. | Please refer to the other sections of the SDS for further information. |
| 14.7 Marine Transport in bulk according to IMO instruments | No data available. | No data available. | No data available. |
| Control Temperature | No data available. | No data available. | No data available. |
| Emergency Temperature | No data available. | No data available. | No data available. |
| ADR Classification Code | M7 | Not applicable. | Not applicable. |
| IMDG Segregation Code | Not applicable. | Not applicable. | NONE |

Please contact the address or phone number listed on the first page of the SDS for additional information on the transport/shipment of the material by rail (RID) or inland waterways (ADN).

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Carcinogenicity

| <u>Ingredient</u> | <u>CAS Nbr</u> | <u>Classification</u> | <u>Regulation</u> |
|---|----------------|-------------------------|---|
| bis-[4-(2,3-epoxipropoxy)phenyl]propane | 1675-54-3 | Gr. 3: Not classifiable | International Agency for Research on Cancer |
| 2,6-Di-tert-butyl-p-cresol | 128-37-0 | Gr. 3: Not classifiable | International Agency for Research on Cancer |

Restrictions on the manufacture, placing on the market and use:

The following substance(s) contained in this product is/are subject through Annex XVII of REACH regulation to restrictions on the manufacture, placing on the market and use when present in certain dangerous substances, mixtures and articles. Users of this product are required to comply with the restrictions placed upon it by the aforementioned provision.

bis-[4-(2,3-epoxipropoxy)phenyl]propane

1675-54-3

Global inventory status

Contact 3M for more information.

DIRECTIVE 2012/18/EU

Seveso hazard categories, Annex 1, Part 1

None

Seveso named dangerous substances, Annex 1, Part 2

None

Regulation (EU) No 649/2012

No chemicals listed

15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out for this mixture. Chemical safety assessments for the contained substances may have been carried out by the registrants of the substances in accordance with Regulation (EC) No 1907/2006, as amended.

SECTION 16: Other information

List of relevant H statements

| | |
|------|---|
| H315 | Causes skin irritation. |
| H317 | May cause an allergic skin reaction. |
| H319 | Causes serious eye irritation. |
| H400 | Very toxic to aquatic life. |
| H410 | Very toxic to aquatic life with long lasting effects. |
| H411 | Toxic to aquatic life with long lasting effects. |

Revision information:

Formulation: Section 16: Annex information was added.
 Section 3: Composition/ Information of ingredients table information was modified.
 Section 8: 8.2. Exposure controls information information was added.
 Section 8: 8.2.3. Environmental exposure controls information information was added.
 Section 8: DNEL table row information was added.
 Section 8: Occupational exposure limit table information was modified.
 Section 8: PNEC table row information was added.
 Section 9: Vapour density value information was modified.
 Section 12: Component ecotoxicity information information was modified.
 Section 12: Mobility in soil information information was added.
 Section 12: No Data text for mobility in soil information was deleted.
 Section 12: Persistence and Degradability information information was modified.
 Section 12: Bioaccumulative potential information information was modified.
 Section 14 Classification Code – Regulation Data information was modified.
 Section 14 Hazard Class + Sub Risk – Regulation Data information was modified.
 Section 14 Hazardous/Not Hazardous for Transportation information was modified.
 Section 14 Other Dangerous Goods – Regulation Data information was modified.
 Section 14 Packing Group – Regulation Data information was modified.
 Section 14 Proper Shipping Name information was modified.
 Section 14 Segregation – Regulation Data information was modified.
 Section 14 UN Number Column data information was modified.

Section 14: Transportation classification information was deleted.

Annex: Prediction of exposure statement information was added.

Annex

| | |
|---|---|
| 1. Title | |
| Substance identification | bis-[4-(2,3-epoxipropoxy)phenyl]propane; EC No. 216-823-5; CAS Nbr 1675-54-3; |
| Exposure Scenario Name | Formulation |
| Lifecycle Stage | Formulation or re-packing |
| Contributing activities | PROC 09 -Transfer of substance or mixture into small containers (dedicated filling line, including weighing) ERC 02 -Formulation into mixture |
| Processes, tasks and activities covered | Batch manufacture of a chemical substance or formulation (including polymerisation reactions). |
| 2. Operational conditions and risk management measures | |
| Operating Conditions | Physical state: Liquid. General operating conditions: Duration of use: 8 hours/day; Emission days per year: <= 225 days per year; |
| Risk management measures | Under the operational conditions described above the following risk management measures apply: General risk management measures: Human health: Protective Gloves - Chemical resistant. Refer to Section 8 of the SDS for specific glove material.; Environmental: Waste Water treatment - Incineration; |
| Waste management measures | Do not apply industrial sludge to natural soils; Prevent leaks and prevent soil / water pollution caused by leaks; |
| 3. Prediction of exposure | |
| Prediction of exposure | Human and environmental exposures are not expected to exceed the DNELs and PNECs when the identified risk management measures are adopted. |

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into the European Union, you are responsible for all regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration.

3M Ireland MSDSs are available at www.3M.com



Safety Data Sheet

Copyright, 2020, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group: 11-3739-7
Revision date: 21/10/2020
Transportation version number:

Version number: 14.00
Supersedes date: 20/02/2019

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

SCOTCH-WELD(TM) EC-9323-150 B/A: Part A

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Adhesive

1.3. Details of the supplier of the safety data sheet

Address: 3M Ireland Limited, The Iveagh Building, The Park, Carrickmines, Dublin 18.
Telephone: +353 1 280 3555
E Mail: tox.uk@mmm.com
Website: www.3M.com

1.4. Emergency telephone number

Emergency medical information: 8am-10pm (seven days) contact National Poisons Information Centre, Beaumont Hospital, Dublin 9 DOV2NO, Ireland. Telephone Number: +353 (0)1 809 2166

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture CLP REGULATION (EC) No 1272/2008

The health and environmental classifications of this material have been derived using the calculation method, except in cases where test data are available or the physical form impacts classification. Classification(s) based on test data or physical form are noted below, if applicable.

CLASSIFICATION:

Serious Eye Damage/Eye Irritation, Category 1 - Eye Dam. 1; H318
Skin Corrosion/Irritation, Category 1B - Skin Corr. 1B; H314
Skin Sensitization, Category 1 - Skin Sens. 1; H317

For full text of H phrases, see Section 16.

2.2. Label elements

CLP REGULATION (EC) No 1272/2008

SIGNAL WORD

DANGER.

Symbols:

GHS05 (Corrosion) | GHS07 (Exclamation mark) |

Pictograms



Ingredients:

| Ingredient | CAS Nbr | EC No. | % by Wt |
|--|-----------|-----------|---------|
| 3,3'-Oxybis(ethyleneoxy)bis(propylamine) | 4246-51-9 | 224-207-2 | 60 - 90 |
| 2,4,6-tris(dimethylaminomethyl)phenol | 90-72-2 | 202-013-9 | 7 - 13 |

HAZARD STATEMENTS:

| | |
|------|--|
| H314 | Causes severe skin burns and eye damage. |
| H317 | May cause an allergic skin reaction. |

PRECAUTIONARY STATEMENTS

Prevention:

| | |
|-------|---|
| P260B | Do not breathe dust. |
| P280D | Wear protective gloves, protective clothing, and eye/face protection. |

Response:

| | |
|---------------------|--|
| P303 + P361 + P353A | IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. |
| P305 + P351 + P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| P310 | Immediately call a POISON CENTRE or doctor/physician. |
| P333 + P313 | If skin irritation or rash occurs: Get medical advice/attention. |

Contains 2% of components with unknown hazards to the aquatic environment.

2.3. Other hazards

None known.

SECTION 3: Composition/information on ingredients

| Ingredient | CAS Nbr | EC No. | REACH Registration No. | % by Wt | Classification |
|---|-------------|-----------|------------------------|---------|---|
| 3,3'-Oxybis(ethyleneoxy)bis(propylamine) | 4246-51-9 | 224-207-2 | 01-2119963377-26 | 60 - 90 | Skin Sens. 1, H317 Skin Corr. 1B, H314 |
| Synthetic amorphous silica, fumed, crystalline-free | 112945-52-5 | | 01-2119379499- | 7 - 13 | Substance with an occupational exposure limit |

| | | | | | |
|---------------------------------------|------------|-----------|------------------|--------|--|
| | | | 16 | | |
| 2,4,6-tris(dimethylaminomethyl)phenol | 90-72-2 | 202-013-9 | 01-2119560597-27 | 7 - 13 | Acute Tox. 4, H302 Skin Corr. 1C, H314; Eye Dam. 1, H318 |
| Glass, oxide, chemicals | 65997-17-3 | 266-046-0 | | 1 - 5 | Substance with an occupational exposure limit |
| Bis[(dimethylamino)methyl]phenol | 71074-89-0 | 275-162-0 | | 1 - 3 | Acute Tox. 4, H302; Skin Corr. 1C, H314 |

Please see section 16 for the full text of any H statements referred to in this section

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Immediately flush with large amounts of water for at least 15 minutes. Remove contaminated clothing. Get immediate medical attention. Wash clothing before reuse.

Eye contact

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

If swallowed

Rinse mouth. Do not induce vomiting. Get immediate medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1 Information on toxicological effects

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

Substance

Carbon monoxide
Carbon dioxide.

Condition

During combustion.
During combustion.

5.3. Advice for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible.

6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Wash contaminated clothing before reuse. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.)

7.2. Conditions for safe storage including any incompatibilities

Store away from heat. Store away from acids. Store away from strong bases. Store away from oxidising agents.

7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

| Ingredient | CAS Nbr | Agency | Limit type | Additional comments |
|-------------------------|----------------|-------------------------|---|----------------------------|
| Silicon dioxide | 112945-52-5 | UK HSC | TWA(as respirable dust):2.4 mg/m ³ ;TWA(as inhalable dust):6 mg/m ³ | |
| Glass, oxide, chemicals | 65997-17-3 | UK HSC | TWA(as fiber):5 mg/m ³ (0.3 fibers/ml) | |
| Glass, oxide, chemicals | 65997-17-3 | Manufacturer determined | TWA(as non-fibrous, respirable)(8 hours):3 mg/m ³ ;TWA(as non-fibrous, inhalable fraction)(8 hours):10 mg/m ³ | |

UK HSC : UK Health and Safety Commission

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

Biological limit values

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

Derived no effect level (DNEL)

| Ingredient | Degradation Product | Population | Human exposure pattern | DNEL |
|--|----------------------------|-------------------|--|------------------------|
| 2,4,6-tris(dimethylaminomethyl) phenol | | Worker | Inhalation, Long-term exposure (8 hours), Systemic effects | 0.31 mg/m ³ |
| 3,3'-Oxybis(ethyleneoxy)bis(propylamine) | | Worker | Dermal, Long-term exposure (8 hours), Systemic effects | 8.3 mg/kg bw/d |
| 3,3'-Oxybis(ethyleneoxy)bis(propylamine) | | Worker | Inhalation, Long-term exposure (8 hours), Local effects | 1 mg/m ³ |
| 3,3'-Oxybis(ethyleneoxy)bis(propylamine) | | Worker | Inhalation, Long-term exposure (8 hours), Systemic effects | 59 mg/m ³ |
| 3,3'-Oxybis(ethyleneoxy)bis(propylamine) | | Worker | Inhalation, Short-term exposure, Local effects | 13 mg/m ³ |
| 3,3'-Oxybis(ethyleneoxy)bis(propylamine) | | Worker | Inhalation, Short-term exposure, Systemic effects | 176 mg/m ³ |

Predicted no effect concentrations (PNEC)

| Ingredient | Degradation Product | Compartment | PNEC |
|--|----------------------------|--------------------------------|-------------------|
| 2,4,6-tris(dimethylaminomethyl) phenol | | Freshwater | 0.084 mg/l |
| 2,4,6-tris(dimethylaminomethyl) phenol | | Intermittent releases to water | 0.84 mg/l |
| 2,4,6-tris(dimethylaminomethyl) phenol | | Marine water | 0.0084 mg/l |
| 2,4,6-tris(dimethylaminomethyl) phenol | | Sewage Treatment Plant | 0.2 mg/l |
| 3,3'-Oxybis(ethyleneoxy)bis(propylamine) | | Freshwater | 0.22 mg/l |
| 3,3'-Oxybis(ethyleneoxy)bis(propylamine) | | Freshwater sediments | 0.809 mg/kg d.w. |
| 3,3'-Oxybis(ethyleneoxy)bis(propylamine) | | Intermittent releases to water | 2.2 mg/l |
| 3,3'-Oxybis(ethyleneoxy)bis(propylamine) | | Marine water | 0.022 mg/l |
| 3,3'-Oxybis(ethyleneoxy)bis(propylamine) | | Marine water sediments | 0.0809 mg/kg d.w. |
| 3,3'-Oxybis(ethyleneoxy)bis(propylamine) | | Sewage Treatment Plant | 125 mg/l |

| | | | |
|------------|--|--|--|
| opylamine) | | | |
|------------|--|--|--|

Recommended monitoring procedures: Information on recommended monitoring procedures can be obtained from Indust. Inspect./Ministry (IE)

8.2. Exposure controls

In addition, refer to the annex for more information.

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Full face shield.

Indirect vented goggles.

Applicable Norms/Standards

Use eye/face protection conforming to EN 166

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended:

| Material | Thickness (mm) | Breakthrough Time |
|------------------|-------------------|-------------------|
| Polymer laminate | No data available | No data available |
| Butyl rubber. | 0.7 | > 8 hours |
| Fluoroelastomer | 0.7 | > 8 hours |

The glove data presented are based on the substance driving dermal toxicity and the conditions present at the time of testing. Breakthrough time may be altered when the glove is subjected to use conditions that place additional stress on the glove.

Applicable Norms/Standards

Use gloves tested to EN 374

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron – Butyl rubber
Apron - polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

Applicable Norms/Standards

Use a respirator conforming to EN 140 or EN 136: filter types A & P

8.2.3. Environmental exposure controls

Refer to Annex

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state

Solid.

Colour

Red

Specific Physical Form:

Paste

Odor

Amine

Odour threshold

No data available.

pH

Not applicable.

Boiling point/boiling range

No data available.

Melting point

No data available.

Flammability (solid, gas)

Not classified

Explosive properties

Not classified

Oxidising properties

Not classified

Flash point

≥ 100 °C [*Test Method: Estimated*]

Autoignition temperature

No data available.

Flammable Limits(LEL)

No data available.

Flammable Limits(UEL)

No data available.

Relative density

1.03 - 1.13 [*Ref Std: WATER=1*]

Water solubility

Negligible

Solubility- non-water

No data available.

Partition coefficient: n-octanol/water

No data available.

Evaporation rate

No data available.

Vapour density

No data available.

Decomposition temperature

No data available.

Viscosity

10 - 25 Pa-s [*@ 23 °C*]

Density

1.08 g/cm³

9.2. Other information

EU Volatile Organic Compounds

No data available.

SECTION 10: Stability and reactivity

10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

Avoid curing large quantities of material to prevent a premature reaction (exotherm) with production of intense heat and smoke.

Heat.
Sparks and/or flames.

10.5 Incompatible materials

Strong acids.
Strong bases.
Strong oxidising agents.

10.6 Hazardous decomposition products

Substance

Condition

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from internal hazard assessments.

11.1 Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

May be harmful if inhaled. Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Skin contact

May be harmful in contact with skin. Corrosive (skin burns): Signs/symptoms may include localised redness, swelling, itching, intense pain, blistering, ulceration, and tissue destruction.

Eye contact

Corrosive (eye burns): Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision.

Ingestion

May be harmful if swallowed.

Gastrointestinal corrosion: Signs/symptoms may include severe mouth, throat and abdominal pain, nausea, vomiting, and diarrhea; blood in the faeces and/or vomitus may also be seen.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

| Name | Route | Species | Value |
|-----------------|----------------------------|---------|--|
| Overall product | Dermal | | No data available; calculated ATE _{2,000} - 5,000 mg/kg |
| Overall product | Inhalation-Dust/Mist(4 hr) | | No data available; calculated ATE ₅ - 12.5 mg/l |
| Overall product | Ingestion | | No data available; calculated ATE _{2,000} - 5,000 mg/kg |

| | | | |
|---|--------------------------------|--------|--|
| 3,3'-Oxybis(ethyleneoxy)bis(propylamine) | Dermal | Rabbit | LD50 2,500 mg/kg |
| 3,3'-Oxybis(ethyleneoxy)bis(propylamine) | Ingestion | Rat | LD50 3,160 mg/kg |
| 2,4,6-tris(dimethylaminomethyl)phenol | Dermal | Rat | LD50 1,280 mg/kg |
| 2,4,6-tris(dimethylaminomethyl)phenol | Ingestion | Rat | LD50 1,000 mg/kg |
| Synthetic amorphous silica, fumed, crystalline-free | Dermal | Rabbit | LD50 > 5,000 mg/kg |
| Synthetic amorphous silica, fumed, crystalline-free | Inhalation-Dust/Mist (4 hours) | Rat | LC50 > 0.691 mg/l |
| Synthetic amorphous silica, fumed, crystalline-free | Ingestion | Rat | LD50 > 5,110 mg/kg |
| Glass, oxide, chemicals | Dermal | | LD50 estimated to be > 5,000 mg/kg |
| Glass, oxide, chemicals | Ingestion | | LD50 estimated to be 2,000 - 5,000 mg/kg |
| Bis[(dimethylamino)methyl]phenol | Ingestion | | LD50 estimated to be 300 - 2,000 mg/kg |

ATE = acute toxicity estimate

Skin Corrosion/Irritation

| Name | Species | Value |
|---|------------------------|---------------------------|
| 3,3'-Oxybis(ethyleneoxy)bis(propylamine) | Rabbit | Corrosive |
| 2,4,6-tris(dimethylaminomethyl)phenol | Rabbit | Corrosive |
| Synthetic amorphous silica, fumed, crystalline-free | Rabbit | No significant irritation |
| Glass, oxide, chemicals | Professional judgement | No significant irritation |
| Bis[(dimethylamino)methyl]phenol | similar compounds | Corrosive |

Serious Eye Damage/Irritation

| Name | Species | Value |
|---|------------------------|---------------------------|
| 3,3'-Oxybis(ethyleneoxy)bis(propylamine) | similar health hazards | Corrosive |
| 2,4,6-tris(dimethylaminomethyl)phenol | Rabbit | Corrosive |
| Synthetic amorphous silica, fumed, crystalline-free | Rabbit | No significant irritation |
| Glass, oxide, chemicals | Professional judgement | No significant irritation |
| Bis[(dimethylamino)methyl]phenol | similar compounds | Corrosive |

Skin Sensitisation

| Name | Species | Value |
|---|------------------|----------------|
| 2,4,6-tris(dimethylaminomethyl)phenol | Guinea pig | Not classified |
| Synthetic amorphous silica, fumed, crystalline-free | Human and animal | Not classified |

Respiratory Sensitisation

For the component/components, either no data is currently available or the data is not sufficient for classification.

Germ Cell Mutagenicity

| Name | Route | Value |
|---------------------------------------|----------|---------------|
| 2,4,6-tris(dimethylaminomethyl)phenol | In Vitro | Not mutagenic |

| | | |
|---|----------|--|
| Synthetic amorphous silica, fumed, crystalline-free | In Vitro | Not mutagenic |
| Glass, oxide, chemicals | In Vitro | Some positive data exist, but the data are not sufficient for classification |

Carcinogenicity

| Name | Route | Species | Value |
|---|----------------|-------------------------|--|
| Synthetic amorphous silica, fumed, crystalline-free | Not specified. | Mouse | Some positive data exist, but the data are not sufficient for classification |
| Glass, oxide, chemicals | Inhalation | Multiple animal species | Some positive data exist, but the data are not sufficient for classification |

Reproductive Toxicity**Reproductive and/or Developmental Effects**

| Name | Route | Value | Species | Test result | Exposure Duration |
|---|-----------|--|---------|-----------------------|----------------------|
| Synthetic amorphous silica, fumed, crystalline-free | Ingestion | Not classified for female reproduction | Rat | NOAEL 509 mg/kg/day | 1 generation |
| Synthetic amorphous silica, fumed, crystalline-free | Ingestion | Not classified for male reproduction | Rat | NOAEL 497 mg/kg/day | 1 generation |
| Synthetic amorphous silica, fumed, crystalline-free | Ingestion | Not classified for development | Rat | NOAEL 1,350 mg/kg/day | during organogenesis |

Target Organ(s)**Specific Target Organ Toxicity - single exposure**

| Name | Route | Target Organ(s) | Value | Species | Test result | Exposure Duration |
|--|------------|------------------------|--|---------|---------------------|-------------------|
| 3,3'-Oxybis(ethyleneoxy)bis(propylamine) | Inhalation | respiratory irritation | Some positive data exist, but the data are not sufficient for classification | | NOAEL Not available | |
| 2,4,6-tris(dimethylaminomethyl) phenol | Inhalation | respiratory irritation | Some positive data exist, but the data are not sufficient for classification | | NOAEL Not available | |

Specific Target Organ Toxicity - repeated exposure

| Name | Route | Target Organ(s) | Value | Species | Test result | Exposure Duration |
|---|------------|---|----------------|---------|---------------------|-----------------------|
| 2,4,6-tris(dimethylaminomethyl) phenol | Dermal | skin liver nervous system auditory system hematopoietic system eyes | Not classified | Rat | NOAEL 125 mg/kg/day | 28 days |
| Synthetic amorphous silica, fumed, crystalline-free | Inhalation | respiratory system silicosis | Not classified | Human | NOAEL Not available | occupational exposure |
| Glass, oxide, chemicals | Inhalation | respiratory system | Not classified | Human | NOAEL not available | occupational exposure |

Aspiration Hazard

For the component/components, either no data is currently available or the data is not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition,

statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

12.1. Toxicity

No product test data available.

| Material | CAS # | Organism | Type | Exposure | Test endpoint | Test result |
|---|-------------|--------------|---|----------|--------------------------|--------------|
| 3,3'-Oxybis(ethyleneoxy)bis(propylamine) | 4246-51-9 | Golden Orfe | Experimental | 96 hours | LC50 | >1,000 mg/l |
| 3,3'-Oxybis(ethyleneoxy)bis(propylamine) | 4246-51-9 | Green algae | Experimental | 72 hours | EC50 | >500 mg/l |
| 3,3'-Oxybis(ethyleneoxy)bis(propylamine) | 4246-51-9 | Water flea | Experimental | 48 hours | EC50 | 218.16 mg/l |
| 3,3'-Oxybis(ethyleneoxy)bis(propylamine) | 4246-51-9 | Green algae | Experimental | 72 hours | Effect Concentration 10% | 5.4 mg/l |
| Synthetic amorphous silica, fumed, crystalline-free | 112945-52-5 | Green Algae | Experimental | 72 hours | EC50 | >100 mg/l |
| Synthetic amorphous silica, fumed, crystalline-free | 112945-52-5 | Water flea | Experimental | 24 hours | EC50 | >100 mg/l |
| Synthetic amorphous silica, fumed, crystalline-free | 112945-52-5 | Zebra Fish | Experimental | 96 hours | LC50 | >100 mg/l |
| Synthetic amorphous silica, fumed, crystalline-free | 112945-52-5 | Green Algae | Experimental | 72 hours | NOEC | 60 mg/l |
| 2,4,6-tris(dimethylaminomethyl)phenol | 90-72-2 | Common Carp | Experimental | 96 hours | LC50 | 175 mg/l |
| 2,4,6-tris(dimethylaminomethyl)phenol | 90-72-2 | Grass Shrimp | Experimental | 96 hours | LC50 | 718 mg/l |
| 2,4,6-tris(dimethylaminomethyl)phenol | 90-72-2 | Green algae | Experimental | 72 hours | EC50 | 84 mg/l |
| 2,4,6-tris(dimethylaminomethyl)phenol | 90-72-2 | Green algae | Experimental | 72 hours | NOEC | 6.25 mg/l |
| Glass, oxide, chemicals | 65997-17-3 | Green algae | Experimental | 72 hours | EC50 | >1,000 mg/l |
| Glass, oxide, chemicals | 65997-17-3 | Water flea | Experimental | 72 hours | EC50 | >1,000 mg/l |
| Glass, oxide, chemicals | 65997-17-3 | Zebra Fish | Experimental | 96 hours | LC50 | >1,000 mg/l |
| Glass, oxide, chemicals | 65997-17-3 | Green algae | Experimental | 72 hours | NOEC | >=1,000 mg/l |
| Bis[(dimethylamino)methyl]phenol | 71074-89-0 | | Data not available or insufficient for classification | | | |

12.2. Persistence and degradability

| Material | CAS Nbr | Test type | Duration | Study Type | Test result | Protocol |
|--|-----------|-----------------------------|----------|-------------------------------|------------------------------------|-----------------------------------|
| 3,3'-Oxybis(ethyleneoxy)bis(propylamine) | 4246-51-9 | Estimated Photolysis | | Photolytic half-life (in air) | 2.96 hours (t 1/2) | Other methods |
| 3,3'-Oxybis(ethyleneoxy)bis(propylamine) | 4246-51-9 | Experimental Biodegradation | 25 days | CO2 evolution | -8 %CO2 evolution/THC O2 evolution | OECD 301B - Modified sturm or CO2 |

| | | | | | | |
|---|-------------|-----------------------------------|---------|-----|-------------|--------------------------------|
| Synthetic amorphous silica, fumed, crystalline-free | 112945-52-5 | Data not available - insufficient | | | N/A | |
| 2,4,6-tris(dimethylaminomethyl)phenol | 90-72-2 | Experimental Biodegradation | 28 days | BOD | 4 % weight | OECD 301D - Closed bottle test |
| Glass, oxide, chemicals | 65997-17-3 | Data not available - insufficient | | | N/A | |
| Bis[(dimethylamino)methyl]phenol | 71074-89-0 | Estimated Biodegradation | 28 days | BOD | 20 % weight | OECD 301C - MITI test (I) |

12.3 : Bioaccumulative potential

| Material | Cas No. | Test type | Duration | Study Type | Test result | Protocol |
|---|-------------|---|----------|------------|-------------|--|
| 3,3'-Oxybis(ethyleneoxy)bis(propylamine) | 4246-51-9 | Experimental Bioconcentration | | Log Kow | -1.25 | Other methods |
| Synthetic amorphous silica, fumed, crystalline-free | 112945-52-5 | Data not available or insufficient for classification | N/A | N/A | N/A | N/A |
| 2,4,6-tris(dimethylaminomethyl)phenol | 90-72-2 | Experimental Bioconcentration | | Log Kow | -0.66 | Other methods |
| Glass, oxide, chemicals | 65997-17-3 | Data not available or insufficient for classification | N/A | N/A | N/A | N/A |
| Bis[(dimethylamino)methyl]phenol | 71074-89-0 | Estimated Bioconcentration | | Log Kow | -2.34 | Estimated; Octanol-water partition coefficient |

12.4. Mobility in soil

Please contact manufacturer for more details

12.5. Results of the PBT and vPvB assessment

This material does not contain any substances that are assessed to be a PBT or vPvB

12.6. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

EU waste code (product as sold)

- 08 04 09* Waste adhesives and sealants containing organic solvents or other dangerous substances
- 20 01 27* Paint, inks, adhesives and resins containing dangerous substances

SECTION 14: Transportation information

ADR: UN3259; Amines, Solid, Corrosive, N.O.S. (3,3'-oxybis(ethyleneoxy)bis(propylamine)); 8; II; (E); C8.
IATA: UN3259; Amines, solid, corrosive, n.o.s. (3,3'-Oxybis(ethyleneoxy)bis(propylamine)); 8; II.
IMDG: UN3259; Amines, Solid, Corrosive, N.O.S. (3,3'-oxybis(ethyleneoxy)bis(propylamine)); 8; II; FA, SB.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out for this mixture. Chemical safety assessments for the contained substances may have been carried out by the registrants of the substances in accordance with Regulation (EC) No 1907/2006, as amended.

SECTION 16: Other information

List of relevant H statements

| | |
|------|--|
| H302 | Harmful if swallowed. |
| H314 | Causes severe skin burns and eye damage. |
| H317 | May cause an allergic skin reaction. |
| H318 | Causes serious eye damage. |

Revision information:

Formulation: Section 16: Annex information was modified.
Professional Mixing and Application: Section 16: Annex information was modified.
Section 1: Emergency telephone information was modified.
CLP: Ingredient table information was modified.
Label: CLP Precautionary - Prevention information was modified.
Section 2: Other hazards phrase information was modified.
Section 3: Composition/ Information of ingredients table information was modified.
Section 5: Fire - Advice for fire fighters information information was modified.
Section 5: Hazardous combustion products table information was modified.
Section 6: Accidental release clean-up information information was modified.
Section 8: DNEL table row information was modified.
Section 8: glove data value information was modified.
Section 8: Occupational exposure limit table information was modified.
Section 8: PNEC table row information was modified.
Section 8: Skin protection - protective clothing information information was modified.
Section 09: Color information was added.
Section 09: Odor information was added.
Sections 3 and 9: Odour, colour, grade information information was deleted.
Section 11: Acute Toxicity table information was modified.
Section 11: Classification disclaimer information was modified.
Section 11: Germ Cell Mutagenicity Table information was modified.
Section 11: Health Effects - Inhalation information information was modified.
Section 11: Serious Eye Damage/Irritation Table information was modified.
Section 11: Skin Corrosion/Irritation Table information was modified.
Section 11: Skin Sensitization Table information was modified.
Section 11: Target Organs - Repeated Table information was modified.

Section 11: Target Organs - Single Table information was modified.

Section 12: Component ecotoxicity information information was modified.

Section 12: Persistence and Degradability information information was modified.

Section 12: Bioaccumulative potential information information was modified.

Section 15: Regulations - Inventories information was deleted.

Section 16: UK disclaimer information was deleted.

Annex

| | |
|---|---|
| 1. Title | |
| Substance identification | 2,4,6-tris(dimethylaminomethyl)phenol; EC No. 202-013-9; CAS Nbr 90-72-2; |
| Exposure Scenario Name | Formulation |
| Lifecycle Stage | Formulation or re-packing |
| Contributing activities | PROC 08b -Transfer of substance or mixture (charging and discharging) at dedicated facilities PROC 09 -Transfer of substance or mixture into small containers (dedicated filling line, including weighing) ERC 02 -Formulation into mixture |
| Processes, tasks and activities covered | Transfer of substances/mixtures into small containers e.g. tubes , bottles or small reservoirs. Transfers with dedicated controls, including loading, filling, dumping, bagging. |
| 2. Operational conditions and risk management measures | |
| Operating Conditions | Physical state: Liquid. General operating conditions: Air exchange rate:: >= 3 times per hour; Indoor use; Partially open and partially closed process; Processing Temperature:: <= 40 degree Celsius; Task: PROC08b; Duration of exposure per day at workplace [for one worker]: 8 hours/day; Task: PROC09; Duration of exposure per day at workplace [for one worker]: <= 4 hour(s); |
| Risk management measures | Under the operational conditions described above the following risk management measures apply: General risk management measures: Human health: Local exhaust ventilation; Protective Gloves - Chemical resistant. Refer to Section 8 of the SDS for specific glove material.; Environmental: None needed; |
| Waste management measures | No use-specific waste management measures are required for this product. Refer to Section 13 of main SDS for disposal instructions: |
| 3. Prediction of exposure | |
| Prediction of exposure | Human and environmental exposures are not expected to exceed the DNELs and PNECs when the identified risk management measures are adopted. |

| | |
|---------------------------------|--|
| 1. Title | |
| Substance identification | 3,3'-Oxybis(ethyleneoxy)bis(propylamine); EC No. 224-207-2; CAS Nbr 4246-51-9; |

| | |
|---|--|
| Exposure Scenario Name | Industrial Transfer |
| Lifecycle Stage | Use at industrial sites |
| Contributing activities | PROC 08b -Transfer of substance or mixture (charging and discharging) at dedicated facilities ERC 02 -Formulation into mixture |
| Processes, tasks and activities covered | Transfer of substance/mixture with dedicated engineering controls. |
| 2. Operational conditions and risk management measures | |
| Operating Conditions | Physical state: Liquid. General operating conditions: Duration of use: 8 hours/day; Frequency of exposure at workplace [for one worker]: 5 days/week; Processing Temperature:: 20 degree Celsius; |
| Risk management measures | Under the operational conditions described above the following risk management measures apply: General risk management measures: Human health: Wear chemically resistant gloves (tested to EN374) in combination with ‘basic’ employee training. Refer to Section 8 of the SDS for specific glove material.; Environmental: None needed; |
| Waste management measures | Do not release to waterways or sewers; Incinerate in a permitted hazardous waste incinerator; |
| 3. Prediction of exposure | |
| Prediction of exposure | Human and environmental exposures are not expected to exceed the DNELs and PNECs when the identified risk management measures are adopted. |

| | |
|---|--|
| 1. Title | |
| Substance identification | 3,3'-Oxybis(ethyleneoxy)bis(propylamine); EC No. 224-207-2; CAS Nbr 4246-51-9; |
| Exposure Scenario Name | Industrial Use of Adhesives |
| Lifecycle Stage | Use at industrial sites |
| Contributing activities | PROC 13 -Treatment of articles by dipping and pouring ERC 06d -Use of reactive process regulators in polymerisation processes at industrial site (inclusion or not into/onto article) |
| Processes, tasks and activities covered | Application of product through a mixing nozzle |
| 2. Operational conditions and risk management measures | |
| Operating Conditions | Physical state: Liquid. General operating conditions: Duration of use: 8 hours/day; Frequency of exposure at workplace [for one worker]: 5 days/week; Processing Temperature:: 20 degree Celsius; |
| Risk management measures | Under the operational conditions described above the following risk management measures apply: General risk management measures: Human health: Wear chemically resistant gloves (tested to EN374) in combination with ‘basic’ employee training. Refer to Section 8 of the SDS for specific glove material.; Environmental: None needed; |
| Waste management measures | Do not release to waterways or sewers; Incinerate in a permitted hazardous waste incinerator; |

| | |
|----------------------------------|--|
| | |
| 3. Prediction of exposure | |
| Prediction of exposure | Human and environmental exposures are not expected to exceed the DNELs and PNECs when the identified risk management measures are adopted. |

| | |
|--|--|
| 1. Title | |
| Substance identification | 2,4,6-tris(dimethylaminomethyl)phenol; EC No. 202-013-9; CAS Nbr 90-72-2; |
| Exposure Scenario Name | Industrial Use of Adhesives |
| Lifecycle Stage | Use at industrial sites |
| Contributing activities | PROC 05 -Mixing or blending in batch processes PROC 08a -Transfer of substance or mixture (charging and discharging) at non-dedicated facilities PROC 10 -Roller application or brushing PROC 13 -Treatment of articles by dipping and pouring ERC 05 -Use at industrial site leading to inclusion into/onto article |
| Processes, tasks and activities covered | Application of product with a roller or brush. Application of product with applicator gun. Mixing operations (open systems). Transfers without dedicated controls, including loading, filling, dumping, bagging. |

| | |
|---|--|
| 2. Operational conditions and risk management measures | |
| Operating Conditions | Physical state: Liquid. General operating conditions: Air exchange rate:: >= 3 times per hour; Duration of exposure per day at workplace [for one worker]: <= 4 hour(s); Indoor use; Processing Temperature:: <= 40 degree Celsius; Task: PROC05; Duration of exposure per day at workplace [for one worker]: 8 hours/day; |
| Risk management measures | Under the operational conditions described above the following risk management measures apply: General risk management measures: Human health: Local exhaust ventilation; Protective Gloves - Chemical resistant. Refer to Section 8 of the SDS for specific glove material.; Environmental: None needed; |
| Waste management measures | Do not release to waterways or sewers; |

| | |
|----------------------------------|--|
| 3. Prediction of exposure | |
| Prediction of exposure | Human and environmental exposures are not expected to exceed the DNELs and PNECs when the identified risk management measures are adopted. |

| | |
|---|--|
| 1. Title | |
| Substance identification | 2,4,6-tris(dimethylaminomethyl)phenol; EC No. 202-013-9; CAS Nbr 90-72-2; |
| Exposure Scenario Name | Hand-mixing of preparations, e.g. plasters, resins, two-component adhesives. |
| Lifecycle Stage | Widespread use by professional workers |
| Contributing activities | PROC 10 -Roller application or brushing ERC 08c -Widespread use leading to inclusion into/onto article (indoor) |
| Processes, tasks and activities covered | Application of product. |
| 2. Operational conditions and risk management measures | |

| | |
|----------------------------------|--|
| Operating Conditions | Physical state: Liquid. General operating conditions: Duration of exposure per day at workplace [for one worker]: 8 hours/day; Indoor use; Processing Temperature:: <= 40 degree Celsius; |
| Risk management measures | Under the operational conditions described above the following risk management measures apply: General risk management measures: Human health: Local exhaust ventilation; Protective Gloves - Chemical resistant. Refer to Section 8 of the SDS for specific glove material.; Environmental: None needed; |
| Waste management measures | Do not release directly to waterways; |
| 3. Prediction of exposure | |
| Prediction of exposure | Human and environmental exposures are not expected to exceed the DNELs and PNECs when the identified risk management measures are adopted. |

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into the European Union, you are responsible for all regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration.

3M Ireland MSDSs are available at www.3M.com