



## Safety Data Sheet

Copyright,2023, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

<b>Document group:</b>	32-6766-3	<b>Version number:</b>	6.00
<b>Revision date:</b>	30/01/2023	<b>Supersedes date:</b>	30/11/2022

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

3M Scotch-Weld(TM) Threadlocker TL42, Blue

#### Product Identification Numbers

UU-0015-0371-1      UU-0015-0390-1

7100034072      7100034098

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### Identified uses

Structural adhesive.

#### 1.3. Details of the supplier of the safety data sheet

**Address:** 3M Ireland Limited, The Iveagh Building, The Park, Carrickmines, Dublin 18.  
**Telephone:** +353 1 280 3555  
**E Mail:** tox.uk@mmm.com  
**Website:** www.3M.com

#### 1.4. Emergency telephone number

Emergency medical information: 8am-10pm (seven days) contact National Poisons Information Centre, Beaumont Hospital, Dublin 9 DOV2NO, Ireland. Telephone Number: +353 (0)1 809 2166

### SECTION 2: Hazard identification

#### 2.1. Classification of the substance or mixture CLP REGULATION (EC) No 1272/2008

The health and environmental classifications of this material have been derived using the calculation method, except in cases where test data are available or the physical form impacts classification. Classification(s) based on test data or physical form are noted below, if applicable.

The aspiration hazard classification is not required due to the product's viscosity.

##### CLASSIFICATION:

Skin Corrosion/Irritation, Category 2 - Skin Irrit. 2; H315

Serious Eye Damage/Eye Irritation, Category 2 - Eye Irrit. 2; H319  
Skin Sensitization, Category 1 - Skin Sens. 1; H317  
Carcinogenicity, Category 1B - Carc. 1B; H350  
Specific Target Organ Toxicity-Repeated Exposure, Category 2 - STOT RE 2; H373  
Specific Target Organ Toxicity-Single Exposure, Category 3 - STOT SE 3; H335  
Hazardous to the Aquatic Environment (Chronic), Category 1 - Aquatic Chronic 1; H410

For full text of H phrases, see Section 16.

## 2.2. Label elements

### CLP REGULATION (EC) No 1272/2008

#### SIGNAL WORD

DANGER.

#### Symbols

GHS07 (Exclamation mark) |GHS08 (Health Hazard) |GHS09 (Environment) |

#### Pictograms



#### Ingredients:

Ingredient	CAS Nbr	EC No.	% by Wt
2,2'-ethylenedioxydiethyl dimethacrylate	109-16-0	203-652-6	30 - 50
HYDROXYPROPYL METHACRYLATE	27813-02-1	248-666-3	1 - 10
2'-Phenylacetohydrazide	114-83-0	204-055-3	<= 0.8
N,N-dimethyl-p-toluidine	99-97-8	202-805-4	<= 0.5
$\alpha$ , $\alpha$ -dimethylbenzyl hydroperoxide	80-15-9	201-254-7	< 2
2,2'-(p-Tolylimino)diethanol	3077-12-1	221-359-1	< 1
acrylic acid	79-10-7	201-177-9	<= 1

#### HAZARD STATEMENTS:

H315	Causes skin irritation.
H319	Causes serious eye irritation.
H317	May cause an allergic skin reaction.
H350	May cause cancer.
H335	May cause respiratory irritation.
H373	May cause damage to organs through prolonged or repeated exposure: nervous system   respiratory system.
H410	Very toxic to aquatic life with long lasting effects.

#### PRECAUTIONARY STATEMENTS

##### Prevention:

P201	Obtain special instructions before use.
P260A	Do not breathe vapours.
P273	Avoid release to the environment.

P280E                                      Wear protective gloves.

**Response:**

P308 + P313                              IF exposed or concerned:    Get medical advice/attention.  
 P333 + P313                              If skin irritation or rash occurs:    Get medical advice/attention.

**For containers not exceeding 125 ml the following Hazard and Precautionary statements may be used:**

**<=125 ml Hazard statements**

H317                                      May cause an allergic skin reaction.  
 H350                                      May cause cancer.

**<=125 ml Precautionary statements**

**Prevention:**

P201                                      Obtain special instructions before use.  
 P280E                                      Wear protective gloves.

**Response:**

P308 + P313                              IF exposed or concerned:    Get medical advice/attention.  
 P333 + P313                              If skin irritation or rash occurs:    Get medical advice/attention.

**SUPPLEMENTAL INFORMATION:**

**Supplemental Precautionary Statements:**

Restricted to professional users.

1% of the mixture consists of components of unknown acute inhalation toxicity.  
 Contains 8% of components with unknown hazards to the aquatic environment.

**2.3. Other hazards**

None known.

This material does not contain any substances that are assessed to be a PBT or vPvB

**SECTION 3: Composition/information on ingredients**

**3.1. Substances**

Not applicable

**3.2. Mixtures**

<b>Ingredient</b>	<b>Identifier(s)</b>	<b>%</b>	<b>Classification according to Regulation (EC) No. 1272/2008 [CLP]</b>
2,2'-ethylenedioxydiethyl dimethacrylate	(CAS-No.) 109-16-0 (EC-No.) 203-652-6 (REACH-No.) 01-2119969287-21	30 - 50	Skin Sens. 1, H317
Bis(isopropyl)naphthalene	(CAS-No.) 38640-62-9 (EC-No.) 254-052-6	20 - 40	Asp. Tox. 1, H304 Eye Irrit. 2, H319 Aquatic Chronic 1, H410,M=1
Polyester resin	Trade Secret	1 - 10	Substance not classified as hazardous
HYDROXYPROPYL METHACRYLATE	(CAS-No.) 27813-02-1 (EC-No.) 248-666-3	1 - 10	Eye Irrit. 2, H319 Skin Sens. 1, H317

2'-Phenylacetohydrazide	(CAS-No.) 114-83-0 (EC-No.) 204-055-3	<= 0.8	Acute Tox. 3, H311 Acute Tox. 3, H301 Skin Sens. 1, H317 STOT RE 1, H372 Aquatic Acute 1, H400,M=1 Aquatic Chronic 1, H410,M=10
Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, hydrolysis products with silica	(CAS-No.) 68909-20-6 (EC-No.) 272-697-1	< 5	EUH066 STOT RE 2, H373
N,N-dimethyl-p-toluidine	(CAS-No.) 99-97-8 (EC-No.) 202-805-4	<= 0.5	Acute Tox. 3, H331 Acute Tox. 3, H311 Acute Tox. 3, H301 STOT RE 2, H373 Aquatic Chronic 3, H412 Nota C Skin Sens. 1B, H317 Carc. 1B, H350
1,2-Benzisothiazol-3(2H)-one 1,1-dioxide	(CAS-No.) 81-07-2 (EC-No.) 201-321-0	1 - 5	Substance not classified as hazardous
2,6-Di-tert-butyl-p-cresol	(CAS-No.) 128-37-0 (EC-No.) 204-881-4	<= 0.5	Aquatic Chronic 1, H410,M=1 Aquatic Acute 1, H400,M=1
$\alpha$ , $\alpha$ -dimethylbenzyl hydroperoxide	(CAS-No.) 80-15-9 (EC-No.) 201-254-7	< 2	Org. Perox. EF, H242 Acute Tox. 2, H330 Acute Tox. 3, H311 Acute Tox. 4, H302 Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT SE 3, H335 STOT RE 1, H372 Aquatic Chronic 2, H411
Naphthalene, (1-methylethyl)-	(CAS-No.) 29253-36-9 (EC-No.) 249-535-3	< 1	Aquatic Acute 1, H400,M=1 Aquatic Chronic 1, H410,M=1
2,2'-(p-Tolylimino)diethanol	(CAS-No.) 3077-12-1 (EC-No.) 221-359-1	< 1	Acute Tox. 4, H302 Eye Dam. 1, H318 Skin Sens. 1B, H317 Aquatic Chronic 3, H412
Titanium dioxide	(CAS-No.) 13463-67-7 (EC-No.) 236-675-5	<= 0.1	Carc. 2, H351 (inhalation)
acrylic acid	(CAS-No.) 79-10-7 (EC-No.) 201-177-9	<= 1	Flam. Liq. 3, H226 Acute Tox. 4, H332 Acute Tox. 4, H312 Acute Tox. 4, H302 Skin Corr. 1A, H314 STOT SE 3, H335 Aquatic Acute 1, H400,M=1 Nota D Aquatic Chronic 2, H411

Please see section 16 for the full text of any H statements referred to in this section

**Specific Concentration Limits**

Ingredient	Identifier(s)	Specific Concentration Limits
acrylic acid	(CAS-No.) 79-10-7 (EC-No.) 201-177-9	(C >= 1%) STOT SE 3, H335
$\alpha$ , $\alpha$ -dimethylbenzyl hydroperoxide	(CAS-No.) 80-15-9 (EC-No.) 201-254-7	(C >= 10%) Skin Corr. 1B, H314 (3% <= C < 10%) Skin Irrit. 2, H315 (C >= 3%) Eye Dam. 1, H318 (1% <= C < 3%) Eye Irrit. 2, H319 (C >= 10%) STOT SE 3, H335

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

**SECTION 4: First aid measures****4.1. Description of first aid measures****Inhalation**

Remove person to fresh air. If you feel unwell, get medical attention.

**Skin contact**

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

**Eye contact**

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

**If swallowed**

Rinse mouth. If you feel unwell, get medical attention.

**4.2. Most important symptoms and effects, both acute and delayed**

The most important symptoms and effects based on the CLP classification include:

Irritating to the respiratory tract (coughing, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain). Irritation to the skin (localized redness, swelling, itching, and dryness). Allergic skin reaction (redness, swelling, blistering, and itching). Serious irritation to the eyes (significant redness, swelling, pain, tearing, and impaired vision). Target organ effects. See Section 11 for additional details.

**4.3. Indication of any immediate medical attention and special treatment required**

Not applicable

**SECTION 5: Fire-fighting measures****5.1. Extinguishing media**

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

**5.2. Special hazards arising from the substance or mixture**

None inherent in this product.

**Hazardous Decomposition or By-Products****Substance****Condition**

Carbon monoxide  
Carbon dioxide.  
Oxides of nitrogen.  
Oxides of sulphur.

During combustion.  
During combustion.  
During combustion.  
During combustion.

### **5.3. Advice for fire-fighters**

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

## **SECTION 6: Accidental release measures**

### **6.1. Personal precautions, protective equipment and emergency procedures**

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

### **6.2. Environmental precautions**

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

### **6.3. Methods and material for containment and cleaning up**

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible.

### **6.4. Reference to other sections**

Refer to Section 8 and Section 13 for more information

## **SECTION 7: Handling and storage**

### **7.1. Precautions for safe handling**

For industrial/occupational use only. Not for consumer sale or use. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (eg. gloves, respirators...) as required.

### **7.2. Conditions for safe storage including any incompatibilities**

Protect from sunlight. Store away from heat. Store away from oxidising agents.

### **7.3. Specific end use(s)**

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

## **SECTION 8: Exposure controls/personal protection**

### **8.1 Control parameters**

#### **Occupational exposure limits**

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
2,6-Di-tert-butyl-p-cresol	128-37-0	Ireland OELs	TWA(8 hours):2 mg/m <sup>3</sup>	
Titanium dioxide	13463-67-7	Ireland OELs	TWA(Total inhalable dust)(8 hours):10 mg/m <sup>3</sup> ;TWA(as respirable dust)(8 hours):4 mg/m <sup>3</sup>	
Silicon dioxide	68909-20-6	Ireland OELs	TWA(Total inhalable dust)(8 hours):6 mg/m <sup>3</sup> ;TWA(as respirable dust)(8 hours):2.4 mg/m <sup>3</sup>	
acrylic acid	79-10-7	Ireland OELs	TWA(8 hours):29 mg/m <sup>3</sup> (10 ppm);TWA(8 hours):10 ppm(29 mg/m <sup>3</sup> );STEL(15 minutes):59 mg/m <sup>3</sup> (20 ppm);STEL(1 minutes):20 ppm(59 mg/m <sup>3</sup> )	

Ireland OELs : Ireland. OELs  
TWA: Time-Weighted-Average  
STEL: Short Term Exposure Limit  
CEIL: Ceiling

### Biological limit values

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

### Derived no effect level (DNEL)

Ingredient	Degradation Product	Population	Human exposure pattern	DNEL
acrylic acid		Worker	Dermal, Short-term exposure, Local effects	1 mg/cm <sup>2</sup>
acrylic acid		Worker	Inhalation, Long-term exposure (8 hours), Local effects	30 mg/m <sup>3</sup>
acrylic acid		Worker	Inhalation, Short-term exposure, Local effects	30 mg/m <sup>3</sup>

### Predicted no effect concentrations (PNEC)

Ingredient	Degradation Product	Compartment	PNEC
acrylic acid		Agricultural soil	1 mg/kg d.w.
acrylic acid		Freshwater	0.003 mg/l
acrylic acid		Freshwater sediments	0.236 mg/kg d.w.
acrylic acid		Intermittent releases to water	0.0013 mg/l
acrylic acid		Marine water	0.0003 mg/l
acrylic acid		Sewage Treatment Plant	0.9 mg/l

**Recommended monitoring procedures:**Information on recommended monitoring procedures can be obtained from Indust. Inspect./Ministry (IE)

## 8.2. Exposure controls

In addition, refer to the annex for more information.

### 8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

### 8.2.2. Personal protective equipment (PPE)

#### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

- Safety glasses with side shields.
- Indirect vented goggles.

*Applicable Norms/Standards*

Use eye protection conforming to EN 166

#### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended:

Material	Thickness (mm)	Breakthrough Time
Polymer laminate	No data available	No data available

*Applicable Norms/Standards*

Use gloves tested to EN 374

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

#### Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

- Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

*Applicable Norms/Standards*

Use a respirator conforming to EN 140 or EN 136: filter types A & P

### 8.2.3. Environmental exposure controls

Refer to Annex

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

<b>Physical state</b>	Liquid.
<b>Specific Physical Form:</b>	Thixotropic liquid.
<b>Colour</b>	Blue
<b>Odor</b>	Mild Odor
<b>Odour threshold</b>	No data available.
<b>Melting point/freezing point</b>	Not applicable.



<b>Boiling point/boiling range</b>	$\geq 148.9$ °C [ <i>@</i> 101,324.72 Pa ]
<b>Flammability (solid, gas)</b>	Not applicable.
<b>Flammable Limits(LEL)</b>	<i>No data available.</i>
<b>Flammable Limits(UEL)</b>	<i>No data available.</i>
<b>Flash point</b>	$\geq 100$ °C [ <i>Test Method:</i> Tagliabue closed cup]
<b>Autoignition temperature</b>	<i>No data available.</i>
<b>Decomposition temperature</b>	<i>No data available.</i>
<b>pH</b>	<i>substance/mixture is non-soluble (in water)</i>
<b>Kinematic Viscosity</b>	12,727 mm <sup>2</sup> /sec
<b>Water solubility</b>	Negligible
<b>Solubility- non-water</b>	<i>No data available.</i>
<b>Partition coefficient: n-octanol/water</b>	<i>No data available.</i>
<b>Vapour pressure</b>	$\leq 666.6$ Pa
<b>Density</b>	1.1 g/ml [ <i>@</i> 20 °C ]
<b>Relative density</b>	1.1 [ <i>@</i> 20 °C ] [ <i>Ref Std:</i> WATER=1]
<b>Relative Vapour Density</b>	1.01 [ <i>Ref Std:</i> AIR=1]

## 9.2. Other information

### 9.2.2 Other safety characteristics

**EU Volatile Organic Compounds**  
**Evaporation rate**

*No data available.*  
 Negligible

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

### 10.2 Chemical stability

Stable.

### 10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

### 10.4 Conditions to avoid

Heat.  
 Light.

### 10.5 Incompatible materials

Strong oxidising agents.

### 10.6 Hazardous decomposition products

**Substance**

None known.

**Condition**

Refer to section 5.2 for hazardous decomposition products during combustion.

## SECTION 11: Toxicological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from internal hazard assessments.

## 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

### Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

#### Skin contact

Skin Irritation: Signs/symptoms may include localised redness, swelling, itching, dryness, cracking, blistering, and pain. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

#### Eye contact

Severe eye irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

#### Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea. May cause additional health effects (see below).

### Additional Health Effects:

#### Prolonged or repeated exposure may cause target organ effects:

Neurological effects: Signs/symptoms may include personality changes, lack of coordination, sensory loss, tingling or numbness of the extremities, weakness, tremors, and changes in blood pressure and heart rate. Respiratory effects: Signs/symptoms may include cough, shortness of breath, chest tightness, wheezing, increased heart rate, bluish coloured skin (cyanosis), sputum production, changes in lung function tests, and respiratory failure.

#### Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

### Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

#### Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation-Vapour(4 hr)		No data available; calculated ATE >50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
2,2'-ethylenedioxydiethyl dimethacrylate	Dermal	Professional judgement	LD50 estimated to be > 5,000 mg/kg
2,2'-ethylenedioxydiethyl dimethacrylate	Ingestion	Rat	LD50 10,837 mg/kg
Bis(isopropyl)naphthalene	Dermal	Rat	LD50 > 4,500 mg/kg
Bis(isopropyl)naphthalene	Inhalation-Dust/Mist	Rat	LC50 > 5.64 mg/l
Bis(isopropyl)naphthalene	Ingestion	Rat	LD50 4,130 mg/kg
HYDROXYPROPYL METHACRYLATE	Dermal	Rabbit	LD50 > 5,000 mg/kg
HYDROXYPROPYL METHACRYLATE	Ingestion	Rat	LD50 > 11,200 mg/kg
Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, hydrolysis products with silica	Dermal	Rabbit	LD50 > 5,000 mg/kg
Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, hydrolysis	Inhalation-	Rat	LC50 > 0.691 mg/l

**3M Scotch-Weld(TM) Threadlocker TL42, Blue**

products with silica	Dust/Mist (4 hours)		
Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, hydrolysis products with silica	Ingestion	Rat	LD50 > 5,110 mg/kg
1,2-Benzisothiazol-3(2H)-one 1,1-dioxide	Dermal		LD50 estimated to be > 5,000 mg/kg
1,2-Benzisothiazol-3(2H)-one 1,1-dioxide	Ingestion	Mouse	LD50 17,000 mg/kg
$\alpha$ , $\alpha$ -dimethylbenzyl hydroperoxide	Dermal	Rat	LD50 500 mg/kg
$\alpha$ , $\alpha$ -dimethylbenzyl hydroperoxide	Inhalation- Vapour (4 hours)	Rat	LC50 1.4 mg/l
$\alpha$ , $\alpha$ -dimethylbenzyl hydroperoxide	Ingestion	Rat	LD50 382 mg/kg
acrylic acid	Dermal	Rabbit	LD50 > 2,000 mg/kg
acrylic acid	Inhalation- Dust/Mist (4 hours)	Rat	LC50 3.8 mg/l
acrylic acid	Ingestion	Rat	LD50 1,250 mg/kg
2'-Phenylacetohydrazide	Dermal		LD50 estimated to be 200 - 1,000 mg/kg
2'-Phenylacetohydrazide	Ingestion	Mouse	LD50 270 mg/kg
2,6-Di-tert-butyl-p-cresol	Dermal	Rat	LD50 > 2,000 mg/kg
2,6-Di-tert-butyl-p-cresol	Ingestion	Rat	LD50 > 2,930 mg/kg
N,N-dimethyl-p-toluidine	Ingestion	Mouse	LD50 140 mg/kg
N,N-dimethyl-p-toluidine	Dermal	Rabbit	LD50 > 2,000 mg/kg
N,N-dimethyl-p-toluidine	Inhalation- Dust/Mist (4 hours)	Rat	LC50 1.4 mg/l
2,2'-(p-Tolylimino)diethanol	Dermal	Rabbit	LD50 > 2,000 mg/kg
2,2'-(p-Tolylimino)diethanol	Ingestion	Rat	LD50 959 mg/kg
Titanium dioxide	Dermal	Rabbit	LD50 > 10,000 mg/kg
Titanium dioxide	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 6.82 mg/l
Titanium dioxide	Ingestion	Rat	LD50 > 10,000 mg/kg

ATE = acute toxicity estimate

**Skin Corrosion/Irritation**

Name	Species	Value
2,2'-ethylenedioxydiethyl dimethacrylate	Guinea pig	Mild irritant
Bis(isopropyl)naphthalene	Rabbit	Minimal irritation
HYDROXYPROPYL METHACRYLATE	Rabbit	Minimal irritation
Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, hydrolysis products with silica	Rabbit	No significant irritation
$\alpha$ , $\alpha$ -dimethylbenzyl hydroperoxide	Rabbit	Corrosive
acrylic acid	Rabbit	Corrosive
2,6-Di-tert-butyl-p-cresol	Human and animal	Minimal irritation
N,N-dimethyl-p-toluidine	Rabbit	No significant irritation
2,2'-(p-Tolylimino)diethanol	Rabbit	No significant irritation
Titanium dioxide	Rabbit	No significant irritation

**Serious Eye Damage/Irritation**

Name	Species	Value
2,2'-ethylenedioxydiethyl dimethacrylate	Professional judgement	Moderate irritant
Bis(isopropyl)naphthalene	Rabbit	Severe irritant
HYDROXYPROPYL METHACRYLATE	Rabbit	Moderate irritant
Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, hydrolysis products with silica	Rabbit	No significant irritation
$\alpha$ , $\alpha$ -dimethylbenzyl hydroperoxide	Rabbit	Corrosive
acrylic acid	Rabbit	Corrosive

**3M Scotch-Weld(TM) Threadlocker TL42, Blue**

2,6-Di-tert-butyl-p-cresol	Rabbit	Mild irritant
N,N-dimethyl-p-toluidine	Rabbit	No significant irritation
2,2'-(p-Tolylimino)diethanol	Rabbit	Corrosive
Titanium dioxide	Rabbit	No significant irritation

**Skin Sensitisation**

Name	Species	Value
2,2'-ethylenedioxydiethyl dimethacrylate	Human and animal	Sensitising
Bis(isopropyl)naphthalene	Guinea pig	Not classified
HYDROXYPROPYL METHACRYLATE	Human and animal	Sensitising
Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, hydrolysis products with silica	Human and animal	Not classified
acrylic acid	Guinea pig	Not classified
2'-Phenylacetohydrazide	Professional judgement	Sensitising
2,6-Di-tert-butyl-p-cresol	Human	Not classified
N,N-dimethyl-p-toluidine	Guinea pig	Sensitising
2,2'-(p-Tolylimino)diethanol	Mouse	Sensitising
Titanium dioxide	Human and animal	Not classified

**Respiratory Sensitisation**

For the component/components, either no data is currently available or the data is not sufficient for classification.

**Germ Cell Mutagenicity**

Name	Route	Value
2,2'-ethylenedioxydiethyl dimethacrylate	In Vitro	Some positive data exist, but the data are not sufficient for classification
Bis(isopropyl)naphthalene	In Vitro	Not mutagenic
Bis(isopropyl)naphthalene	In vivo	Not mutagenic
HYDROXYPROPYL METHACRYLATE	In vivo	Not mutagenic
HYDROXYPROPYL METHACRYLATE	In Vitro	Some positive data exist, but the data are not sufficient for classification
Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, hydrolysis products with silica	In Vitro	Not mutagenic
$\alpha$ , $\alpha$ -dimethylbenzyl hydroperoxide	In vivo	Not mutagenic
$\alpha$ , $\alpha$ -dimethylbenzyl hydroperoxide	In Vitro	Some positive data exist, but the data are not sufficient for classification
acrylic acid	In vivo	Not mutagenic
acrylic acid	In Vitro	Some positive data exist, but the data are not sufficient for classification
2'-Phenylacetohydrazide	In Vitro	Some positive data exist, but the data are not sufficient for classification
2,6-Di-tert-butyl-p-cresol	In Vitro	Not mutagenic
2,6-Di-tert-butyl-p-cresol	In vivo	Not mutagenic
N,N-dimethyl-p-toluidine	In vivo	Not mutagenic
N,N-dimethyl-p-toluidine	In Vitro	Some positive data exist, but the data are not sufficient for classification
2,2'-(p-Tolylimino)diethanol	In Vitro	Not mutagenic
Titanium dioxide	In Vitro	Not mutagenic
Titanium dioxide	In vivo	Not mutagenic

**Carcinogenicity**

Name	Route	Species	Value
2,2'-ethylenedioxydiethyl dimethacrylate	Dermal	Mouse	Not carcinogenic
Bis(isopropyl)naphthalene	Ingestion	Rat	Not carcinogenic
Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, hydrolysis products with silica	Not specified.	Mouse	Some positive data exist, but the data are not sufficient for classification
acrylic acid	Ingestion	Rat	Not carcinogenic
acrylic acid	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
2,6-Di-tert-butyl-p-cresol	Ingestion	Multiple animal species	Some positive data exist, but the data are not sufficient for classification
N,N-dimethyl-p-toluidine	Ingestion	Multiple animal species	Carcinogenic.
Titanium dioxide	Ingestion	Multiple animal species	Not carcinogenic
Titanium dioxide	Inhalation	Rat	Carcinogenic.

**Reproductive Toxicity****Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test result	Exposure Duration
2,2'-ethylenedioxydiethyl dimethacrylate	Ingestion	Not classified for female reproduction	Mouse	NOAEL 1 mg/kg/day	1 generation
2,2'-ethylenedioxydiethyl dimethacrylate	Ingestion	Not classified for male reproduction	Mouse	NOAEL 1 mg/kg/day	1 generation
2,2'-ethylenedioxydiethyl dimethacrylate	Ingestion	Not classified for development	Mouse	NOAEL 1 mg/kg/day	1 generation
Bis(isopropyl)naphthalene	Ingestion	Not classified for development	Rat	NOAEL 625 mg/kg/day	during organogenesis
HYDROXYPROPYL METHACRYLATE	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	prematuring into lactation
HYDROXYPROPYL METHACRYLATE	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	49 days
HYDROXYPROPYL METHACRYLATE	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	during gestation
Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, hydrolysis products with silica	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, hydrolysis products with silica	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, hydrolysis products with silica	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis
acrylic acid	Ingestion	Not classified for female reproduction	Rat	NOAEL 460 mg/kg/day	2 generation
acrylic acid	Ingestion	Not classified for male reproduction	Rat	NOAEL 460 mg/kg/day	2 generation
acrylic acid	Inhalation	Not classified for development	Rat	NOAEL 1.1 mg/l	during organogenesis
acrylic acid	Ingestion	Not classified for development	Rat	NOAEL 53 mg/kg/day	2 generation
2,6-Di-tert-butyl-p-cresol	Ingestion	Not classified for female reproduction	Rat	NOAEL 500 mg/kg/day	2 generation
2,6-Di-tert-butyl-p-cresol	Ingestion	Not classified for male reproduction	Rat	NOAEL 500 mg/kg/day	2 generation
2,6-Di-tert-butyl-p-cresol	Ingestion	Not classified for development	Rat	NOAEL 100 mg/kg/day	2 generation
N,N-dimethyl-p-toluidine	Ingestion	Not classified for female reproduction	Rat	NOAEL 60	90 days

				mg/kg/day	
--	--	--	--	-----------	--

**Target Organ(s)**

**Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Bis(isopropyl)naphthalene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
HYDROXYPROPYL METHACRYLATE	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
$\alpha$ , $\alpha$ -dimethylbenzyl hydroperoxide	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	occupational exposure
$\alpha$ , $\alpha$ -dimethylbenzyl hydroperoxide	Inhalation	respiratory irritation	May cause respiratory irritation	Human	NOAEL Not available	occupational exposure
$\alpha$ , $\alpha$ -dimethylbenzyl hydroperoxide	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	
acrylic acid	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
2,2'-(p-Tolylimino)diethanol	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	

**Specific Target Organ Toxicity - repeated exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
2,2'-ethylenedioxydiethyl dimethacrylate	Dermal	kidney and/or bladder   blood	Not classified	Mouse	NOAEL 833 mg/kg/day	78 weeks
Bis(isopropyl)naphthalene	Ingestion	hematopoietic system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 170 mg/kg/day	6 months
Bis(isopropyl)naphthalene	Ingestion	liver   immune system   kidney and/or bladder	Not classified	Rat	NOAEL 170 mg/kg/day	6 months
HYDROXYPROPYL METHACRYLATE	Inhalation	blood	Not classified	Rat	NOAEL 0.5 mg/l	21 days
HYDROXYPROPYL METHACRYLATE	Ingestion	hematopoietic system   heart   endocrine system   liver   immune system   nervous system   kidney and/or bladder	Not classified	Rat	NOAEL 1,000 mg/kg/day	41 days
Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, hydrolysis products with silica	Inhalation	respiratory system   silicosis	Not classified	Human	NOAEL Not available	occupational exposure
$\alpha$ , $\alpha$ -dimethylbenzyl hydroperoxide	Inhalation	nervous system   respiratory system	Causes damage to organs through prolonged or repeated exposure	Rat	LOAEL 0.2 mg/l	7 days
$\alpha$ , $\alpha$ -dimethylbenzyl hydroperoxide	Inhalation	heart   liver   kidney and/or bladder	Not classified	Rat	NOAEL 0.03 mg/l	90 days
2'-Phenylacetohydrazide	Ingestion	hematopoietic system	Causes damage to organs through prolonged or repeated exposure	Dog	LOAEL 4 mg/kg/day	7 days
2,6-Di-tert-butyl-p-cresol	Ingestion	liver	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 250 mg/kg/day	28 days
2,6-Di-tert-butyl-p-cresol	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 500 mg/kg/day	2 generation
2,6-Di-tert-butyl-p-cresol	Ingestion	blood	Not classified	Rat	LOAEL 420 mg/kg/day	40 days

**3M Scotch-Weld(TM) Threadlocker TL42, Blue**

2,6-Di-tert-butyl-p-cresol	Ingestion	endocrine system	Not classified	Rat	NOAEL 25 mg/kg/day	2 generation
2,6-Di-tert-butyl-p-cresol	Ingestion	heart	Not classified	Mouse	NOAEL 3,480 mg/kg/day	10 weeks
N,N-dimethyl-p-toluidine	Ingestion	hematopoietic system	May cause damage to organs though prolonged or repeated exposure	Rat	NOAEL 20 mg/kg/day	3 months
N,N-dimethyl-p-toluidine	Ingestion	respiratory system	May cause damage to organs though prolonged or repeated exposure	Rat	NOAEL 20 mg/kg/day	2 years
N,N-dimethyl-p-toluidine	Ingestion	liver   immune system   kidney and/or bladder   heart   skin   endocrine system   gastrointestinal tract   bone, teeth, nails, and/or hair   muscles   nervous system   eyes   vascular system	Not classified	Rat	NOAEL 60 mg/kg/day	2 years
Titanium dioxide	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 0.01 mg/l	2 years
Titanium dioxide	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not available	occupational exposure

**Aspiration Hazard**

Name	Value
Bis(isopropyl)naphthalene	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

**11.2. Information on other hazards**

This material does not contain any substances that are assessed to be an endocrine disruptor for human health.

**SECTION 12: Ecological information**

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

**12.1. Toxicity**

No product test data available.

Material	CAS #	Organism	Type	Exposure	Test endpoint	Test result
2,2'-ethylenedioxydiethyl dimethacrylate	109-16-0	Green algae	Experimental	72 hours	ErC50	>100 mg/l
2,2'-ethylenedioxydiethyl dimethacrylate	109-16-0	Zebra Fish	Experimental	96 hours	LC50	16.4 mg/l
2,2'-ethylenedioxydiethyl dimethacrylate	109-16-0	Green algae	Experimental	72 hours	NOEC	18.6 mg/l
2,2'-ethylenedioxydiethyl dimethacrylate	109-16-0	Water flea	Experimental	21 days	NOEC	32 mg/l

**3M Scotch-Weld(TM) Threadlocker TL42, Blue**

Bis(isopropyl)naphthalene	38640-62-9	Bacteria	Experimental	N/A	EC10	>0.16 mg/l
Bis(isopropyl)naphthalene	38640-62-9	Medaka	Experimental	96 hours	LC50	2.44 mg/l
Bis(isopropyl)naphthalene	38640-62-9	Water flea	Experimental	48 hours	EL50	1.7 mg/l
Bis(isopropyl)naphthalene	38640-62-9	Green algae	Experimental	72 hours	NOEC	0.15 mg/l
Bis(isopropyl)naphthalene	38640-62-9	Water flea	Experimental	21 days	NOEC	0.013 mg/l
HYDROXYPROPYL METHACRYLATE	27813-02-1	Bacteria	Experimental	N/A	EC10	1,140 mg/l
HYDROXYPROPYL METHACRYLATE	27813-02-1	Golden Orfe	Experimental	48 hours	EC50	493 mg/l
HYDROXYPROPYL METHACRYLATE	27813-02-1	Green algae	Experimental	72 hours	ErC50	>97.2 mg/l
HYDROXYPROPYL METHACRYLATE	27813-02-1	Water flea	Experimental	48 hours	EC50	>143 mg/l
HYDROXYPROPYL METHACRYLATE	27813-02-1	Green algae	Experimental	72 hours	NOEC	97.2 mg/l
HYDROXYPROPYL METHACRYLATE	27813-02-1	Water flea	Experimental	21 days	NOEC	45.2 mg/l
2'-Phenylacetohydrazide	114-83-0	Medaka	Analogous Compound	96 hours	LC50	0.016 mg/l
2'-Phenylacetohydrazide	114-83-0	Water flea	Analogous Compound	48 hours	EC50	0.016 mg/l
2'-Phenylacetohydrazide	114-83-0	Zebra Fish	Analogous Compound	16 days	NOEC	0.00049 mg/l
2,6-Di-tert-butyl-p-cresol	128-37-0	Activated sludge	Experimental	3 hours	EC50	>10,000 mg/l
2,6-Di-tert-butyl-p-cresol	128-37-0	Green algae	Experimental	72 hours	EC50	>0.4 mg/l
2,6-Di-tert-butyl-p-cresol	128-37-0	Water flea	Experimental	48 hours	EC50	0.48 mg/l
2,6-Di-tert-butyl-p-cresol	128-37-0	Zebra Fish	Experimental	96 hours	No tox obs at lmt of water sol	>100 mg/l
2,6-Di-tert-butyl-p-cresol	128-37-0	Green algae	Experimental	72 hours	EC10	0.4 mg/l
2,6-Di-tert-butyl-p-cresol	128-37-0	Medaka	Experimental	42 days	NOEC	0.053 mg/l
2,6-Di-tert-butyl-p-cresol	128-37-0	Water flea	Experimental	21 days	NOEC	0.023 mg/l
N,N-dimethyl-p-toluidine	99-97-8	Green algae	Estimated	72 hours	EC50	22 mg/l
N,N-dimethyl-p-toluidine	99-97-8	Water flea	Estimated	48 hours	EC50	13.7 mg/l
N,N-dimethyl-p-toluidine	99-97-8	Fathead minnow	Experimental	96 hours	LC50	46 mg/l
1,2-Benzisothiazol-3(2H)-one 1,1-dioxide	81-07-2	Guppy	Analogous Compound	96 hours	LC50	>100 mg/l
1,2-Benzisothiazol-3(2H)-one 1,1-dioxide	81-07-2	Activated sludge	Experimental	30 minutes	LOEC	>1,000 mg/l
1,2-Benzisothiazol-3(2H)-one 1,1-dioxide	81-07-2	Green algae	Experimental	72 hours	ErC50	>200 mg/l
1,2-Benzisothiazol-3(2H)-one 1,1-dioxide	81-07-2	Water flea	Experimental	48 hours	EC50	>1,000 mg/l
Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, hydrolysis products with silica	68909-20-6	Algae or other aquatic plants	Estimated	72 hours	EC50	>100 mg/l
$\alpha$ , $\alpha$ -dimethylbenzyl hydroperoxide	80-15-9	Bacteria	Experimental	18 hours	EC10	0.103 mg/l
$\alpha$ , $\alpha$ -dimethylbenzyl hydroperoxide	80-15-9	Green algae	Experimental	72 hours	EC50	3.1 mg/l
$\alpha$ , $\alpha$ -dimethylbenzyl hydroperoxide	80-15-9	Rainbow trout	Experimental	96 hours	LC50	3.9 mg/l



**3M Scotch-Weld(TM) Threadlocker TL42, Blue**

$\alpha$ , $\alpha$ -dimethylbenzyl hydroperoxide	80-15-9	Water flea	Experimental	48 hours	EC50	18.84 mg/l
$\alpha$ , $\alpha$ -dimethylbenzyl hydroperoxide	80-15-9	Green algae	Experimental	72 hours	NOEC	1 mg/l
2,2'-(p-Tolylimino)diethanol	3077-12-1	Activated sludge	Analogous Compound	3 hours	EC50	>1,000 mg/l
2,2'-(p-Tolylimino)diethanol	3077-12-1	Common Carp	Analogous Compound	96 hours	LC50	>100 mg/l
2,2'-(p-Tolylimino)diethanol	3077-12-1	Green algae	Analogous Compound	72 hours	ErC50	>100 mg/l
2,2'-(p-Tolylimino)diethanol	3077-12-1	Water flea	Analogous Compound	48 hours	EC50	48 mg/l
2,2'-(p-Tolylimino)diethanol	3077-12-1	Green algae	Analogous Compound	72 hours	NOEC	100 mg/l
acrylic acid	79-10-7	Green algae	Experimental	72 hours	EC50	0.13 mg/l
acrylic acid	79-10-7	Rainbow trout	Experimental	96 hours	LC50	27 mg/l
acrylic acid	79-10-7	Water flea	Experimental	48 hours	EC50	95 mg/l
acrylic acid	79-10-7	Green algae	Experimental	72 hours	EC10	0.03 mg/l
acrylic acid	79-10-7	Water flea	Experimental	21 days	NOEC	3.8 mg/l
acrylic acid	79-10-7	N/A	Experimental	7 days	LD50	>=98 mg per kg of bodyweight
acrylic acid	79-10-7	N/A	Experimental	48 hours	NOEC	0.9 mg/l
acrylic acid	79-10-7	Activated sludge	Experimental	30 minutes	NOEC	100 mg/l
acrylic acid	79-10-7	Redworm	Experimental	14 days	LC50	>1,000 mg/kg (Dry Weight)
acrylic acid	79-10-7	Soil microbes	Experimental	28 days	NOEC	100 mg/kg (Dry Weight)
Naphthalene, (1-methylethyl)-	29253-36-9	Green algae	Experimental	72 hours	EC50	0.245 mg/l
Naphthalene, (1-methylethyl)-	29253-36-9	Medaka	Experimental	96 hours	LC50	0.74 mg/l
Naphthalene, (1-methylethyl)-	29253-36-9	Water flea	Experimental	48 hours	EC50	0.67 mg/l
Naphthalene, (1-methylethyl)-	29253-36-9	Water flea	Estimated	21 days	NOEC	0.013 mg/l
Naphthalene, (1-methylethyl)-	29253-36-9	Green algae	Experimental	72 hours	NOEC	0.079 mg/l
Titanium dioxide	13463-67-7	Activated sludge	Experimental	3 hours	NOEC	>=1,000 mg/l
Titanium dioxide	13463-67-7	Diatom	Experimental	72 hours	EC50	>10,000 mg/l
Titanium dioxide	13463-67-7	Fathead minnow	Experimental	96 hours	LC50	>100 mg/l
Titanium dioxide	13463-67-7	Water flea	Experimental	48 hours	EC50	>100 mg/l
Titanium dioxide	13463-67-7	Diatom	Experimental	72 hours	NOEC	5,600 mg/l

**12.2. Persistence and degradability**

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
2,2'-ethylenedioxydiethyl dimethacrylate	109-16-0	Experimental Biodegradation	28 days	CO2 evolution	85 %CO2 evolution/THC O2 evolution	OECD 301B - Modified sturm or CO2
Bis(isopropyl)naphthalene	38640-62-9	Data not availbl-insufficient	N/A	N/A	N/A	N/A
HYDROXYPROPYL METHACRYLATE	27813-02-1	Experimental Biodegradation	28 days	BOD	81 %BOD/ThOD	OECD 301C - MITI test (I)
2'-Phenylacetohydrazide	114-83-0	Analogous	28 days	Dissolv. Organic	97 %removal	OECD 301E - Modif. OECD

**3M Scotch-Weld(TM) Threadlocker TL42, Blue**

		Compound Biodegradation		Carbon Deplet	of DOC	Screen
2,6-Di-tert-butyl-p-cresol	128-37-0	Data not available - insufficient	N/A	N/A	N/A	N/A
N,N-dimethyl-p-toluidine	99-97-8	Estimated Biodegradation	14 days	BOD	0 %BOD/ThOD	OECD 301C - MITI test (I)
1,2-Benzisothiazol-3(2H)-one 1,1-dioxide	81-07-2	Analogous Compound Biodegradation	28 days	BOD	32.09 %BOD/ThOD	OECD 301F - Manometric respirometry
Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, hydrolysis products with silica	68909-20-6	Data not available - insufficient	N/A	N/A	N/A	N/A
$\alpha$ , $\alpha$ -dimethylbenzyl hydroperoxide	80-15-9	Experimental Biodegradation	28 days	BOD	0 %BOD/ThOD	OECD 301C - MITI test (I)
2,2'-(p-Tolylimino)diethanol	3077-12-1	Analogous Compound Biodegradation	29 days	CO2 evolution	1.5 %CO2 evolution/THCO2 evolution	OECD 301B - Modified Sturm or CO2
acrylic acid	79-10-7	Experimental Biodegradation	28 days	Percent degraded	81 %BOD/ThOD	OECD 301D - Closed bottle test
acrylic acid	79-10-7	Estimated Photolysis		Photolytic half-life (in air)	3.2 days (t 1/2)	
acrylic acid	79-10-7	Experimental Biodegradation	3 days	Percent degraded	72.9 %CO2 evolution/THCO2 evolution	
Naphthalene, (1-methylethyl)-	29253-36-9	Experimental Biodegradation	28 days	CO2 evolution	63 %CO2 evolution/THCO2 evolution	OECD 310 CO2 Headspace
Titanium dioxide	13463-67-7	Data not available - insufficient	N/A	N/A	N/A	N/A

**12.3 : Bioaccumulative potential**

Material	Cas No.	Test type	Duration	Study Type	Test result	Protocol
2,2'-ethylenedioxydiethyl dimethacrylate	109-16-0	Experimental Bioconcentration		Log Kow	2.3	EC A.8 Partition Coefficient
Bis(isopropyl)naphthalene	38640-62-9	Experimental BCF - Fish	36 days	Bioaccumulation factor	1800-6400	OECD305-Bioconcentration
Bis(isopropyl)naphthalene	38640-62-9	Modeled Bioconcentration		Log Kow	6.081	Episuite™
HYDROXYPROPYL METHACRYLATE	27813-02-1	Experimental Bioconcentration		Log Kow	0.97	EC A.8 Partition Coefficient
2'-Phenylacetohydrazide	114-83-0	Modeled BCF - Fish		Bioaccumulation factor	5	Catalogic™
2,6-Di-tert-butyl-p-cresol	128-37-0	Experimental BCF - Fish	56 days	Bioaccumulation factor	1277	OECD305-Bioconcentration
N,N-dimethyl-p-toluidine	99-97-8	Experimental Bioconcentration		Log Kow	1.73	
1,2-Benzisothiazol-3(2H)-one 1,1-dioxide	81-07-2	Experimental Bioconcentration		Log Kow	-0.024	OECD 117 log Kow HPLC method
Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, hydrolysis products with silica	68909-20-6	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
$\alpha$ , $\alpha$ -dimethylbenzyl hydroperoxide	80-15-9	Experimental Bioconcentration		Log Kow	1.82	
2,2'-(p-Tolylimino)diethanol	3077-12-1	Experimental Bioconcentration		Log Kow	2.0	
acrylic acid	79-10-7	Experimental Bioconcentration		Log Kow	0.46	OECD 107 log Kow shake flask mtd
Naphthalene, (1-methylethyl)-	29253-36-9	Experimental BCF - Fish	56 days	Bioaccumulation factor	870	OECD305-Bioconcentration
Titanium dioxide	13463-67-7	Experimental BCF - Fish	42 days	Bioaccumulation factor	9.6	

**12.4. Mobility in soil**

Material	Cas No.	Test type	Study Type	Test result	Protocol
Bis(isopropyl)naphthalene	38640-62-9	Modeled Mobility in Soil	Koc	36,000 l/kg	Episuite™
HYDROXYPROPYL METHACRYLATE	27813-02-1	Experimental Mobility in Soil	Koc	10 l/kg	Episuite™
2'-Phenylacetohydrazide	114-83-0	Modeled Mobility in Soil	Koc	64 l/kg	Episuite™
1,2-Benzisothiazol-3(2H)-one 1,1-dioxide	81-07-2	Modeled Mobility in Soil	Koc	23 l/kg	Episuite™
2,2'-(p-Tolylimino)diethanol	3077-12-1	Experimental Mobility in Soil	Koc	214 l/kg	EC C.19 Estim. of Koc by HPLC
acrylic acid	79-10-7	Experimental Mobility in Soil	Koc	6-137 l/kg	40CFR796.2750 Sed/Soil Adsorp
Naphthalene, (1-methylethyl)-	29253-36-9	Estimated Mobility in Soil	Koc	7,500 l/kg	Episuite™

**12.5. Results of the PBT and vPvB assessment**

This material does not contain any substances that are assessed to be a PBT or vPvB

**12.6. Endocrine disrupting properties**

This material does not contain any substances that are assessed to be an endocrine disruptor for environmental effects

**12.7. Other adverse effects**

No information available.

**SECTION 13: Disposal considerations**

**13.1 Waste treatment methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

**EU waste code (product as sold)**

- 08 04 09\* Waste adhesives and sealants containing organic solvents or other dangerous substances
- 20 01 27\* Paint, inks, adhesives and resins containing dangerous substances

**SECTION 14: Transportation information**

	Ground Transport (ADR)	Air Transport (IATA)	Marine Transport (IMDG)

<b>14.1 UN number or ID number</b>	UN3082	UN3082	UN3082
<b>14.2 UN proper shipping name</b>	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.(BIS(ISOPROPYL)NAPHTHALENE)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.(BIS(ISOPROPYL)NAPHTHALENE)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.(BIS(ISOPROPYL)NAPHTHALENE)
<b>14.3 Transport hazard class(es)</b>	9	9	9
<b>14.4 Packing group</b>	III	III	III
<b>14.5 Environmental hazards</b>	Environmentally Hazardous	Not applicable	Marine Pollutant
<b>14.6 Special precautions for user</b>	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.
<b>14.7 Marine Transport in bulk according to IMO instruments</b>	No data available.	No data available.	No data available.
<b>Control Temperature</b>	No data available.	No data available.	No data available.
<b>Emergency Temperature</b>	No data available.	No data available.	No data available.
<b>ADR Classification Code</b>	M6	Not applicable.	Not applicable.
<b>IMDG Segregation Code</b>	Not applicable.	Not applicable.	NONE

Please contact the address or phone number listed on the first page of the SDS for additional information on the transport/shipment of the material by rail (RID) or inland waterways (ADN).

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Carcinogenicity

<u>Ingredient</u>	<u>CAS Nbr</u>	<u>Classification</u>	<u>Regulation</u>
2,6-Di-tert-butyl-p-cresol	128-37-0	Gr. 3: Not classifiable	International Agency for Research on Cancer
acrylic acid	79-10-7	Gr. 3: Not classifiable	International Agency for Research on Cancer
N,N-dimethyl-p-toluidine	99-97-8	Carc. 1B	3M Classified according to Regulation (EC) No 1272/2008

**3M Scotch-Weld(TM) Threadlocker TL42, Blue**

N,N-dimethyl-p-toluidine	99-97-8	Grp. 2B: Possible human carc.	International Agency for Research on Cancer
1,2-Benzisothiazol-3(2H)-one 1,1-dioxide	81-07-2	Gr. 3: Not classifiable	International Agency for Research on Cancer
Titanium dioxide	13463-67-7	Grp. 2B: Possible human carc.	International Agency for Research on Cancer

**Global inventory status**

Contact 3M for more information. The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

**DIRECTIVE 2012/18/EU**

Seveso hazard categories, Annex 1, Part 1

Hazard Categories	Qualifying quantity (tonnes) for the application of	
	Lower-tier requirements	Upper-tier requirements
E1 Hazardous to the Aquatic environment	100	200

Seveso named dangerous substances, Annex 1, Part 2

Dangerous Substances	Identifier(s)	Qualifying quantity (tonnes) for the application of	
		Lower-tier requirements	Upper-tier requirements
acrylic acid	79-10-7	50	200
$\alpha$ , $\alpha$ -dimethylbenzyl hydroperoxide	80-15-9	50	200
N,N-dimethyl-p-toluidine	99-97-8	50	200

**Regulation (EU) No 649/2012**

No chemicals listed

**15.2. Chemical Safety Assessment**

A chemical safety assessment has not been carried out for this mixture. Chemical safety assessments for the contained substances may have been carried out by the registrants of the substances in accordance with Regulation (EC) No 1907/2006, as amended.

**SECTION 16: Other information****List of relevant H statements**

EUH066	Repeated exposure may cause skin dryness or cracking.
H226	Flammable liquid and vapour.
H242	Heating may cause a fire.
H301	Toxic if swallowed.

H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H350	May cause cancer.
H351i	Suspected of causing cancer by inhalation.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure: nervous system   respiratory system.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

**Revision information:**

- Section 2: <125ml Hazard - Health information was modified.
  - Section 2: <125ml Precautionary - Prevention information was modified.
  - Section 2: <125ml Precautionary - Response information was modified.
  - CLP: Ingredient table information was modified.
  - Label: CLP Classification information was modified.
  - Label: CLP Precautionary - Prevention information was modified.
  - Label: CLP Precautionary - Response information was modified.
  - Label: Signal Word information was modified.
  - Section 02: SDS Elements: CLP Supplemental Precautionary Statements information was added.
  - Section 3: Composition/ Information of ingredients table information was modified.
  - Section 8: Eye/face protection information information was modified.
  - Section 8: Personal Protection - Skin/body information information was added.
  - Section 8: Skin protection - protective clothing information information was added.
  - Section 11: Acute Toxicity table information was modified.
  - Section 11: Germ Cell Mutagenicity Table information was modified.
  - Section 11: Reproductive Toxicity Table information was modified.
  - Section 11: Serious Eye Damage/Irritation Table information was modified.
  - Section 11: Skin Corrosion/Irritation Table information was modified.
  - Section 11: Skin Sensitization Table information was modified.
  - Section 11: Target Organs - Repeated Table information was modified.
  - Section 12: Component ecotoxicity information information was modified.
  - Section 12: Mobility in soil information information was modified.
  - Section 12: Persistence and Degradability information information was modified.
  - Section 12: Bioaccumulative potential information information was modified.
  - Section 15: Carcinogenicity information information was modified.
- Two-column table displaying the unique list of H Codes and statements (std phrases) for all components of the given material. information was modified.

**Annex**

1. Title	
Substance identification	acrylic acid; EC No. 201-177-9; CAS Nbr 79-10-7;
Exposure Scenario Name	Industrial Use of Adhesives
Lifecycle Stage	Use at industrial sites
Contributing activities	PROC 13 -Treatment of articles by dipping and pouring ERC 06c -Use of monomer in polymerisation processes at industrial site (inclusion or not into/onto article)
Processes, tasks and activities covered	Application of product.
2. Operational conditions and risk management measures	
Operating Conditions	<b>Physical state:</b> Liquid. <b>General operating conditions:</b> Duration of use: > 4 hours task; Indoor use with Local Exhaust Ventilation; Outdoor use;
Risk management measures	Under the operational conditions described above the following risk management measures apply: <b>General risk management measures:</b> <b>Human health:</b> Protective Gloves - Chemical resistant. Refer to Section 8 of the SDS for specific glove material.; Safety glasses with side shields.; <b>Environmental:</b> None needed;
Waste management measures	No use-specific waste management measures are required for this product. Refer to Section 13 of main SDS for disposal instructions;
3. Prediction of exposure	
Prediction of exposure	Human and environmental exposures are not expected to exceed the DNELs and PNECs when the identified risk management measures are adopted.

1. Title	
Substance identification	acrylic acid; EC No. 201-177-9; CAS Nbr 79-10-7;
Exposure Scenario Name	Professional Use of Adhesives
Lifecycle Stage	Widespread use by professional workers
Contributing activities	PROC 13 -Treatment of articles by dipping and pouring ERC 08c -Widespread use leading to inclusion into/onto article (indoor)
Processes, tasks and activities covered	Application of product.
2. Operational conditions and risk management measures	
Operating Conditions	<b>Physical state:</b> Liquid. <b>General operating conditions:</b> Duration of exposure per day at workplace [for one worker]: > 4 hours task; Indoor use with Local Exhaust Ventilation; Outdoor use;  <b>Task: Application of product without local exhaust ventilation;</b> Indoor use; Duration of use: <= 1 hours per task;
Risk management measures	Under the operational conditions described above the following risk management measures apply: <b>General risk management measures:</b> <b>Human health:</b> Protective Gloves - Chemical resistant. Refer to Section 8 of the SDS for

	specific glove material.; Safety glasses with side shields.; <b>Environmental:</b> None needed;
<b>Waste management measures</b>	No use-specific waste management measures are required for this product. Refer to Section 13 of main SDS for disposal instructions:
<b>3. Prediction of exposure</b>	
<b>Prediction of exposure</b>	Human and environmental exposures are not expected to exceed the DNELs and PNECs when the identified risk management measures are adopted.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into the European Union, you are responsible for all regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration.

**3M Ireland MSDSs are available at [www.3M.com](http://www.3M.com)**