



## Safety Data Sheet

Copyright, 2023, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

<b>Document group:</b>	30-0188-0	<b>Version number:</b>	6.00
<b>Revision date:</b>	03/11/2023	<b>Supersedes date:</b>	22/08/2023

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

3M™ Scotchkote™ Electrical Coating FD

#### Product Identification Numbers

80-6116-1578-4

7100095977

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### Identified uses

Electrical

#### 1.3. Details of the supplier of the safety data sheet

**Address:** 3M Ireland Limited, The Iveagh Building, The Park, Carrickmines, Dublin 18.  
**Telephone:** +353 1 280 3555  
**E Mail:** tox.uk@mmm.com  
**Website:** www.3M.com

#### 1.4. Emergency telephone number

Emergency medical information: 8am-10pm (seven days) contact National Poisons Information Centre, Beaumont Hospital, Dublin 9 DOV2NO, Ireland. Telephone Number: +353 (0)1 809 2166

### SECTION 2: Hazard identification

#### 2.1. Classification of the substance or mixture

CLP REGULATION (EC) No 1272/2008

The health and environmental classifications of this material have been derived using the calculation method, except in cases where test data are available or the physical form impacts classification. Classification(s) based on test data or physical form are noted below, if applicable.

##### CLASSIFICATION:

Flammable Liquid, Category 2 - Flam. Liq. 2; H225  
Serious Eye Damage/Eye Irritation, Category 1 - Eye Dam. 1; H318

Skin Sensitization, Category 1 - Skin Sens. 1; H317  
Specific Target Organ Toxicity-Single Exposure, Category 3 - STOT SE 3; H336  
Hazardous to the Aquatic Environment (Chronic), Category 3 - Aquatic Chronic 3; H412

For full text of H phrases, see Section 16.

## 2.2. Label elements

### CLP REGULATION (EC) No 1272/2008

#### SIGNAL WORD

DANGER.

#### Symbols

GHS02 (Flame) |GHS05 (Corrosion) |GHS07 (Exclamation mark) |

#### Pictograms



#### Ingredients:

Ingredient	CAS Nbr	EC No.	% by Wt
acetone	67-64-1	200-662-2	60 - 75
FUMARATED ROSIN	65997-04-8	266-040-8	5 - 10

#### HAZARD STATEMENTS:

H225	Highly flammable liquid and vapour.
H318	Causes serious eye damage.
H317	May cause an allergic skin reaction.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.

#### PRECAUTIONARY STATEMENTS

##### General:

P102 Keep out of reach of children.

##### Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P261A Avoid breathing vapours.  
P280B Wear protective gloves and eye/face protection.

##### Response:

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P310 Immediately call a POISON CENTRE or doctor/physician.

##### Storage:

P405 Store locked up.

##### Disposal:

P501 Dispose of contents/container in accordance with applicable local/regional/national/international

regulations.

### SUPPLEMENTAL INFORMATION:

#### Supplemental Hazard Statements:

EUH066

Repeated exposure may cause skin dryness or cracking.

Contains 6% of components with unknown hazards to the aquatic environment.

#### 2.3. Other hazards

None known.

This material does not contain any substances that are assessed to be a PBT or vPvB

## SECTION 3: Composition/information on ingredients

#### 3.1. Substances

Not applicable

#### 3.2. Mixtures

Ingredient	Identifier(s)	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
acetone	(CAS-No.) 67-64-1 (EC-No.) 200-662-2 (REACH-No.) 01-2119471330-49	60 - 75	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 EUH066
Acrylonitrile-Butadiene Polymer	(CAS-No.) 9003-18-3	10 - 20	Substance not classified as hazardous
FUMARATED ROSIN	(CAS-No.) 65997-04-8 (EC-No.) 266-040-8	5 - 10	Eye Dam. 1, H318 Skin Sens. 1A, H317
Formaldehyde, polymer with 4-(1,1-dimethylethyl) phenol	(CAS-No.) 25085-50-1	5 - 10	Substance not classified as hazardous
salicylic acid	(CAS-No.) 69-72-7 (EC-No.) 200-712-3	< 3	Acute Tox. 4, H302 Eye Dam. 1, H318 Repr. 2, H361d
zinc oxide	(CAS-No.) 1314-13-2 (EC-No.) 215-222-5	< 2	Aquatic Acute 1, H400,M=1 Aquatic Chronic 1, H410,M=1
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene	(CAS-No.) 68411-46-1 (EC-No.) 270-128-1	< 0.5	Repr. 2, H361f Aquatic Acute 1, H400,M=1 Aquatic Chronic 1, H410,M=1
4-tert-butylphenol	(CAS-No.) 98-54-4 (EC-No.) 202-679-0	< 0.3	Skin Irrit. 2, H315 Eye Dam. 1, H318 Repr. 2, H361f Aquatic Chronic 1, H410,M=1
toluene	(CAS-No.) 108-88-3 (EC-No.) 203-625-9	< 0.3	Flam. Liq. 2, H225 Asp. Tox. 1, H304 Skin Irrit. 2, H315 Repr. 2, H361d STOT SE 3, H336

			STOT RE 2, H373 Aquatic Chronic 3, H412
--	--	--	--

Please see section 16 for the full text of any H statements referred to in this section

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

**SECTION 4: First aid measures**

**4.1. Description of first aid measures**

**Inhalation**

Remove person to fresh air. If you feel unwell, get medical attention.

**Skin contact**

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

**Eye contact**

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

**If swallowed**

Rinse mouth. If you feel unwell, get medical attention.

**4.2. Most important symptoms and effects, both acute and delayed**

The most important symptoms and effects based on the CLP classification include:  
Allergic skin reaction (redness, swelling, blistering, and itching). Toxic by eye contact. Serious damage to the eyes (corneal cloudiness, severe pain, tearing, ulcerations, and significantly impaired or loss of vision). Central nervous system depression (headache, dizziness, drowsiness, incoordination, nausea, slurred speech, giddiness, and unconsciousness).

**4.3. Indication of any immediate medical attention and special treatment required**

Not applicable

**SECTION 5: Fire-fighting measures**

**5.1. Extinguishing media**

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

**5.2. Special hazards arising from the substance or mixture**

Closed containers exposed to heat from fire may build pressure and explode.

**Hazardous Decomposition or By-Products**

<u>Substance</u>	<u>Condition</u>
Hydrocarbons.	During combustion.
Carbon monoxide	During combustion.
Carbon dioxide.	During combustion.
Oxides of nitrogen.	During combustion.

**5.3. Advice for fire-fighters**

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapours in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

### 6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

### 6.3. Methods and material for containment and cleaning up

Contain spill. Cover spill area with a fire-extinguishing foam. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible.

### 6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Keep out of reach of children. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.) Wear low static or properly grounded shoes. Use personal protective equipment (eg. gloves, respirators...) as required. To minimize the risk of ignition, determine applicable electrical classifications for the process using this product and select specific local exhaust ventilation equipment to avoid flammable vapour accumulation. Ground/bond container and receiving equipment if there is potential for static electricity accumulation during transfer.

### 7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store away from heat. Store away from acids. Store away from oxidising agents.

### 7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
------------	---------	--------	------------	---------------------

toluene	108-88-3	Ireland OELs	TWA(8 hours):192 mg/m <sup>3</sup> (50 ppm);TWA(8 hours):50 ppm(192 mg/m <sup>3</sup> );STEL(15 minutes):384 mg/m <sup>3</sup> (100 ppm);STEL(15 minutes):100 ppm(384 mg/m <sup>3</sup> )	SKIN
zinc oxide	1314-13-2	Ireland OELs	TWA(Respirable fraction & fume)(8 hours):2 mg/m <sup>3</sup> ;STEL(Respirable fraction & fume)(15 minutes):10 mg/m <sup>3</sup>	
acetone	67-64-1	Ireland OELs	TWA(8 hours):1210 mg/m <sup>3</sup> (500 ppm);TWA(8 hours):500 ppm(1210 mg/m <sup>3</sup> )	

Ireland OELs : Ireland. OELs  
TWA: Time-Weighted-Average  
STEL: Short Term Exposure Limit  
CEIL: Ceiling

**Biological limit values**

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

**Derived no effect level (DNEL)**

Ingredient	Degradation Product	Population	Human exposure pattern	DNEL
acetone		Worker	Dermal, Long-term exposure (8 hours), Systemic effects	186 mg/kg bw/d
acetone		Worker	Inhalation, Long-term exposure (8 hours), Systemic effects	1,210 mg/m <sup>3</sup>
acetone		Worker	Inhalation, Short-term exposure, Local effects	2,420 mg/m <sup>3</sup>

**Predicted no effect concentrations (PNEC)**

Ingredient	Degradation Product	Compartment	PNEC
acetone		Agricultural soil	29.5 mg/kg d.w.
acetone		Freshwater	10.6 mg/l
acetone		Freshwater sediments	30.4 mg/kg d.w.
acetone		Intermittent releases to water	21 mg/l
acetone		Marine water	1.06 mg/l
acetone		Marine water sediments	3.04 mg/kg d.w.
acetone		Sewage Treatment Plant	100 mg/l

**Recommended monitoring procedures:**Information on recommended monitoring procedures can be obtained from Indust. Inspect./Ministry (IE)

**8.2. Exposure controls**

In addition, refer to the annex for more information.

**8.2.1. Engineering controls**

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

Use explosion-proof ventilation equipment.

### 8.2.2. Personal protective equipment (PPE)

#### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

- Full face shield.
- Indirect vented goggles.

#### *Applicable Norms/Standards*

Use eye/face protection conforming to EN 166

#### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended:

Material	Thickness (mm)	Breakthrough Time
Polymer laminate	No data available	No data available

#### *Applicable Norms/Standards*

Use gloves tested to EN 374

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

#### Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours

For questions about suitability for a specific application, consult with your respirator manufacturer.

#### *Applicable Norms/Standards*

Use a respirator conforming to EN 140 or EN 136: filter type A

### 8.2.3. Environmental exposure controls

Refer to Annex

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	Liquid.
Specific Physical Form:	Viscous.
Colour	Dark Brown
Odor	Sharp Solvent
Odour threshold	No data available.

<b>Melting point/freezing point</b>	<i>Not applicable.</i>
<b>Boiling point/boiling range</b>	$\geq 56$ °C [ <i>Details:acetone</i> ]
<b>Flammability (solid, gas)</b>	Not applicable.
<b>Flammable Limits(LEL)</b>	2.6 %
<b>Flammable Limits(UEL)</b>	12.8 %
<b>Flash point</b>	-20 °C [ <i>Test Method:Closed Cup</i> ]
<b>Autoignition temperature</b>	465 °C
<b>Decomposition temperature</b>	<i>No data available.</i>
<b>pH</b>	<i>substance/mixture is non-soluble (in water)</i>
<b>Kinematic Viscosity</b>	374 mm <sup>2</sup> /sec
<b>Water solubility</b>	Slight (less than 10%)
<b>Solubility- non-water</b>	<i>No data available.</i>
<b>Partition coefficient: n-octanol/water</b>	<i>No data available.</i>
<b>Vapour pressure</b>	$\leq 24,664.6$ Pa [ <i>@ 20 °C</i> ]
<b>Density</b>	0.87 g/ml
<b>Relative density</b>	0.87 [ <i>Ref Std:WATER=1</i> ]
<b>Relative Vapour Density</b>	2 [ <i>Ref Std:AIR=1</i> ]

## 9.2. Other information

### 9.2.2 Other safety characteristics

<b>Average particle size</b>	<i>No data available.</i>
<b>Bulk density</b>	<i>No data available.</i>
<b>EU Volatile Organic Compounds</b>	<i>No data available.</i>
<b>Evaporation rate</b>	1.9 [ <i>Ref Std:ETHER=1</i> ]
<b>Molecular weight</b>	<i>No data available.</i>
<b>Percent volatile</b>	40 - 75 % weight
<b>Softening point</b>	<i>No data available.</i>
<b>Solids content</b>	$\geq 28$ % weight

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

### 10.2 Chemical stability

Stable.

### 10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

### 10.4 Conditions to avoid

Heat.  
Sparks and/or flames.

### 10.5 Incompatible materials

Strong oxidising agents.

### 10.6 Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.



## SECTION 11: Toxicological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from internal hazard assessments.

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

#### Skin contact

Prolonged or repeated exposure may cause: Dermal Defatting: Signs/symptoms may include localized redness, itching, drying and cracking of skin. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

#### Eye contact

Corrosive (eye burns): Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision.

#### Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea. May cause additional health effects (see below).

#### Additional Health Effects:

#### Single exposure may cause target organ effects:

Central nervous system (CNS) depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

#### Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

#### Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

#### Acute Toxicity

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
acetone	Dermal	Rabbit	LD50 > 15,688 mg/kg
acetone	Inhalation-Vapour (4 hours)	Rat	LC50 76 mg/l
acetone	Ingestion	Rat	LD50 5,800 mg/kg
Acrylonitrile-Butadiene Polymer	Dermal	Rabbit	LD50 > 15,000 mg/kg
Acrylonitrile-Butadiene Polymer	Ingestion	Rat	LD50 > 30,000 mg/kg
FUMARATED ROSIN	Dermal	Rat	LD50 > 2,000 mg/kg
FUMARATED ROSIN	Ingestion	Rat	LD50 > 2,000 mg/kg
Formaldehyde, polymer with 4-(1,1-dimethylethyl) phenol	Dermal		LD50 estimated to be > 5,000 mg/kg

**3M™ Scotchkote™ Electrical Coating FD**

Formaldehyde, polymer with 4-(1,1-dimethylethyl) phenol	Ingestion	Rat	LD50 5,660 mg/kg
salicylic acid	Dermal	Rat	LD50 > 2,000 mg/kg
salicylic acid	Ingestion	Rat	LD50 891 mg/kg
zinc oxide	Dermal		LD50 estimated to be > 5,000 mg/kg
zinc oxide	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 5.7 mg/l
zinc oxide	Ingestion	Rat	LD50 > 5,000 mg/kg
toluene	Dermal	Rat	LD50 12,000 mg/kg
toluene	Inhalation-Vapour (4 hours)	Rat	LC50 30 mg/l
toluene	Ingestion	Rat	LD50 5,550 mg/kg
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene	Dermal	Rat	LD50 > 2,000 mg/kg
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene	Ingestion	Rat	LD50 > 5,000 mg/kg
4-tert-butylphenol	Dermal	Rabbit	LD50 2,318 mg/kg
4-tert-butylphenol	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 5.6 mg/l
4-tert-butylphenol	Ingestion	Rat	LD50 4,000 mg/kg

ATE = acute toxicity estimate

**Skin Corrosion/Irritation**

Name	Species	Value
acetone	Mouse	Minimal irritation
Acrylonitrile-Butadiene Polymer	Professional judgement	No significant irritation
FUMARATED ROSIN	Rabbit	No significant irritation
salicylic acid	Rabbit	No significant irritation
zinc oxide	Human and animal	No significant irritation
toluene	Rabbit	Irritant
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene	Rabbit	Mild irritant
4-tert-butylphenol	Rabbit	Irritant

**Serious Eye Damage/Irritation**

Name	Species	Value
acetone	Rabbit	Severe irritant
Acrylonitrile-Butadiene Polymer	Professional judgement	No significant irritation
FUMARATED ROSIN	Rabbit	Corrosive
salicylic acid	Rabbit	Corrosive
zinc oxide	Rabbit	Mild irritant
toluene	Rabbit	Moderate irritant
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene	Rabbit	Mild irritant
4-tert-butylphenol	Rabbit	Corrosive

**Skin Sensitisation**

Name	Species	Value
FUMARATED ROSIN	Mouse	Sensitising
Formaldehyde, polymer with 4-(1,1-dimethylethyl) phenol	Human	Some positive data exist, but the data are not sufficient for classification
salicylic acid	Mouse	Not classified

**3M™ Scotchkote™ Electrical Coating FD**

zinc oxide	Guinea pig	Not classified
toluene	Guinea pig	Not classified
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene	Guinea pig	Not classified
4-tert-butylphenol	Human and animal	Not classified

**Photosensitisation**

Name	Species	Value
salicylic acid	Mouse	Not sensitising

**Respiratory Sensitisation**

For the component/components, either no data is currently available or the data is not sufficient for classification.

**Germ Cell Mutagenicity**

Name	Route	Value
acetone	In vivo	Not mutagenic
acetone	In Vitro	Some positive data exist, but the data are not sufficient for classification
FUMARATED ROSIN	In Vitro	Not mutagenic
salicylic acid	In Vitro	Not mutagenic
salicylic acid	In vivo	Not mutagenic
zinc oxide	In Vitro	Some positive data exist, but the data are not sufficient for classification
zinc oxide	In vivo	Some positive data exist, but the data are not sufficient for classification
toluene	In Vitro	Not mutagenic
toluene	In vivo	Not mutagenic
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene	In Vitro	Not mutagenic
4-tert-butylphenol	In Vitro	Not mutagenic

**Carcinogenicity**

Name	Route	Species	Value
acetone	Not specified.	Multiple animal species	Not carcinogenic
toluene	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
toluene	Ingestion	Rat	Some positive data exist, but the data are not sufficient for classification
toluene	Inhalation	Mouse	Some positive data exist, but the data are not sufficient for classification
4-tert-butylphenol	Ingestion	Multiple animal species	Some positive data exist, but the data are not sufficient for classification

**Reproductive Toxicity****Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test result	Exposure Duration
acetone	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,700 mg/kg/day	13 weeks
acetone	Inhalation	Not classified for development	Rat	NOAEL 5.2 mg/l	during organogenesis
FUMARATED ROSIN	Ingestion	Not classified for female reproduction	Rat	NOAEL 450 mg/kg/day	prematuring into lactation

FUMARATED ROSIN	Ingestion	Not classified for male reproduction	Rat	NOAEL 650 mg/kg/day	28 days
FUMARATED ROSIN	Ingestion	Not classified for development	Rat	NOAEL 370 mg/kg/day	during gestation
salicylic acid	Ingestion	Toxic to development	Rat	NOAEL 75 mg/kg/day	during organogenesis
zinc oxide	Ingestion	Not classified for reproduction and/or development	Multiple animal species	NOAEL 125 mg/kg/day	premating & during gestation
toluene	Inhalation	Not classified for female reproduction	Human	NOAEL Not available	occupational exposure
toluene	Inhalation	Not classified for male reproduction	Rat	NOAEL 2.3 mg/l	1 generation
toluene	Ingestion	Toxic to development	Rat	LOAEL 520 mg/kg/day	during gestation
toluene	Inhalation	Toxic to development	Human	NOAEL Not available	poisoning and/or abuse
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene	Ingestion	Not classified for male reproduction	Rat	NOAEL 54 mg/kg/day	2 generation
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene	Ingestion	Not classified for development	Rat	NOAEL 18 mg/kg/day	2 generation
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene	Ingestion	Toxic to female reproduction	Rat	NOAEL 54 mg/kg/day	2 generation
4-tert-butylphenol	Ingestion	Not classified for male reproduction	Rat	NOAEL 600 mg/kg/day	2 generation
4-tert-butylphenol	Ingestion	Not classified for development	Rat	NOAEL 70 mg/kg/day	2 generation
4-tert-butylphenol	Ingestion	Toxic to female reproduction	Rat	NOAEL 200 mg/kg/day	2 generation

**Target Organ(s)**

**Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
acetone	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
acetone	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
acetone	Inhalation	immune system	Not classified	Human	NOAEL 1.19 mg/l	6 hours
acetone	Inhalation	liver	Not classified	Guinea pig	NOAEL Not available	
acetone	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse
FUMARATED ROSIN	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available.	
toluene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
toluene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
toluene	Inhalation	immune system	Not classified	Mouse	NOAEL 0.004 mg/l	3 hours
toluene	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL not available	
4-tert-butylphenol	Inhalation	respiratory irritation	May cause respiratory irritation	Rat	LOAEL 5.6 mg/l	4 hours

**Specific Target Organ Toxicity - repeated exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure
------	-------	-----------------	-------	---------	-------------	----------

**3M™ Scotchkote™ Electrical Coating FD**

						<b>Duration</b>
acetone	Dermal	eyes	Not classified	Guinea pig	NOAEL Not available	3 weeks
acetone	Inhalation	hematopoietic system	Not classified	Human	NOAEL 3 mg/l	6 weeks
acetone	Inhalation	immune system	Not classified	Human	NOAEL 1.19 mg/l	6 days
acetone	Inhalation	kidney and/or bladder	Not classified	Guinea pig	NOAEL 119 mg/l	not available
acetone	Inhalation	heart   liver	Not classified	Rat	NOAEL 45 mg/l	8 weeks
acetone	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 900 mg/kg/day	13 weeks
acetone	Ingestion	heart	Not classified	Rat	NOAEL 2,500 mg/kg/day	13 weeks
acetone	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 200 mg/kg/day	13 weeks
acetone	Ingestion	liver	Not classified	Mouse	NOAEL 3,896 mg/kg/day	14 days
acetone	Ingestion	eyes	Not classified	Rat	NOAEL 3,400 mg/kg/day	13 weeks
acetone	Ingestion	respiratory system	Not classified	Rat	NOAEL 2,500 mg/kg/day	13 weeks
acetone	Ingestion	muscles	Not classified	Rat	NOAEL 2,500 mg/kg	13 weeks
acetone	Ingestion	skin   bone, teeth, nails, and/or hair	Not classified	Mouse	NOAEL 11,298 mg/kg/day	13 weeks
FUMARATED ROSIN	Ingestion	endocrine system   immune system	Not classified	Rat	NOAEL 450 mg/kg/day	53 days
FUMARATED ROSIN	Ingestion	nervous system   eyes	Not classified	Rat	NOAEL 705 mg/kg/day	90 days
FUMARATED ROSIN	Ingestion	gastrointestinal tract   hematopoietic system   kidney and/or bladder   respiratory system	Not classified	Rat	NOAEL 450 mg/kg/day	53 days
salicylic acid	Ingestion	liver	Not classified	Rat	NOAEL 500 mg/kg/day	3 days
zinc oxide	Ingestion	nervous system	Not classified	Rat	NOAEL 600 mg/kg/day	10 days
zinc oxide	Ingestion	endocrine system   hematopoietic system   kidney and/or bladder	Not classified	Other	NOAEL 500 mg/kg/day	6 months
toluene	Inhalation	auditory system   nervous system   eyes   olfactory system	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	poisoning and/or abuse
toluene	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 2.3 mg/l	15 months
toluene	Inhalation	heart   liver   kidney and/or bladder	Not classified	Rat	NOAEL 11.3 mg/l	15 weeks
toluene	Inhalation	endocrine system	Not classified	Rat	NOAEL 1.1 mg/l	4 weeks
toluene	Inhalation	immune system	Not classified	Mouse	NOAEL Not available	20 days
toluene	Inhalation	bone, teeth, nails, and/or hair	Not classified	Mouse	NOAEL 1.1 mg/l	8 weeks
toluene	Inhalation	hematopoietic system   vascular system	Not classified	Human	NOAEL Not available	occupational exposure

**3M™ Scotchkote™ Electrical Coating FD**

toluene	Inhalation	gastrointestinal tract	Not classified	Multiple animal species	NOAEL 11.3 mg/l	15 weeks
toluene	Ingestion	nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 625 mg/kg/day	13 weeks
toluene	Ingestion	heart	Not classified	Rat	NOAEL 2,500 mg/kg/day	13 weeks
toluene	Ingestion	liver   kidney and/or bladder	Not classified	Multiple animal species	NOAEL 2,500 mg/kg/day	13 weeks
toluene	Ingestion	hematopoietic system	Not classified	Mouse	NOAEL 600 mg/kg/day	14 days
toluene	Ingestion	endocrine system	Not classified	Mouse	NOAEL 105 mg/kg/day	28 days
toluene	Ingestion	immune system	Not classified	Mouse	NOAEL 105 mg/kg/day	4 weeks
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene	Ingestion	nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 54 mg/kg/day	98 days
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene	Ingestion	endocrine system   liver   kidney and/or bladder   heart   gastrointestinal tract   bone, teeth, nails, and/or hair   hematopoietic system   immune system   muscles   eyes   respiratory system	Not classified	Rat	NOAEL 225 mg/kg/day	28 days
4-tert-butylphenol	Ingestion	endocrine system   liver   kidney and/or bladder	Not classified	Rat	NOAEL 600 mg/kg/day	2 generation
4-tert-butylphenol	Ingestion	blood	Not classified	Rat	NOAEL 200 mg/kg	6 weeks

**Aspiration Hazard**

Name	Value
toluene	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

**11.2. Information on other hazards**

This material does not contain any substances that are assessed to be an endocrine disruptor for human health.

**SECTION 12: Ecological information**

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

**12.1. Toxicity**

No product test data available.

Material	CAS #	Organism	Type	Exposure	Test endpoint	Test result
acetone	67-64-1	Algae or other aquatic plants	Experimental	96 hours	EC50	11,493 mg/l

**3M™ Scotchkote™ Electrical Coating FD**

acetone	67-64-1	Invertebrate	Experimental	24 hours	LC50	2,100 mg/l
acetone	67-64-1	Rainbow trout	Experimental	96 hours	LC50	5,540 mg/l
acetone	67-64-1	Water flea	Experimental	21 days	NOEC	1,000 mg/l
acetone	67-64-1	Bacteria	Experimental	16 hours	NOEC	1,700 mg/l
acetone	67-64-1	Redworm	Experimental	48 hours	LC50	>100
Acrylonitrile-Butadiene Polymer	9003-18-3	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
FUMARATED ROSIN	65997-04-8	Fathead minnow	Experimental	96 hours	No tox obs at lmt of water sol	>100 mg/l
FUMARATED ROSIN	65997-04-8	Green algae	Experimental	72 hours	No tox obs at lmt of water sol	>100 mg/l
FUMARATED ROSIN	65997-04-8	Water flea	Experimental	48 hours	EL50	>100 mg/l
FUMARATED ROSIN	65997-04-8	Green algae	Experimental	72 hours	No tox obs at lmt of water sol	100 mg/l
FUMARATED ROSIN	65997-04-8	Activated sludge	Analogous Compound	3 hours	EC50	>1,000 mg/l
Formaldehyde, polymer with 4-(1,1-dimethylethyl) phenol	25085-50-1	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
salicylic acid	69-72-7	Green algae	Experimental	72 hours	EC50	>100 mg/l
salicylic acid	69-72-7	Medaka	Experimental	96 hours	LC50	>100 mg/l
salicylic acid	69-72-7	Water flea	Experimental	48 hours	EC50	870 mg/l
salicylic acid	69-72-7	Water flea	Experimental	21 days	NOEC	10 mg/l
salicylic acid	69-72-7	Activated sludge	Experimental	3 hours	EC50	>3,200
salicylic acid	69-72-7	Bacteria	Experimental	18 hours	EC10	465
zinc oxide	1314-13-2	Activated sludge	Estimated	3 hours	EC50	6.5 mg/l
zinc oxide	1314-13-2	Green algae	Estimated	72 hours	EC50	0.052 mg/l
zinc oxide	1314-13-2	Rainbow trout	Estimated	96 hours	LC50	0.21 mg/l
zinc oxide	1314-13-2	Water flea	Estimated	48 hours	EC50	0.07 mg/l
zinc oxide	1314-13-2	Green algae	Estimated	72 hours	NOEC	0.006 mg/l
zinc oxide	1314-13-2	Water flea	Estimated	7 days	NOEC	0.02 mg/l
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene	68411-46-1	Water flea	Experimental	24 hours	EC50	0.82 mg/l
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene	68411-46-1	Zebra Fish	Experimental	96 hours	LC50	>47.05 mg/l
4-tert-butylphenol	98-54-4	Ciliated protozoa	Experimental	60 hours	IC50	18.4 mg/l
4-tert-butylphenol	98-54-4	Green algae	Experimental	72 hours	ErC50	14 mg/l
4-tert-butylphenol	98-54-4	Invertebrate	Experimental	96 hours	LC50	1.9 mg/l
4-tert-butylphenol	98-54-4	Medaka	Experimental	96 hours	LC50	5.1 mg/l

**3M™ Scotchkote™ Electrical Coating FD**

4-tert-butylphenol	98-54-4	Water flea	Experimental	48 hours	EC50	3.9 mg/l
4-tert-butylphenol	98-54-4	Fathead minnow	Experimental	128 days	NOEC	0.01 mg/l
4-tert-butylphenol	98-54-4	Green algae	Experimental	72 hours	NOEC	0.32 mg/l
4-tert-butylphenol	98-54-4	Water flea	Experimental	21 days	NOEC	0.73 mg/l
toluene	108-88-3	Coho Salmon	Experimental	96 hours	LC50	5.5 mg/l
toluene	108-88-3	Grass Shrimp	Experimental	96 hours	LC50	9.5 mg/l
toluene	108-88-3	Green algae	Experimental	72 hours	EC50	12.5 mg/l
toluene	108-88-3	Leopard frog	Experimental	9 days	LC50	0.39 mg/l
toluene	108-88-3	Pink Salmon	Experimental	96 hours	LC50	6.41 mg/l
toluene	108-88-3	Water flea	Experimental	48 hours	EC50	3.78 mg/l
toluene	108-88-3	Coho Salmon	Experimental	40 days	NOEC	1.39 mg/l
toluene	108-88-3	Diatom	Experimental	72 hours	NOEC	10 mg/l
toluene	108-88-3	Water flea	Experimental	7 days	NOEC	0.74 mg/l
toluene	108-88-3	Activated sludge	Experimental	12 hours	IC50	292 mg/l
toluene	108-88-3	Bacteria	Experimental	16 hours	NOEC	29 mg/l
toluene	108-88-3	Bacteria	Experimental	24 hours	EC50	84 mg/l
toluene	108-88-3	Redworm	Experimental	28 days	LC50	>150 mg per kg of bodyweight
toluene	108-88-3	Soil microbes	Experimental	28 days	NOEC	<26 mg/kg (Dry Weight)

**12.2. Persistence and degradability**

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
acetone	67-64-1	Experimental Biodegradation	28 days	BOD	78 %BOD/ThOD	OECD 301D - Closed bottle test
acetone	67-64-1	Experimental Photolysis		Photolytic half-life (in air)	147 days (t 1/2)	
Acrylonitrile-Butadiene Polymer	9003-18-3	Data not available - insufficient	N/A	N/A	N/A	N/A
FUMARATED ROSIN	65997-04-8	Experimental Biodegradation	28 days	BOD	15 %BOD/ThOD	OECD 301D - Closed bottle test
Formaldehyde, polymer with 4-(1,1-dimethylethyl) phenol	25085-50-1	Experimental Biodegradation	28 days	CO2 evolution	0 %CO2 evolution/THCO2 evolution	
salicylic acid	69-72-7	Experimental Biodegradation	14 days	BOD	88.1 %BOD/ThOD	OECD 301C - MITI test (I)
zinc oxide	1314-13-2	Data not available - insufficient	N/A	N/A	N/A	N/A
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene	68411-46-1	Experimental Biodegradation	28 days	CO2 evolution	<=1 %CO2 evolution/THCO2 evolution	OECD 301B - Modified sturm or CO2
4-tert-butylphenol	98-54-4	Experimental Biodegradation	28 days	Dissolv. Organic Carbon Deplet	98 %removal of DOC	EC C.4.A. DOC Die-Away Test
toluene	108-88-3	Experimental Biodegradation	20 days	BOD	80 %BOD/ThOD	APHA Std Meth Water/Wastewater
toluene	108-88-3	Experimental Photolysis		Photolytic half-life (in air)	5.2 days (t 1/2)	

**12.3 : Bioaccumulative potential**



Material	Cas No.	Test type	Duration	Study Type	Test result	Protocol
acetone	67-64-1	Experimental BCF - Other		Bioaccumulation factor	0.65	
acetone	67-64-1	Experimental Bioconcentration		Log Kow	-0.24	
Acrylonitrile-Butadiene Polymer	9003-18-3	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
FUMARATED ROSIN	65997-04-8	Experimental Bioconcentration		Log Kow	≥4.4	OECD 117 log Kow HPLC method
Formaldehyde, polymer with 4-(1,1-dimethylethyl) phenol	25085-50-1	Estimated Bioconcentration		Bioaccumulation factor	7.4	
salicylic acid	69-72-7	Experimental Bioconcentration		Log Kow	2.26	
zinc oxide	1314-13-2	Experimental BCF - Fish	56 days	Bioaccumulation factor	≤217	OECD305-Bioconcentration
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene	68411-46-1	Analogous Compound BCF - Fish	42 days	Bioaccumulation factor	1730	
4-tert-butylphenol	98-54-4	Experimental BCF - Fish	56 days	Bioaccumulation factor	88	OECD305-Bioconcentration
4-tert-butylphenol	98-54-4	Experimental Bioconcentration		Log Kow	3	OECD 117 log Kow HPLC method
toluene	108-88-3	Experimental BCF - Other	72 hours	Bioaccumulation factor	90	
toluene	108-88-3	Experimental Bioconcentration		Log Kow	2.73	

#### 12.4. Mobility in soil

Material	Cas No.	Test type	Study Type	Test result	Protocol
acetone	67-64-1	Modeled Mobility in Soil	Koc	9.7 l/kg	Episuite™
salicylic acid	69-72-7	Modeled Mobility in Soil	Koc	<1 l/kg	Episuite™
4-tert-butylphenol	98-54-4	Modeled Mobility in Soil	Koc	840 l/kg	Episuite™
toluene	108-88-3	Experimental Mobility in Soil	Koc	37-160 l/kg	

#### 12.5. Results of the PBT and vPvB assessment

This material does not contain any substances that are assessed to be a PBT or vPvB

#### 12.6. Endocrine disrupting properties

Ingredient	CAS Nbr	Environmental endocrine disruptor information
4-tert-butylphenol	98-54-4	This chemical has been determined to cause long-term effects in fish, including feminization of gonadal ducts in male fish and elevated levels of vitellogenin in female fish.

#### 12.7. Other adverse effects

No information available.

## SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. As a disposal alternative, utilize an acceptable permitted waste disposal facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

**EU waste code (product as sold)**

- 08 04 09\* Waste adhesives and sealants containing organic solvents or other dangerous substances
- 20 01 27\* Paint, inks, adhesives and resins containing dangerous substances

**SECTION 14: Transportation information**

	<b>Ground Transport (ADR)</b>	<b>Air Transport (IATA)</b>	<b>Marine Transport (IMDG)</b>
<b>14.1 UN number or ID number</b>	UN1866	UN1866	UN1866
<b>14.2 UN proper shipping name</b>	RESIN SOLUTION	RESIN SOLUTION	RESIN SOLUTION(ZINC OXIDE)
<b>14.3 Transport hazard class(es)</b>	3	3	3
<b>14.4 Packing group</b>	II	II	II
<b>14.5 Environmental hazards</b>	Environmentally Hazardous	Not applicable	Marine Pollutant
<b>14.6 Special precautions for user</b>	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.
<b>14.7 Marine Transport in bulk according to IMO instruments</b>	No data available.	No data available.	No data available.
<b>Control Temperature</b>	No data available.	No data available.	No data available.
<b>Emergency Temperature</b>	No data available.	No data available.	No data available.
<b>ADR Classification Code</b>	F1	Not applicable.	Not applicable.

<b>IMDG Segregation Code</b>	Not applicable.	Not applicable.	NONE
------------------------------	-----------------	-----------------	------

Please contact the address or phone number listed on the first page of the SDS for additional information on the transport/shipment of the material by rail (RID) or inland waterways (ADN).

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Carcinogenicity

**Ingredient**  
toluene

**CAS Nbr**  
108-88-3

**Classification**  
Gr. 3: Not classifiable

**Regulation**  
International Agency  
for Research on Cancer

#### Restrictions on the manufacture, placing on the market and use:

The following substance(s) contained in this product is/are subject through Annex XVII of REACH regulation to restrictions on the manufacture, placing on the market and use when present in certain dangerous substances, mixtures and articles. Users of this product are required to comply with the restrictions placed upon it by the aforementioned provision.

**Ingredient**  
toluene

**CAS Nbr**  
108-88-3

Restriction status: listed in REACH Annex XVII

Restricted uses: See Annex XVII to Regulation (EC) No 1907/2006 for Conditions of Restriction

#### Authorization status under REACH:

The following substance/s contained in this product might be or is/are subject to authorization in accordance with REACH:

**Ingredient**  
4-tert-butylphenol

**CAS Nbr**  
98-54-4

Authorization status: listed in the Candidate List of Substances of Very High Concern for Authorization

#### Regulation (EU) 2019/1148 (marketing and use of explosive precursors)

This product is regulated by Regulation (EU) 2019/1148: all suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point. Please see your local legislation.

#### Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

#### DIRECTIVE 2012/18/EU

Seveso hazard categories, Annex 1, Part 1

Hazard Categories	Qualifying quantity (tonnes) for the application of	
	Lower-tier requirements	Upper-tier requirements
P5c FLAMMABLE LIQUIDS*	5000	50000

\*If maintained at a temperature above its boiling point or if particular processing conditions, such as high pressure or high temperature, may create major-accident hazards, P5a or P5b FLAMMABLE LIQUIDS may apply

Seveso named dangerous substances, Annex 1, Part 2

Dangerous Substances	Identifier(s)	Qualifying quantity (tonnes) for the application of	
		Lower-tier requirements	Upper-tier requirements
acetone	67-64-1	10	50
4-tert-butylphenol	98-54-4	100	200
toluene	108-88-3	10	50
zinc oxide	1314-13-2	100	200

**Regulation (EU) No 649/2012**

No chemicals listed

**15.2. Chemical Safety Assessment**

A chemical safety assessment has not been carried out for this mixture. Chemical safety assessments for the contained substances may have been carried out by the registrants of the substances in accordance with Regulation (EC) No 1907/2006, as amended.

**SECTION 16: Other information**

**List of relevant H statements**

EUH066	Repeated exposure may cause skin dryness or cracking.
H225	Highly flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H361f	Suspected of damaging fertility.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

**Revision information:**

- CLP: Ingredient table information was modified.
- Label: CLP Classification information was modified.
- Label: CLP Precautionary - Prevention information was modified.
- Label: CLP Precautionary - Response information was modified.
- Label: Graphic information was modified.
- Section 3: Composition/ Information of ingredients table information was modified.
- Section 03: SCL table information was deleted.
- Section 04: First Aid - Symptoms and Effects (CLP) information was modified.
- Section 4: First aid for eye contact information information was modified.
- Section 7: Precautions safe handling information information was modified.
- Section 8: Eye/face protection information information was modified.
- Section 8: glove data value information was deleted.
- Section 8: glove data value information was modified.

Section 8: Occupational exposure limit table information was modified.  
 Section 8: Personal Protection - Skin/body information information was added.  
 Section 8: Personal Protection - Skin/hand information information was modified.  
 Section 8: Skin protection - protective clothing information information was added.  
 Section 11: Acute Toxicity table information was modified.  
 Section 11: Aspiration Hazard Table information was modified.  
 Section 11: Carcinogenicity Table information was modified.  
 Section 11: Germ Cell Mutagenicity Table information was modified.  
 Section 11: Health Effects - Eye information information was modified.  
 Section 11: Health Effects - Skin information information was modified.  
 Section 11: Prolonged or repeated exposure may cause standard phrases information was deleted.  
 Section 11: Reproductive Toxicity Table information was modified.  
 Section 11: Serious Eye Damage/Irritation Table information was modified.  
 Section 11: Skin Corrosion/Irritation Table information was modified.  
 Section 11: Skin Sensitization Table information was modified.  
 Section 11: Target Organs - Repeated Table information was modified.  
 Section 11: Target Organs - Single Table information was modified.  
 Section 12: Component ecotoxicity information information was modified.  
 Section 12: Endocrine disruptor table row information was added.  
 Section 12: Mobility in soil information information was modified.  
 Section 12: No endocrine disruptor information available warning information was deleted.  
 Section 12: Persistence and Degradability information information was modified.  
 Section 12: Bioaccumulative potential information information was modified.  
 Section 15: Authorization status under REACH: SVHC Authorization ingredient information information was added.  
 Section 15: Restrictions on manufacture ingredients information information was modified.  
 Section 15: Seveso Substance Text information was modified.  
 Two-column table displaying the unique list of H Codes and statements (std phrases) for all components of the given material. information was modified.

## Annex

<b>1. Title</b>	
<b>Substance identification</b>	acetone; EC No. 200-662-2; CAS Nbr 67-64-1;
<b>Exposure Scenario Name</b>	Industrial Use of Coatings
<b>Lifecycle Stage</b>	Use at industrial sites
<b>Contributing activities</b>	PROC 10 -Roller application or brushing ERC 04 -Use of non-reactive processing aid at industrial site (no inclusion into or onto article)
<b>Processes, tasks and activities covered</b>	Application of product with a roller or brush.
<b>2. Operational conditions and risk management measures</b>	
<b>Operating Conditions</b>	<b>Physical state:</b> Liquid. <b>General operating conditions:</b> Duration of use: 8 hours/day; Emission days per year: <= 360 days per year;
<b>Risk management measures</b>	Under the operational conditions described above the following risk management measures apply: <b>General risk management measures:</b> <b>Human health:</b> Goggles - Chemical resistant; Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour); Wear chemically resistant gloves (tested to EN374) in combination with ‘basic’

	employee training. Refer to Section 8 of the SDS for specific glove material.; <b>Environmental:</b> None needed;
<b>Waste management measures</b>	No use-specific waste management measures are required for this product. Refer to Section 13 of main SDS for disposal instructions:
<b>3. Prediction of exposure</b>	
<b>Prediction of exposure</b>	Human and environmental exposures are not expected to exceed the DNELs and PNECs when the identified risk management measures are adopted.

<b>1. Title</b>	
<b>Substance identification</b>	acetone; EC No. 200-662-2; CAS Nbr 67-64-1;
<b>Exposure Scenario Name</b>	Professional Use of Coatings
<b>Lifecycle Stage</b>	Widespread use by professional workers
<b>Contributing activities</b>	PROC 10 -Roller application or brushing PROC 11 -Non industrial spraying ERC 08a -Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) ERC 08d -Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor)
<b>Processes, tasks and activities covered</b>	Application with a wipe. Spraying of substances/mixtures.
<b>2. Operational conditions and risk management measures</b>	
<b>Operating Conditions</b>	<b>Physical state:</b> Liquid. <b>General operating conditions:</b> Duration of use: 8 hours/day; Emission days per year: <= 360 days per year;
<b>Risk management measures</b>	Under the operational conditions described above the following risk management measures apply: <b>General risk management measures:</b> <b>Human health:</b> Goggles - Chemical resistant; Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour); Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training. Refer to Section 8 of the SDS for specific glove material.; <b>Environmental:</b> None needed; ; The following task-specific risk management measures apply in addition to those listed above: <b>Task: PROC11;</b> <b>Human Health;</b> Local exhaust ventilation;
<b>Waste management measures</b>	No use-specific waste management measures are required for this product. Refer to Section 13 of main SDS for disposal instructions:
<b>3. Prediction of exposure</b>	
<b>Prediction of exposure</b>	Human and environmental exposures are not expected to exceed the DNELs and PNECs when the identified risk management measures are adopted.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into the European Union,

you are responsible for all regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration.

**3M Ireland MSDSs are available at [www.3M.com](http://www.3M.com)**