



## Safety Data Sheet

Copyright, 2019, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

**Document Group:** 31-5491-1 **Version Number:** 3.00  
**Revision Date:** 04/09/2019 **Supersedes Date:** 16/03/2017  
**Transportation version number:**

### IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

#### 1.1. Product identifier

3M(TM) Scotch-Weld(TM) Acrylic Adhesive DP8405NS, Green

#### Product Identification Numbers

62-2856-1445-9

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### Identified uses

Adhesive

#### 1.3. Details of the supplier of the safety data sheet

**ADDRESS:** 3M Israel, 91 Medinat Ha'Yehudim Street, Herzeliya 46120  
**Telephone:** 09-961 5000  
**E Mail:** innovation.il@mmm.com  
**Website:** www.3M.com/il

#### 1.4. Emergency telephone number

09-961 5000

This product is a kit or a multipart product which consists of multiple, independently packaged components. An SDS for each of these components is included. Please do not separate the component SDSs from this cover page. The document numbers of the SDSs for components of this product are:

31-5470-5, 31-5479-6

### TRANSPORTATION INFORMATION

### KIT LABEL

#### 2.1. Classification of the substance or mixture CLP REGULATION (EC) No 1272/2008

##### CLASSIFICATION:

Flammable Liquid, Category 2 - Flam. Liq. 2; H225  
Serious Eye Damage/Eye Irritation, Category 2 - Eye Irrit. 2; H319

Skin Corrosion/Irritation, Category 2 - Skin Irrit. 2; H315  
Skin Sensitization, Category 1 - Skin Sens. 1; H317  
Specific Target Organ Toxicity-Single Exposure, Category 3 - STOT SE 3; H335  
Hazardous to the Aquatic Environment (Chronic), Category 2 - Aquatic Chronic 2; H411

For full text of H phrases, see Section 16.

**2.2. Label elements**

**CLP REGULATION (EC) No 1272/2008**

**SIGNAL WORD**

Danger

**Symbols:**

GHS02 (Flame) |GHS07 (Exclamation mark) |GHS09 (Environment) |

**Pictograms**



**HAZARD STATEMENTS:**

H225 Highly flammable liquid and vapor.  
H319 Causes serious eye irritation.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H335 May cause respiratory irritation.  
  
H411 Toxic to aquatic life with long lasting effects.

**PRECAUTIONARY STATEMENTS**

**Prevention:**

P210A Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P261A Avoid breathing vapors.  
P280E Wear protective gloves.

**Response:**

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

**Disposal:**

P501 Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

**For containers not exceeding 125 ml the following Hazard and Precautionary statements may be used:**

**<=125 ml Hazard statements**

H317 May cause an allergic skin reaction.

**<=125 ml Precautionary statements**





## Safety Data Sheet

Copyright,2021, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

<b>Document Group:</b>	31-5470-5	<b>Version Number:</b>	3.02
<b>Revision Date:</b>	06/04/2021	<b>Supersedes Date:</b>	27/10/2017
<b>Transportation version number:</b>			

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

3M(TM) Scotch-Weld(TM) Acrylic Adhesive DP8405NS, Green, Part A

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### Identified uses

Adhesive

#### 1.3. Details of the supplier of the safety data sheet

**ADDRESS:** 3M Israel, 91 Medinat Ha'Yehudim Street, Herzeliya 46120  
**Telephone:** 09-961 5000  
**E Mail:** innovation.il@mmm.com  
**Website:** www.3M.com/il

#### 1.4. Emergency telephone number

09-961 5000

### SECTION 2: Hazard identification

#### 2.1. Classification of the substance or mixture

CLP REGULATION (EC) No 1272/2008

The health and environmental classifications of this material have been derived using the calculation method, except in cases where test data are available or the physical form impacts classification. Classification(s) based on test data or physical form are noted below, if applicable.

##### CLASSIFICATION:

#### 2.2. Label elements

CLP REGULATION (EC) No 1272/2008

##### Ingredients:

Ingredient	C.A.S. No.	EC No.	% by Wt
TERT-BUTYL PEROXY-3,5,5-TRIMETHYLHEXANOATE	13122-18-4	236-050-7	0.1 - 10

**For containers not exceeding 125 ml the following Hazard and Precautionary statements may be used:**

Contains 39% of components with unknown hazards to the aquatic environment.

**Notes on labelling:**

The organic peroxide classification from CAS# 13122-18-4 does not apply to the material. The calculated available oxygen content is less than 1%.

**2.3. Other hazards**

None known

## SECTION 3: Composition/information on ingredients

**3.1. Substances**

Not applicable

**3.2. Mixtures**

Ingredient	Identifier(s)	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Dibenzoate Propanol (REACH Reg. No.:01-2119529241-49)	(CAS-No.) 27138-31-4 (EC-No.) 248-258-5	45 - 65	**Aquatic Chronic 3**, H412
STYRENE, POLYMER WITH 1,3-BUTADIENE, BUTYL ACRYLATE AND METHYL METHACRYLATE	(CAS-No.) 25101-28-4	10 - 30	Substance not classified as hazardous
Catalyst	Trade Secret	1 - 15	Substance not classified as hazardous
TERT-BUTYL PEROXY-3,5,5-TRIMETHYLHEXANOATE	(CAS-No.) 13122-18-4 (EC-No.) 236-050-7	0.1 - 10	**Org. Perox. CD**, H242 **Aquatic Acute 1**, H400,M=1 **Aquatic Chronic 1**, H410,M=1 **Skin Sens. 1B**, H317

Please see section 16 for the full text of any H statements referred to in this section

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

## SECTION 4: First aid measures

**4.1. Description of first aid measures**

**Inhalation:**

Remove person to fresh air. If you feel unwell, get medical attention.

**Skin Contact:**

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

**Eye Contact:**

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

**If Swallowed:**

Rinse mouth. If you feel unwell, get medical attention.

**4.2. Most important symptoms and effects, both acute and delayed**

The most important symptoms and effects based on the CLP classification include:

Allergic skin reaction (redness, swelling, blistering, and itching).

**4.3. Indication of any immediate medical attention and special treatment required**

Not applicable

**SECTION 5: Fire-fighting measures**

**5.1. Extinguishing media**

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

**5.2. Special hazards arising from the substance or mixture**

Part of the oxygen for combustion is supplied by the peroxide itself.

**Hazardous Decomposition or By-Products**

Substance

Carbon monoxide

Carbon dioxide

Condition

During Combustion

During Combustion

**5.3. Advice for fire-fighters**

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

**SECTION 6: Accidental release measures**

**6.1. Personal precautions, protective equipment and emergency procedures**

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

**6.2. Environmental precautions**

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

**6.3. Methods and material for containment and cleaning up**

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

**6.4. Reference to other sections**

Refer to Section 8 and Section 13 for more information

**SECTION 7: Handling and storage**

**7.1. Precautions for safe handling**

Avoid breathing dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the

workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.)

### **7.2. Conditions for safe storage including any incompatibilities**

Keep cool. Store away from heat. Store away from acids. Store away from strong bases. Store away from oxidizing agents. Store away from amines.

### **7.3. Specific end use(s)**

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

## **SECTION 8: Exposure controls/personal protection**

### **8.1. Control parameters**

#### **Occupational exposure limits**

No occupational exposure limit values exist for any of the components listed in Section 3 of this SDS.

### **8.2. Exposure controls**

#### **8.2.1. Engineering controls**

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

#### **8.2.2. Personal protective equipment (PPE)**

##### **Eye/face protection**

None required.

##### **Skin/hand protection**

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

##### **Respiratory protection**

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

## **SECTION 9: Physical and chemical properties**

### **9.1. Information on basic physical and chemical properties**

**Physical state**

Liquid

**Specific Physical Form:**

Paste

<b>Color</b>	Blue
<b>Odor</b>	Ester
<b>Odor threshold</b>	<i>No Data Available</i>
<b>Melting point/freezing point</b>	<i>Not Applicable</i>
<b>Boiling point/boiling range</b>	>=65.6 °C
<b>Flammability (solid, gas)</b>	Not Applicable
<b>Flammable Limits(LEL)</b>	<i>No Data Available</i>
<b>Flammable Limits(UEL)</b>	<i>No Data Available</i>
<b>Flash Point</b>	> 93.3 °C [Test Method:Closed Cup]
<b>Autoignition temperature</b>	<i>No Data Available</i>
<b>Decomposition temperature</b>	<i>No Data Available</i>
<b>pH</b>	<i>substance/mixture is non-soluble (in water)</i>
<b>Kinematic Viscosity</b>	18,518.5185185185 mm2/sec
<b>Water solubility</b>	Nil
<b>Solubility- non-water</b>	<i>No Data Available</i>
<b>Partition coefficient: n-octanol/ water</b>	<i>No Data Available</i>
<b>Vapor Pressure</b>	<i>No Data Available</i>
<b>Density</b>	1.08 g/ml
<b>Relative Density</b>	1.08 [Ref Std: WATER=1]
<b>Relative Vapor Density</b>	<i>No Data Available</i>

## 9.2. Other information

### 9.2.2 Other safety characteristics

<b>EU Volatile Organic Compounds</b>	<i>No Data Available</i>
<b>Evaporation rate</b>	<i>No Data Available</i>
<b>Molecular weight</b>	<i>No Data Available</i>

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

### 10.2. Chemical stability

Stable.

### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

### 10.4. Conditions to avoid

Heat  
Sparks and/or flames

### 10.5. Incompatible materials

Amines  
Strong acids  
Strong bases  
Strong oxidizing agents

### 10.6. Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.



## SECTION 11: Toxicological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from internal hazard assessments.

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

#### Skin Contact:

Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

#### Eye Contact:

Contact with the eyes during product use is not expected to result in significant irritation.

#### Ingestion:

May be harmful if swallowed.

#### Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

#### Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE 2,000 - 5,000 mg/kg
Dibenzoate Propanol	Dermal	Rat	LD50 > 2,000 mg/kg
Dibenzoate Propanol	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 200 mg/l
Dibenzoate Propanol	Ingestion	Rat	LD50 3,295 mg/kg
STYRENE, POLYMER WITH 1,3-BUTADIENE, BUTYL ACRYLATE AND METHYL METHACRYLATE	Dermal		LD50 estimated to be > 5,000 mg/kg
STYRENE, POLYMER WITH 1,3-BUTADIENE, BUTYL ACRYLATE AND METHYL METHACRYLATE	Ingestion	Rat	LD50 > 5,000 mg/kg
Catalyst	Dermal	Professional judgement	LD50 estimated to be 2,000 - 5,000 mg/kg
Catalyst	Ingestion	Rat	LD50 > 2,000 mg/kg
TERT-BUTYL PEROXY-3,5,5-TRIMETHYLHEXANOATE	Dermal	Rat	LD50 > 2,000 mg/kg
TERT-BUTYL PEROXY-3,5,5-TRIMETHYLHEXANOATE	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.8 mg/l
TERT-BUTYL PEROXY-3,5,5-TRIMETHYLHEXANOATE	Ingestion	Rat	LD50 12,905 mg/kg

ATE = acute toxicity estimate

#### Skin Corrosion/Irritation

Name	Species	Value
------	---------	-------

Dibenzoate Propanol	Rabbit	No significant irritation
TERT-BUTYL PEROXY-3,5,5-TRIMETHYLHEXANOATE	Rabbit	No significant irritation

**Serious Eye Damage/Irritation**

Name	Species	Value
Dibenzoate Propanol	Rabbit	No significant irritation
TERT-BUTYL PEROXY-3,5,5-TRIMETHYLHEXANOATE	Rabbit	No significant irritation

**Skin Sensitization**

Name	Species	Value
Dibenzoate Propanol	Guinea pig	Not classified
Catalyst	Mouse	Not classified
TERT-BUTYL PEROXY-3,5,5-TRIMETHYLHEXANOATE	Guinea pig	Sensitizing

**Respiratory Sensitization**

For the component/components, either no data are currently available or the data are not sufficient for classification.

**Germ Cell Mutagenicity**

Name	Route	Value
Dibenzoate Propanol	In Vitro	Not mutagenic
Catalyst	In Vitro	Not mutagenic

**Carcinogenicity**

For the component/components, either no data are currently available or the data are not sufficient for classification.

**Reproductive Toxicity**

**Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test Result	Exposure Duration
Dibenzoate Propanol	Ingestion	Not classified for female reproduction	Rat	NOAEL 500 mg/kg/day	2 generation
Dibenzoate Propanol	Ingestion	Not classified for male reproduction	Rat	NOAEL 400 mg/kg/day	2 generation
Dibenzoate Propanol	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	during gestation

**Target Organ(s)**

**Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Catalyst	Ingestion	nervous system	Not classified	Rat	NOAEL 2,000 mg/kg	

**Specific Target Organ Toxicity - repeated exposure**

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Dibenzoate Propanol	Ingestion	hematopoietic system   liver	Not classified	Rat	NOAEL 2,500 mg/kg/day	90 days

**Aspiration Hazard**

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

**11.2. Information on other hazards**

This material does not contain any substances that are assessed to be an endocrine disruptor for human health.

**SECTION 12: Ecological information**

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

**12.1. Toxicity**

No product test data available

Material	CAS #	Organism	Type	Exposure	Test Endpoint	Test Result
Dibenzoate Propanol	27138-31-4	Fathead Minnow	Experimental	96 hours	LC50	3.7 mg/l
Dibenzoate Propanol	27138-31-4	Green Algae	Experimental	72 hours	EL50	4.9 mg/l
Dibenzoate Propanol	27138-31-4	Water flea	Experimental	48 hours	EL50	19.31 mg/l
Dibenzoate Propanol	27138-31-4	Green Algae	Experimental	72 hours	EC10	0.89 mg/l
STYRENE, POLYMER WITH 1,3- BUTADIENE, BUTYL ACRYLATE AND METHYL METHACRYLATE	25101-28-4		Data not available or insufficient for classification			N/A
Catalyst	Trade Secret		Data not available or insufficient for classification			N/A
TERT-BUTYL PEROXY-3,5,5- TRIMETHYLHEXAN OATE	13122-18-4	Activated sludge	Experimental	3 hours	NOEC	26.3 mg/l
TERT-BUTYL PEROXY-3,5,5- TRIMETHYLHEXAN OATE	13122-18-4	Green Algae	Experimental		EC50	0.51 mg/l
TERT-BUTYL PEROXY-3,5,5- TRIMETHYLHEXAN OATE	13122-18-4	Rainbow Trout	Experimental		LC50	7 mg/l
TERT-BUTYL PEROXY-3,5,5- TRIMETHYLHEXAN OATE	13122-18-4	Water flea	Experimental		EC50	>100 mg/l
TERT-BUTYL PEROXY-3,5,5- TRIMETHYLHEXAN OATE	13122-18-4	Green Algae	Experimental		NOEC	0.125 mg/l

**12.2. Persistence and degradability**

**3M(TM) Scotch-Weld(TM) Acrylic Adhesive DP8405NS, Green, Part A**

Material	CAS No.	Test Type	Duration	Study Type	Test Result	Protocol
Dibenzoate Propanol	27138-31-4	Experimental Biodegradation	28 days	Carbon dioxide evolution	85 % weight	OECD 301B - Mod. Sturm or CO2
STYRENE, POLYMER WITH 1,3-BUTADIENE, BUTYL ACRYLATE AND METHYL METHACRYLATE	25101-28-4	Data not available - insufficient			N/A	
Catalyst	Trade Secret	Estimated Photolysis		Photolytic half-life (in air)	1.48 days (t 1/2)	Non-standard method
Catalyst	Trade Secret	Experimental Biodegradation	28 days	Carbon dioxide evolution	29.1 %CO2 evolution/THC O2 evolution	OECD 301B - Mod. Sturm or CO2
TERT-BUTYL PEROXY-3,5,5-TRIMETHYLHEXANOATE	13122-18-4	Estimated Biodegradation	28	Biological Oxygen Demand	14 % BOD/ThBOD	OECD 301C - MITI (I)

**12.3. Bioaccumulative potential**

Material	Cas No.	Test Type	Duration	Study Type	Test Result	Protocol
Dibenzoate Propanol	27138-31-4	Estimated Bioconcentration		Bioaccumulation Factor	8	Est: Bioconcentration factor
STYRENE, POLYMER WITH 1,3-BUTADIENE, BUTYL ACRYLATE AND METHYL METHACRYLATE	25101-28-4	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Catalyst	Trade Secret	Experimental Bioconcentration		Log of Octanol/H2O part. coeff	2.57	Non-standard method
TERT-BUTYL PEROXY-3,5,5-TRIMETHYLHEXANOATE	13122-18-4	Estimated Bioconcentration		Bioaccumulation Factor	363	Est: Bioconcentration factor

**12.4. Mobility in soil**

Material	Cas No.	Test Type	Study Type	Test Result	Protocol
Catalyst	Trade Secret	Estimated Mobility in Soil	Koc	<2 l/kg	ACD/Labs ChemSketch™

**12.5. Results of the PBT and vPvB assessment**

This material does not contain any substances that are assessed to be a PBT or vPvB

**12.6. Endocrine disrupting properties**

This material does not contain any substances that are assessed to be an endocrine disruptor for environmental effects

**12.7. Other adverse effects**

No information available

**SECTION 13: Disposal considerations****13.1 Waste treatment methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel

during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/CE and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor

**EU waste code (product as sold)**

080409*	Waste adhesives and sealants containing organic solvents or other dangerous substances
200127*	Paint, inks, adhesives and resins containing dangerous substances

**SECTION 14: Transportation information**

ADR/IMDG/IATA: Not hazardous for transport.

**SECTION 15: Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**SECTION 16: Other information**

**List of relevant H statements**

H242	Heating may cause a fire.
H317	May cause an allergic skin reaction.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

**Revision information:**

EU Section 09: pH information information was added.  
Section 02: <125ml Hazard - Health information was deleted.  
Section 02: <125ml Precautionary - Prevention information was deleted.  
Section 02: <125ml Precautionary - Response information was deleted.  
Section 02: H phrase reference information was deleted.  
Section 02: Label Elements: CLP Classification information was deleted.  
Section 02: Label Elements: CLP Environmental Hazard Statements information was deleted.  
Section 02: Label Elements: CLP Percent Unknown information was modified.  
Section 02: Label Elements: CLP Precautionary - Disposal information was deleted.  
Section 02: Label Elements: CLP Precautionary - Prevention information was deleted.  
Section 02: Label Elements: CLP Precautionary - Response information was deleted.  
Section 02: Label Elements: Graphic information was deleted.  
Section 02: Label Elements: Signal Word information was deleted.  
Section 03: Composition table % Column heading information was added.  
Section 03: Composition/ Information of ingredients table information was modified.  
Section 03: Substance not applicable information was added.  
Section 04: First Aid - Symptoms and Effects (CLP) information was added.

Section 04: Information on toxicological effects information was modified.  
Section 09: Color information was added.  
Section 09: Evaporation Rate information information was deleted.  
Section 09: Explosive properties information information was deleted.  
Section 09: Kinematic Viscosity information information was added.  
Section 09: Melting point information information was modified.  
Section 09: Odor information was added.  
Section 09: Odor, color, grade information information was deleted.  
Section 09: Oxidising properties information information was deleted.  
Section 09: pH information information was deleted.  
Section 09: Property description for optional properties information was modified.  
Section 09: Vapor density value information was added.  
Section 09: Viscosity information information was deleted.  
Section 11: Acute Toxicity table information was modified.  
Section 11: Classification disclaimer information was modified.  
Section 11: Germ Cell Mutagenicity Table information was modified.  
Section 11: Health Effects - Skin information was modified.  
Section 11: No endocrine disruptor information available warning information was added.  
Section 11: Reproductive and/or Developmental Effects text information was deleted.  
Section 11: Skin Sensitization Table information was modified.  
Section 11: Target Organs - Single Table information was modified.  
Section 12: 12.6. Endocrine Disrupting Properties information was added.  
Section 12: 12.7. Other adverse effects information was modified.  
Section 12: Component ecotoxicity information information was modified.  
Section 12: Contact manufacturer for more detail. information was deleted.  
Section 12: Mobility in soil information information was added.  
Section 12: No endocrine disruptor information available warning information was added.  
Section 12: No PBT/vPvB information available warning information was modified.  
Section 12: Persistence and Degradability information information was modified.  
Section 12: Biocumulative potential information information was modified.  
Section 14: Transportation classification information was modified.  
Section 15: Regulations - Inventories information was deleted.  
Section 16: UK disclaimer information was deleted.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

**3M Israel SDSs are available at [www.3M.com/il](http://www.3M.com/il)**



## Safety Data Sheet

Copyright,2021, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

**Document Group:** 31-5479-6 **Version Number:** 3.01  
**Revision Date:** 04/08/2021 **Supersedes Date:** 04/09/2019  
**Transportation version number:**

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

3M(TM) Scotch-Weld(TM) Acrylic Adhesive DP8405NS, Green, Part B

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### Identified uses

Adhesive

#### 1.3. Details of the supplier of the safety data sheet

**ADDRESS:** 3M Israel, 91 Medinat Ha'Yehudim Street, Herzeliya 46120  
**Telephone:** 09-961 5000  
**E Mail:** innovation.il@mmm.com  
**Website:** www.3M.com/il

#### 1.4. Emergency telephone number

09-961 5000

### SECTION 2: Hazard identification

#### 2.1. Classification of the substance or mixture

CLP REGULATION (EC) No 1272/2008

The health and environmental classifications of this material have been derived using the calculation method, except in cases where test data are available or the physical form impacts classification. Classification(s) based on test data or physical form are noted below, if applicable.

##### CLASSIFICATION:

#### 2.2. Label elements

CLP REGULATION (EC) No 1272/2008

##### Ingredients:

Ingredient	C.A.S. No.	EC No.	% by Wt
Methyl Methacrylate	80-62-6	201-297-1	45 - 65
2-hydroxyethyl methacrylate	868-77-9	212-782-2	0.1 - 10

**For containers not exceeding 125 ml the following Hazard and Precautionary statements may be used:**

**Notes on labelling:**

Nota L applied to CAS # 64742-55-8.

**2.3. Other hazards**

None known

**SECTION 3: Composition/information on ingredients**

**3.1. Substances**

Not applicable

**3.2. Mixtures**

<b>Ingredient</b>	<b>Identifier(s)</b>	<b>%</b>	<b>Classification according to Regulation (EC) No. 1272/2008 [CLP]</b>
Methyl Methacrylate (REACH Reg. No.:01-2119452498-28)	(CAS-No.) 80-62-6 (EC-No.) 201-297-1	45 - 65	**Flam. Liq. 2**, H225 **Skin Irrit. 2**, H315 **Skin Sens. 1**, H317 **STOT SE 3**, H335 Nota D
Acrylonitrile-Butadiene Polymer	(CAS-No.) 9003-18-3	1 - 20	Substance not classified as hazardous
Fillers (NJTS Reg. No. 04499600-6923)	Trade Secret	1 - 20	Substance with a national occupational exposure limit
2-hydroxyethyl methacrylate (REACH Reg. No.:01-2119490169-29)	(CAS-No.) 868-77-9 (EC-No.) 212-782-2	0.1 - 10	**Skin Irrit. 2**, H315 **Eye Irrit. 2**, H319 **Skin Sens. 1**, H317 Nota D
Bisphenol A Polyethylene Glycol Diether Dimethacrylate	(CAS-No.) 41637-38-1	0.1 - 10	Substance not classified as hazardous
Dispersing Agent (NJTS Reg. No. 04499600-6929)	Trade Secret	0.1 - 5	Substance with a national occupational exposure limit
Phosphate Esters of PPG Methacrylate	(CAS-No.) 95175-93-2	< 3	**Skin Irrit. 2**, H315 **Eye Dam. 1**, H318
Hydrotreated light paraffinic distillates (petroleum)	(CAS-No.) 64742-55-8 (EC-No.) 265-158-7	< 1	Nota L **Asp. Tox. 1**, H304
COPPER NAPHTHENATES	(CAS-No.) 1338-02-9 (EC-No.) 215-657-0	< 0.2	**Flam. Liq. 3**, H226 **Acute Tox. 4**, H302 **Aquatic Acute 1**, H400,M=10 **Aquatic Chronic 1**, H410,M=1

Please see section 16 for the full text of any H statements referred to in this section

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS



## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

#### Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

#### Eye Contact:

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

#### If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

### 4.2. Most important symptoms and effects, both acute and delayed

No critical symptoms or effects. See Section 11.1, information on toxicological effects.

### 4.3. Indication of any immediate medical attention and special treatment required

Not applicable

## SECTION 5: Fire-fighting measures

### 5.1. Extinguishing media

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

### 5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

### Hazardous Decomposition or By-Products

<u>Substance</u>	<u>Condition</u>
Carbon monoxide	During Combustion
Carbon dioxide	During Combustion
Hydrogen Chloride	During Combustion
Oxides of Nitrogen	During Combustion

### 5.3. Advice for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. When fire fighting conditions are severe and total thermal decomposition of the product is possible, wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

**6.2. Environmental precautions**

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

**6.3. Methods and material for containment and cleaning up**

Contain spill. Cover spill area with a fire-extinguishing foam. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

**6.4. Reference to other sections**

Refer to Section 8 and Section 13 for more information

**SECTION 7: Handling and storage**

**7.1. Precautions for safe handling**

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Wear low static or properly grounded shoes. To minimize the risk of ignition, determine applicable electrical classifications for the process using this product and select specific local exhaust ventilation equipment to avoid flammable vapor accumulation. Ground/bond container and receiving equipment if there is potential for static electricity accumulation during transfer.

**7.2. Conditions for safe storage including any incompatibilities**

Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store away from heat. Store away from acids. Store away from strong bases. Store away from oxidizing agents. Store away from amines.

**7.3. Specific end use(s)**

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

**SECTION 8: Exposure controls/personal protection**

**8.1. Control parameters**

**Occupational exposure limits**

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

<b>Ingredient</b>	<b>C.A.S. No.</b>	<b>Agency</b>	<b>Limit type</b>	<b>Additional Comments</b>
COPPER COMPOUNDS	1338-02-9	ACGIH	TWA(as Cu, fume):0.2 mg/m3;TWA(as Cu dust or mist):1 mg/m3	
Mineral oils (untreated and mildly treated)	64742-55-8	ACGIH	Limit value not established:	A2: Suspected human carcin., Cntrl all exposr-low as possib
Methyl Methacrylate	80-62-6	ACGIH	TWA:50 ppm;STEL:100 ppm	A4: Not class. as human carcin, Dermal Sensitizer

Dispersing Agent (NJTS Reg. No. 04499600-6929)	Trade Secret	ACGIH	TWA(respirable fraction):3 mg/m3;TWA(inhalable fraction):10 mg/m3	A4: Not class. as human carcin
Fillers (NJTS Reg. No. 04499600-6923)	Trade Secret	ACGIH	TWA(respirable fraction):2 mg/m3	A4: Not class. as human carcin

ACGIH : American Conference of Governmental Industrial Hygienists

CMRG : Chemical Manufacturer's Recommended Guidelines

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

## 8.2. Exposure controls

### 8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment. Use explosion-proof ventilation equipment.

### 8.2.2. Personal protective equipment (PPE)

#### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect Vented Goggles

#### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Butyl Rubber

Polymer laminate

#### Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	Liquid
Specific Physical Form:	Paste
Color	White
Odor	Methacrylate
Odor threshold	<i>No Data Available</i>
Melting point/freezing point	<i>Not Applicable</i>
Boiling point/boiling range	>=37.8 °C
Flammability (solid, gas)	Not Applicable
Flammable Limits(LEL)	<i>No Data Available</i>

<b>Flammable Limits(UEL)</b>	<i>No Data Available</i>
<b>Flash Point</b>	$\geq 10$ °C [ <i>Test Method: Closed Cup</i> ]
<b>Autoignition temperature</b>	<i>No Data Available</i>
<b>Decomposition temperature</b>	<i>No Data Available</i>
<b>pH</b>	<i>substance/mixture is non-soluble (in water)</i>
<b>Kinematic Viscosity</b>	56,074.7663551402 mm <sup>2</sup> /sec
<b>Water solubility</b>	Nil
<b>Solubility- non-water</b>	<i>No Data Available</i>
<b>Partition coefficient: n-octanol/ water</b>	<i>No Data Available</i>
<b>Vapor Pressure</b>	<i>No Data Available</i>
<b>Density</b>	1.07 g/ml
<b>Relative Density</b>	1.07 [ <i>Ref Std: WATER=1</i> ]
<b>Relative Vapor Density</b>	<i>No Data Available</i>

## 9.2. Other information

### 9.2.2 Other safety characteristics

<b>EU Volatile Organic Compounds</b>	<i>No Data Available</i>
<b>Evaporation rate</b>	<i>No Data Available</i>
<b>Molecular weight</b>	<i>No Data Available</i>

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

### 10.2. Chemical stability

Stable.

### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

### 10.4. Conditions to avoid

Heat  
Sparks and/or flames

### 10.5. Incompatible materials

Amines  
Strong acids  
Strong bases  
Strong oxidizing agents

### 10.6. Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

## SECTION 11: Toxicological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from internal hazard assessments.

**11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008****Signs and Symptoms of Exposure**

Based on test data and/or information on the components, this material may produce the following health effects:

**Inhalation:**

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May cause additional health effects (see below).

**Skin Contact:**

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

**Eye Contact:**

Severe Eye Irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

**Ingestion:**

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

**Additional Health Effects:****Prolonged or repeated exposure may cause target organ effects:**

Olfactory Effects: Signs/symptoms may include decreased ability to detect odors and/or complete loss of smell.

**Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

**Acute Toxicity**

Name	Route	Species	Value
Overall product	Inhalation-Vapor(4 hr)		No data available; calculated ATE >50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Methyl Methacrylate	Dermal	Rabbit	LD50 > 5,000 mg/kg
Methyl Methacrylate	Inhalation-Vapor (4 hours)	Rat	LC50 29 mg/l
Methyl Methacrylate	Ingestion	Rat	LD50 7,900 mg/kg
Acrylonitrile-Butadiene Polymer	Dermal	Rabbit	LD50 > 15,000 mg/kg
Acrylonitrile-Butadiene Polymer	Ingestion	Rat	LD50 > 30,000 mg/kg
Bisphenol A Polyethylene Glycol Diether Dimethacrylate	Dermal	Rat	LD50 > 2,000 mg/kg
Bisphenol A Polyethylene Glycol Diether Dimethacrylate	Ingestion	Rat	LD50 > 35,000 mg/kg
Fillers (NJTS Reg. No. 04499600-6923)	Dermal		LD50 estimated to be > 5,000 mg/kg
Fillers (NJTS Reg. No. 04499600-6923)	Ingestion	Human	LD50 > 15,000 mg/kg
2-hydroxyethyl methacrylate	Dermal	Rabbit	LD50 > 5,000 mg/kg
2-hydroxyethyl methacrylate	Ingestion	Rat	LD50 5,564 mg/kg
Phosphate Esters of PPG Methacrylate	Ingestion	Rat	LD50 > 5,000 mg/kg
Phosphate Esters of PPG Methacrylate	Dermal	similar health hazards	LD50 estimated to be > 5,000 mg/kg
COPPER NAPHTHENATES	Dermal	similar compounds	LD50 > 2,000 mg/kg
COPPER NAPHTHENATES	Ingestion	similar	LD50 >300, <2,000 mg/kg

**3M(TM) Scotch-Weld(TM) Acrylic Adhesive DP8405NS, Green, Part B**

		compounds	
--	--	-----------	--

ATE = acute toxicity estimate

**Skin Corrosion/Irritation**

Name	Species	Value
Methyl Methacrylate	Human and animal	Mild irritant
Acrylonitrile-Butadiene Polymer	Professional judgement	No significant irritation
Bisphenol A Polyethylene Glycol Diether Dimethacrylate	Rabbit	Minimal irritation
Fillers (NJTS Reg. No. 04499600-6923)	Professional judgement	No significant irritation
2-hydroxyethyl methacrylate	Rabbit	Minimal irritation
Phosphate Esters of PPG Methacrylate	Not available	Irritant
COPPER NAPHTHENATES	Rabbit	No significant irritation

**Serious Eye Damage/Irritation**

Name	Species	Value
Methyl Methacrylate	Rabbit	Moderate irritant
Acrylonitrile-Butadiene Polymer	Professional judgement	No significant irritation
Bisphenol A Polyethylene Glycol Diether Dimethacrylate	Rabbit	No significant irritation
Fillers (NJTS Reg. No. 04499600-6923)	Professional judgement	No significant irritation
2-hydroxyethyl methacrylate	Rabbit	Moderate irritant
Phosphate Esters of PPG Methacrylate	Not available	Corrosive
COPPER NAPHTHENATES	In vitro data	No significant irritation

**Skin Sensitization**

Name	Species	Value
Methyl Methacrylate	Human and animal	Sensitizing
Bisphenol A Polyethylene Glycol Diether Dimethacrylate	Guinea pig	Not classified
2-hydroxyethyl methacrylate	Human and animal	Sensitizing
COPPER NAPHTHENATES	Guinea pig	Not classified

**Respiratory Sensitization**

Name	Species	Value
Methyl Methacrylate	Human	Not classified

**Germ Cell Mutagenicity**

**3M(TM) Scotch-Weld(TM) Acrylic Adhesive DP8405NS, Green, Part B**

Name	Route	Value
Methyl Methacrylate	In vivo	Not mutagenic
Methyl Methacrylate	In Vitro	Some positive data exist, but the data are not sufficient for classification
Bisphenol A Polyethylene Glycol Diether Dimethacrylate	In Vitro	Not mutagenic
2-hydroxyethyl methacrylate	In vivo	Not mutagenic
2-hydroxyethyl methacrylate	In Vitro	Some positive data exist, but the data are not sufficient for classification

**Carcinogenicity**

Name	Route	Species	Value
Methyl Methacrylate	Ingestion	Rat	Not carcinogenic
Methyl Methacrylate	Inhalation	Human and animal	Not carcinogenic
Fillers (NJTS Reg. No. 04499600-6923)	Inhalation	Multiple animal species	Not carcinogenic

**Reproductive Toxicity**

**Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test Result	Exposure Duration
Methyl Methacrylate	Inhalation	Not classified for male reproduction	Mouse	NOAEL 36.9 mg/l	
Methyl Methacrylate	Inhalation	Not classified for development	Rat	NOAEL 8.3 mg/l	during organogenesis
2-hydroxyethyl methacrylate	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	prematuring & during gestation
2-hydroxyethyl methacrylate	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	49 days
2-hydroxyethyl methacrylate	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	prematuring & during gestation

**Target Organ(s)**

**Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Methyl Methacrylate	Inhalation	respiratory irritation	May cause respiratory irritation	Human	NOAEL Not available	occupational exposure
Phosphate Esters of PPG Methacrylate	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	

**Specific Target Organ Toxicity - repeated exposure**

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Methyl Methacrylate	Dermal	peripheral nervous system	Not classified	Human	NOAEL Not available	occupational exposure
Methyl Methacrylate	Inhalation	olfactory system	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure
Methyl Methacrylate	Inhalation	kidney and/or bladder	Not classified	Multiple animal species	NOAEL Not available	14 weeks
Methyl Methacrylate	Inhalation	liver	Not classified	Mouse	NOAEL 12.3 mg/l	14 weeks
Methyl Methacrylate	Inhalation	respiratory system	Not classified	Human	NOAEL Not available	occupational exposure

**3M(TM) Scotch-Weld(TM) Acrylic Adhesive DP8405NS, Green, Part B**

Fillers (NJTS Reg. No. 04499600-6923)	Inhalation	pneumoconiosis	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL NA	occupational exposure
Fillers (NJTS Reg. No. 04499600-6923)	Inhalation	pulmonary fibrosis	Not classified	Rat	NOAEL Not available	

**Aspiration Hazard**

For the component/components, either no data are currently available or the data are not sufficient for classification.

**Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.**

**11.2. Information on other hazards**

This material does not contain any substances that are assessed to be an endocrine disruptor for human health.

**SECTION 12: Ecological information**

**The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.**

**12.1. Toxicity**

No product test data available

Material	CAS #	Organism	Type	Exposure	Test Endpoint	Test Result
Methyl Methacrylate	80-62-6	Green Algae	Experimental	72 hours	EC50	>110 mg/l
Methyl Methacrylate	80-62-6	Rainbow Trout	Experimental	96 hours	LC50	>79 mg/l
Methyl Methacrylate	80-62-6	Water flea	Experimental	48 hours	EC50	69 mg/l
Methyl Methacrylate	80-62-6	Green algae	Experimental	72 hours	NOEC	110 mg/l
Methyl Methacrylate	80-62-6	Water flea	Experimental	21 days	NOEC	37 mg/l
Methyl Methacrylate	80-62-6	Activated sludge	Experimental	30 minutes	EC20	150 mg/l
Methyl Methacrylate	80-62-6	Soil microbes	Experimental	28 days	NOEC	>1,000 mg/kg (Dry Weight)
Acrylonitrile-Butadiene Polymer	9003-18-3		Data not available or insufficient for classification			N/A
Fillers (NJTS Reg. No. 04499600-6923)	Trade Secret	Water flea	Experimental	48 hours	LC50	>1,100 mg/l
2-hydroxyethyl methacrylate	868-77-9	Turbot	Analogous Compound	96 hours	LC50	833 mg/l
2-hydroxyethyl methacrylate	868-77-9	Fathead Minnow	Experimental	96 hours	LC50	227 mg/l
2-hydroxyethyl methacrylate	868-77-9	Green algae	Experimental	72 hours	EC50	710 mg/l
2-hydroxyethyl methacrylate	868-77-9	Water flea	Experimental	48 hours	EC50	380 mg/l
2-hydroxyethyl methacrylate	868-77-9	Green Algae	Experimental	72 hours	NOEC	160 mg/l
2-hydroxyethyl methacrylate	868-77-9	Water flea	Experimental	21 days	NOEC	24.1 mg/l
2-hydroxyethyl methacrylate	868-77-9		Experimental	16 hours	EC0	>3,000 mg/l
2-hydroxyethyl methacrylate	868-77-9		Experimental	18 hours	LD50	<98 mg per kg of bodyweight



**3M(TM) Scotch-Weld(TM) Acrylic Adhesive DP8405NS, Green, Part B**

Bisphenol A Polyethylene Glycol Diether Dimethacrylate	41637-38-1	Activated sludge	Estimated	3 hours	EC50	>1,000 mg/l
Bisphenol A Polyethylene Glycol Diether Dimethacrylate	41637-38-1	Green Algae	Estimated	72 hours	EL50	>100 mg/l
Bisphenol A Polyethylene Glycol Diether Dimethacrylate	41637-38-1	Water flea	Estimated	48 hours	EL50	>100 mg/l
Bisphenol A Polyethylene Glycol Diether Dimethacrylate	41637-38-1	Zebra Fish	Estimated	96 hours	LL50	>100 mg/l
Dispersing Agent (NJTS Reg. No. 04499600-6929)	Trade Secret	Green algae	Experimental	72 hours	EC50	>100 mg/l
Dispersing Agent (NJTS Reg. No. 04499600-6929)	Trade Secret	Medaka	Experimental	96 hours	LC50	>100 mg/l
Dispersing Agent (NJTS Reg. No. 04499600-6929)	Trade Secret	Green algae	Experimental	72 hours	NOEC	100 mg/l
Phosphate Esters of PPG Methacrylate	95175-93-2		Data not available or insufficient for classification			N/A
Hydrotreated light paraffinic distillates (petroleum)	64742-55-8	Fathead Minnow	Estimated	96 hours	LL50	>100 mg/l
Hydrotreated light paraffinic distillates (petroleum)	64742-55-8	Water flea	Estimated	48 hours	EL50	>100 mg/l
Hydrotreated light paraffinic distillates (petroleum)	64742-55-8	Green Algae	Estimated	72 hours	NOEL	100 mg/l
Hydrotreated light paraffinic distillates (petroleum)	64742-55-8	Water flea	Estimated	21 days	NOEC	10 mg/l
COPPER NAPHTHENATES	1338-02-9	Green Algae	Estimated	72 hours	EC50	0.629 mg/l
COPPER NAPHTHENATES	1338-02-9	Water flea	Estimated	48 hours	EC50	0.0756 mg/l
COPPER NAPHTHENATES	1338-02-9	Zebra Fish	Estimated	96 hours	LC50	0.0702 mg/l
COPPER NAPHTHENATES	1338-02-9	Algae or other aquatic plants	Estimated	hours	NOEC	0.132 mg/l
COPPER NAPHTHENATES	1338-02-9	Fathead Minnow	Estimated	32 days	EC10	0.0354 mg/l
COPPER NAPHTHENATES	1338-02-9	Water flea	Estimated	21 days	NOEC	0.0756 mg/l

**12.2. Persistence and degradability**

Material	CAS No.	Test Type	Duration	Study Type	Test Result	Protocol
Methyl Methacrylate	80-62-6	Experimental Biodegradation	14 days	Biological Oxygen Demand	94 % BOD/ThBOD	OECD 301C - MITI (I)
Acrylonitrile-Butadiene Polymer	9003-18-3	Data not availbl- insufficient			N/A	
Fillers (NJTS Reg. No. 04499600-6923)	Trade Secret	Data not availbl- insufficient			N/A	
2-hydroxyethyl methacrylate	868-77-9	Experimental Hydrolysis		Hydrolytic half-life (pH 10)	10.9 days (t 1/2)	OECD 111 Hydrolysis func of pH
2-hydroxyethyl methacrylate	868-77-9	Experimental Biodegradation	28 days	Biological Oxygen Demand	84 %BOD/CO D	OECD 301D - Closed Bottle Test
Bisphenol A Polyethylene Glycol Diether Dimethacrylate	41637-38-1	Experimental Biodegradation	28 days	Percent degraded	24 %degraded	Non-standard method
Dispersing Agent (NJTS Reg. No. 04499600-6929)	Trade Secret	Experimental Biodegradation	24 days	Carbon dioxide evolution	91 % weight	OECD 301B - Mod. Sturm or CO2

**3M(TM) Scotch-Weld(TM) Acrylic Adhesive DP8405NS, Green, Part B**

Phosphate Esters of PPG Methacrylate	95175-93-2	Data not available or insufficient			N/A	
Hydrotreated light paraffinic distillates (petroleum)	64742-55-8	Estimated Biodegradation	28 days	Carbon dioxide evolution	22 %CO <sub>2</sub> evolution/THC O <sub>2</sub> evolution	OECD 301B - Mod. Sturm or CO <sub>2</sub>
COPPER NAPHTHENATES	1338-02-9	Data not available or insufficient			N/A	

**12.3. Bioaccumulative potential**

Material	Cas No.	Test Type	Duration	Study Type	Test Result	Protocol
Methyl Methacrylate	80-62-6	Experimental Bioconcentration		Log of Octanol/H <sub>2</sub> O part. coeff	1.38	OECD 107 log Kow shke flask mtd
Acrylonitrile-Butadiene Polymer	9003-18-3	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Fillers (NJTS Reg. No. 04499600-6923)	Trade Secret	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
2-hydroxyethyl methacrylate	868-77-9	Experimental Bioconcentration		Log of Octanol/H <sub>2</sub> O part. coeff	0.42	OECD 107 log Kow shke flask mtd
Bisphenol A Polyethylene Glycol Diether Dimethacrylate	41637-38-1	Estimated Bioconcentration		Bioaccumulation Factor	6.6	Non-standard method
Dispersing Agent (NJTS Reg. No. 04499600-6929)	Trade Secret	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Phosphate Esters of PPG Methacrylate	95175-93-2	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Hydrotreated light paraffinic distillates (petroleum)	64742-55-8	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
COPPER NAPHTHENATES	1338-02-9	Estimated BCF-Carp	42 days	Bioaccumulation Factor	≤27	OECD 305E-Bioaccum Fl-thru fis

**12.4. Mobility in soil**

Material	Cas No.	Test Type	Study Type	Test Result	Protocol
Methyl Methacrylate	80-62-6	Experimental Mobility in Soil	Koc	8 l/kg	
2-hydroxyethyl methacrylate	868-77-9	Experimental Mobility in Soil	Koc	42.7 l/kg	

**12.5. Results of the PBT and vPvB assessment**

This material does not contain any substances that are assessed to be a PBT or vPvB

**12.6. Endocrine disrupting properties**

This material does not contain any substances that are assessed to be an endocrine disruptor for environmental effects

**12.7. Other adverse effects**

No information available

**SECTION 13: Disposal considerations****13.1 Waste treatment methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate uncured product in a permitted waste incineration facility. Combustion products will include halogen acid (HCl/HF/HBr). Facility must be capable of handling halogenated materials. As a disposal alternative, utilize an acceptable permitted waste disposal facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/CE and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor

**EU waste code (product as sold)**

080409\* Waste adhesives and sealants containing organic solvents or other dangerous substances  
200127\* Paint, inks, adhesives and resins containing dangerous substances

**SECTION 14: Transportation information**

ADR: UN1133; Adhesives; 3; II; (D/E); F1. (ENG)

IATA: UN1133; Adhesives; 3; II. (ENG)

IMDG: UN1133; Adhesives; 3; II; Marine Pollutant: Copper Salt; FE,SD. (ENG)

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****Carcinogenicity****Ingredient**

Methyl Methacrylate

**C.A.S. No.**

80-62-6

**Classification**

Gr. 3: Not classifiable

**Regulation**

International Agency for Research on Cancer

**Global inventory status**

Contact 3M for more information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

**SECTION 16: Other information****List of relevant H statements**

H225 Highly flammable liquid and vapor.  
H226 Flammable liquid and vapor.  
H302 Harmful if swallowed.  
H304 May be fatal if swallowed and enters airways.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H318 Causes serious eye damage.

H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

**Revision information:**

EU Section 09: pH information information was added.  
Section 02: <125ml Hazard - Health information was deleted.  
Section 02: <125ml Precautionary - Prevention information was deleted.  
Section 02: <125ml Precautionary - Response information was deleted.  
Section 02: CLP Ingredient table information was modified.  
Section 02: H phrase reference information was deleted.  
Section 02: Label Elements: CLP Classification information was deleted.  
Section 02: Label Elements: CLP Percent Unknown information was deleted.  
Section 02: Label Elements: CLP Precautionary - Prevention information was deleted.  
Section 02: Label Elements: CLP Precautionary - Response information was deleted.  
Section 02: Label Elements: Graphic information was deleted.  
Section 02: Label Elements: Signal Word information was deleted.  
Section 03: Composition table % Column heading information was added.  
Section 03: Composition/ Information of ingredients table information was modified.  
Section 03: Substance not applicable information was added.  
Section 04: Information on toxicological effects information was modified.  
Section 06: Accidental release clean-up information information was modified.  
Section 08: Occupational exposure limit table information was modified.  
Section 09: Evaporation Rate information information was deleted.  
Section 09: Explosive properties information information was deleted.  
Section 09: Kinematic Viscosity information information was added.  
Section 09: Melting point information information was modified.  
Section 09: Oxidising properties information information was deleted.  
Section 09: pH information information was deleted.  
Section 09: Property description for optional properties information was modified.  
Section 09: Vapor density value information was added.  
Section 09: Vapor density value information was deleted.  
Section 09: Viscosity information information was deleted.  
Section 11: Acute Toxicity table information was modified.  
Section 11: Classification disclaimer information was modified.  
Section 11: Germ Cell Mutagenicity Table information was modified.  
Section 11: No endocrine disruptor information available warning information was added.  
Section 11: Reproductive Toxicity Table information was modified.  
Section 11: Serious Eye Damage/Irritation Table information was modified.  
Section 11: Skin Corrosion/Irritation Table information was modified.  
Section 11: Skin Sensitization Table information was modified.  
Section 12: 12.6. Endocrine Disrupting Properties information was added.  
Section 12: 12.7. Other adverse effects information was modified.  
Section 12: Component ecotoxicity information information was modified.  
Section 12: Contact manufacturer for more detail. information was deleted.  
Section 12: Mobility in soil information information was added.  
Section 12: No endocrine disruptor information available warning information was added.  
Section 12: Persistence and Degradability information information was modified.  
Section 12: Bioaccumulative potential information information was modified.  
Section 15: Regulations - Inventories information was added.  
Section 16: UK disclaimer information was deleted.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the

product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

**3M Israel SDSs are available at [www.3M.com/il](http://www.3M.com/il)**