



## Safety Data Sheet

Copyright,2021, 3M India Limited.All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

|                        |            |                         |            |
|------------------------|------------|-------------------------|------------|
| <b>Document group:</b> | 22-0525-0  | <b>Version number:</b>  | 1.02       |
| <b>Issue Date:</b>     | 03/05/2021 | <b>Supersedes date:</b> | 14/04/2021 |

This Safety Data Sheet has been prepared in accordance with the GHS guidelines & India Hazardous substances (Classification, Labeling & Packaging) Draft Rules 2011.

### SECTION 1: Identification

#### 1.1. Product identifier

3M™ Scotch-Weld™ Epoxy Adhesive 460 Off-White, Part B

#### Product Identification Numbers

62-3593-8530-9      62-3593-9532-4

#### 1.2. Recommended use and restrictions on use

##### Recommended use

Structural adhesive.

#### 1.3. Supplier's details

**Address:** 3M India Limited, plot-48-51, Electronic city, Hosur road, Bangalore-560100  
**Telephone:** 080-45543000, contact Product EHS team  
**E Mail:** productehs.in@mmm.com  
**Website:** <http://solutions.3mindia.co.in>

#### 1.4. Emergency telephone number

080-45543000 (Contact hours: 8:00 AM to 5:00 PM)

### SECTION 2: Hazard identification

Under MSIHC Rules, information is noted below on flammability, acute toxicity and explosivity relevant to this product. In line with international standards, information on other hazard classes and associated precautionary statements relevant to this product are included as well.

#### 2.1. Classification of the substance or mixture

Serious Eye Damage/Irritation: Category 2B.

Skin Corrosion/Irritation: Category 3.

Skin Sensitizer: Category 1.

Reproductive Toxicity: Category 1B.

Acute Aquatic Toxicity: Category 2.

Chronic Aquatic Toxicity: Category 2.

#### 2.2. Label elements

**Signal Word**

DANGER!

**Symbols**

Exclamation mark | Health Hazard | Environment

**Pictograms**



**HAZARD STATEMENTS:**

- H320 Causes eye irritation.
- H316 Causes mild skin irritation.
- H317 May cause an allergic skin reaction.
- H360 May damage fertility or the unborn child.
  
- H411 Toxic to aquatic life with long lasting effects.

**PRECAUTIONARY STATEMENTS**

**Prevention:**

- P201 Obtain special instructions before use.
- P280E Wear protective gloves.
- P273 Avoid release to the environment.

**Response:**

- P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.
- P308 + P313 IF exposed or concerned: Get medical advice/attention.

**Disposal:**

- P501 Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

**2.3. Other hazards**

None known.

**SECTION 3: Composition/information on ingredients**

This material is a mixture.

| Ingredient                                    | CAS Nbr      | % by Wt |
|---|--------------|---------|
| Epoxy Resin                                   | 25068-38-6   | 80 - 95 |
| Acrylic Polymer (NJTS Reg No. 04499600-5018P) | Trade Secret | 1 - 20  |
| Toluene                                       | 108-88-3     | < 0.5   |
| methylene chloride                            | 75-09-2      | < 0.01  |

**SECTION 4: First aid measures**

**4.1. Description of first aid measures**

**Inhalation**

Remove person to fresh air. If you feel unwell, get medical attention.

**Skin contact**

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

**Eye contact**

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

**If swallowed**

Rinse mouth. If you feel unwell, get medical attention.

**4.2. Most important symptoms and effects, both acute and delayed**

Allergic skin reaction (redness, swelling, blistering, and itching).

**4.3. Indication of any immediate medical attention and special treatment required**

Not applicable

**SECTION 5: Fire-fighting measures**

**5.1. Suitable Extinguishing media**

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

**5.2. Special hazards arising from the substance or mixture**

None inherent in this product.

**Hazardous Decomposition or By-Products**

**Substance**

Aldehydes.  
Carbon monoxide.  
Carbon dioxide.  
Hydrogen Chloride  
Irritant vapours or gases.

**Condition**

During combustion.  
During combustion.  
During combustion.  
During combustion.  
During combustion.

**5.3. Special protective actions for fire-fighters**

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

**SECTION 6: Accidental release measures**

**6.1. Personal precautions, protective equipment and emergency procedures**

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

**6.2. Environmental precautions**

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

**6.3. Methods and material for containment and cleaning up**

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible in

accordance with applicable local/regional/national/international regulations.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

For industrial/occupational use only. Not for consumer sale or use. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (eg. gloves, respirators...) as required.

### 7.2. Conditions for safe storage including any incompatibilities

Store away from oxidising agents.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

| Ingredient         | CAS Nbr  | Agency | Limit type | Additional comments                         |
|--------------------|----------|--------|------------|---|
| Toluene            | 108-88-3 | ACGIH  | TWA:20 ppm | A4: Not class. as human carcin, Ototoxicant |
| methylene chloride | 75-09-2  | ACGIH  | TWA:50 ppm | A3: Confirmed animal carcin.                |

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

### 8.2. Exposure controls

#### 8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

#### 8.2.2. Personal protective equipment (PPE)

##### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect vented goggles.

##### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended: Polymer laminate

**Respiratory protection**

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties**

|  |   |
|--|---|
| <b>Physical state</b>                                    | Liquid.   |
| <b>Specific Physical Form:</b>                           | Paste   |
| <b>Color</b>   | White   |
| <b>Odor</b>  | Very Mild Odor  |
| <b>Odour threshold</b>                                   | <i>No data available.</i>   |
| <b>pH</b>  | <i>Not applicable.</i>  |
| <b>Melting point/Freezing point: NA</b>                  | <i>No data available.</i>   |
| <b>Boiling point/Initial boiling point/Boiling range</b> | >=260 °C  |
| <b>Flash point</b>                                       | 248.9 °C [ <i>Test Method: Closed Cup</i> ]   |
| <b>Evaporation rate</b>                                  | <i>Not applicable.</i>  |
| <b>Flammability (solid, gas)</b>                         | Not applicable.   |
| <b>Flammable Limits(LEL)</b>                             | <i>Not applicable.</i>  |
| <b>Flammable Limits(UEL)</b>                             | <i>Not applicable.</i>  |
| <b>Vapour pressure</b>                                   | <i>Not applicable.</i>  |
| <b>Vapor Density and/or Relative Vapor Density</b>       | <i>Not applicable.</i>  |
| <b>Density</b>   | 1.14 g/ml   |
| <b>Relative density</b>                                  | 1.14 [ <i>Ref Std: WATER=1</i> ]  |
| <b>Water solubility</b>                                  | Nil   |
| <b>Solubility- non-water</b>                             | <i>No data available.</i>   |
| <b>Partition coefficient: n-octanol/water</b>            | <i>No data available.</i>   |
| <b>Autoignition temperature</b>                          | <i>No data available.</i>   |
| <b>Decomposition temperature</b>                         | <i>No data available.</i>   |
| <b>Viscosity/Kinematic Viscosity</b>                     | 20,000 - 50,000 mPa-s [ <i>@ 23 °C</i> ]  |
| <b>Volatile organic compounds (VOC)</b>                  |   |
| <b>Percent volatile</b>                                  |   |
| <b>VOC less H2O &amp; exempt solvents</b>                | 0 g/l [ <i>Test Method: calculated SCAQMD rule 443.1</i> ]<br>[ <i>Details: when used as intended with Part A</i> ] |
| <b>VOC less H2O &amp; exempt solvents</b>                | 5 g/l [ <i>Test Method: calculated SCAQMD rule 443.1</i> ] [ <i>Details: as supplied</i> ]                          |
| <b>VOC less H2O &amp; exempt solvents</b>                | 0 % [ <i>Test Method: calculated SCAQMD rule 443.1</i> ]<br>[ <i>Details: when used as intended with Part A</i> ]   |
| <b>Molecular weight</b>                                  | <i>No data available.</i>   |

**Nanoparticles**

This material contains nanoparticles.

**SECTION 10: Stability and reactivity****10.1 Reactivity**

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

### 10.2 Chemical stability

Stable.

### 10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

### 10.4 Conditions to avoid

Heat is generated during cure. Do not cure a mass larger than 50 grams in a confined space to prevent a premature exothermic reaction with production of intense heat and smoke.

### 10.5 Incompatible materials

Strong oxidising agents.

### 10.6 Hazardous decomposition products

| <u>Substance</u> | <u>Condition</u> |
|------------------|------------------|
| None known.      |                  |

Refer to section 5.2 for hazardous decomposition products during combustion.

## SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

### 11.1 Information on Toxicological effects

#### Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### Inhalation

May cause additional health effects (see below).

#### Skin contact

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

#### Eye contact

Moderate eye irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

#### Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea. May cause additional health effects (see below).

#### Additional Health Effects:

#### Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

#### Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or

the data are not sufficient for classification.

**Acute Toxicity**

| Name  | Route                      | Species | Value  |
|---|----------------------------|---------|--|
| Overall product                               | Ingestion                  |         | No data available; calculated ATE >5,000 mg/kg |
| Epoxy Resin                                   | Dermal                     | Rat     | LD50 > 1,600 mg/kg                             |
| Epoxy Resin                                   | Ingestion                  | Rat     | LD50 > 1,000 mg/kg                             |
| Acrylic Polymer (NJTS Reg No. 04499600-5018P) | Dermal                     | Rabbit  | LD50 > 5,000 mg/kg                             |
| Acrylic Polymer (NJTS Reg No. 04499600-5018P) | Ingestion                  | Rat     | LD50 > 5,000 mg/kg                             |
| Toluene                                       | Dermal                     | Rat     | LD50 12,000 mg/kg                              |
| Toluene                                       | Inhalation-Vapor (4 hours) | Rat     | LC50 30 mg/l                                   |
| Toluene                                       | Ingestion                  | Rat     | LD50 5,550 mg/kg                               |
| methylene chloride                            | Dermal                     | Rat     | LD50 > 2,000 mg/kg                             |
| methylene chloride                            | Inhalation-Vapor (4 hours) | Rat     | LC50 63.7 mg/l                                 |
| methylene chloride                            | Ingestion                  | Rat     | LD50 1,410 mg/kg                               |

ATE = acute toxicity estimate

**Skin Corrosion/Irritation**

| Name  | Species                | Value              |
|---|------------------------|--------------------|
| Epoxy Resin                                   | Rabbit                 | Mild irritant      |
| Acrylic Polymer (NJTS Reg No. 04499600-5018P) | Professional judgement | Minimal irritation |
| Toluene                                       | Rabbit                 | Irritant           |
| methylene chloride                            | Rabbit                 | Irritant           |

**Serious Eye Damage/Irritation**

| Name  | Species                | Value             |
|---|------------------------|-------------------|
| Epoxy Resin                                   | Rabbit                 | Moderate irritant |
| Acrylic Polymer (NJTS Reg No. 04499600-5018P) | Professional judgement | Mild irritant     |
| Toluene                                       | Rabbit                 | Moderate irritant |
| methylene chloride                            | Rabbit                 | Severe irritant   |

**Sensitization:**

**Skin Sensitisation**

| Name        | Species          | Value          |
|-------------|------------------|----------------|
| Epoxy Resin | Human and animal | Sensitising    |
| Toluene     | Guinea pig       | Not classified |

**Respiratory Sensitisation**

| Name        | Species | Value          |
|-------------|---------|----------------|
| Epoxy Resin | Human   | Not classified |

**Germ Cell Mutagenicity**

| Name | Route | Value |
|------|-------|-------|
|      |       |       |

**3M™ Scotch-Weld™ Epoxy Adhesive 460 Off-White, Part B**

|                    |          |  |
|--------------------|----------|--|
| Epoxy Resin        | In vivo  | Not mutagenic  |
| Epoxy Resin        | In Vitro | Some positive data exist, but the data are not sufficient for classification |
| Toluene            | In Vitro | Not mutagenic  |
| Toluene            | In vivo  | Not mutagenic  |
| methylene chloride | In vivo  | Not mutagenic  |
| methylene chloride | In Vitro | Some positive data exist, but the data are not sufficient for classification |

**Carcinogenicity**

| Name               | Route      | Species                 | Value  |
|--------------------|------------|-------------------------|--|
| Epoxy Resin        | Dermal     | Mouse                   | Some positive data exist, but the data are not sufficient for classification |
| Toluene            | Dermal     | Mouse                   | Some positive data exist, but the data are not sufficient for classification |
| Toluene            | Ingestion  | Rat                     | Some positive data exist, but the data are not sufficient for classification |
| Toluene            | Inhalation | Mouse                   | Some positive data exist, but the data are not sufficient for classification |
| methylene chloride | Inhalation | Multiple animal species | Carcinogenic.  |

**Reproductive Toxicity**
**Reproductive and/or Developmental Effects**

| Name               | Route      | Value                                  | Species                 | Test result         | Exposure Duration      |
|--------------------|------------|--|-------------------------|---------------------|------------------------|
| Epoxy Resin        | Ingestion  | Not classified for female reproduction | Rat                     | NOAEL 750 mg/kg/day | 2 generation           |
| Epoxy Resin        | Ingestion  | Not classified for male reproduction   | Rat                     | NOAEL 750 mg/kg/day | 2 generation           |
| Epoxy Resin        | Dermal     | Not classified for development         | Rabbit                  | NOAEL 300 mg/kg/day | during organogenesis   |
| Epoxy Resin        | Ingestion  | Not classified for development         | Rat                     | NOAEL 750 mg/kg/day | 2 generation           |
| Toluene            | Inhalation | Not classified for female reproduction | Human                   | NOAEL Not available | occupational exposure  |
| Toluene            | Inhalation | Not classified for male reproduction   | Rat                     | NOAEL 2.3 mg/l      | 1 generation           |
| Toluene            | Ingestion  | Toxic to development                   | Rat                     | LOAEL 520 mg/kg/day | during gestation       |
| Toluene            | Inhalation | Toxic to development                   | Human                   | NOAEL Not available | poisoning and/or abuse |
| methylene chloride | Inhalation | Not classified for female reproduction | Rat                     | NOAEL 5.2 mg/l      | 2 generation           |
| methylene chloride | Inhalation | Not classified for male reproduction   | Rat                     | NOAEL 5.2 mg/l      | 2 generation           |
| methylene chloride | Inhalation | Not classified for development         | Multiple animal species | NOAEL 4.3 mg/l      | during gestation       |

**Target Organ(s)**
**Specific Target Organ Toxicity - single exposure**

| Name    | Route      | Target Organ(s)                   | Value  | Species | Test result         | Exposure Duration |
|---------|------------|-----------------------------------|--|---------|---------------------|-------------------|
| Toluene | Inhalation | central nervous system depression | May cause drowsiness or dizziness  | Human   | NOAEL Not available |                   |
| Toluene | Inhalation | respiratory irritation            | Some positive data exist, but the data are not sufficient for classification | Human   | NOAEL Not available |                   |
| Toluene | Inhalation | immune system                     | Not classified   | Mouse   | NOAEL 0.004 mg/l    | 3 hours           |
| Toluene | Ingestion  | central nervous                   | May cause drowsiness or  | Human   | NOAEL Not           | poisoning         |



**3M™ Scotch-Weld™ Epoxy Adhesive 460 Off-White, Part B**

|                    |            |                                   |  |       |                     |                       |
|--------------------|------------|-----------------------------------|--|-------|---------------------|-----------------------|
|                    |            | system depression                 | dizziness  |       | available           | and/or abuse          |
| methylene chloride | Dermal     | blood                             | Some positive data exist, but the data are not sufficient for classification | Rat   | NOAEL Not available | 4 hours               |
| methylene chloride | Inhalation | central nervous system depression | May cause drowsiness or dizziness  | Human | NOAEL Not available | occupational exposure |
| methylene chloride | Inhalation | blood                             | Some positive data exist, but the data are not sufficient for classification | Human | NOAEL Not available |                       |
| methylene chloride | Inhalation | respiratory irritation            | Some positive data exist, but the data are not sufficient for classification |       | NOAEL Not available |                       |

**Specific Target Organ Toxicity - repeated exposure**

| Name        | Route      | Target Organ(s)  | Value  | Species                 | Test result           | Exposure Duration      |
|-------------|------------|--|--|-------------------------|-----------------------|------------------------|
| Epoxy Resin | Dermal     | liver  | Not classified   | Rat                     | NOAEL 1,000 mg/kg/day | 2 years                |
| Epoxy Resin | Dermal     | nervous system   | Not classified   | Rat                     | NOAEL 1,000 mg/kg/day | 13 weeks               |
| Epoxy Resin | Ingestion  | auditory system   heart   endocrine system   hematopoietic system   liver   eyes   kidney and/or bladder | Not classified   | Rat                     | NOAEL 1,000 mg/kg/day | 28 days                |
| Toluene     | Inhalation | auditory system   eyes   olfactory system  | Causes damage to organs through prolonged or repeated exposure               | Human                   | NOAEL Not available   | poisoning and/or abuse |
| Toluene     | Inhalation | nervous system   | May cause damage to organs through prolonged or repeated exposure            | Human                   | NOAEL Not available   | poisoning and/or abuse |
| Toluene     | Inhalation | respiratory system   | Some positive data exist, but the data are not sufficient for classification | Rat                     | LOAEL 2.3 mg/l        | 15 months              |
| Toluene     | Inhalation | heart   liver   kidney and/or bladder  | Not classified   | Rat                     | NOAEL 11.3 mg/l       | 15 weeks               |
| Toluene     | Inhalation | endocrine system   | Not classified   | Rat                     | NOAEL 1.1 mg/l        | 4 weeks                |
| Toluene     | Inhalation | immune system  | Not classified   | Mouse                   | NOAEL Not available   | 20 days                |
| Toluene     | Inhalation | bone, teeth, nails, and/or hair  | Not classified   | Mouse                   | NOAEL 1.1 mg/l        | 8 weeks                |
| Toluene     | Inhalation | hematopoietic system   vascular system   | Not classified   | Human                   | NOAEL Not available   | occupational exposure  |
| Toluene     | Inhalation | gastrointestinal tract   | Not classified   | Multiple animal species | NOAEL 11.3 mg/l       | 15 weeks               |
| Toluene     | Ingestion  | nervous system   | Some positive data exist, but the data are not sufficient for classification | Rat                     | NOAEL 625 mg/kg/day   | 13 weeks               |
| Toluene     | Ingestion  | heart  | Not classified   | Rat                     | NOAEL 2,500 mg/kg/day | 13 weeks               |
| Toluene     | Ingestion  | liver   kidney and/or bladder  | Not classified   | Multiple animal species | NOAEL 2,500 mg/kg/day | 13 weeks               |
| Toluene     | Ingestion  | hematopoietic system   | Not classified   | Mouse                   | NOAEL 600 mg/kg/day   | 14 days                |
| Toluene     | Ingestion  | endocrine system   | Not classified   | Mouse                   | NOAEL 105 mg/kg/day   | 28 days                |
| Toluene     | Ingestion  | immune system  | Not classified   | Mouse                   | NOAEL 105 mg/kg/day   | 4 weeks                |

**3M™ Scotch-Weld™ Epoxy Adhesive 460 Off-White, Part B**

|                    |            |                       |  |                         |                       |           |
|--------------------|------------|-----------------------|--|-------------------------|-----------------------|-----------|
| methylene chloride | Inhalation | kidney and/or bladder | Some positive data exist, but the data are not sufficient for classification | Rat                     | LOAEL 6.95 mg/l       | 2 years   |
| methylene chloride | Inhalation | liver                 | Some positive data exist, but the data are not sufficient for classification | Rat                     | NOAEL 0.17 mg/l       | 2 years   |
| methylene chloride | Inhalation | respiratory system    | Some positive data exist, but the data are not sufficient for classification | Multiple animal species | LOAEL 35 mg/l         | 8 weeks   |
| methylene chloride | Inhalation | heart                 | Not classified   | Human                   | NOAEL Not available   |           |
| methylene chloride | Inhalation | immune system         | Not classified   | Rat                     | NOAEL 18 mg/l         | 28 days   |
| methylene chloride | Ingestion  | liver                 | Some positive data exist, but the data are not sufficient for classification | Rat                     | LOAEL 1,200 mg/kg/day | 3 months  |
| methylene chloride | Ingestion  | blood                 | Not classified   | Rat                     | NOAEL 249 mg/kg/day   | 2 years   |
| methylene chloride | Ingestion  | kidney and/or bladder | Not classified   | Rat                     | NOAEL 1,469 mg/kg/day | 3 months  |
| methylene chloride | Ingestion  | eyes                  | Not classified   | Rat                     | NOAEL 249 mg/kg/day   | 104 weeks |

**Aspiration Hazard**

| Name    | Value             |
|---------|-------------------|
| Toluene | Aspiration hazard |

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

**SECTION 12: Ecological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labelling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

**12.1. Toxicity**

**Acute aquatic hazard:**

GHS Acute 2: Toxic to aquatic life.

**Chronic aquatic hazard:**

GHS Chronic 2: Toxic to aquatic life with long lasting effects.

No product test data available.

| Material               | CAS Nbr      | Organism         | Type                  | Exposure | Test endpoint | Test result |
|------------------------|--------------|------------------|-----------------------|----------|---------------|-------------|
| Epoxy Resin            | 25068-38-6   | Activated sludge | Estimated             | 3 hours  | IC50          | >100 mg/l   |
| Epoxy Resin            | 25068-38-6   | Green Algae      | Estimated             | 72 hours | EC50          | >11 mg/l    |
| Epoxy Resin            | 25068-38-6   | Rainbow trout    | Estimated             | 96 hours | LC50          | 2 mg/l      |
| Epoxy Resin            | 25068-38-6   | Water flea       | Estimated             | 48 hours | EC50          | 1.8 mg/l    |
| Epoxy Resin            | 25068-38-6   | Green Algae      | Estimated             | 72 hours | NOEC          | 4.2 mg/l    |
| Epoxy Resin            | 25068-38-6   | Water flea       | Estimated             | 21 days  | NOEC          | 0.3 mg/l    |
| Acrylic Polymer (NJTS) | Trade Secret |                  | Data not available or |          |               | N/A         |

|                         |          |                  |                                 |            |      |                              |
|-------------------------|----------|------------------|---------------------------------|------------|------|------------------------------|
| Reg No. 04499600-5018P) |          |                  | insufficient for classification |            |      |                              |
| Toluene                 | 108-88-3 | Coho Salmon      | Experimental                    | 96 hours   | LC50 | 5.5 mg/l                     |
| Toluene                 | 108-88-3 | Grass Shrimp     | Experimental                    | 96 hours   | LC50 | 9.5 mg/l                     |
| Toluene                 | 108-88-3 | Green Algae      | Experimental                    | 72 hours   | EC50 | 12.5 mg/l                    |
| Toluene                 | 108-88-3 | Leopard frog     | Experimental                    | 9 days     | LC50 | 0.39 mg/l                    |
| Toluene                 | 108-88-3 | Pink Salmon      | Experimental                    | 96 hours   | LC50 | 6.41 mg/l                    |
| Toluene                 | 108-88-3 | Water flea       | Experimental                    | 48 hours   | EC50 | 3.78 mg/l                    |
| Toluene                 | 108-88-3 | Coho Salmon      | Experimental                    | 40 days    | NOEC | 1.39 mg/l                    |
| Toluene                 | 108-88-3 | Diatom           | Experimental                    | 72 hours   | NOEC | 10 mg/l                      |
| Toluene                 | 108-88-3 | Water flea       | Experimental                    | 7 days     | NOEC | 0.74 mg/l                    |
| Toluene                 | 108-88-3 | Activated sludge | Experimental                    | 12 hours   | IC50 | 292 mg/l                     |
| Toluene                 | 108-88-3 | Bacteria         | Experimental                    | 16 hours   | NOEC | 29 mg/l                      |
| Toluene                 | 108-88-3 | Bacteria         | Experimental                    | 24 hours   | EC50 | 84 mg/l                      |
| Toluene                 | 108-88-3 | Redworm          | Experimental                    | 28 days    | LC50 | >150 mg per kg of bodyweight |
| Toluene                 | 108-88-3 | Soil microbes    | Experimental                    | 28 days    | NOEC | <26 mg/kg (Dry Weight)       |
| methylene chloride      | 75-09-2  | Fathead minnow   | Experimental                    | 96 hours   | LC50 | 193 mg/l                     |
| methylene chloride      | 75-09-2  | Green Algae      | Experimental                    | 72 hours   | EC50 | 242 mg/l                     |
| methylene chloride      | 75-09-2  | Water flea       | Experimental                    | 48 hours   | LC50 | 27 mg/l                      |
| methylene chloride      | 75-09-2  | Fathead minnow   | Experimental                    | 28 days    | NOEC | 83 mg/l                      |
| methylene chloride      | 75-09-2  | Green Algae      | Experimental                    | 72 hours   | EC10 | 115 mg/l                     |
| methylene chloride      | 75-09-2  | Activated sludge | Experimental                    | 40 minutes | EC50 | 2,590 mg/l                   |

**12.2. Persistence and degradability**

| Material                                      | CAS Nbr      | Test type                       | Duration | Study Type                    | Test result       | Protocol                            |
|---|--------------|---------------------------------|----------|-------------------------------|-------------------|-------------------------------------|
| Epoxy Resin                                   | 25068-38-6   | Estimated Hydrolysis            |          | Hydrolytic half-life          | 117 hours (t 1/2) | Non-standard method                 |
| Epoxy Resin                                   | 25068-38-6   | Estimated Biodegradation        | 28 days  | BOD                           | 5 %BOD/COD        | OECD 301F - Manometric respirometry |
| Acrylic Polymer (NJTS Reg No. 04499600-5018P) | Trade Secret | Data not available-insufficient |          |                               | N/A               |                                     |
| Toluene                                       | 108-88-3     | Experimental Photolysis         |          | Photolytic half-life (in air) | 5.2 days (t 1/2)  |                                     |
| Toluene                                       | 108-88-3     | Experimental Biodegradation     | 20 days  | BOD                           | 80 % BOD/ThBOD    | APHA Std Meth Water/Wastewater      |
| methylene chloride                            | 75-09-2      | Experimental Photolysis         |          | Photolytic half-life (in air) | 226 days (t 1/2)  |                                     |
| methylene chloride                            | 75-09-2      | Experimental Biodegradation     | 28 days  | BOD                           | 68 % BOD/ThBOD    | OECD 301D - Closed bottle test      |

**12.3 : Bioaccumulative potential**

| Material                                      | CAS Nbr      | Test type   | Duration | Study Type             | Test result | Protocol                 |
|---|--------------|---|----------|------------------------|-------------|--------------------------|
| Epoxy Resin                                   | 25068-38-6   | Estimated Bioconcentration                            |          | Log Kow                | 3.242       | Non-standard method      |
| Acrylic Polymer (NJTS Reg No. 04499600-5018P) | Trade Secret | Data not available or insufficient for classification | N/A      | N/A                    | N/A         | N/A                      |
| Toluene                                       | 108-88-3     | Experimental BCF - Other                              | 72 hours | Bioaccumulation factor | 90          |                          |
| Toluene                                       | 108-88-3     | Experimental Bioconcentration                         |          | Log Kow                | 2.73        |                          |
| methylene chloride                            | 75-09-2      | Experimental BCF-Carp                                 | 42 days  | Bioaccumulation factor | ≤40         | OECD305-Bioconcentration |
| methylene chloride                            | 75-09-2      | Experimental Bioconcentration                         |          | Log Kow                | 1.25        |                          |

**12.4. Mobility in soil**

Please contact manufacturer for more details

**12.5 Other Adverse effects**

No information available.

**SECTION 13: Disposal considerations****13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerised) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Combustion products will include halogen acid (HCl/HF/HBr). Facility must be capable of handling halogenated materials. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

**SECTION 14: Transport Information****Air Transport (IATA) Regulations**

UN No UN3082

Proper Shipping Name ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN)

Hazard Class/Division 9

Subsidiary Risk Not applicable

Packing Group: III

**Marine Transport (IMDG)**

UN No UN3082

**Proper Shipping Name** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN)  
**Hazard Class/Division** 9  
**Subsidiary Risk** Not applicable  
**Packing Group:** III  
**Environmental Hazards:** Marine Pollutant: Yes

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Japan Chemical Substance Control Law. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

#### Applicable Environmental, Health and Safety Regulations

The Manufacture, Storage and Import of Hazardous Chemical Rules, 1989  
Hazardous Waste(Management , Handling & Transboundary) Rules, 2008  
Hazardous Chemicals (Classification, Packaging and Labelling Draft Rules), 2011

The following ingredients are listed as hazardous on Part II of Schedule I of the India Manufacture, Storage and Import of Hazardous Chemicals (MSIHC) rules  
methylene chloride  
Toluene

The following ingredients are classified as hazardous based on the criteria listed under Part I of Schedule I of the India Manufacture, Storage and Import of Hazardous Chemicals (MSIHC) rules:  
The product is classified as Non-Hazardous as per MSIHC Rules, 1989.

## SECTION 16: Other information

#### NFPA Hazard Classification

**Health:** 2    **Flammability:** 1    **Instability:** 0    **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

#### Revision information:

Label: GHS Classification information was modified.  
Label: GHS Precautionary - Prevention information was modified.  
Label: GHS Precautionary - Response information was modified.  
Label: Graphic information was modified.  
Label: Signal Word information was modified.  
Label: Symbol information was modified.  
Section 2: Ingredient table information was modified.

Section 7: Precautions safe handling information information was modified.

Section 8: Occupational exposure limit table information was modified.

Section 11: Acute Toxicity table information was modified.

Section 11: Aspiration Hazard Table information was added.

Section 11: Aspiration Hazard text information was deleted.

Section 11: Carcinogenicity Table information was modified.

Section 11: Germ Cell Mutagenicity Table information was modified.

Section 11: Health Effects - Ingestion information information was modified.

Section 11: Health Effects - Inhalation information information was modified.

Section 11: Reproductive Hazards information information was added.

Section 11: Reproductive Toxicity Table information was modified.

Section 11: Serious Eye Damage/Irritation Table information was modified.

Section 11: Skin Corrosion/Irritation Table information was modified.

Section 11: Skin Sensitization Table information was modified.

Section 11: Target Organs - Repeated Table information was modified.

Section 11: Target Organs - Single Table information was modified.

Section 12: Component ecotoxicity information information was modified.

Section 12: Persistence and Degradability information information was modified.

Section 12: Biocumulative potential information information was modified.

Section 15: MSIHC Ingredients information was modified.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

**3M India SDSs are available at <http://solutions.3mindia.co.in>**