



Safety Data Sheet

Copyright,2021, 3M India Limited.All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group: 29-0522-2 **Version number:** 1.02
Issue Date: 08/01/2021 **Supersedes date:** 04/12/2020

This Safety Data Sheet has been prepared in accordance with the GHS guidelines & India Hazardous substances (Classification, Labeling & Packaging) Draft Rules 2011.

SECTION 1: Identification

1.1. Product identifier

3M™ Filtek™ Z250 XT Nano Hybrid Universal Restorative

Product Identification Numbers

70-2010-7910-3	70-2010-7911-1	70-2010-7912-9	70-2010-7913-7	70-2010-7914-5
70-2010-7915-2	70-2010-7916-0	70-2010-7917-8	70-2010-7918-6	70-2010-7919-4
70-2010-7920-2	70-2010-7921-0	70-2010-7922-8	70-2010-7924-4	70-2010-7925-1
70-2010-7926-9	70-2010-7927-7	70-2010-7928-5	70-2010-7929-3	70-2010-7930-1
70-2010-7931-9	70-2010-7932-7	70-2010-7933-5	70-2010-7934-3	70-2010-7935-0
70-2010-8811-2	70-2010-8940-9	70-2010-8942-5	70-2010-8946-6	70-2010-8950-8
70-2010-8951-6	EH-2010-1503-7	EH-2010-1504-5	EH-2010-1505-2	EH-2010-1506-0
EH-2010-1507-8	EH-2010-1508-6	EH-2010-1509-4	EH-2010-1510-2	EH-2010-1513-6
EH-2010-1514-4	HB-0042-0995-1	HB-0042-0999-3	HB-0042-1000-9	HB-0042-1001-7
HB-0042-1002-5	HB-0042-1003-3	HB-0042-1004-1	HB-0042-1005-8	HB-0042-1006-6
HB-0042-1007-4	HB-0042-1008-2	HB-0042-1009-0	HB-0042-6796-7	HB-0042-8997-9
HB-0045-0672-9	HB-0045-0673-7	HB-0045-0676-0	HB-0045-0687-7	HB-0045-0688-5
HB-0045-0689-3	HB-0045-0690-1	HB-0045-0691-9	HB-0045-0692-7	HB-0045-0693-5
HB-0045-0694-3	HB-0045-0695-0	HB-0045-3428-3	HB-0045-3429-1	HB-0045-7056-8
HB-0045-7057-6	HB-0045-7058-4	HB-0045-7059-2	HB-0045-7060-0	HB-0046-1264-2
UU-0091-3127-5	UU-0091-3128-3	UU-0091-3129-1	UU-0091-3130-9	UU-0091-3131-7
UU-0091-3132-5	UU-0091-3133-3	UU-0091-3134-1	UU-0091-3135-8	UU-0091-3136-6
UU-0091-3137-4	UU-0091-3138-2	UU-0091-3139-0	UU-0091-3140-8	UU-0091-3141-6

1.2. Recommended use and restrictions on use

Recommended use

Dental Product, Restorative

Restrictions on use

For use by dental professionals only.

1.3. Supplier's details

Address: 3M India Limited, plot-48-51, Electronic city, Hosur road, Bangalore-560100
Telephone: 080-45543000, contact Product EHS team
E Mail: productehs.in@mmm.com
Website: <http://solutions.3mindia.co.in>

1.4. Emergency telephone number

080-45543000 (Contact hours: 8:00 AM to 5:00 PM)

SECTION 2: Hazard identification

Under MSIHC Rules, information is noted below on flammability, acute toxicity and explosivity relevant to this product. In line with international standards, information on other hazard classes and associated precautionary statements relevant to this product are included as well.

2.1. Classification of the substance or mixture

Acute Toxicity (oral): Category 5.

Skin Sensitizer: Category 1.

Chronic Aquatic Toxicity: Category 2.

2.2. Label elements

Signal Word

WARNING!

Symbols

Exclamation mark | Environment |

Pictograms



HAZARD STATEMENTS:

H303 May be harmful if swallowed.
H317 May cause an allergic skin reaction.

H411 Toxic to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENTS

Prevention:

P280E Wear protective gloves.
P273 Avoid release to the environment.

Response:

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

Disposal:

P501 Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

2.3. Other hazards

None known.

SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	CAS Nbr	% by Wt
------------	---------	---------

3M™ Filtek™ Z250 XT Nano Hybrid Universal Restorative

Silane Treated Ceramic	444758-98-9	70 - 85
(1-methylethylidene)bis[4,1-phenyleneoxy(2-hydroxy-3,1-propanediyl)] bismethacrylate	1565-94-2	1 - 10
Bisphenol A Polyethylene Glycol Diether Dimethacrylate (BISEMA-6)	41637-38-1	1 - 10
Diurethane Dimethacrylate (UDMA)	72869-86-4	1 - 10
Silane Treated Silica	248596-91-0	1 - 10

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye contact

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

No critical symptoms or effects. See Section 11.1, information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable Extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

<u>Substance</u>	<u>Condition</u>
Carbon monoxide.	During combustion.
Carbon dioxide.	During combustion.

5.3. Special protective actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

A no-touch technique is recommended. If skin contact occurs, wash skin with soap and water. Acrylates may penetrate commonly-used gloves. If product contacts glove, remove and discard glove, wash hands immediately with soap and water and then re-glove. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Do not get in eyes.

7.2. Conditions for safe storage including any incompatibilities

No special storage requirements.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

No occupational exposure limit values exist for any of the components listed in Section 3 of this Safety Data Sheet.

8.2. Exposure controls

8.2.1. Engineering controls

Use in a well-ventilated area.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety glasses with side shields.

Skin/hand protection

See Section 7.1 for additional information on skin protection.

Respiratory protection

None required.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Solid.
Specific Physical Form:	Paste
Color	Tooth

3M™ Filtek™ Z250 XT Nano Hybrid Universal Restorative

Odor	Slight Acrylate
Odour threshold	<i>No data available.</i>
pH	<i>Not applicable.</i>
Melting point/Freezing point: NA	<i>No data available.</i>
Boiling point/Initial boiling point/Boiling range	<i>Not applicable.</i>
Flash point	No flash point
Evaporation rate	<i>Not applicable.</i>
Flammability (solid, gas)	Not classified
Flammable Limits(LEL)	<i>Not applicable.</i>
Flammable Limits(UEL)	<i>Not applicable.</i>
Vapour pressure	<i>Not applicable.</i>
Vapor Density and/or Relative Vapor Density	<i>Not applicable.</i>
Density	2.1 g/cm ³
Relative density	2.1 [Ref Std:WATER=1]
Water solubility	Negligible
Solubility- non-water	<i>No data available.</i>
Partition coefficient: n-octanol/water	<i>Not applicable.</i>
Autoignition temperature	<i>No data available.</i>
Decomposition temperature	<i>No data available.</i>
Viscosity/Kinematic Viscosity	<i>No data available.</i>
Volatile organic compounds (VOC)	
Percent volatile	
VOC less H₂O & exempt solvents	
Molecular weight	<i>No data available.</i>

Nanoparticles

This material contains nanoparticles.

SECTION 10: Stability and reactivity**10.1 Reactivity**

This material is considered to be non reactive under normal use conditions

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

Light.

10.5 Incompatible materials

None known.

10.6 Hazardous decomposition products**Substance****Condition**

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1 Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

This product may have a characteristic odour; however, no adverse health effects are anticipated.

Skin contact

Contact with the skin during product use is not expected to result in significant irritation. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye contact

Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion

May be harmful if swallowed.

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE2,000 - 5,000 mg/kg
Silane Treated Ceramic	Dermal		LD50 estimated to be > 5,000 mg/kg
Silane Treated Ceramic	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
Silane Treated Silica	Dermal		LD50 estimated to be > 5,000 mg/kg
Silane Treated Silica	Ingestion		LD50 estimated to be > 5,000 mg/kg
Bisphenol A Polyethylene Glycol Diether Dimethacrylate (BISEMA-6)	Dermal	Professional judgement	LD50 estimated to be > 5,000 mg/kg
Diurethane Dimethacrylate (UDMA)	Dermal	Professional judgement	LD50 estimated to be > 5,000 mg/kg
Bisphenol A Polyethylene Glycol Diether Dimethacrylate (BISEMA-6)	Ingestion	Rat	LD50 > 2,000 mg/kg
Diurethane Dimethacrylate (UDMA)	Ingestion	Rat	LD50 > 5,000 mg/kg
(1-methylethylidene)bis[4,1-phenyleneoxy(2-hydroxy-3,1-propanediyl)] bismethacrylate	Dermal	Professional judgement	LD50 estimated to be > 5,000 mg/kg
(1-methylethylidene)bis[4,1-phenyleneoxy(2-hydroxy-3,1-propanediyl)] bismethacrylate	Ingestion	Rat	LD50 > 11,700 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
------	---------	-------

3M™ Filtek™ Z250 XT Nano Hybrid Universal Restorative

Silane Treated Ceramic	similar compounds	No significant irritation
Silane Treated Silica	Professional judgement	No significant irritation
(1-methylethylidene)bis[4,1-phenyleneoxy(2-hydroxy-3,1-propanediyl)] bismethacrylate	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
Silane Treated Ceramic	similar compounds	Mild irritant
Silane Treated Silica	Professional judgement	No significant irritation
(1-methylethylidene)bis[4,1-phenyleneoxy(2-hydroxy-3,1-propanediyl)] bismethacrylate	In vitro data	No significant irritation

Sensitization:

Skin Sensitisation

Name	Species	Value
Silane Treated Ceramic	similar compounds	Not classified
Bisphenol A Polyethylene Glycol Diether Dimethacrylate (BISEMA-6)	Guinea pig	Not classified
Diurethane Dimethacrylate (UDMA)	Guinea pig	Sensitising
(1-methylethylidene)bis[4,1-phenyleneoxy(2-hydroxy-3,1-propanediyl)] bismethacrylate	Mouse	Not classified

Respiratory Sensitisation

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Bisphenol A Polyethylene Glycol Diether Dimethacrylate (BISEMA-6)	In Vitro	Not mutagenic
(1-methylethylidene)bis[4,1-phenyleneoxy(2-hydroxy-3,1-propanediyl)] bismethacrylate	In Vitro	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
Silane Treated Ceramic	Inhalation	similar compounds	Some positive data exist, but the data are not sufficient for classification

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
(1-methylethylidene)bis[4,1-phenyleneoxy(2-hydroxy-3,1-propanediyl)] bismethacrylate	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	during gestation

3M™ Filtek™ Z250 XT Nano Hybrid Universal Restorative**Target Organ(s)****Specific Target Organ Toxicity - single exposure**

For the component/components, either no data are currently available or the data are not sufficient for classification.

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Silane Treated Ceramic	Inhalation	pulmonary fibrosis	Not classified	similar compounds	NOAEL Not available	
(1-methylethylidene)bis[4,1-phenyleneoxy(2-hydroxy-3,1-propanediyl)] bismethacrylate	Ingestion	endocrine system hematopoietic system liver heart skin gastrointestinal tract bone, teeth, nails, and/or hair immune system muscles nervous system eyes kidney and/or bladder respiratory system vascular system	Not classified	Rat	NOAEL 1,000 mg/kg/day	90 days

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labelling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

12.1. Toxicity**Acute aquatic hazard:**

Not acutely toxic to aquatic life by GHS criteria.

Chronic aquatic hazard:

GHS Chronic 2: Toxic to aquatic life with long lasting effects.

No product test data available.

Material	CAS Nbr	Organism	Type	Exposure	Test endpoint	Test result
Silane Treated Ceramic	444758-98-9		Data not available or insufficient for classification			N/A
(1-methylethylidene)bis[4,1-	1565-94-2	Green Algae	Endpoint not reached	96 hours		>100 mg/l

3M™ Filtek™ Z250 XT Nano Hybrid Universal Restorative

phenyleneoxy(2-hydroxy-3,1-propanediyl)] bismethacrylate						
(1-methylethylidene)bis[4,1-phenyleneoxy(2-hydroxy-3,1-propanediyl)] bismethacrylate	1565-94-2	Water flea	Endpoint not reached	48 hours		>100 mg/l
(1-methylethylidene)bis[4,1-phenyleneoxy(2-hydroxy-3,1-propanediyl)] bismethacrylate	1565-94-2	Common Carp	Estimated	96 hours	No tox obs at lmt of water sol	>100 mg/l
(1-methylethylidene)bis[4,1-phenyleneoxy(2-hydroxy-3,1-propanediyl)] bismethacrylate	1565-94-2	Green Algae	Experimental	96 hours	Effect Concentration 10%	1.1 mg/l
Bisphenol A Polyethylene Glycol Diether Dimethacrylate (BISEMA-6)	41637-38-1	Activated sludge	Estimated	3 hours	EC50	>1,000 mg/l
Bisphenol A Polyethylene Glycol Diether Dimethacrylate (BISEMA-6)	41637-38-1	Green algae	Estimated	72 hours	No tox obs at lmt of water sol	>100 mg/l
Bisphenol A Polyethylene Glycol Diether Dimethacrylate (BISEMA-6)	41637-38-1	Rainbow trout	Estimated	96 hours	No tox obs at lmt of water sol	>100 mg/l
Bisphenol A Polyethylene Glycol Diether Dimethacrylate (BISEMA-6)	41637-38-1	Green algae	Estimated	72 hours	No tox obs at lmt of water sol	>100 mg/l
Diurethane Dimethacrylate (UDMA)	72869-86-4	Green algae	Endpoint not reached	72 hours	Effect Growth Rate Conc 50%	>100 mg/l
Diurethane Dimethacrylate (UDMA)	72869-86-4	Water flea	Experimental	48 hours	EC50	>100 mg/l
Diurethane Dimethacrylate (UDMA)	72869-86-4	Zebra Fish	Experimental	96 hours	LC50	10.1 mg/l
Diurethane	72869-86-4	Green algae	Endpoint not	72 hours	Effect Conc.	>100 mg/l

3M™ Filtek™ Z250 XT Nano Hybrid Universal Restorative

Dimethacrylate (UDMA)			reached		10% - Growth Rate	
Silane Treated Silica	248596-91-0		Data not available or insufficient for classification			N/A

12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Silane Treated Ceramic	444758-98-9	Data not available-insufficient			N/A	
(1-methylethylidene)bis[4,1-phenyleneoxy(2-hydroxy-3,1-propanediyl)] bismethacrylate	1565-94-2	Experimental Biodegradation	28 days	BOD	21 % BOD/ThBOD	similar to OECD 301F
Bisphenol A Polyethylene Glycol Diether Dimethacrylate (BISEMA-6)	41637-38-1	Experimental Biodegradation	28 days	BOD	24 % BOD/ThBOD	OECD 301D - Closed bottle test
Diurethane Dimethacrylate (UDMA)	72869-86-4	Experimental Biodegradation	28 days	CO2 evolution	22 %CO2 evolution/THCO2 evolution (does not pass 10-day window)	OECD 301B - Modified sturm or CO2
Silane Treated Silica	248596-91-0	Data not available-insufficient			N/A	

12.3 : Bioaccumulative potential

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Silane Treated Ceramic	444758-98-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
(1-methylethylidene)bis[4,1-phenyleneoxy(2-hydroxy-3,1-propanediyl)] bismethacrylate	1565-94-2	Experimental Bioconcentration		Log Kow	4.63	Non-standard method
Bisphenol A Polyethylene Glycol Diether Dimethacrylate (BISEMA-6)	41637-38-1	Estimated Bioconcentration		Bioaccumulation factor	6.6	Estimated: Bioconcentration factor
Bisphenol A	41637-38-1	Experimental		Log Kow	≥4.66	OECD 117 log Kow

3M™ Filtek™ Z250 XT Nano Hybrid Universal Restorative

Polyethylene Glycol Diether Dimethacrylate (BISEMA-6)		Bioconcentration				HPLC method
Diurethane Dimethacrylate (UDMA)	72869-86-4	Experimental Bioconcentration		Log Kow	3.39	Non-standard method
Silane Treated Silica	248596-91-0	Data not available or insufficient for classification	N/A	N/A	N/A	N/A

12.4. Mobility in soil

Please contact manufacturer for more details

12.5 Other Adverse effects

No information available.

SECTION 13: Disposal considerations**13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility.

SECTION 14: Transport Information

Not hazardous for transportation.

Air Transport (IATA) Regulations

UN No Not applicable

Proper Shipping Name Not applicable

Hazard Class/Division Not applicable

Subsidiary Risk Not applicable

Packing Group: Not applicable

Marine Transport (IMDG)

UN No Not applicable

Proper Shipping Name Not applicable

Hazard Class/Division Not applicable

Subsidiary Risk Not applicable

Packing Group: Not applicable

Environmental Hazards: Not applicable

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****Global inventory status**

Contact 3M for more information.

Applicable Environmental, Health and Safety Regulations

The Manufacture, Storage and Import of Hazardous Chemical Rules, 1989

3M™ Filtek™ Z250 XT Nano Hybrid Universal Restorative

The Bio Medical Waste (Management & Handling) Rules, 1998
Hazardous Chemicals (Classification, Packaging and Labelling Draft Rules), 2011

The following ingredients are listed as hazardous on Part II of Schedule I of the India Manufacture, Storage and Import of Hazardous Chemicals (MSIHC) rules
None.

The following ingredients are classified as hazardous based on the criteria listed under Part I of Schedule I of the India Manufacture, Storage and Import of Hazardous Chemicals (MSIHC) rules:
The product is classified as Non-Hazardous as per MSIHC Rules, 1989.

SECTION 16: Other information

NFPA Hazard Classification

Health: 2 **Flammability:** 1 **Instability:** 0 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Revision information:

Section 1: Product identification numbers information was added.
Section 1: Product name information was modified.
Section 2: Ingredient table information was modified.
Section 04: Information on toxicological effects information was deleted.
Section 09: Nanoparticle information was modified.
Section 11: Acute Toxicity table information was modified.
Section 11: Carcinogenicity Table information was modified.
Section 11: Germ Cell Mutagenicity Table information was modified.
Section 11: Serious Eye Damage/Irritation Table information was modified.
Section 11: Skin Corrosion/Irritation Table information was modified.
Section 11: Skin Sensitization Table information was modified.
Section 11: Target Organs - Repeated Table information was modified.
Section 12: Component ecotoxicity information information was modified.
Section 12: Persistence and Degradability information information was modified.
Section 12: Biocumulative potential information information was modified.
Section 15: MSIHC Part I of Schedule I ingredients information was added.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

3M India SDSs are available at <http://solutions.3mindia.co.in>