

# Safety Data Sheet

Copyright, 2022, 3M India Limited. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

**Document group:** 26-0572-3 **Version number:** 1.08

**Issue Date:** 24/03/2022 **Supersedes date:** 26/08/2020

This Safety Data Sheet has been prepared in accordance with the GHS guidelines & India Hazardous substances (Classification, Labeling & Packaging) Draft Rules 2011.

# **SECTION 1: Identification**

#### 1.1. Product identifier

3M Choke and Carb Cleaner

### **Product Identification Numbers**

IA-2601-0457-4 IA-2601-6449-5 IC-2601-6351-9 IC-2601-6449-1 IS-2601-0019-0

IS-2601-0073-7 IS-2601-0087-7 IS-2601-0106-5

#### 1.2. Recommended use and restrictions on use

### Recommended use

Automotive., Cleaning Carburettor of Automobile

### 1.3. Supplier's details

Address: 3M India Limited, plot-48-51, Electronic city, Hosur road, Bangalore-560100

**Telephone:** 080-45543000, contact Product EHS team

E Mail: productehs.in@mmm.com
Website: http://solutions.3mindia.co.in

#### 1.4. Emergency telephone number

080-45543000 (Contact hours: 8:00 AM to 5:00 PM)

### **SECTION 2: Hazard identification**

Under MSIHC Rules, information is noted below on flammability, acute toxicity and explosivity relevant to this product. In line with international standards, information on other hazard classes and associated precautionary statements relevant to this product are included as well.

### 2.1. Classification of the substance or mixture

Flammable Aerosol: Category 1.
Acute Toxicity (oral): Category 4.
Acute Toxicity (dermal): Category 5.
Acute Toxicity (inhalation): Category 5.
Skin Corrosion/Irritation: Category 2.
Serious Eye Damage/Irritation: Category 2A

Reproductive Toxicity: Category 1B.

Specific Target Organ Toxicity (single exposure): Category 1.

### 3M Choke and Carb Cleaner

Specific Target Organ Toxicity (repeated exposure): Category 1. Specific Target Organ Toxicity (single exposure): Category 3.

Acute Aquatic Toxicity: Category 2. Chronic Aquatic Toxicity: Category 3.

### 2.2. Label elements

## Signal Word

Danger

### **Symbols**

Flame | Exclamation mark | Health Hazard |

### **Pictograms**







### **HAZARD STATEMENTS:**

H222 Extremely flammable aerosol.

H229 Pressurised container. may burst if heated.

Harmful if swallowed. H302

May be harmful in contact with skin. H313

Causes skin irritation. H315 Causes serious eye irritation. H319 May be harmful if inhaled. H333

May damage fertility or the unborn child. H360 May cause drowsiness or dizziness. H336

Causes damage to organs: cardiovascular system | sensory organs. H370

H372 Causes damage to organs through prolonged or repeated exposure: nervous system

sensory organs.

H401 Toxic to aquatic life.

Harmful to aquatic life with long lasting effects. H412

### PRECAUTIONARY STATEMENTS

General:

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

**Prevention:** 

P201 Obtain special instructions before use.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

Do not breathe dust/fume/gas/mist/vapours/spray. P260 Use only outdoors or in a well-ventilated area. P271

Wear protective gloves. P280E

**Response:** 

P302 + P352IF ON SKIN: Wash with plenty of soap and water.

P305 + P351 + P338IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

Page: 2 of 17

### 3M Choke and Carb Cleaner

lenses, if present and easy to do. Continue rinsing.

P308 + P311 IF exposed or concerned: Call a POISON CENTER or doctor/physician.

P332 + P313 If skin irritation occurs: Get medical advice/attention.

**Storage:** 

P405 Store locked up.

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50C/122F.

Disposal:

P501 Dispose of contents/container in accordance with applicable

local/regional/national/international regulations.

#### 2.3. Other hazards

Intentional misuse by deliberately concentrating and inhaling contents can be harmful or fatal.

# **SECTION 3: Composition/information on ingredients**

This material is a mixture.

Ingredient	CAS Nbr	% by Wt
Toluene	108-88-3	30 - 60
4-Hydroxy-4-methylpentan-2-one	123-42-2	10 - 30
Hydrocarbons, C3-4-rich, petroleum distillates (Propellant)	68512-91-4	10 - 30
Methanol	67-56-1	10 - 30
Xylene	1330-20-7	10 - 30

# **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

### Inhalation

Remove person to fresh air. Get medical attention.

#### Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

#### Eve contact

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

### If swallowed

Rinse mouth. If you feel unwell, get medical attention.

# 4.2. Most important symptoms and effects, both acute and delayed

No critical symptoms or effects. See Section 11.1, information on toxicological effects.

### 4.3. Indication of any immediate medical attention and special treatment required

his product contains methanol. If there is a reasonable suspicion of methanol poisoning, intravenous (IV) administration with either fomepizole (preferred) or ethanol (if fomepizole is unavailable) should be considered as part of the medical management. Exposure may increase myocardial irritability. Do not administer sympathomimetic drugs unless absolutely necessary.

# **SECTION 5: Fire-fighting measures**

### 5.1. Suitable Extinguishing media

Use a fire fighting agent suitable for the surrounding fire.

### 5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

### **Hazardous Decomposition or By-Products**

<u>Substance</u> Carbon monoxide. Carbon dioxide.

### Condition

During combustion.

During combustion.

# 5.3. Special protective actions for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture.

# **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

### 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

If possible, seal leaking container. Place leaking containers in a well-ventilated area, preferably an operating exhaust hood, or if necessary outdoors on an impermeable surface until appropriate packaging for the leaking container or its contents is available. Contain spill. Cover spill area with a fire-extinguishing foam. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

# **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

Do not use in a confined area with minimal air exchange. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (eg. gloves, respirators...) as required.

### 7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Protect from sunlight. Do not expose to temperatures exceeding 50C/122F. Store away from heat. Store away from acids. Store away from strong bases. Store away from oxidising agents.

# **SECTION 8: Exposure controls/personal protection**

### 8.1 Control parameters

### Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
Toluene	108-88-3	ACGIH	TWA:20 ppm	A4: Not class. as human carcin, Ototoxicant
4-Hydroxy-4-methylpentan-2-one	123-42-2	ACGIH	TWA:50 ppm	
Xylene	1330-20-7	ACGIH	TWA:100 ppm;STEL:150 ppm	A4: Not class. as human carcin
Methanol	67-56-1	ACGIH	TWA:200 ppm;STEL:250 ppm	Danger of cutaneous absorption

ACGIH: American Conference of Governmental Industrial Hygienists

AIHA: American Industrial Hygiene Association

CMRG: Chemical Manufacturer's Recommended Guidelines

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

### 8.2. Exposure controls

### 8.2.1. Engineering controls

Do not remain in area where available oxygen may be reduced. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

### 8.2.2. Personal protective equipment (PPE)

### **Eve/face protection**

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect vented goggles.

#### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Fluoroelastomer

Polymer laminate

### Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours

Half facepiece or full facepiece supplied-air respirator

For questions about suitability for a specific application, consult with your respirator manufacturer.

# **SECTION 9: Physical and chemical properties**

Page: 5 of 17

# 9.1. Information on basic physical and chemical properties

Physical state	Liquid.
Specific Physical Form:	Aerosol
Color	Straw
Odor	Solvent
Odour threshold	No data available.
pH	No data available.
Melting point/Freezing point: NA	No data available.
Boiling point/Initial boiling point/Boiling range	No data available.
Flash point	-50 °C
Evaporation rate	No data available.
Flammability (solid, gas)	Not applicable.
Flammable Limits(LEL)	No data available.
Flammable Limits(UEL)	No data available.
Vapour pressure	No data available.
Vapor Density and/or Relative Vapor Density	No data available.
Density	0.83 - 0.86 g/cm3
Relative density	0.83 - 0.86 [ <i>Ref Std</i> :WATER=1]
Water solubility	Nil
Solubility- non-water	No data available.
Partition coefficient: n-octanol/water	No data available.
Autoignition temperature	No data available.
Decomposition temperature	No data available.
Viscosity/Kinematic Viscosity	No data available.
Volatile organic compounds (VOC)	No data available.
Percent volatile	No data available.
VOC less H2O & exempt solvents	No data available.

### **Nanoparticles**

This material does not contain nanoparticles.

# **SECTION 10: Stability and reactivity**

### **10.1 Reactivity**

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

# 10.2 Chemical stability

Stable.

# 10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

# 10.4 Conditions to avoid

Heat.

High shear and high temperature conditions Sparks and/or flames.

# 10.5 Incompatible materials

Reducing agents.

Strong acids.

Strong bases.

Strong oxidising agents.

Page: 6 of 17

# 10.6 Hazardous decomposition products **Substance**

Condition

Formaldehyde

Not specified.

Refer to section 5.2 for hazardous decomposition products during combustion.

# **SECTION 11: Toxicological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

### 11.1 Information on Toxicological effects

#### Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### Inhalation

May be harmful if inhaled. Simple asphyxiation: Signs/symptoms may include increased heart rate, rapid respirations, drowsiness, headache, incoordination, altered judgement, nausea, vomiting, lethargy, seizures, coma, and may be fatal. Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

#### Skin contact

May be harmful in contact with skin.

Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain. May cause additional health effects (see below).

### **Eve contact**

Severe eye irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

### Ingestion

Harmful if swallowed.

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea. May cause additional health effects (see below).

### **Additional Health Effects:**

### Single exposure may cause target organ effects:

Auditory effects: Signs/symptoms may include hearing impairment, balance dysfunction and ringing in the ears. Central nervous system (CNS) depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness. May cause blindness. Single exposure, above recommended guidelines, may cause: Cardiac Sensitization: Signs/symptoms may include irregular heartbeat (arrhythmia), faintness, chest pain, and may be fatal.

### Prolonged or repeated exposure may cause target organ effects:

Ocular effects: Signs/symptoms may include blurred or significantly impaired vision. Auditory effects: Signs/symptoms may include hearing impairment, balance dysfunction and ringing in the ears. Olfactory effects: Signs/symptoms may include decreased ability to detect odours and complete loss of smell. Neurological effects: Signs/symptoms may include personality changes, lack of coordination, sensory loss, tingling or numbness of the extremities, weakness, tremors, and

changes in blood pressure and heart rate.

# Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

# **Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

**Acute Toxicity** 

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >2,000 - ≤5,000
			mg/kg
Overall product	Inhalation-		No data available; calculated ATE >20 - ≤50 mg/l
	Vapor(4 hr)		
Overall product	Ingestion		No data available; calculated ATE >300 - ≤2,000
			mg/kg
Toluene	Dermal	Rat	LD50 12,000 mg/kg
Toluene	Inhalation-	Rat	LC50 30 mg/l
	Vapor (4		
	hours)		
Toluene	Ingestion	Rat	LD50 5,550 mg/kg
Hydrocarbons, C3-4-rich, petroleum distillates (Propellant)	Inhalation-	Rat	LC50 > 200,000 ppm
	Gas (4		
	hours)		
Methanol	Dermal		LD50 estimated to be 1,000 - 2,000 mg/kg
Methanol	Inhalation-		LC50 estimated to be 10 - 20 mg/l
	Vapor		
Methanol	Ingestion		LD50 estimated to be 50 - 300 mg/kg
Xylene	Dermal	Rabbit	LD50 > 4,200 mg/kg
Xylene	Inhalation-	Rat	LC50 29 mg/l
	Vapor (4		
	hours)		
Xylene	Ingestion	Rat	LD50 3,523 mg/kg
4-Hydroxy-4-methylpentan-2-one	Dermal	Rabbit	LD50 13,645 mg/kg
4-Hydroxy-4-methylpentan-2-one	Inhalation-	Rat	LC50 > 7.6 mg/l
	Vapor (4		
	hours)		
4-Hydroxy-4-methylpentan-2-one	Ingestion	Rat	LD50 3,002 mg/kg

ATE = acute toxicity estimate

### Skin Corrosion/Irritation

Name	Species	Value
Toluene	Rabbit	Irritant
Hydrocarbons, C3-4-rich, petroleum distillates (Propellant)	Rabbit	Minimal irritation
Methanol	Rabbit	Mild irritant
Xylene	Rabbit	Mild irritant
4-Hydroxy-4-methylpentan-2-one	Rabbit	No significant irritation

**Serious Eye Damage/Irritation** 

Name	Species	Value
Toluene	Rabbit	Moderate irritant
Hydrocarbons, C3-4-rich, petroleum distillates (Propellant)	Rabbit	Mild irritant
Methanol	Rabbit	Moderate irritant
Xylene	Rabbit	Mild irritant
4-Hydroxy-4-methylpentan-2-one	Rabbit	Severe irritant

### **Sensitization:**

# **Skin Sensitisation**

Name	Species	Value
Toluene	Guinea	Not classified
	pig	
Methanol	Guinea	Not classified
	pig	
4-Hydroxy-4-methylpentan-2-one	Guinea	Not classified
	pig	

# **Respiratory Sensitisation**

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Toluene Toluene	In Vitro In vivo	Not mutagenic Not mutagenic
Hydrocarbons, C3-4-rich, petroleum distillates (Propellant)	In Vitro	Not mutagenic
Methanol	In Vitro	Some positive data exist, but the data are not sufficient for classification
Methanol	In vivo	Some positive data exist, but the data are not sufficient for classification
Xylene	In Vitro	Not mutagenic
Xylene	In vivo	Not mutagenic
4-Hydroxy-4-methylpentan-2-one	In Vitro	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

Name	Route	Species	Value
Toluene	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Toluene	Ingestion	Rat	Some positive data exist, but the data are not sufficient for classification
Toluene	Inhalation	Mouse	Some positive data exist, but the data are not sufficient for classification
Methanol	Inhalation	Multiple animal species	Not carcinogenic
Xylene	Dermal	Rat	Not carcinogenic
Xylene	Ingestion	Multiple animal species	Not carcinogenic
Xylene	Inhalation	Human	Some positive data exist, but the data are not sufficient for classification

# **Reproductive Toxicity**

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
Toluene	Inhalation	Not classified for female reproduction	Human	NOAEL Not available	occupational exposure
Toluene	Inhalation	Not classified for male reproduction	Rat	NOAEL 2.3 mg/l	1 generation
Toluene	Ingestion	Toxic to development	Rat	LOAEL 520 mg/kg/day	during gestation
Toluene	Inhalation	Toxic to development	Human	NOAEL Not available	poisoning and/or abuse
Methanol	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,600 mg/kg/day	21 days
Methanol	Ingestion	Toxic to development	Mouse	LOAEL 4,000 mg/kg/day	during organogenesis

Page: 9 of 17

Methanol	Inhalation	Toxic to development	Mouse	NOAEL 1.3	during
				mg/l	organogenesis
Xylene	Inhalation	Not classified for female reproduction	Human	NOAEL Not	occupational
				available	exposure
Xylene	Ingestion	Not classified for development	Mouse	NOAEL Not	during
				available	organogenesis
Xylene	Inhalation	Not classified for development	Multiple	NOAEL Not	during
			animal	available	gestation
			species		
4-Hydroxy-4-methylpentan-2-one	Ingestion	Not classified for female reproduction	Rat	NOAEL 300	premating
	_	_		mg/kg/day	into lactation
4-Hydroxy-4-methylpentan-2-one	Ingestion	Not classified for male reproduction	Rat	NOAEL 300	44 days
	_	-		mg/kg/day	
4-Hydroxy-4-methylpentan-2-one	Ingestion	Toxic to development	Rabbit	NOAEL 100	during
		_		mg/kg/day	gestation

# Lactation

Name	Route	Species	Value
Xylene	Ingestion	Mouse	Not classified for effects on or via lactation

# Target Organ(s)

**Specific Target Organ Toxicity - single exposure** 

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Toluene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Toluene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Toluene	Inhalation	immune system	Not classified	Mouse	NOAEL 0.004 mg/l	3 hours
Toluene	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse
Hydrocarbons, C3-4-rich, petroleum distillates (Propellant)	Inhalation	cardiac sensitization	Causes damage to organs	Human	NOAEL Not available	
Hydrocarbons, C3-4-rich, petroleum distillates (Propellant)	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Hydrocarbons, C3-4-rich, petroleum distillates (Propellant)	Inhalation	respiratory irritation	Not classified	Human	NOAEL Not available	
Methanol	Inhalation	blindness	Causes damage to organs	Human	NOAEL Not available	occupational exposure
Methanol	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	not available
Methanol	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL Not available	6 hours
Methanol	Ingestion	blindness	Causes damage to organs	Human	NOAEL Not available	poisoning and/or abuse
Methanol	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse
Xylene	Inhalation	auditory system	Causes damage to organs	Rat	LOAEL 6.3 mg/l	8 hours
Xylene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Xylene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Xylene	Inhalation	eyes	Not classified	Rat	NOAEL 3.5 mg/l	not available
Xylene	Inhalation	liver	Not classified	Multiple animal	NOAEL Not available	

				species		
Xylene	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Multiple animal species	NOAEL Not available	
Xylene	Ingestion	eyes	Not classified	Rat	NOAEL 250 mg/kg	not applicable
4-Hydroxy-4- methylpentan-2-one	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Multiple animal species	NOAEL Not available	
4-Hydroxy-4- methylpentan-2-one	Inhalation	respiratory irritation	May cause respiratory irritation	Human	NOAEL Not available	
4-Hydroxy-4- methylpentan-2-one	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
4-Hydroxy-4- methylpentan-2-one	Ingestion	blood	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 1,882 mg/kg	
4-Hydroxy-4- methylpentan-2-one	Ingestion	liver	Not classified	Rat	NOAEL 1,882 mg/kg	not applicable

**Specific Target Organ Toxicity - repeated exposure** 

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Toluene	Inhalation	auditory system   eyes   olfactory system	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	poisoning and/or abuse
Toluene	Inhalation	nervous system	May cause damage to organs though prolonged or repeated exposure	Human	NOAEL Not available	poisoning and/or abuse
Toluene	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 2.3 mg/l	15 months
Toluene	Inhalation	heart   liver   kidney and/or bladder	Not classified	Rat	NOAEL 11.3 mg/l	15 weeks
Toluene	Inhalation	endocrine system	Not classified	Rat	NOAEL 1.1 mg/l	4 weeks
Toluene	Inhalation	immune system	Not classified	Mouse	NOAEL Not available	20 days
Toluene	Inhalation	bone, teeth, nails, and/or hair	Not classified	Mouse	NOAEL 1.1 mg/l	8 weeks
Toluene	Inhalation	hematopoietic system   vascular system	Not classified	Human	NOAEL Not available	occupational exposure
Toluene	Inhalation	gastrointestinal tract	Not classified	Multiple animal species	NOAEL 11.3 mg/l	15 weeks
Toluene	Ingestion	nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 625 mg/kg/day	13 weeks
Toluene	Ingestion	heart	Not classified	Rat	NOAEL 2,500 mg/kg/day	13 weeks
Toluene	Ingestion	liver   kidney and/or bladder	Not classified	Multiple animal species	NOAEL 2,500 mg/kg/day	13 weeks
Toluene	Ingestion	hematopoietic system	Not classified	Mouse	NOAEL 600 mg/kg/day	14 days
Toluene	Ingestion	endocrine system	Not classified	Mouse	NOAEL 105 mg/kg/day	28 days
Toluene	Ingestion	immune system	Not classified	Mouse	NOAEL 105 mg/kg/day	4 weeks
Methanol	Inhalation	liver	Not classified	Rat	NOAEL 6.55 mg/l	4 weeks
Methanol	Inhalation	respiratory system	Not classified	Rat	NOAEL 13.1 mg/l	6 weeks
Methanol	Ingestion	liver   nervous system	Not classified	Rat	NOAEL 2,500	90 days

					mg/kg/day	
Xylene	Inhalation	nervous system	Causes damage to organs through prolonged or repeated exposure	Rat	LOAEL 0.4 mg/l	4 weeks
Xylene	Inhalation	auditory system	May cause damage to organs though prolonged or repeated exposure	Rat	LOAEL 7.8 mg/l	5 days
Xylene	Inhalation	liver	Not classified	Multiple animal species	NOAEL Not available	
Xylene	Inhalation	heart   endocrine system   gastrointestinal tract   hematopoietic system   muscles   kidney and/or bladder   respiratory system	Not classified	Multiple animal species	NOAEL 3.5 mg/l	13 weeks
Xylene	Ingestion	auditory system	Not classified	Rat	NOAEL 900 mg/kg/day	2 weeks
Xylene	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 1,500 mg/kg/day	90 days
Xylene	Ingestion	liver	Not classified	Multiple animal species	NOAEL Not available	
Xylene	Ingestion	heart   skin   endocrine system   bone, teeth, nails, and/or hair   hematopoietic system   immune system   nervous system   respiratory system	Not classified	Mouse	NOAEL 1,000 mg/kg/day	103 weeks
4-Hydroxy-4- methylpentan-2-one	Inhalation	liver   kidney and/or bladder	Not classified	Rat	NOAEL 4.5 mg/l	6 weeks
4-Hydroxy-4- methylpentan-2-one	Ingestion	endocrine system   liver   kidney and/or bladder   hematopoietic system   nervous system   eyes	Not classified	Rat	NOAEL 600 mg/kg/day	13 weeks

**Aspiration Hazard** 

Name	Value
Toluene	Aspiration hazard
Xylene	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

# **SECTION 12: Ecological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labelling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

# 12.1. Toxicity

## Acute aquatic hazard:

GHS Acute 2: Toxic to aquatic life.

# Chronic aquatic hazard:

GHS Chronic 3: Harmful to aquatic life with long lasting effects.

No product test data available.

Material	CAS Nbr	Organism	Туре	Exposure	Test endpoint	Test result
Toluene	108-88-3	Coho Salmon	Experimental	96 hours	LC50	5.5 mg/l
Toluene	108-88-3	Grass Shrimp	Experimental	96 hours	LC50	9.5 mg/l
Toluene	108-88-3	Green Algae	Experimental	72 hours	EC50	12.5 mg/l
Toluene	108-88-3	Leopard frog	Experimental	9 days	LC50	0.39 mg/l
Toluene	108-88-3	Pink Salmon	Experimental	96 hours	LC50	6.41 mg/l
Toluene	108-88-3	Water flea	Experimental	48 hours	EC50	3.78 mg/l
Toluene	108-88-3	Coho Salmon	Experimental	40 days	NOEC	1.39 mg/l
Toluene	108-88-3	Diatom	Experimental	72 hours	NOEC	10 mg/l
Toluene	108-88-3	Water flea	Experimental	7 days	NOEC	0.74 mg/l
Toluene	108-88-3	Activated sludge	Experimental	12 hours	IC50	292 mg/l
Toluene	108-88-3	Bacteria	Experimental	16 hours	NOEC	29 mg/l
Toluene	108-88-3	Bacteria	Experimental	24 hours	EC50	84 mg/l
Toluene	108-88-3	Redworm	Experimental	28 days	LC50	>150 mg per kg of bodyweight
Toluene	108-88-3	Soil microbes	Experimental	28 days	NOEC	<26 mg/kg (Dry Weight)
4-Hydroxy-4- methylpentan- 2-one	123-42-2	Activated sludge	Experimental	3 hours	EC50	>1,000 mg/l
4-Hydroxy-4- methylpentan- 2-one	123-42-2	Bacteria	Experimental	16 hours	NOEC	825 mg/l
4-Hydroxy-4- methylpentan- 2-one	123-42-2	Green algae	Experimental	72 hours	EC50	>1,000 mg/l
4-Hydroxy-4- methylpentan- 2-one	123-42-2	Inland Silverside	Experimental	96 hours	LC50	420 mg/l
4-Hydroxy-4- methylpentan- 2-one	123-42-2	Medaka	Experimental	96 hours	LC50	>100 mg/l
4-Hydroxy-4- methylpentan- 2-one	123-42-2	Water flea	Experimental	48 hours	EC50	>1,000 mg/l
4-Hydroxy-4- methylpentan- 2-one	123-42-2	Green algae	Experimental	72 hours	NOEC	1,000 mg/l
4-Hydroxy-4- methylpentan- 2-one	123-42-2	Water flea	Experimental	21 days	NOEC	100 mg/l
Hydrocarbons, C3-4-rich, petroleum distillates (Propellant)	68512-91-4		Data not available or insufficient for classification			N/A
Methanol	67-56-1	Activated	Experimental	3 hours	IC50	>1,000 mg/l

		sludge				
Methanol	67-56-1	Algae or other aquatic plants	Experimental	96 hours	EC50	16.9 mg/l
Methanol	67-56-1	Bluegill	Experimental	96 hours	LC50	15,400 mg/l
Methanol	67-56-1	Green Algae	Experimental	96 hours	EC50	22,000 mg/l
Methanol	67-56-1	Water flea	Experimental	24 hours	EC50	20,803 mg/l
Methanol	67-56-1	Algae or other aquatic plants	Experimental	96 hours	NOEC	9.96 mg/l
Methanol	67-56-1	Water flea	Experimental	21 days	NOEC	122 mg/l
Xylene	1330-20-7	Activated sludge	Estimated	3 hours	NOEC	157 mg/l
Xylene	1330-20-7	Green Algae	Estimated	72 hours	EC50	4.36 mg/l
Xylene	1330-20-7	Rainbow trout	Estimated	96 hours	LC50	2.6 mg/l
Xylene	1330-20-7	Water flea	Estimated	48 hours	EC50	3.82 mg/l
Xylene	1330-20-7	Green Algae	Estimated	72 hours	NOEC	0.44 mg/l
Xylene	1330-20-7	Water flea	Estimated	7 days	NOEC	0.96 mg/l
Xylene	1330-20-7	Rainbow trout	Experimental	56 days	NOEC	>1.3 mg/l

# 12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Toluene	108-88-3	Experimental		Photolytic half-	5.2 days (t 1/2)	
		Photolysis		life (in air)		
Toluene	108-88-3	Experimental	20 days	BOD	80 %	APHA Std Meth
		Biodegradation			BOD/ThOD	Water/Wastewater
4-Hydroxy-4-	123-42-2	Experimental	28 days	Dissolv.	98.5 %removal	
methylpentan-		Biodegradation		Organic	of DOC	
2-one				Carbon Deplet		
Hydrocarbons,	68512-91-4	Data not	N/A	N/A	N/A	N/A
C3-4-rich,		available-				
petroleum		insufficient				
distillates						
(Propellant)						
Methanol	67-56-1	Experimental	14 days	BOD	92 %	OECD 301C - MITI
		Biodegradation			BOD/ThOD	test (I)
Xylene	1330-20-7	Experimental		Photolytic half-	1.4 days (t 1/2)	
		Photolysis		life (in air)		
Xylene	1330-20-7	Experimental	28 days	BOD	90-98 %	OECD 301F -
		Biodegradation			BOD/ThOD	Manometric
						respirometry

# 12.3 : Bioaccumulative potential

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Toluene	108-88-3	Experimental	72 hours	Bioaccumulatio	90	
		BCF - Other		n factor		
Toluene	108-88-3	Experimental Bioconcentrati		Log Kow	2.73	
		on				
4-Hydroxy-4-	123-42-2	Experimental		Log Kow	-0.14	Non-standard method
methylpentan-		Bioconcentrati				
2-one		on				
Hydrocarbons,	68512-91-4	Data not	N/A	N/A	N/A	N/A
C3-4-rich,		available or				

petroleum distillates (Propellant)		insufficient for classification				
Methanol	67-56-1	Experimental Bioconcentrati on		Log Kow	-0.77	Non-standard method
Xylene	1330-20-7	Experimental BCF - Rainbow Trout	_	Bioaccumulatio n factor	25.9	

### 12.4. Mobility in soil

Please contact manufacturer for more details

#### 12.5 Other Adverse effects

No information available.

# **SECTION 13: Disposal considerations**

### 13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. Facility must be capable of handling aerosol cans. As a disposal alternative, utilize an acceptable permitted waste disposal facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

# **SECTION 14: Transport Information**

### Air Transport (IATA)Regulations

UN No UN1950

Proper Shipping Name AEROSOLS, FLAMMABLE (Contains Propellant)

Hazard Classs/Division 2.1 Subsidiary Risk Not applicable Packing Group: Not applicable

Marine Transport (IMDG)

UN No UN1950

Proper Shipping Name AEROSOLS, FLAMMABLE (Contains Propellant)

Hazard Classs/Division 2.1
Subsidiary Risk Not applicable
Packing Group: Not applicable

Environmental Hazards: Not applicable

# **SECTION 15: Regulatory information**

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

### Global inventory status

Contact 3M for more information.

### Applicable Environmental, Health and Safety Regulations

The Manufacture, Storage and Import of Hazardous Chemical Rules, 1989

Hazardous Waste(Management, Handling & Transboundary) Rules, 2008 Hazardous Chemicals (Classification, Packaging and Labelling Draft Rules), 2011 Central Motor Vehicle Rules, 1989

The following ingredients are listed as hazardous on Part II of Schedule I of the India Manufacture, Storage and Import of Hazardous Chemicals (MSIHC) rules

Methanol

Toluene

The following ingredients are classified as hazardous based on the criteria listed under Part I of Schedule I of the India Manufacture, Storage and Import of Hazardous Chemicals (MSIHC) rules:

The product is classified as Extremely Flammable (Aerosol).

# **SECTION 16: Other information**

### NFPA Hazard Classification

Health: 2 Flammability: 4 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

#### **Revision information:**

Section 1: Product identification numbers information was modified.

Label: GHS Classification information was modified.

Label: GHS Precautionary - General information was modified.

Label: GHS Precautionary - Prevention information was modified.

Label: GHS Precautionary - Response information was modified.

Label: GHS Precautionary - Storage information was modified.

Label: GHS Target Organ Hazard Statement information was modified.

Label: Signal Word information was modified.

Label: Symbol information was modified.

Section 04: Information on toxicological effects information was deleted.

Section 8: Occupational exposure limit table information was modified.

Section 09: Percent Volatile information was modified.

Section 09: VOC Less H2O & Exempt Solvents information was modified.

Section 09: Volatile Organic Compounds information was modified.

Section 11: Acute Toxicity table information was modified.

Section 11: Germ Cell Mutagenicity Table information was modified.

Section 11: Serious Eye Damage/Irritation Table information was modified.

Section 11: Single exposure may cause standard phrases information was modified.

Section 11: Skin Corrosion/Irritation Table information was modified.

Section 11: Target Organs - Single Table information was modified.

Section 12: Component ecotoxicity information information was modified.

Section 12: Persistence and Degradability information information was modified.

Section 12:Bioccumulative potential information information was modified.

Section 15: MSIHC Part I of Schedule I ingredients information was modified.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

3M Choke and Carb Cleaner	
BM India SDSs are available at http://solutions.3mindia.co.in	