



Safety Data Sheet

Copyright,2020, 3M India Limited.All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	10-9671-8	Version number:	1.00
Issue Date:	12/01/2020	Supersedes date:	Initial issue.

This Safety Data Sheet has been prepared in accordance with the GHS guidelines & India Hazardous substances (Classification, Labeling & Packaging) Draft Rules 2011.

SECTION 1: Identification

1.1. Product identifier

3M Scotch-Weld 2290 Epoxy Adhesive, Amber

Product Identification Numbers

62-3847-7530-0

1.2. Recommended use and restrictions on use

Recommended use

Industrial use.

1.3. Supplier's details

Address: 3M India Limited, plot-48-51, Electronic city, Hosur road, Bangalore-560100
Telephone: 080-45543000, contact Product EHS team
E Mail: productehs.in@mmm.com
Website: <http://solutions.3mindia.co.in>

1.4. Emergency telephone number

080-45543000 (Contact hours: 8:00 AM to 5:00 PM)

SECTION 2: Hazard identification

Under MSIHC Rules, information is noted below on flammability, acute toxicity and explosivity relevant to this product. In line with international standards, information on other hazard classes and associated precautionary statements relevant to this product are included as well.

2.1. Classification of the substance or mixture

Flammable Liquid: Category 2.
Acute Toxicity (oral): Category 5.
Serious Eye Damage/Irritation: Category 1.
Skin Corrosion/Irritation: Category 3.
Skin Sensitizer: Category 1.
Reproductive Toxicity: Category 1B.
Carcinogenicity: Category 2.
Germ Cell Mutagenicity: Category 2.
Specific Target Organ Toxicity (single exposure): Category 3.

Acute Aquatic Toxicity: Category 2.
Chronic Aquatic Toxicity: Category 3.

2.2. Label elements

Signal Word

DANGER!

Symbols

Flame | Corrosion | Exclamation mark | Health Hazard |

Pictograms



HAZARD STATEMENTS:

H225	Highly flammable liquid and vapour.
H303	May be harmful if swallowed.
H318	Causes serious eye damage.
H316	Causes mild skin irritation.
H317	May cause an allergic skin reaction.
H336	May cause drowsiness or dizziness.
H360	May damage fertility or the unborn child.
H351	Suspected of causing cancer.
H341	Suspected of causing genetic defects.
H401	Toxic to aquatic life.
H412	Harmful to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENTS

Prevention:

P201	Obtain special instructions before use.
P210A	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P280B	Wear protective gloves and eye/face protection.

Response:

P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER or doctor/physician.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
P370 + P378G	In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

Disposal:

P501	Dispose of contents/container in accordance with applicable local/regional/national/international regulations.
------	--

2.3. Other hazards

None known.

SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	CAS Nbr	% by Wt
methyl ethyl ketone	78-93-3	55 - 65
phenoxy resin	25068-38-6	10 - 20
tetrahydrofuran	109-99-9	10 - 20
phenoxy resin	5026-74-4	1 - 10
1-methyl-2-pyrrolidinone	872-50-4	1 - 5
dicyandiamide	461-58-5	< 1
Toluene	108-88-3	< 0.2

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye contact

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1 Information on toxicological effects

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable Extinguishing media

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products

Substance

Aldehydes.
Hydrocarbons.
Carbon monoxide.
Carbon dioxide.
Hydrogen Chloride
Hydrogen cyanide.
Ketones.

Condition

During combustion.
During combustion.
During combustion.
During combustion.
During combustion.
During combustion.
During combustion.

Oxides of nitrogen.

During combustion.

5.3. Special protective actions for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Cover spill area with a fire-extinguishing foam. An appropriate aqueous film forming foam (AFFF) is recommended. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

For industrial/occupational use only. Not for consumer sale or use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.) Wear low static or properly grounded shoes. Use personal protective equipment (eg. gloves, respirators...) as required. To minimize the risk of ignition, determine applicable electrical classifications for the process using this product and select specific local exhaust ventilation equipment to avoid flammable vapor accumulation. Ground/bond container and receiving equipment if there is potential for static electricity accumulation during transfer.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store away from heat. Store away from acids. Store away from oxidising agents.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

3M Scotch-Weld 2290 Epoxy Adhesive, Amber

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
Toluene	108-88-3	ACGIH	TWA:20 ppm	A4: Not class. as human carcin
tetrahydrofuran	109-99-9	ACGIH	TWA:50 ppm;STEL:100 ppm	A3: Confirmed animal carcin., SKIN
methyl ethyl ketone	78-93-3	ACGIH	TWA:200 ppm;STEL:300 ppm	
1-methyl-2-pyrrolidinone	872-50-4	AIHA	TWA:40 mg/m ³ (10 ppm)	SKIN

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment. Use explosion-proof ventilation equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Full face shield.

Indirect vented goggles.

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid.
Color	Clear Yellow
Odor	Ketones.
Odour threshold	<i>No data available.</i>
pH	<i>No data available.</i>
Melting point/Freezing point: NA	<i>No data available.</i>
Boiling point/Initial boiling point/Boiling range	66.1 °C [<i>Details:Conditions: THF</i>]
Flash point	-14.4 °C [<i>Test Method:Tagliabue closed cup</i>]
Evaporation rate	>=2 [<i>Ref Std:ETHER=1</i>]
Flammability (solid, gas)	Not applicable.
Flammable Limits(LEL)	2 % volume
Flammable Limits(UEL)	11.8 % volume
Vapour pressure	19,331.7 Pa [<i>Details:CONDITIONS: @ 68F</i>]
Vapour density	2.5 [<i>Ref Std:AIR=1</i>]
Density	0.89 g/ml
Relative density	0.89 [<i>Ref Std:WATER=1</i>]
Water solubility	Slight (less than 10%)
Solubility- non-water	<i>No data available.</i>
Partition coefficient: n-octanol/water	<i>No data available.</i>
Autoignition temperature	<i>No data available.</i>
Decomposition temperature	<i>No data available.</i>
Viscosity	45 - 90 mPa-s
Molecular weight	<i>No data available.</i>
VOC less H2O & exempt solvents	701 g/l [<i>Test Method:calculated SCAQMD rule 443.1</i>]
VOC less H2O & exempt solvents	78.8 % [<i>Test Method:calculated per CARB title 2</i>]

SECTION 10: Stability and reactivity**10.1 Reactivity**

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

Heat.

Sparks and/or flames.

10.5 Incompatible materials

Strong oxidising agents.

10.6 Hazardous decomposition products**Substance**

None known.

Condition

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1 Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

Skin contact

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching. May cause additional health effects (see below).

Eye contact

Corrosive (eye burns): Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision.

Ingestion

May be harmful if swallowed.

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea. May cause additional health effects (see below).

Additional Health Effects:

Single exposure may cause target organ effects:

Central nervous system (CNS) depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

Genotoxicity:

Genotoxicity and Mutagenicity: May interact with genetic material and possibly alter gene expression.

Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation-Vapor(4 hr)		No data available; calculated ATE >50 mg/l
Overall product	Ingestion		No data available; calculated ATE 2,000 - 5,000 mg/kg
methyl ethyl ketone	Dermal	Rabbit	LD50 > 8,050 mg/kg

3M Scotch-Weld 2290 Epoxy Adhesive, Amber

methyl ethyl ketone	Inhalation-Vapor (4 hours)	Rat	LC50 34.5 mg/l
methyl ethyl ketone	Ingestion	Rat	LD50 2,737 mg/kg
tetrahydrofuran	Dermal	Rat	LD50 > 2,000 mg/kg
tetrahydrofuran	Inhalation-Vapor (4 hours)	Rat	LC50 54 mg/l
tetrahydrofuran	Ingestion	Rat	LD50 3,180 mg/kg
phenoxy resin	Dermal	Rat	LD50 > 1,600 mg/kg
phenoxy resin	Ingestion	Rat	LD50 > 1,000 mg/kg
phenoxy resin	Dermal	Rabbit	LD50 > 4,000 mg/kg
phenoxy resin	Ingestion	Rat	LD50 500-5000 mg/kg
1-methyl-2-pyrrolidinone	Dermal	Rabbit	LD50 4,000 mg/kg
1-methyl-2-pyrrolidinone	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 5.1 mg/l
1-methyl-2-pyrrolidinone	Ingestion	Rat	LD50 4,320 mg/kg
dicyandiamide	Dermal	Rabbit	LD50 > 10,000 mg/kg
dicyandiamide	Ingestion	Rat	LD50 > 30,000 mg/kg
Toluene	Dermal	Rat	LD50 12,000 mg/kg
Toluene	Inhalation-Vapor (4 hours)	Rat	LC50 30 mg/l
Toluene	Ingestion	Rat	LD50 5,550 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
methyl ethyl ketone	Rabbit	Minimal irritation
tetrahydrofuran	Rabbit	Minimal irritation
phenoxy resin	Rabbit	Mild irritant
phenoxy resin	Rabbit	Irritant
1-methyl-2-pyrrolidinone	Rabbit	Minimal irritation
dicyandiamide	Human and animal	Minimal irritation
Toluene	Rabbit	Irritant

Serious Eye Damage/Irritation

Name	Species	Value
methyl ethyl ketone	Rabbit	Severe irritant
tetrahydrofuran	Rabbit	Corrosive
phenoxy resin	Rabbit	Moderate irritant
phenoxy resin	Rabbit	Severe irritant
1-methyl-2-pyrrolidinone	Rabbit	Severe irritant
dicyandiamide	Professional judgement	Mild irritant
Toluene	Rabbit	Moderate irritant

Skin Sensitisation

Name	Species	Value
tetrahydrofuran	Human and animal	Not classified
phenoxy resin	Human and animal	Sensitising
phenoxy resin	Guinea	Sensitising

3M Scotch-Weld 2290 Epoxy Adhesive, Amber

	pig	
1-methyl-2-pyrrolidinone	Human and animal	Not classified
dicyandiamide	Guinea pig	Not classified
Toluene	Guinea pig	Not classified

Respiratory Sensitisation

Name	Species	Value
phenoxy resin	Human	Not classified

Germ Cell Mutagenicity

Name	Route	Value
methyl ethyl ketone	In Vitro	Not mutagenic
tetrahydrofuran	In Vitro	Not mutagenic
tetrahydrofuran	In vivo	Not mutagenic
phenoxy resin	In vivo	Not mutagenic
phenoxy resin	In Vitro	Some positive data exist, but the data are not sufficient for classification
phenoxy resin	In Vitro	Some positive data exist, but the data are not sufficient for classification
phenoxy resin	In vivo	Mutagenic
1-methyl-2-pyrrolidinone	In vivo	Not mutagenic
1-methyl-2-pyrrolidinone	In Vitro	Some positive data exist, but the data are not sufficient for classification
dicyandiamide	In Vitro	Not mutagenic
Toluene	In Vitro	Not mutagenic
Toluene	In vivo	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
methyl ethyl ketone	Inhalation	Human	Not carcinogenic
tetrahydrofuran	Inhalation	Multiple animal species	Carcinogenic.
phenoxy resin	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
1-methyl-2-pyrrolidinone	Inhalation	Rat	Not carcinogenic
dicyandiamide	Ingestion	Rat	Not carcinogenic
Toluene	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Toluene	Ingestion	Rat	Some positive data exist, but the data are not sufficient for classification
Toluene	Inhalation	Mouse	Some positive data exist, but the data are not sufficient for classification

Reproductive Toxicity**Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test result	Exposure Duration
methyl ethyl ketone	Inhalation	Not classified for development	Rat	LOAEL 8.8 mg/l	during gestation
tetrahydrofuran	Ingestion	Not classified for female reproduction	Rat	NOAEL 782 mg/kg/day	2 generation
tetrahydrofuran	Ingestion	Not classified for male reproduction	Rat	NOAEL 782 mg/kg/day	2 generation
tetrahydrofuran	Ingestion	Not classified for development	Rat	NOAEL 305 mg/kg/day	2 generation
tetrahydrofuran	Inhalation	Not classified for development	Mouse	NOAEL 1.8	during

3M Scotch-Weld 2290 Epoxy Adhesive, Amber

				mg/l	gestation
phenoxy resin	Ingestion	Not classified for female reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
phenoxy resin	Ingestion	Not classified for male reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
phenoxy resin	Dermal	Not classified for development	Rabbit	NOAEL 300 mg/kg/day	during organogenesis
phenoxy resin	Ingestion	Not classified for development	Rat	NOAEL 750 mg/kg/day	2 generation
1-methyl-2-pyrrolidinone	Inhalation	Not classified for development	Rat	LOAEL 0.68 mg/l	during gestation
1-methyl-2-pyrrolidinone	Ingestion	Toxic to female reproduction	Rat	LOAEL 50 mg/kg/day	2 generation
1-methyl-2-pyrrolidinone	Ingestion	Toxic to male reproduction	Rat	LOAEL 50 mg/kg/day	2 generation
1-methyl-2-pyrrolidinone	Dermal	Toxic to development	Rat	NOAEL 237 mg/kg/day	during organogenesis
1-methyl-2-pyrrolidinone	Ingestion	Toxic to development	Rat	NOAEL 160 mg/kg/day	2 generation
dicyandiamide	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	prematuring & during gestation
dicyandiamide	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	44 days
dicyandiamide	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	prematuring & during gestation
Toluene	Inhalation	Not classified for female reproduction	Human	NOAEL Not available	occupational exposure
Toluene	Inhalation	Not classified for male reproduction	Rat	NOAEL 2.3 mg/l	1 generation
Toluene	Ingestion	Toxic to development	Rat	LOAEL 520 mg/kg/day	during gestation
Toluene	Inhalation	Toxic to development	Human	NOAEL Not available	poisoning and/or abuse

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
methyl ethyl ketone	Inhalation	central nervous system depression	May cause drowsiness or dizziness	official classification	NOAEL Not available	
methyl ethyl ketone	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
methyl ethyl ketone	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	
methyl ethyl ketone	Ingestion	liver	Not classified	Rat	NOAEL Not available	not applicable
methyl ethyl ketone	Ingestion	kidney and/or bladder	Not classified	Rat	LOAEL 1,080 mg/kg	not applicable
tetrahydrofuran	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
tetrahydrofuran	Inhalation	respiratory irritation	May cause respiratory irritation		NOAEL Not available	
tetrahydrofuran	Inhalation	respiratory system	Not classified	Rabbit	NOAEL 2.9 mg/l	4 hours
tetrahydrofuran	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Rat	NOAEL 180 mg/kg	not applicable
1-methyl-2-pyrrolidinone	Inhalation	respiratory irritation	Not classified	Human	NOAEL 0.05 mg/l	8 hours

3M Scotch-Weld 2290 Epoxy Adhesive, Amber

Toluene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Toluene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Toluene	Inhalation	immune system	Not classified	Mouse	NOAEL 0.004 mg/l	3 hours
Toluene	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
methyl ethyl ketone	Dermal	nervous system	Not classified	Guinea pig	NOAEL Not available	31 weeks
methyl ethyl ketone	Inhalation	liver kidney and/or bladder heart endocrine system gastrointestinal tract bone, teeth, nails, and/or hair hematopoietic system immune system muscles	Not classified	Rat	NOAEL 14.7 mg/l	90 days
methyl ethyl ketone	Ingestion	liver	Not classified	Rat	NOAEL Not available	7 days
methyl ethyl ketone	Ingestion	nervous system	Not classified	Rat	NOAEL 173 mg/kg/day	90 days
tetrahydrofuran	Inhalation	liver	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 0.6 mg/l	12 weeks
tetrahydrofuran	Inhalation	respiratory system	Not classified	Rat	NOAEL 2.9 mg/l	12 weeks
tetrahydrofuran	Inhalation	kidney and/or bladder	Not classified	Rat	NOAEL 0.6 mg/l	105 weeks
tetrahydrofuran	Ingestion	liver	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL Not available	2 weeks
phenoxy resin	Dermal	liver	Not classified	Rat	NOAEL 1,000 mg/kg/day	2 years
phenoxy resin	Dermal	nervous system	Not classified	Rat	NOAEL 1,000 mg/kg/day	13 weeks
phenoxy resin	Ingestion	auditory system heart endocrine system hematopoietic system liver eyes kidney and/or bladder	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
1-methyl-2-pyrrolidinone	Inhalation	bone marrow immune system respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 0.5 mg/l	4 weeks
1-methyl-2-pyrrolidinone	Ingestion	endocrine system	Not classified	Rat	NOAEL 250 mg/kg/day	90 days
1-methyl-2-pyrrolidinone	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 2,060 mg/kg/day	4 weeks
1-methyl-2-pyrrolidinone	Ingestion	nervous system	Not classified	Rat	NOAEL 1,057 mg/kg/day	90 days
1-methyl-2-pyrrolidinone	Ingestion	hematopoietic system	Not classified	Mouse	NOAEL 300 mg/kg/day	90 days
1-methyl-2-pyrrolidinone	Ingestion	liver	Not classified	Mouse	NOAEL 150 mg/kg/day	3 months
dicyandiamide	Ingestion	kidney and/or	Not classified	Rat	NOAEL	13 weeks

3M Scotch-Weld 2290 Epoxy Adhesive, Amber

		bladder			6,822 mg/kg/day	
Toluene	Inhalation	auditory system eyes olfactory system	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	poisoning and/or abuse
Toluene	Inhalation	nervous system	May cause damage to organs though prolonged or repeated exposure	Human	NOAEL Not available	poisoning and/or abuse
Toluene	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 2.3 mg/l	15 months
Toluene	Inhalation	heart liver kidney and/or bladder	Not classified	Rat	NOAEL 11.3 mg/l	15 weeks
Toluene	Inhalation	endocrine system	Not classified	Rat	NOAEL 1.1 mg/l	4 weeks
Toluene	Inhalation	immune system	Not classified	Mouse	NOAEL Not available	20 days
Toluene	Inhalation	bone, teeth, nails, and/or hair	Not classified	Mouse	NOAEL 1.1 mg/l	8 weeks
Toluene	Inhalation	hematopoietic system vascular system	Not classified	Human	NOAEL Not available	occupational exposure
Toluene	Inhalation	gastrointestinal tract	Not classified	Multiple animal species	NOAEL 11.3 mg/l	15 weeks
Toluene	Ingestion	nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 625 mg/kg/day	13 weeks
Toluene	Ingestion	heart	Not classified	Rat	NOAEL 2,500 mg/kg/day	13 weeks
Toluene	Ingestion	liver kidney and/or bladder	Not classified	Multiple animal species	NOAEL 2,500 mg/kg/day	13 weeks
Toluene	Ingestion	hematopoietic system	Not classified	Mouse	NOAEL 600 mg/kg/day	14 days
Toluene	Ingestion	endocrine system	Not classified	Mouse	NOAEL 105 mg/kg/day	28 days
Toluene	Ingestion	immune system	Not classified	Mouse	NOAEL 105 mg/kg/day	4 weeks

Aspiration Hazard

Name	Value
Toluene	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labelling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

12.1. Toxicity

Acute aquatic hazard:

GHS Acute 2: Toxic to aquatic life.

Chronic aquatic hazard:

GHS Chronic 3: Harmful to aquatic life with long lasting effects.

3M Scotch-Weld 2290 Epoxy Adhesive, Amber

No product test data available.

Material	CAS Nbr	Organism	Type	Exposure	Test endpoint	Test result
methyl ethyl ketone	78-93-3	Fathead minnow	Experimental	96 hours	LC50	2,993 mg/l
methyl ethyl ketone	78-93-3	Green algae	Experimental	96 hours	EC50	2,029 mg/l
methyl ethyl ketone	78-93-3	Water flea	Experimental	48 hours	EC50	308 mg/l
methyl ethyl ketone	78-93-3	Green Algae	Experimental	96 hours	Effect Concentration 10%	1,289 mg/l
methyl ethyl ketone	78-93-3	Water flea	Experimental	21 days	NOEC	100 mg/l
phenoxy resin	25068-38-6	Rainbow trout	Estimated	96 hours	LC50	2 mg/l
phenoxy resin	25068-38-6	Water flea	Estimated	48 hours	LC50	1.8 mg/l
phenoxy resin	25068-38-6	Green Algae	Experimental	72 hours	EC50	>11 mg/l
phenoxy resin	25068-38-6	Green Algae	Experimental	72 hours	NOEC	4.2 mg/l
phenoxy resin	25068-38-6	Water flea	Experimental	21 days	NOEC	0.3 mg/l
tetrahydrofuran	109-99-9	Fathead minnow	Experimental	96 hours	LC50	2,160 mg/l
tetrahydrofuran	109-99-9	Water flea	Experimental	48 hours	LC50	3,485 mg/l
tetrahydrofuran	109-99-9	Fathead minnow	Experimental	33 days	NOEC	216 mg/l
phenoxy resin	5026-74-4	Water flea	Estimated	48 hours	EC50	18 mg/l
phenoxy resin	5026-74-4	Common Carp	Experimental	96 hours	LC50	4.2 mg/l
phenoxy resin	5026-74-4	Green algae	Experimental	96 hours	EC50	13 mg/l
phenoxy resin	5026-74-4	Green algae	Experimental	96 hours	NOEC	4.2 mg/l
phenoxy resin	5026-74-4	Water flea	Experimental	21 days	NOEC	0.42 mg/l
1-methyl-2-pyrrolidinone	872-50-4	Grass Shrimp	Experimental	96 hours	EC50	1,107 mg/l
1-methyl-2-pyrrolidinone	872-50-4	Green algae	Experimental	72 hours	EC50	600.5 mg/l
1-methyl-2-pyrrolidinone	872-50-4	Rainbow trout	Experimental	96 hours	LC50	>500 mg/l
1-methyl-2-pyrrolidinone	872-50-4	Water flea	Experimental	48 hours	EC50	4,897 mg/l
1-methyl-2-pyrrolidinone	872-50-4	Green algae	Experimental	72 hours	Effect Concentration 10%	92.6 mg/l
1-methyl-2-pyrrolidinone	872-50-4	Water flea	Experimental	21 days	NOEC	12.5 mg/l
dicyandiamide	461-58-5	Bluegill	Experimental	96 hours	LC50	>1,000 mg/l
dicyandiamide	461-58-5	Green algae	Experimental	72 hours	EC50	>1,000 mg/l
dicyandiamide	461-58-5	Water flea	Experimental	48 hours	EC50	3,177 mg/l
dicyandiamide	461-58-5	Green algae	Experimental	72 hours	NOEC	310 mg/l
dicyandiamide	461-58-5	Water flea	Experimental	21 days	NOEC	25 mg/l
Toluene	108-88-3	Coho Salmon	Experimental	96 hours	LC50	5.5 mg/l
Toluene	108-88-3	Fish other	Experimental	96 hours	LC50	6.41 mg/l
Toluene	108-88-3	Green Algae	Experimental	72 hours	EC50	12.5 mg/l
Toluene	108-88-3	Water flea	Experimental	48 hours	EC50	3.78 mg/l
Toluene	108-88-3	Coho salmon	Experimental	40 days	NOEC	3.2 mg/l

3M Scotch-Weld 2290 Epoxy Adhesive, Amber

Toluene	108-88-3	Water flea	Experimental	7 days	NOEC	0.74 mg/l
---------	----------	------------	--------------	--------	------	-----------

12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
methyl ethyl ketone	78-93-3	Experimental Biodegradation	28 days	BOD	98 % BOD/ThBOD	OECD 301D - Closed bottle test
phenoxy resin	25068-38-6	Experimental Hydrolysis		Hydrolytic half-life	117 hours (t 1/2)	Other methods
phenoxy resin	25068-38-6	Experimental Biodegradation	28 days	BOD	5 %BOD/COD	OECD 301F - Manometric respirometry
tetrahydrofuran	109-99-9	Experimental Biodegradation	28 days	BOD	39 % BOD/ThBOD	Other methods
phenoxy resin	5026-74-4	Experimental Hydrolysis		Hydrolytic half-life	4.1 days (t 1/2)	Other methods
phenoxy resin	5026-74-4	Experimental Biodegradation	29 days	CO2 evolution	≤10 % weight	OECD 301B - Modified sturm or CO2
1-methyl-2-pyrrolidinone	872-50-4	Experimental Biodegradation	28 days	BOD	73 % BOD/ThBOD	OECD 301C - MITI test (I)
dicyandiamide	461-58-5	Experimental Biodegradation	28 days	Dissolv. Organic Carbon Deplet	0 % weight	OECD 301E - Modified OECD Scre
Toluene	108-88-3	Experimental Photolysis		Photolytic half-life (in air)	5.2 days (t 1/2)	Other methods
Toluene	108-88-3	Experimental Biodegradation	20 days	BOD	80 % weight	

12.3 : Bioaccumulative potential

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
methyl ethyl ketone	78-93-3	Experimental Bioconcentration		Log Kow	0.29	Other methods
phenoxy resin	25068-38-6	Experimental Bioconcentration		Log Kow	3.242	Other methods
tetrahydrofuran	109-99-9	Experimental Bioconcentration		Log Kow	0.45	Other methods
phenoxy resin	5026-74-4	Estimated Bioconcentration		Log Kow	0.87	Other methods
1-methyl-2-pyrrolidinone	872-50-4	Experimental Bioconcentration		Log Kow	-0.46	Other methods
dicyandiamide	461-58-5	Experimental BCF-Carp	42 days	Bioaccumulation factor	≤=3.1	OECD 305C-Bioaccum degree fish
Toluene	108-88-3	Experimental Bioconcentration		Log Kow	2.73	Other methods

12.4. Mobility in soil

Please contact manufacturer for more details

12.5 Other Adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerised) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Combustion products will include halogen acid (HCl/HF/HBr). Facility must be capable of handling halogenated materials. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

SECTION 14: Transport Information

Air Transport (IATA) Regulations

UN No UN1133

Proper Shipping Name Adhesives

Hazard Class/Division 3

Subsidiary Risk Not applicable

Packing Group: II

Marine Transport (IMDG)

UN No UN1133

Proper Shipping Name Adhesives

Hazard Class/Division 3

Subsidiary Risk Not applicable

Packing Group: II

Environmental Hazards: Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Japan Chemical Substance Control Law. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

Applicable Environmental, Health and Safety Regulations

The Manufacture, Storage and Import of Hazardous Chemical Rules, 1989

3M Scotch-Weld 2290 Epoxy Adhesive, Amber

Hazardous Waste(Management , Handling & Transboundary) Rules, 2008
Hazardous Chemicals (Classification, Packaging and Labelling Draft Rules), 2011

The following ingredients are listed as hazardous on Part II of Schedule I of the India Manufacture, Storage and Import of Hazardous Chemicals (MSIHC) rules

2-Butanone
methyl ethyl ketone
tetrahydrofuran
Toluene

The following ingredients are classified as hazardous based on the criteria listed under Part I of Schedule I of the India Manufacture, Storage and Import of Hazardous Chemicals (MSIHC) rules:
The product is classified as Very Highly Flammable liquid as per MSIHC Rules, 1989.

SECTION 16: Other information

NFPA Hazard Classification

Health: 3 **Flammability:** 3 **Instability:** 0 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Revision information:

No revision information

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

3M India SDSs are available at <http://solutions.3mindia.co.in>