

# Safety Data Sheet

Copyright, 2021, 3M India Limited. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

**Document group:** 10-3186-3 **Version number:** 1.02

**Issue Date:** 20/04/2021 **Supersedes date:** 05/12/2020

This Safety Data Sheet has been prepared in accordance with the GHS guidelines & India Hazardous substances (Classification, Labeling & Packaging) Draft Rules 2011.

# **SECTION 1: Identification**

#### 1.1. Product identifier

3M™ Scotch-Weld™ Urethane Adhesive 3549 B/A and 3M™ Scotch-Weld™ Urethane Adhesive DP640, Part B

#### **Product Identification Numbers**

62-3549-8501-2

#### 1.2. Recommended use and restrictions on use

### Recommended use

Structural adhesive.

## 1.3. Supplier's details

Address: 3M India Limited, plot-48-51, Electronic city, Hosur road, Bangalore-560100

**Telephone:** 080-45543000, contact Product EHS team

E Mail: productehs.in@mmm.com
Website: http://solutions.3mindia.co.in

# 1.4. Emergency telephone number

080-45543000 (Contact hours: 8:00 AM to 5:00 PM)

# **SECTION 2: Hazard identification**

Under MSIHC Rules, information is noted below on flammability, acute toxicity and explosivity relevant to this product. In line with international standards, information on other hazard classes and associated precautionary statements relevant to this product are included as well.

### 2.1. Classification of the substance or mixture

Reproductive Toxicity: Category 1B.

Specific Target Organ Toxicity (repeated exposure): Category 1.

### 2.2. Label elements

### Signal Word

DÅNGER!

### **Symbols**

Health Hazard |

### **Pictograms**



## **HAZARD STATEMENTS:**

H360 May damage fertility or the unborn child.

H372 Causes damage to organs through prolonged or repeated exposure:

respiratory system

### PRECAUTIONARY STATEMENTS

**Prevention:** 

P201 Obtain special instructions before use.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P280E Wear protective gloves.

**Response:** 

P308 + P313 IF exposed or concerned: Get medical advice/attention.

#### 2.3. Other hazards

None known.

# **SECTION 3: Composition/information on ingredients**

This material is a mixture.

Ingredient	CAS Nbr	% by Wt
Polyester Resin (NJTS Reg. No. 04499600-	Trade Secret	40 - 70
7133)		
Propane-1,2-diol, propoxylated	25322-69-4	10 - 30
Talc	14807-96-6	10 - 30
Polyoxypropylenetriol	25723-16-4	1 - 10
Zeolites	1318-02-1	1 - 10
o-diethylbisaniline	13680-35-8	1 - 5
Toluene	108-88-3	< 1

# **SECTION 4: First aid measures**

# 4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Wash with soap and water. If you are concerned, get medical advice.

Eve contact

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If swallowed

### 3M™ Scotch-Weld™ Urethane Adhesive 3549 B/A and 3M™ Scotch-Weld™ Urethane Adhesive DP640, Part B

Rinse mouth. If you feel unwell, get medical attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

Target organ effects following prolonged or repeated exposure. See Section 11 for additional details.

### 4.3. Indication of any immediate medical attention and special treatment required

Not applicable

# **SECTION 5: Fire-fighting measures**

### 5.1. Suitable Extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

### 5.2. Special hazards arising from the substance or mixture

None inherent in this product.

### **Hazardous Decomposition or By-Products**

**Substance** 

Carbon monoxide. Carbon dioxide.

Irritant vapours or gases.

# **Condition**

During combustion. During combustion.

During combustion.

## 5.3. Special protective actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

# **SECTION 6: Accidental release measures**

## 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

### **6.2.** Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

### 6.3. Methods and material for containment and cleaning up

Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

# **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (eg. gloves, respirators...) as required.

### 7.2. Conditions for safe storage including any incompatibilities

Store away from oxidising agents.

# **SECTION 8: Exposure controls/personal protection**

### 8.1 Control parameters

### Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
Toluene	108-88-3	ACGIH	TWA:20 ppm	A4: Not class. as human
				carcin, Ototoxicant
Aluminum, insoluble compounds	1318-02-1	ACGIH	TWA(respirable fraction):1	A4: Not class. as human
			mg/m3	carcin
Talc	14807-96-6	ACGIH	TWA(respirable fraction):2	A4: Not class. as human
			mg/m3	carcin
Propane-1,2-diol, propoxylated	25322-69-4	AIHA	TWA(as aerosol):10 mg/m3	

ACGIH: American Conference of Governmental Industrial Hygienists

AIHA: American Industrial Hygiene Association

CMRG: Chemical Manufacturer's Recommended Guidelines

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

### 8.2. Exposure controls

### 8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

# 8.2.2. Personal protective equipment (PPE)

### **Eve/face protection**

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety glasses with side shields.

### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Fluoroelastomer

Polymer laminate

# **Respiratory protection**

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

# **SECTION 9: Physical and chemical properties**

9.1. Information on basic physical and chemical properties

Information on basic physical and chemical properti	les	
Physical state	Liquid.	
Specific Physical Form:	Paste	
Color	Off-White	
Odor	Slight Polyester	
Odour threshold	No data available.	
pH	Not applicable.	
Melting point/Freezing point: NA	No data available.	
Boiling point/Initial boiling point/Boiling range	>=179 °C	
Flash point	>=178.9 °C [Test Method:Closed Cup]	
Evaporation rate	Not applicable.	
Flammability (solid, gas)	Not applicable.	
Flammable Limits(LEL)	Not applicable.	
Flammable Limits(UEL)	Not applicable.	
Vapour pressure	Not applicable.	
Vapor Density and/or Relative Vapor Density	Not applicable.	
Density	1.31 g/ml	
Relative density	1.31 [Ref Std:WATER=1]	
Water solubility	Negligible	
Solubility- non-water	No data available.	
Partition coefficient: n-octanol/water	No data available.	
Autoignition temperature	No data available.	
Decomposition temperature	No data available.	
Viscosity/Kinematic Viscosity	10,000 - 40,000 mPa-s [@ 23 °C ] [Test Method:Brookfield]	
Volatile organic compounds (VOC)		
Percent volatile		
VOC less H2O & exempt solvents	0 g/l [Test Method:calculated SCAQMD rule 443.1]	
	[Details: when used as intended with Part A]	
VOC less H2O & exempt solvents	6.78 g/l [Test Method:calculated SCAQMD rule 443.1]	
	[Details:as supplied]	
Molecular weight	No data available.	

## Nanoparticles

This material does not contain nanoparticles.

# **SECTION 10: Stability and reactivity**

# **10.1 Reactivity**

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

# 10.2 Chemical stability

Stable.

# 10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

# 10.4 Conditions to avoid

None known.

### 10.5 Incompatible materials

Strong oxidising agents.

### 10.6 Hazardous decomposition products

**Substance** 

Condition

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

# **SECTION 11: Toxicological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

# 11.1 Information on Toxicological effects

#### Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### Inhalation

May cause additional health effects (see below).

#### Skin contact

Contact with the skin during product use is not expected to result in significant irritation.

# Eye contact

Contact with the eyes during product use is not expected to result in significant irritation.

#### Ingestion

May cause additional health effects (see below).

### **Additional Health Effects:**

# Prolonged or repeated exposure may cause target organ effects:

Pneumoconiosis: Sign/symptoms may include persistent cough, breathlessness, chest pain, increased amounts of sputum, and changes in lung function tests.

## Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

# **Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

**Acute Toxicity** 

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Polyester Resin (NJTS Reg. No. 04499600-7133)	Ingestion	Rat	LD50 > 15,000 mg/kg
Propane-1,2-diol, propoxylated	Dermal	Rabbit	LD50 > 10,000 mg/kg
Propane-1,2-diol, propoxylated	Ingestion	Rat	LD50 > 2,000 mg/kg

Talc	Dermal		LD50 estimated to be > 5,000 mg/kg
Talc	Ingestion		LD50 estimated to be > 5,000 mg/kg
Polyoxypropylenetriol	Dermal	Rat	LD50 > 2,000 mg/kg
Polyoxypropylenetriol	Ingestion	Rat	LD50 > 2,500 mg/kg
Zeolites	Dermal	Rabbit	LD50 > 2,000 mg/kg
Zeolites	Inhalation-	Rat	LC50 > 4.57 mg/l
	Dust/Mist		
	(4 hours)		
Zeolites	Ingestion	Rat	LD50 > 5,000 mg/kg
Toluene	Dermal	Rat	LD50 12,000 mg/kg
Toluene	Inhalation-	Rat	LC50 30 mg/l
	Vapor (4		
	hours)		
Toluene	Ingestion	Rat	LD50 5,550 mg/kg
o-diethylbisaniline	Ingestion	Rat	LD50 1,901 mg/kg

ATE = acute toxicity estimate

# **Skin Corrosion/Irritation**

Name	Species	Value
Propane-1,2-diol, propoxylated	Rabbit	No significant irritation
Talc	Rabbit	No significant irritation
Polyoxypropylenetriol	Rabbit	No significant irritation
Zeolites	Rabbit	No significant irritation
Toluene	Rabbit	Irritant
o-diethylbisaniline	Rabbit	Minimal irritation

**Serious Eye Damage/Irritation** 

zerrous zye z umuge/irrituteton		
Name	Species	Value
Propane-1,2-diol, propoxylated	Rabbit	No significant irritation
Talc	Rabbit	No significant irritation
Polyoxypropylenetriol	Rabbit	Mild irritant
Zeolites	Rabbit	Mild irritant
Toluene	Rabbit	Moderate irritant
o-diethylbisaniline	Rabbit	No significant irritation

## **Sensitization:**

# **Skin Sensitisation**

Name	Species	Value
Toluene	Guinea	Not classified
	pig	

**Respiratory Sensitisation** 

Name	Species	Value
Talc	Human	Not classified

**Germ Cell Mutagenicity** 

Name	Route	Value
Talc	In Vitro	Not mutagenic
Talc	In vivo	Not mutagenic
Toluene	In Vitro	Not mutagenic
Toluene	In vivo	Not mutagenic
o-diethylbisaniline	In Vitro	Not mutagenic

Carcinogenicity

	Name	Route	Species	Value
--	------	-------	---------	-------

Talc	Inhalation	Rat	Some positive data exist, but the data are not sufficient for classification
Toluene	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Toluene	Ingestion	Rat	Some positive data exist, but the data are not sufficient for classification
Toluene	Inhalation	Mouse	Some positive data exist, but the data are not sufficient for classification

# **Reproductive Toxicity**

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
Talc	Ingestion	Not classified for development	Rat	NOAEL 1,600 mg/kg	during organogenesis
Toluene	Inhalation	Not classified for female reproduction	Human	NOAEL Not available	occupational exposure
Toluene	Inhalation	Not classified for male reproduction	Rat	NOAEL 2.3 mg/l	1 generation
Toluene	Ingestion	Toxic to development	Rat	LOAEL 520 mg/kg/day	during gestation
Toluene	Inhalation	Toxic to development	Human	NOAEL Not available	poisoning and/or abuse

# Target Organ(s)

**Specific Target Organ Toxicity - single exposure** 

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Toluene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Toluene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Toluene	Inhalation	immune system	Not classified	Mouse	NOAEL 0.004 mg/l	3 hours
Toluene	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse

**Specific Target Organ Toxicity - repeated exposure** 

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Talc	Inhalation	pneumoconiosis	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure
Talc	Inhalation	pulmonary fibrosis   respiratory system	Not classified	Rat	NOAEL 18 mg/m3	113 weeks
Toluene	Inhalation	auditory system   eyes   olfactory system	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	poisoning and/or abuse
Toluene	Inhalation	nervous system	May cause damage to organs though prolonged or repeated exposure	Human	NOAEL Not available	poisoning and/or abuse
Toluene	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 2.3 mg/l	15 months
Toluene	Inhalation	heart   liver   kidney and/or bladder	Not classified	Rat	NOAEL 11.3 mg/l	15 weeks
Toluene	Inhalation	endocrine system	Not classified	Rat	NOAEL 1.1 mg/l	4 weeks
Toluene	Inhalation	immune system	Not classified	Mouse	NOAEL Not available	20 days
Toluene	Inhalation	bone, teeth, nails, and/or hair	Not classified	Mouse	NOAEL 1.1 mg/l	8 weeks
Toluene	Inhalation	hematopoietic	Not classified	Human	NOAEL Not	occupational

Page: 8 of 14

		system   vascular system			available	exposure
Toluene	Inhalation	gastrointestinal tract	Not classified	Multiple animal species	NOAEL 11.3 mg/l	15 weeks
Toluene	Ingestion	nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 625 mg/kg/day	13 weeks
Toluene	Ingestion	heart	Not classified	Rat	NOAEL 2,500 mg/kg/day	13 weeks
Toluene	Ingestion	liver   kidney and/or bladder	Not classified	Multiple animal species	NOAEL 2,500 mg/kg/day	13 weeks
Toluene	Ingestion	hematopoietic system	Not classified	Mouse	NOAEL 600 mg/kg/day	14 days
Toluene	Ingestion	endocrine system	Not classified	Mouse	NOAEL 105 mg/kg/day	28 days
Toluene	Ingestion	immune system	Not classified	Mouse	NOAEL 105 mg/kg/day	4 weeks

### **Aspiration Hazard**

Name	Value
Toluene	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

# **SECTION 12: Ecological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labelling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

### 12.1. Toxicity

### Acute aquatic hazard:

Not acutely toxic to aquatic life by GHS criteria.

### Chronic aquatic hazard:

Not chronically toxic to aquatic life by GHS criteria.

No product test data available.

Material	CAS Nbr	Organism	Type	Exposure	Test endpoint	Test result
Polyester Resin	Trade Secret		Data not available or			N/A
(NJTS Reg. No. 04499600- 7133)			insufficient for classification			
Propane-1,2- diol, propoxylated	25322-69-4	Activated sludge	Experimental	3 hours	EC50	>1,000 mg/l
Propane-1,2- diol, propoxylated	25322-69-4	Green algae	Experimental	72 hours	EC50	>100 mg/l
Propane-1,2-diol,	25322-69-4	Water flea	Experimental	48 hours	EC50	105.8 mg/l

propoxylated						
Propane-1,2-	25322-69-4	Zebra Fish	Experimental	96 hours	LC50	>100 mg/l
diol,	23322 07 .	20014 1 1511	Z. iperimentar	Jo Hours	Eeso	100 1119/1
propoxylated						
Propane-1,2-	25322-69-4	Green algae	Experimental	72 hours	NOEC	>100 mg/l
diol,			2.19 41.1114.1141	7 2 110 6115	1,020	100 mg/1
propoxylated						
Propane-1,2-	25322-69-4	Water flea	Experimental	21 days	NOEC	>=10 mg/l
diol,					1.000	1 1129
propoxylated						
Talc	14807-96-6		Data not			N/A
			available or			
			insufficient for			
			classification			
Polyoxypropyl	25723-16-4	Activated	Experimental	3 hours	EC10	>10,000 mg/l
enetriol		sludge				
Polyoxypropyl	25723-16-4	Green algae	Experimental	72 hours	EC50	>100 mg/l
enetriol						_
Polyoxypropyl	25723-16-4	Water flea	Experimental	48 hours	EC50	>100 mg/l
enetriol						
Polyoxypropyl	25723-16-4	Zebra Fish	Experimental	96 hours	LC50	>100 mg/l
enetriol						
Polyoxypropyl	25723-16-4	Green algae	Experimental	72 hours	NOEC	100 mg/l
enetriol						
Polyoxypropyl	25723-16-4	Water flea	Experimental	21 days	NOEC	8.5 mg/l
enetriol						
Zeolites	1318-02-1	Green algae	Experimental	96 hours	EC50	>100 mg/l
Zeolites	1318-02-1	Zebra Fish	Experimental	96 hours	LC50	>100 mg/l
Zeolites	1318-02-1	Green algae	Experimental	72 hours	NOEC	>100 mg/l
Zeolites	1318-02-1	Water flea	Experimental	21 days	NOEC	100 mg/l
0-	13680-35-8	Green Algae	Endpoint not	72 hours	EC50	>100 mg/l
diethylbisanilin			reached			
e						
0-	13680-35-8	Activated	Experimental	3 hours	NOEC	1,000 mg/l
diethylbisanilin		sludge				
e						
0-	13680-35-8	Water flea	Experimental	48 hours	No tox obs at	>100 mg/l
diethylbisanilin					lmt of water sol	
e						
0-	13680-35-8	Zebra Fish	Experimental	96 hours	LC50	1.32 mg/l
diethylbisanilin						
e						
0-	13680-35-8	Green Algae	Experimental	72 hours	NOEC	0.19 mg/l
diethylbisanilin						
e E 1	100.00.2	0.1.0.1	D	0.6.1	T 050	5.5 /1
Toluene	108-88-3	Coho Salmon	Experimental	96 hours	LC50	5.5 mg/l
Toluene	108-88-3	Grass Shrimp	Experimental	96 hours	LC50	9.5 mg/l
Toluene	108-88-3	Green Algae	Experimental	72 hours	EC50	12.5 mg/l
Toluene	108-88-3	Leopard frog	Experimental	9 days	LC50	0.39 mg/l
Toluene	108-88-3	Pink Salmon	Experimental	96 hours	LC50	6.41 mg/l
Toluene	108-88-3	Water flea	Experimental	48 hours	EC50	3.78 mg/l
Toluene	108-88-3	Coho Salmon	Experimental	40 days	NOEC	1.39 mg/l
Toluene	108-88-3	Diatom	Experimental	72 hours	NOEC	10 mg/l
Toluene	108-88-3	Water flea	Experimental	7 days	NOEC	0.74 mg/l

Toluene	108-88-3	Activated	Experimental	12 hours	IC50	292 mg/l
		sludge				
Toluene	108-88-3	Bacteria	Experimental	16 hours	NOEC	29 mg/l
Toluene	108-88-3	Bacteria	Experimental	24 hours	EC50	84 mg/l
Toluene	108-88-3	Redworm	Experimental	28 days	LC50	>150 mg per kg of
				-		bodyweight
Toluene	108-88-3	Soil microbes	Experimental	28 days	NOEC	<26 mg/kg (Dry
						Weight)

# 12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Polyester Resin (NJTS Reg. No. 04499600-7133)	Trade Secret	Data not available- insufficient			N/A	
Propane-1,2- diol, propoxylated	25322-69-4	Experimental Biodegradation	28 days	BOD	89 % weight	OECD 301F - Manometric respirometry
Talc	14807-96-6	Data not available-insufficient			N/A	
Polyoxypropyl enetriol	25723-16-4	Experimental Biodegradation	28 days	BOD	84 % BOD/ThBOD	Non-standard method
Zeolites	1318-02-1	Data not available-insufficient			N/A	
o- diethylbisanilin e	13680-35-8	Experimental Biodegradation	28 days	Readily Biodegradable	4.18 % BOD/ThBOD	OECD 301C - MITI test (I)
Toluene	108-88-3	Experimental Photolysis		Photolytic half- life (in air)	5.2 days (t 1/2)	
Toluene	108-88-3	Experimental Biodegradation	20 days	BOD	80 % BOD/ThBOD	APHA Std Meth Water/Wastewater

# 12.3 : Bioaccumulative potential

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Polyester Resin	Trade Secret	Data not	N/A	N/A	N/A	N/A
(NJTS Reg.		available or				
No. 04499600-		insufficient for				
7133)		classification				
Propane-1,2-	25322-69-4	Experimental		Log Kow	< 0.9	Non-standard method
diol,		Bioconcentrati				
propoxylated		on				
Talc	14807-96-6	Data not	N/A	N/A	N/A	N/A
		available or				
		insufficient for				
		classification				
Polyoxypropyl	25723-16-4	Experimental		Log Kow	1.8	Non-standard method
enetriol		Bioconcentrati				
		on				
Zeolites	1318-02-1	Data not	N/A	N/A	N/A	N/A
		available or				

		insufficient for				
		classification				
0-	13680-35-8	Estimated		Bioaccumulatio	2344	Estimated:
diethylbisanilin		Bioconcentrati		n factor		Bioconcentration factor
e		on				
Toluene	108-88-3	Experimental	72 hours	Bioaccumulatio	90	
		BCF - Other		n factor		
Toluene	108-88-3	Experimental		Log Kow	2.73	
		Bioconcentrati				
		on				

### 12.4. Mobility in soil

Please contact manufacturer for more details

#### 12.5 Other Adverse effects

No information available.

# **SECTION 13: Disposal considerations**

### 13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerised) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. If no other disposal options are available, waste product—that has been completely cured or polymerised may be placed in a landfill properly designed for industrial waste. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

# **SECTION 14: Transport Information**

Not hazardous for transportation.

### Air Transport (IATA)Regulations

UN No Not applicable

Proper Shipping Name Not applicable Hazard Classs/Division Not applicable Subsidiary Risk Not applicable Packing Group: Not applicable

Marine Transport (IMDG)
UN No Not applicable

Proper Shipping Name Not applicable Hazard Classs/Division Not applicable Subsidiary Risk Packing Group: Not applicable Not applicable

Environmental Hazards: Not applicable

# **SECTION 15: Regulatory information**

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

### Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Japan Chemical Substance Control Law. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

# Applicable Environmental, Health and Safety Regulations

The Manufacture, Storage and Import of Hazardous Chemical Rules, 1989 Hazardous Waste(Management, Handling & Transboundary) Rules, 2008 Hazardous Chemicals (Classification, Packaging and Labelling Draft Rules), 2011

The following ingredients are listed as hazardous on Part II of Schedule I of the India Manufacture, Storage and Import of Hazardous Chemicals (MSIHC) rules
Toluene

The following ingredients are classified as hazardous based on the criteria listed under Part I of Schedule I of the India Manufacture, Storage and Import of Hazardous Chemicals (MSIHC) rules:
The product is classified as Non-Hazardous as per MSIHC Rules, 1989.

# **SECTION 16: Other information**

### NFPA Hazard Classification

Health: 0 Flammability: 1 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

### **Revision information:**

Section 1: Product name information was modified.

Label: GHS Classification information was added.

Label: GHS Classification information was modified.

Label: GHS Precautionary - Prevention information was modified.

Label: GHS Precautionary - Response information was added.

Section 2: Ingredient table information was modified.

Section 04: First Aid - Symptoms and Effects (GHS) information was added.

Section 4: First aid for skin contact information information was modified.

Section 04: Information on toxicological effects information was deleted.

Section 7: Precautions safe handling information information was modified.

Section 8: Eye protection information information was deleted.

Section 8: Eye/face protection information information was added.

Section 8: Occupational exposure limit table information was modified.

Section 8: Personal Protection - Eye information information was added.

Section 8: Personal Protection - Skin/hand information information was modified.

Section 8: Skin protection - recommended gloves information information was added.

Section 8: Skin protection - recommended gloves text information was added.

### 3M™ Scotch-Weld™ Urethane Adhesive 3549 B/A and 3M™ Scotch-Weld™ Urethane Adhesive DP640, Part B

- Section 09: Odor information was modified.
- Section 11: Acute Toxicity table information was modified.
- Section 11: Aspiration Hazard Table information was added.
- Section 11: Aspiration Hazard text information was deleted.
- Section 11: Carcinogenicity Table information was modified.
- Section 11: Germ Cell Mutagenicity Table information was modified.
- Section 11: Health Effects Ingestion information information was modified.
- Section 11: Reproductive Hazards information information was added.
- Section 11: Reproductive Toxicity Table information was modified.
- Section 11: Serious Eye Damage/Irritation Table information was modified.
- Section 11: Skin Corrosion/Irritation Table information was modified.
- Section 11: Skin Sensitization Table information was added.
- Section 11: Skin Sensitization text information was deleted.
- Section 11: Specific Target Organ Toxicity single exposure text information was deleted.
- Section 11: Target Organs Repeated Table information was modified.
- Section 11: Target Organs Single Table information was added.
- Section 12: Component ecotoxicity information information was modified.
- Section 12: Persistence and Degradability information information was modified.
- Section 12:Bioccumulative potential information information was modified.
- Section 15: MSIHC Ingredients information was modified.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

3M India SDSs are available at http://solutions.3mindia.co.in