

Safety Data Sheet

Copyright, 2022, 3M India Limited. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document group:
 10-2459-5
 Version number:
 1.03

 Issue Date:
 22/05/2022
 Supersedes date:
 22/04/2021

This Safety Data Sheet has been prepared in accordance with the GHS guidelines & India Hazardous substances (Classification, Labeling & Packaging) Draft Rules 2011.

SECTION 1: Identification

1.1. Product identifier

3MTM Nitrile Plastic Adhesive 826

1.2. Recommended use and restrictions on use

Recommended use

Adhesive, Industrial use.

1.3. Supplier's details

Address: 3M India Limited, plot-48-51, Electronic city, Hosur road, Bangalore-560100

Telephone: 080-45543000, contact Product EHS team

E Mail: productehs.in@mmm.com
Website: http://solutions.3mindia.co.in

1.4. Emergency telephone number

080-45543000 (Contact hours: 8:00 AM to 5:00 PM)

SECTION 2: Hazard identification

Under MSIHC Rules, information is noted below on flammability, acute toxicity and explosivity relevant to this product. In line with international standards, information on other hazard classes and associated precautionary statements relevant to this product are included as well.

2.1. Classification of the substance or mixture

Flammable Liquid: Category 2.

Skin Corrosion/Irritation: Category 1C. Serious Eye Damage/Irritation: Category 1.

Carcinogenicity: Category 1B. Reproductive Toxicity: Category 2.

Specific Target Organ Toxicity (single exposure): Category 1. Specific Target Organ Toxicity (repeated exposure): Category 1. Specific Target Organ Toxicity (single exposure): Category 3.

Acute Aquatic Toxicity: Category 3. Chronic Aquatic Toxicity: Category 3.

2.2. Label elements

Signal Word

Danger

Symbols

Flame | Corrosion | Exclamation mark | Health Hazard |

Pictograms



HAZARD STATEMENTS:

H225 Highly flammable liquid and vapour.
H314 Causes severe skin burns and eye damage.

H350 May cause cancer.

H361 Suspected of damaging fertility or the unborn child.

H336 May cause drowsiness or dizziness.

H370 Causes damage to organs: blood or blood-forming organs | cardiovascular system |

kidney/urinary tract | nervous system | respiratory system.

H372 Causes damage to organs through prolonged or repeated exposure: blood or blood-

forming organs | cardiovascular system | kidney/urinary tract | liver | respiratory

system.

H373 May cause damage to organs through prolonged or repeated exposure: nervous

system.

H412 Harmful to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENTS

Prevention:

P201 Obtain special instructions before use.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P280J Wear protective gloves, protective clothing, respiratory protection, and eye/face

protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin

with water or shower.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER or doctor/physician.

P370 + P378 In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry

chemical or carbon dioxide to extinguish.

2.3. Other hazards

- May cause chemical gastrointestinal burns.

SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	CAS Nbr	% by Wt	
Ethyl acetate	141-78-6	50 - 60	
Acrylonitrile-Butadiene Polymer	9003-18-3	10 - 20	
Ethanol	64-17-5	10 - 20	
Phenolic Resin	9039-25-2	10 - 20	
Butanone	78-93-3	5 - 10	
Phenol	108-95-2	1 - 5	
DIPHENYLAMINE	122-39-4	< 1	
Cresol	1319-77-3	< 0.5	
Methanol	67-56-1	< 0.5	
Methyl Isobutyl Ketone	108-10-1	< 0.5	
2,5-Di-tert-pentylhydroquinone	79-74-3	< 0.15	

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Immediately flush with large amounts of water for at least 15 minutes. Remove contaminated clothing. Get immediate medical attention. Wash clothing before reuse.

Eye contact

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

If swallowed

Rinse mouth. Do not induce vomiting. Get immediate medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Skin burns (localized redness, swelling, itching, intense pain, blistering, and tissue destruction). Serious damage to the eyes (corneal cloudiness, severe pain, tearing, ulcerations, and significantly impaired or loss of vision). Central nervous system depression (headache, dizziness, drowsiness, incoordination, nausea, slurred speech, giddiness, and unconsciousness). Target organ effects. See Section 11 for additional details. Target organ effects following prolonged or repeated exposure. See Section 11 for additional details.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable Extinguishing media

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products

SubstanceConditionHydrocarbons.During combustion.FormaldehydeDuring combustion.Carbon monoxide.During combustion.

Carbon dioxide.
Oxides of nitrogen.

During combustion. During combustion.

5.3. Special protective actions for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Cover spill area with a fire-extinguishing foam. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

For industrial/occupational use only. Not for consumer sale or use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.) Wear low static or properly grounded shoes. Use personal protective equipment (eg. gloves, respirators...) as required. To minimize the risk of ignition, determine applicable electrical classifications for the process using this product and select specific local exhaust ventilation equipment to avoid flammable vapor accumulation. Ground/bond container and receiving equipment if there is potential for static electricity accumulation during transfer.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store away from heat. Store away from acids. Store away from oxidising agents.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available

for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
Methyl Isobutyl Ketone	108-10-1	ACGIH	TWA:20 ppm;STEL:75 ppm	A3: Confirmed animal
				carcin.
Phenol	108-95-2	ACGIH	TWA:5 ppm	A4: Not class. as human
				carcin, Danger of
				cutaneous absorption
DIPHENYLAMINE	122-39-4	ACGIH	TWA:10 mg/m ³	A4: Not class. as human
				carcin
Cresol	1319-77-3	ACGIH	TWA(inhalable fraction and	A4: Not class. as human
			vapor):20 mg/m3	carcin, Danger of
				cutaneous absorption
Ethyl acetate	141-78-6	ACGIH	TWA:400 ppm	
Ethanol	64-17-5	ACGIH	STEL:1000 ppm	A3: Confirmed animal
				carcin.
Methanol	67-56-1	ACGIH	TWA:200 ppm;STEL:250 ppm	Danger of cutaneous
				absorption
Butanone	78-93-3	ACGIH	TWA:200 ppm;STEL:300 ppm	

ACGIH: American Conference of Governmental Industrial Hygienists

AIHA: American Industrial Hygiene Association

CMRG: Chemical Manufacturer's Recommended Guidelines

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment. Use explosion-proof ventilation equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Full face shield.

Indirect vented goggles.

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Butyl rubber.

Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron – Butyl rubber Apron - polymer laminate

Rubber boots.

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates Half facepiece or full facepiece supplied-air respirator

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

information on basic physical and chemical properties	
Physical state	Liquid.
Color	Light Amber
Odor	Solvent
Odour threshold	No data available.
pH	Not applicable.
Melting point/Freezing point: NA	Not applicable.
Boiling point/Initial boiling point/Boiling range	>=77 °C
Flash point	1.7 °C [Test Method:Closed Cup]
Evaporation rate	3 [Ref Std:ETHER=1]
Flammability (solid, gas)	Not applicable.
Flammable Limits(LEL)	1.8 % volume
Flammable Limits(UEL)	19 % volume
Vapour pressure	<=13,332.2 Pa [@ 27.2 °C]
Vapor Density and/or Relative Vapor Density	3 [Ref Std:AIR=1]
Density	0.94 g/ml
Relative density	0.94 [<i>Ref Std</i> :WATER=1]
Water solubility	Slight (less than 10%)
Solubility- non-water	No data available.
Partition coefficient: n-octanol/water	No data available.
Autoignition temperature	365 °C [Details:Ethanol]
Decomposition temperature	No data available.
Viscosity/Kinematic Viscosity	2,000 mPa-s [@ 27 °C]
Volatile organic compounds (VOC)	No data available.
Percent volatile	No data available.
VOC less H2O & exempt solvents	<=740 g/l [Test Method:calculated SCAQMD rule 443.1]
Molecular weight	No data available.
Solids content	20 - 40 %

SECTION 10: Stability and reactivity

10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

Heat.

Sparks and/or flames.

10.5 Incompatible materials

Strong acids.

10.6 Hazardous decomposition products

Substance

Condition

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1 Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

Skin contact

Corrosive (skin burns): Signs/symptoms may include localised redness, swelling, itching, intense pain, blistering, ulceration, and tissue destruction. May cause additional health effects (see below).

Eye contact

Corrosive (eye burns): Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision.

Ingestion

Gastrointestinal corrosion: Signs/symptoms may include severe mouth, throat and abdominal pain, nausea, vomiting, and diarrhea; blood in the faeces and/or vomitus may also be seen. May cause additional health effects (see below).

Additional Health Effects:

Single exposure may cause target organ effects:

Cardiac effects: Signs/symptoms may include irregular heartbeat (arrhythmia), changes in heart rate, damage to heart muscle, heart attack, and may be fatal. Hematopoietic effects: Signs/symptoms may include generalised weakness, fatigue and alterations in numbers of circulating blood cells. Central nervous system (CNS) depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness. Neurological effects: Signs/symptoms may include personality changes, lack of coordination, sensory loss, tingling or numbness of the extremities, weakness, tremors, and changes in blood pressure and heart rate. Respiratory effects: Signs/symptoms may include cough, shortness of breath, chest tightness, wheezing, increased heart rate, bluish coloured skin (cyanosis), sputum production, changes in lung function tests, and respiratory failure. Kidney/Bladder effects: Signs/symptoms may include changes in urine production, abdominal or lower back pain, increased protein in urine, increased blood urea nitrogen (BUN), blood in urine, and painful urination.

Prolonged or repeated exposure may cause target organ effects:

Cardiac effects: Signs/symptoms may include irregular heartbeat (arrhythmia), changes in heart rate, damage to heart muscle, heart attack, and may be fatal. Hematopoietic effects: Signs/symptoms may include generalised weakness, fatigue and alterations in numbers of circulating blood cells. Liver effects: Signs/symptoms may include loss of appetite, weight loss, fatigue, weakness, abdominal tenderness and jaundice. Neurological effects: Signs/symptoms may include personality changes, lack of coordination, sensory loss, tingling or numbness of the extremities, weakness, tremors, and changes in blood pressure and heart rate. Respiratory effects: Signs/symptoms may include cough, shortness of breath, chest tightness, wheezing, increased heart rate, bluish coloured skin (cyanosis), sputum production, changes in lung function tests, and respiratory failure. Kidney/Bladder effects: Signs/symptoms may include changes in urine production, abdominal or lower back pain, increased protein in urine, increased blood urea nitrogen (BUN), blood in urine, and painful urination.

Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

Additional information:

This product contains ethanol. Alcoholic beverages and ethanol in alcoholic beverages have been classified by the International Agency for Research on Cancer as carcinogenic to humans. There are also data associating human consumption of alcoholic beverages with developmental toxicity and liver toxicity. Exposure to ethanol during the foreseeable use of this product is not expected to cause cancer, developmental toxicity, or liver toxicity.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value	
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg	
Overall product	Inhalation- Vapor(4 hr)		No data available; calculated ATE >50 mg/l	
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg	
Ethyl acetate	Dermal	Rabbit	LD50 > 18,000 mg/kg	
Ethyl acetate	Inhalation- Vapor (4 hours)	Rat	LC50 70.5 mg/l	
Ethyl acetate	Ingestion	Rat	LD50 5,620 mg/kg	
Ethanol	Dermal	Rabbit	LD50 > 15,800 mg/kg	
Ethanol	Inhalation- Vapor (4 hours)	Rat	LC50 124.7 mg/l	
Ethanol	Ingestion	Rat	LD50 17,800 mg/kg	
Phenolic Resin	Dermal		LD50 estimated to be > 5,000 mg/kg	
Phenolic Resin	Inhalation- Dust/Mist		LC50 estimated to be > 12.5 mg/l	
Phenolic Resin	Ingestion		LD50 estimated to be > 5,000 mg/kg	
Acrylonitrile-Butadiene Polymer	Dermal	Rabbit	LD50 > 15,000 mg/kg	
Acrylonitrile-Butadiene Polymer	Ingestion	Rat	LD50 > 30,000 mg/kg	
Butanone	Dermal	Rabbit	LD50 > 8,050 mg/kg	
Butanone	Inhalation- Vapor (4 hours)	Rat	LC50 34.5 mg/l	
Butanone	Ingestion	Rat	LD50 2,737 mg/kg	
Phenol	Inhalation- Vapor		LC50 estimated to be 2 - 10 mg/l	
Phenol	Dermal	Rat	LD50 670 mg/kg	
Phenol	Ingestion	Rat	LD50 340 mg/kg	
Cresol	Dermal	Rat	LD50 242 mg/kg	

Cresol	Ingestion	Rat	LD50 1,454 mg/kg
Methanol	Dermal		LD50 estimated to be 1,000 - 2,000 mg/kg
Methanol	Inhalation- Vapor		LC50 estimated to be 10 - 20 mg/l
Methanol	Ingestion		LD50 estimated to be 50 - 300 mg/kg
Methyl Isobutyl Ketone	Dermal	Rabbit	LD50 > 16,000 mg/kg
Methyl Isobutyl Ketone	Inhalation- Vapor (4 hours)	Rat	LC50 11 mg/l
Methyl Isobutyl Ketone	Ingestion	Rat	LD50 3,038 mg/kg
DIPHENYLAMINE	Ingestion	Guinea pig	LD50 300 mg/kg
2,5-Di-tert-pentylhydroquinone	Dermal	Rabbit	LD50 > 3,160 mg/kg
DIPHENYLAMINE	Dermal	Rabbit	LD50 > 2,000 mg/kg
2,5-Di-tert-pentylhydroquinone	Ingestion	Rat	LD50 1,900 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Ethyl acetate	Rabbit	Minimal irritation
Ethanol	Rabbit	No significant irritation
Phenolic Resin	Professio	No significant irritation
	nal judgemen t	
Acrylonitrile-Butadiene Polymer	Professio nal judgemen t	No significant irritation
Butanone	Rabbit	Minimal irritation
Phenol	Rat	Corrosive
Methanol	Rabbit	Mild irritant
Methyl Isobutyl Ketone	Rabbit	Mild irritant
2,5-Di-tert-pentylhydroquinone	Rabbit	No significant irritation
DIPHENYLAMINE	Rabbit	Minimal irritation

Serious Eve Damage/Irritation

Name	Species	Value
Ethyl acetate	Rabbit	Mild irritant
Ethanol	Rabbit	Severe irritant
Phenolic Resin	Professio	Mild irritant
	nal judgemen t	
Acrylonitrile-Butadiene Polymer	Professio nal judgemen t	No significant irritation
Butanone	Rabbit	Severe irritant
Phenol	Rabbit	Corrosive
Methanol	Rabbit	Moderate irritant
Methyl Isobutyl Ketone	Rabbit	Mild irritant
2,5-Di-tert-pentylhydroquinone	Rabbit	Mild irritant
DIPHENYLAMINE	Rabbit	Corrosive

Sensitization:

Skin Sensitisation

Name	Species	Value
Ethyl acetate	Guinea	Not classified

	pig	
Ethanol	Human	Not classified
Phenol	Guinea	Not classified
	pig	
Methanol	Guinea	Not classified
	pig	
Methyl Isobutyl Ketone	Guinea	Not classified
	pig	
2,5-Di-tert-pentylhydroquinone	Human	Not classified
DIPHENYLAMINE	Human	Not classified
	and	
	animal	

Respiratory Sensitisation

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value	
Ethyl acetate	In Vitro	Not mutagenic	
Ethyl acetate	In vivo	Not mutagenic	
Ethanol	In Vitro	Some positive data exist, but the data are not sufficient for classification	
Ethanol	In vivo	Some positive data exist, but the data are not sufficient for classification	
Butanone	In Vitro	Not mutagenic	
Phenol	In Vitro	Some positive data exist, but the data are not sufficient for classification	
Phenol	In vivo	Some positive data exist, but the data are not sufficient for classification	
Methanol	In Vitro	Some positive data exist, but the data are not sufficient for classification	
Methanol	In vivo	Some positive data exist, but the data are not sufficient for classification	
Methyl Isobutyl Ketone	In Vitro	Not mutagenic	
DIPHENYLAMINE	In vivo	Not mutagenic	
DIPHENYLAMINE	In Vitro	Some positive data exist, but the data are not sufficient for classification	

Carcinogenicity

Name	Route	Species	Value
Ethanol	Ingestion	Multiple animal species	Some positive data exist, but the data are not sufficient for classification
Butanone	Inhalation	Human	Not carcinogenic
Phenol	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Phenol	Ingestion	Rat	Some positive data exist, but the data are not sufficient for classification
Methanol	Inhalation	Multiple animal species	Not carcinogenic
Methyl Isobutyl Ketone	Inhalation	Multiple animal species	Carcinogenic.
DIPHENYLAMINE	Ingestion	Multiple animal species	Carcinogenic.

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure
					Duration

Page: 10 of 20

Ethanol	Inhalation	Not classified for development	Rat	NOAEL 38 mg/l	during gestation
Ethanol	Ingestion	Not classified for development	Rat	NOAEL 5,200 mg/kg/day	premating & during gestation
Butanone	Inhalation	Not classified for development	Rat	LOAEL 8.8 mg/l	during gestation
Phenol	Ingestion	Not classified for female reproduction	Rat	NOAEL 321 mg/kg/day	2 generation
Phenol	Ingestion	Not classified for male reproduction	Rat	NOAEL 321 mg/kg/day	2 generation
Phenol	Ingestion	Not classified for development	Rat	NOAEL 120 mg/kg/day	during organogenesis
Methanol	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,600 mg/kg/day	21 days
Methanol	Ingestion	Toxic to development	Mouse	LOAEL 4,000 mg/kg/day	during organogenesis
Methanol	Inhalation	Toxic to development	Mouse	NOAEL 1.3 mg/l	during organogenesis
Methyl Isobutyl Ketone	Inhalation	Not classified for female reproduction	Multiple animal species	NOAEL 8.2 mg/l	2 generation
Methyl Isobutyl Ketone	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	13 weeks
Methyl Isobutyl Ketone	Inhalation	Not classified for male reproduction	Multiple animal species	NOAEL 8.2 mg/l	2 generation
Methyl Isobutyl Ketone	Inhalation	Not classified for development	Mouse	NOAEL 12.3 mg/l	during organogenesis
DIPHENYLAMINE	Ingestion	Not classified for female reproduction	Rat	NOAEL 1500 ppm in the diet	2 generation
DIPHENYLAMINE	Ingestion	Not classified for male reproduction	Rat	NOAEL 1500 ppm in the diet	2 generation
DIPHENYLAMINE	Ingestion	Not classified for development	Rat	NOAEL 500 ppm in the diet	2 generation

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Ethyl acetate	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Ethyl acetate	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Ethyl acetate	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Ethanol	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	LOAEL 9.4 mg/l	not available
Ethanol	Inhalation	central nervous system depression	Not classified	Human and animal	NOAEL not available	
Ethanol	Ingestion	central nervous system depression	Not classified	Multiple animal species	NOAEL not available	
Ethanol	Ingestion	kidney and/or bladder	Not classified	Dog	NOAEL 3,000 mg/kg	
Butanone	Inhalation	central nervous system depression	May cause drowsiness or dizziness	official classifica	NOAEL Not available	

				tion		
Butanone	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Butanone	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professio nal judgeme nt	NOAEL Not available	
Butanone	Ingestion	liver			NOAEL Not available	not applicable
Butanone	Ingestion	kidney and/or bladder			LOAEL 1,080 mg/kg	not applicable
Phenol	Dermal	hematoppoitic system	Causes damage to organs	Rat	LOAEL 108 mg/kg	not available
Phenol	Dermal	heart nervous system kidney and/or bladder	Causes damage to organs	Rat	LOAEL 107 mg/kg	24 hours
Phenol	Dermal	liver	Not classified	Human	NOAEL Not available	not available
Phenol	Inhalation	respiratory irritation	May cause respiratory irritation	Multiple animal species	NOAEL Not available	not available
Phenol	Ingestion	kidney and/or bladder	Causes damage to organs	Rat	NOAEL 120 mg/kg/day	not applicable
Phenol	Ingestion	respiratory system	Causes damage to organs	Human	NOAEL not available	poisoning and/or abuse
Phenol	Ingestion	endocrine system liver	ne system Not classified		NOAEL 224 mg/kg	not applicable
Phenol	Ingestion	heart	Not classified	Human	NOAEL Not available	poisoning and/or abuse
Methanol	Inhalation	blindness	Causes damage to organs	Human	NOAEL Not available	occupational exposure
Methanol	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	not available
Methanol	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL Not available	6 hours
Methanol	Ingestion	blindness	Causes damage to organs	Human	NOAEL Not available	poisoning and/or abuse
Methanol	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse
Methyl Isobutyl Ketone	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	LOAEL 0.1 mg/l	2 hours
Methyl Isobutyl Ketone	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Methyl Isobutyl Ketone	Inhalation	vascular system	Not classified	Dog	NOAEL Not available	not available
Methyl Isobutyl Ketone	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Rat	LOAEL 900 mg/kg	not applicable
DIPHENYLAMINE	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Ethyl acetate	Inhalation	endocrine system liver nervous system	Not classified	Rat	NOAEL 0.043 mg/l	90 days
Ethyl acetate	Inhalation	hematopoietic system	Not classified	Rabbit	LOAEL 16 mg/l	40 days
Ethyl acetate	Ingestion	hematopoietic system liver kidney and/or bladder	Not classified	Rat	NOAEL 3,600 mg/kg/day	90 days
Ethanol	Inhalation	liver	Some positive data exist, but the	Rabbit	LOAEL 124	365 days

Page: 12 of 20

			data are not sufficient for classification		mg/l	
Ethanol	Inhalation	hematopoietic	Not classified	Rat	NOAEL 25	14 days
LuidiiVi	iiiiaiatioii	system immune system	Trot classificu	Rat	mg/l	14 days
Ethanol	Ingestion	liver	data are not sufficient for classification		LOAEL 8,000 mg/kg/day	4 months
Ethanol	Ingestion	kidney and/or bladder			NOAEL 3,000 mg/kg/day	7 days
Butanone	Dermal	nervous system	Not classified	Guinea pig	NOAEL Not available	31 weeks
Butanone	Inhalation	liver kidney and/or bladder heart endocrine system gastrointestinal tract bone, teeth, nails, and/or hair hematopoietic system immune system muscles	Not classified	Rat	NOAEL 14.7 mg/l	90 days
Butanone	Ingestion	liver	Not classified	Rat	NOAEL Not available	7 days
Butanone	Ingestion	nervous system	Not classified	Rat	NOAEL 173 mg/kg/day	90 days
Phenol	Dermal	nervous system	May cause damage to organs though prolonged or repeated exposure	Rabbit	LOAEL 260 mg/kg/day	18 days
Phenol	Inhalation	heart liver kidney and/or bladder respiratory system	Causes damage to organs through prolonged or repeated exposure	Guinea pig	LOAEL 0.1 mg/l	41 days
Phenol	Inhalation	nervous system	May cause damage to organs though prolonged or repeated exposure	Multiple animal species	LOAEL 0.1 mg/l	14 days
Phenol	Inhalation	hematopoietic system	Not classified	Human	NOAEL Not available	occupational exposure
Phenol	Inhalation	immune system	Not classified	Rat	NOAEL 0.1 mg/l	2 weeks
Phenol	Ingestion	kidney and/or bladder	Causes damage to organs through prolonged or repeated exposure	Rat	NOAEL 12 mg/kg/day	14 days
Phenol	Ingestion	hematopoietic system	Causes damage to organs through prolonged or repeated exposure	Mouse	LOAEL 1.8 mg/kg/day	28 days
Phenol	Ingestion	nervous system	May cause damage to organs though prolonged or repeated exposure	Rat	LOAEL 308 mg/kg/day	13 weeks
Phenol	Ingestion	liver	Not classified	Rat	NOAEL 40 mg/kg/day	14 days
Phenol	Ingestion	respiratory system	Not classified	Rat	LOAEL 40 mg/kg/day	14 days
Phenol	Ingestion	immune system	Not classified	Mouse	NOAEL 1.8 mg/kg/day	28 days
Phenol	Ingestion	endocrine system	Not classified	Rat	NOAEL 120 mg/kg/day	14 days
Phenol	Ingestion	skin bone, teeth, nails, and/or hair	Not classified	Multiple animal species	NOAEL 1,204 mg/kg/day	103 weeks
Methanol	Inhalation	liver	Not classified	Rat	NOAEL 6.55 mg/l	4 weeks
Methanol	Inhalation	respiratory system	Not classified	Rat	NOAEL 13.1 mg/l	6 weeks
Methanol	Ingestion	liver nervous system	Not classified	Rat	NOAEL 2,500 mg/kg/day	90 days
Methyl Isobutyl Ketone	Inhalation	liver	Not classified	Rat	NOAEL 0.41 mg/l	13 weeks
Methyl Isobutyl Ketone	Inhalation	heart	Not classified	Multiple animal	NOAEL 0.8 mg/l	2 weeks

Page: 13 of 20

				anagios		
Mal II I a III a	T 1 1 4	1:1 1/	N. 4 1 'C' 1	species	NOAEL 0.4	00.1
Methyl Isobutyl Ketone	Inhalation	kidney and/or	Not classified	Multiple	NOAEL 0.4	90 days
		bladder		animal	mg/l	
				species		
Methyl Isobutyl Ketone	Inhalation	respiratory system	Not classified	Multiple	NOAEL 4.1	14 weeks
				animal	mg/l	
				species		
Methyl Isobutyl Ketone	Inhalation	endocrine system	Not classified	Multiple	NOAEL 0.41	90 days
		hematopoietic		animal	mg/l	
		system		species		
Methyl Isobutyl Ketone	Inhalation	nervous system	Not classified	Multiple	NOAEL 0.41	13 weeks
				animal	mg/l	
				species	-	
Methyl Isobutyl Ketone	Ingestion	endocrine system	Not classified	Rat	NOAEL	13 weeks
,		hematopoietic			1,000	
		system liver			mg/kg/day	
		kidney and/or				
		bladder				
Methyl Isobutyl Ketone	Ingestion	heart immune	Not classified	Rat	NOAEL	120 days
		system muscles			1,040	
		nervous system			mg/kg/day	
		respiratory system				
DIPHENYLAMINE	Dermal	skin	Not classified	Rat	LOAEL 500	90 days
					mg/kg/day	,
DIPHENYLAMINE	Dermal	kidney and/or	Not classified	Rat	NOAEL	90 days
		bladder			2,000	
		hematopoietic			mg/kg/day	
		system				
DIPHENYLAMINE	Ingestion	hematopoietic	Some positive data exist, but the	Rat	NOAEL 333	28 days
	3.2	system kidney	data are not sufficient for		mg/kg/day	
		and/or bladder	classification			
DIPHENYLAMINE	Ingestion	gastrointestinal tract	Not classified	Rat	NOAEL 333	28 days
· · · · · · · · ·	3.2				mg/kg/day	
DIPHENYLAMINE	Ingestion	liver	Not classified	Rat	NOAEL	28 days
					1,000	
					mg/kg/day	
			1		mg/kg/day	1

Aspiration Hazard

Name	Value
Methyl Isobutyl Ketone	Some positive data exist, but the data are not sufficient for
	classification

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labelling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

12.1. Toxicity

Acute aquatic hazard:

GHS Acute 3: Harmful to aquatic life.

Chronic aquatic hazard:

GHS Chronic 3: Harmful to aquatic life with long lasting effects.

No product test data available.

Material	CAS Nbr	Organism	Туре	Exposure	Test endpoint	Test result
Ethyl acetate	141-78-6	Bacteria	Experimental	18 hours	EC10	2,900 mg/l
Ethyl acetate	141-78-6	Fish	Experimental	96 hours	LC50	212.5 mg/l
Ethyl acetate	141-78-6	Invertebrate	Experimental	48 hours	EC50	165 mg/l
Ethyl acetate	141-78-6	Green algae	Experimental	72 hours	NOEC	100 mg/l
Ethyl acetate	141-78-6	Water flea	Experimental	21 days	NOEC	2.4 mg/l
Acrylonitrile-	9003-18-3		Data not			N/A
Butadiene			available or			
Polymer			insufficient for			
			classification			
Ethanol	64-17-5	Fathead	Experimental	96 hours	LC50	14,200 mg/l
		minnow				
Ethanol	64-17-5	Fish	Experimental	96 hours	LC50	11,000 mg/l
Ethanol	64-17-5	Green algae	Experimental	72 hours	EC50	275 mg/l
Ethanol	64-17-5	Water flea	Experimental	48 hours	LC50	5,012 mg/l
Ethanol	64-17-5	Green algae	Experimental	72 hours	ErC10	11.5 mg/l
Ethanol	64-17-5	Water flea	Experimental	10 days	NOEC	9.6 mg/l
Phenolic Resin	9039-25-2		Data not			N/A
			available or insufficient for			
			classification			
Butanone	78-93-3	Fathead	Experimental	96 hours	LC50	2,993 mg/l
Dutanone	76-73-3	minnow	Experimental	90 Hours	LC30	2,993 mg/1
Butanone	78-93-3	Green algae	Experimental	96 hours	ErC50	2,029 mg/l
Butanone	78-93-3	Water flea	Experimental	48 hours	EC50	308 mg/l
Butanone	78-93-3	Green algae	Experimental	96 hours	ErC10	1,289 mg/l
Butanone	78-93-3	Water flea	Experimental	21 days	NOEC	100 mg/l
Butanone	78-93-3	Bacteria	Experimental	16 hours	LOEC	1,150 mg/l
Phenol	108-95-2	Bacteria	Experimental	24 hours	IC50	21 mg/l
Phenol	108-95-2	Green algae	Experimental	96 hours	EC50	61.1 mg/l
Phenol	108-95-2	Rainbow trout	Experimental	96 hours	LC50	8.9 mg/l
Phenol	108-95-2	Water flea	Experimental	48 hours	EC50	3.1 mg/l
Phenol	108-95-2	Fish	Experimental	60 days	NOEC	0.077 mg/l
Phenol	108-95-2	Water flea	Experimental	16 days	NOEC	0.16 mg/l
DIPHENYLA	122-39-4	Green algae	Experimental	72 hours	EC50	0.43 mg/l
MINE						
DIPHENYLA	122-39-4	Invertebrate	Experimental	96 hours	EC50	1.22 mg/l
MINE						
DIPHENYLA	122-39-4	Rainbow trout	Experimental	96 hours	LC50	2.2 mg/l
MINE	122 20 4	W-4 0	Experimental	40 1,	ECEO	0.21/1
DIPHENYLA MINE	122-39-4	Water flea	Experimental	48 hours	EC50	0.31 mg/l
DIPHENYLA	122-39-4	Green algae	Experimental	72 hours	NOEC	0.027 mg/l
MINE	122-39-4	Green argae	Experimental	72 Hours	NOLC	0.027 mg/1
DIPHENYLA	122-39-4	Water flea	Experimental	21 days	NOEC	0.13 mg/l
MINE	122 37 7	1, 4101 1104	Zaperimentui	21 days	l'iole	0.13 1116/1
Cresol	1319-77-3	Activated	Estimated	3 hours	EC50	461.4 mg/l
		sludge				3
Cresol	1319-77-3	Fish	Estimated	96 hours	LC50	3.36 mg/l
Cresol	1319-77-3	Fish	Estimated	96 hours	LC50	4.4 mg/l
Cresol	1319-77-3	Water flea	Estimated	48 hours	EC50	7.7 mg/l
Cresol	1319-77-3	Fathead	Estimated	32 days	NOEC	1.35 mg/l

Page: 15 of 20

		minnow				
Cresol	1319-77-3	Water flea	Estimated	21 days	NOEC	1 mg/l
Methanol	67-56-1	Activated sludge	Experimental	3 hours	IC50	>1,000 mg/l
Methanol	67-56-1	Algae or other aquatic plants	Experimental	96 hours	EC50	16.9 mg/l
Methanol	67-56-1	Bluegill	Experimental	96 hours	LC50	15,400 mg/l
Methanol	67-56-1	Green algae	Experimental	96 hours	EC50	22,000 mg/l
Methanol	67-56-1	Water flea	Experimental	24 hours	EC50	20,803 mg/l
Methanol	67-56-1	Algae or other aquatic plants	Experimental	96 hours	NOEC	9.96 mg/l
Methanol	67-56-1	Water flea	Experimental	21 days	NOEC	122 mg/l
Methyl Isobutyl Ketone	108-10-1	Green algae	Experimental	96 hours	EC50	400 mg/l
Methyl Isobutyl Ketone	108-10-1	Water flea	Experimental	48 hours	EC50	>200 mg/l
Methyl Isobutyl Ketone	108-10-1	Zebra Fish	Experimental	96 hours	LC50	>179 mg/l
Methyl Isobutyl Ketone	108-10-1	Fathead minnow	Experimental	32 days	NOEC	56.2 mg/l
Methyl Isobutyl Ketone	108-10-1	Water flea	Experimental	21 days	NOEC	78 mg/l
Methyl Isobutyl Ketone	108-10-1	Activated sludge	Experimental	30 minutes	EC50	>1,000
2,5-Di-tert- pentylhydroqui none	79-74-3	Activated sludge	Experimental	3 hours	EC50	>100 mg/l
2,5-Di-tert- pentylhydroqui none	79-74-3	Bluegill	Experimental	96 hours	LC50	0.013 mg/l
2,5-Di-tert- pentylhydroqui none	79-74-3	Green algae	Experimental	96 hours	EC50	2.9 mg/l
2,5-Di-tert- pentylhydroqui none	79-74-3	Water flea	Experimental	48 hours	LC50	0.9 mg/l

12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Ethyl acetate	141-78-6	Experimental		Photolytic half-	20.0 days (t	Non-standard method
		Photolysis		life (in air)	1/2)	
Ethyl acetate	141-78-6	Experimental	14 days	BOD	94 %BOD/ThB	OECD 301C - MITI
		Biodegradation	-		OD	test (I)
Acrylonitrile-	9003-18-3	Data not	N/A	N/A	N/A	N/A
Butadiene		available-				
Polymer		insufficient				
Ethanol	64-17-5	Experimental	14 days	BOD	89 %BOD/ThB	OECD 301C - MITI

Page: 16 of 20

		Biodegradation			OD	test (I)
Phenolic Resin	9039-25-2	Data not available-insufficient	N/A	N/A	N/A	N/A
Butanone	78-93-3	Experimental Biodegradation	28 days	BOD	98 %BOD/ThB OD	OECD 301D - Closed bottle test
Phenol	108-95-2	Experimental Biodegradation	100 hours	BOD	62 %BOD/ThB OD	OECD 301C - MITI test (I)
DIPHENYLA MINE	122-39-4	Experimental Biodegradation	28 days	BOD	26 % weight	OECD 301D - Closed bottle test
Cresol	1319-77-3	Estimated Biodegradation	28 days	BOD	65 %BOD/ThB OD	OECD 301D - Closed bottle test
Methanol	67-56-1	Experimental Biodegradation	14 days	BOD	92 %BOD/ThB OD	OECD 301C - MITI test (I)
Methyl Isobutyl Ketone	108-10-1	Experimental Photolysis		Photolytic half- life (in air)	2.3 days (t 1/2)	
Methyl Isobutyl Ketone	108-10-1	Experimental Biodegradation	28 days	BOD	83 %BOD/ThB OD	OECD 301F - Manometric respirometry
2,5-Di-tert- pentylhydroqui none	79-74-3	Data not available-insufficient	N/A	N/A	N/A	N/A

12.3 : Bioaccumulative potential

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Ethyl acetate	141-78-6	Experimental Bioconcentrati		Log Kow	0.68	Non-standard method
Acrylonitrile- Butadiene Polymer	9003-18-3	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Ethanol	64-17-5	Experimental Bioconcentrati on		Log Kow	-0.35	Non-standard method
Phenolic Resin	9039-25-2	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Butanone	78-93-3	Experimental Bioconcentrati on		Log Kow	0.3	OECD 117 log Kow HPLC method
Phenol	108-95-2	Experimental Bioconcentrati on		Log Kow	1.47	Non-standard method
DIPHENYLA MINE	122-39-4	Experimental BCF - Carp	56 days	Bioaccumulatio n factor	253	OECD 305E - Bioaccumulation flow- through fish test
Cresol	1319-77-3	Experimental Bioconcentrati on		Log Kow	1.95	Non-standard method
Methanol	67-56-1	Experimental		Log Kow	-0.77	Non-standard method

		Bioconcentrati			
		on			
Methyl	108-10-1	Experimental	Log Kow	1.9	OECD 117 log Kow
Isobutyl		Bioconcentrati			HPLC method
Ketone		on			
2,5-Di-tert-	79-74-3	Experimental	Log Kow	3.3	Non-standard method
pentylhydroqui		Bioconcentrati			
none		on			

12.4. Mobility in soil

Please contact manufacturer for more details

12.5 Other Adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. As a disposal alternative, utilize an acceptable permitted waste disposal facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

SECTION 14: Transport Information

Air Transport (IATA)Regulations

UN No UN1133

Proper Shipping Name Adhesives

Hazard Classs/Division 3
Subsidiary Risk Not applicable

Packing Group: II

Marine Transport (IMDG)

UN No UN1133

Proper Shipping Name Adhesives

Hazard Classs/Division 3
Subsidiary Risk Not applicable

Packing Group: II

Environmental Hazards: Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Japan Chemical Substance Control Law. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in

compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

Applicable Environmental, Health and Safety Regulations

The Manufacture, Storage and Import of Hazardous Chemical Rules, 1989 Hazardous Waste(Management, Handling & Transboundary) Rules, 2008 Hazardous Chemicals (Classification, Packaging and Labelling Draft Rules), 2011

The following ingredients are listed as hazardous on Part II of Schedule I of the India Manufacture, Storage and Import of Hazardous Chemicals (MSIHC) rules

2-Butanone

Ethyl acetate

Ethanol

Methanol

Butanone

Methyl Isobutyl Ketone

Phenol

The following ingredients are classified as hazardous based on the criteria listed under Part I of Schedule I of the India Manufacture, Storage and Import of Hazardous Chemicals (MSIHC) rules:

The product is classified as Very Highly Flammable liquid as per MSIHC Rules, 1989.

SECTION 16: Other information

NFPA Hazard Classification

Health: 3 Flammability: 3 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Revision information:

Section 1: Product identification numbers information was deleted.

Label: GHS Classification information was modified.

Label: GHS Precautionary - Disposal information was deleted.

Label: GHS Precautionary - Prevention information was modified.

Label: GHS Precautionary - Response information was modified.

Label: GHS Target Organ Hazard Statement information was modified.

Label: Signal Word information was modified.

Label: Symbol information was modified.

Section 2: Ingredient table information was modified.

Section 8: Occupational exposure limit table information was modified.

Section 09: Nanoparticle information was deleted.

Section 09: Percent Volatile information was modified.

Section 09: Volatile Organic Compounds information was modified.

Section 11: Acute Toxicity table information was modified.

Section 11: Carcinogenicity Table information was modified.

Section 11: Germ Cell Mutagenicity Table information was modified.

Section 11: Reproductive Toxicity Table information was modified.

Section 11: Serious Eye Damage/Irritation Table information was modified.

3MTM Nitrile Plastic Adhesive 826

Section 11: Skin Corrosion/Irritation Table information was modified.

Section 11: Skin Sensitization Table information was modified.

Section 11: Target Organs - Repeated Table information was modified.

Section 11: Target Organs - Single Table information was modified.

Section 12: Component ecotoxicity information information was modified.

Prints No Data if Adverse effects information is not present information was added.

Section 12: Persistence and Degradability information information was modified.

Section 12:Bioccumulative potential information information was modified.

Section 15: MSIHC Ingredients information was modified.

DISCLAIMER: The information in this Safety Data Sheet (SDS) is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this SDS or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own evaluation to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into India, you are responsible to comply with all applicable regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration/notification.

3M India SDSs are available at http://solutions.3mindia.co.in