

Safety Data Sheet

Copyright, 2022, 3M India Limited. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document group:
 16-5850-9
 Version number:
 1.02

 Issue Date:
 22/05/2022
 Supersedes date:
 31/12/2021

This Safety Data Sheet has been prepared in accordance with the GHS guidelines & India Hazardous substances (Classification, Labeling & Packaging) Draft Rules 2011.

SECTION 1: Identification

1.1. Product identifier

3MTM Marine Adhesive Sealant Fast Cure 5200, White; PN 06520, 05220, 06534, 06535

1.2. Recommended use and restrictions on use

Recommended use

Adhesive Sealant, Sealant.

1.3. Supplier's details

Address: 3M India Limited, plot-48-51, Electronic city, Hosur road, Bangalore-560100

Telephone: 080-45543000, contact Product EHS team

E Mail: productehs.in@mmm.com
Website: http://solutions.3mindia.co.in

1.4. Emergency telephone number

080-45543000 (Contact hours: 8:00 AM to 5:00 PM)

SECTION 2: Hazard identification

Under MSIHC Rules, information is noted below on flammability, acute toxicity and explosivity relevant to this product. In line with international standards, information on other hazard classes and associated precautionary statements relevant to this product are included as well.

2.1. Classification of the substance or mixture

Skin Corrosion/Irritation: Category 3. Respiratory Sensitizer: Category 1.

Skin Sensitizer: Category 1.

Reproductive Toxicity: Category 1B.

Specific Target Organ Toxicity (repeated exposure): Category 1.

Acute Aquatic Toxicity: Category 2. Chronic Aquatic Toxicity: Category 2.

2.2. Label elements

Signal Word

Danger

Symbols

Health Hazard | Environment |

Pictograms





HAZARD STATEMENTS:

H316 Causes mild skin irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction. H360 May damage fertility or the unborn child.

H372 Causes damage to organs through prolonged or repeated exposure: respiratory system.

H411 Toxic to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENTS

General:

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

Prevention:

P201 Obtain special instructions before use.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P273 Avoid release to the environment.

P280K Wear protective gloves and respiratory protection.

Response:

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P308 + P313 IF exposed or concerned: Get medical advice/attention.
P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.
P342 + P311 If experiencing respiratory symptoms: Call a POISON CENTER or

doctor/physician.

P391 Collect spillage.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents/container in accordance with applicable

local/regional/national/international regulations.

2.3. Other hazards

Persons previously sensitised to isocyanates may develop a cross-sensitisation reaction to other isocyanates. Titanium dioxide - no exposure Although titanium dioxide is classified as a carcinogen, exposures associated with this health effect are not expected during normal, intended use of this product.

SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	CAS Nbr	% by Wt
Urethane Polymer	51447-37-1	40 - 70
Titanium dioxide	13463-67-7	10 - 30
Synthetic Amorphous Silica	112945-52-5	1 - 5
4,4'-methylenediphenyl diisocyanate	101-68-8	< 2.4
Zinc oxide	1314-13-2	< 2.3
Alkyl Isocyanate Silane	85702-90-5	< 2
Aluminium hydroxide	21645-51-2	< 2
2-(2-Ethoxyethoxy)ethyl acetate	112-15-2	< 2.0
Fumed silica	7631-86-9	1 - 2
Toluene	108-88-3	< 1
Heptane	142-82-5	< 0.3
(Gamma-mercaptopropyl)trimethoxysilane	4420-74-0	< 0.2

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye contact

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Allergic respiratory reaction (difficulty breathing, wheezing, cough, and tightness of chest). Allergic skin reaction (redness, swelling, blistering, and itching). Target organ effects following prolonged or repeated exposure. See Section 11 for additional details.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable Extinguishing media

Use a fire fighting agent suitable for the surrounding fire.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

Substance	Condition
Isocyanates	During combustion.
Carbon monoxide.	During combustion.
Carbon dioxide.	During combustion.
Hydrogen cyanide.	During combustion.
Oxides of nitrogen.	During combustion.
Oxides of sulphur.	During combustion.

Toxic vapour, gas, particulate.

During combustion.

5.3. Special protective actions for fire-fighters

No special protective actions for fire-fighters are anticipated.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Pour isocyanate decontaminant solution (90% water, 8% concentrated ammonia, 2% detergent) on spill and allow to react for 10 minutes. Or pour water on spill and allow to react for more than 30 minutes. Cover with absorbent material. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a container approved for transportation by appropriate authorities, but do not seal the container for 48 hours to avoid pressure build-up. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Keep out of reach of children. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Use personal protective equipment (eg. gloves, respirators...) as required.

7.2. Conditions for safe storage including any incompatibilities

Keep container tightly closed to prevent contamination with water or air. If contamination is suspected, do not reseal container. Store away from amines.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
4,4'-methylenediphenyl	101-68-8	ACGIH	TWA:0.005 ppm	
diisocyanate				
Toluene	108-88-3	ACGIH	TWA:20 ppm	A4: Not class. as human
				carcin, Ototoxicant
Zinc oxide	1314-13-2	ACGIH	TWA(respirable fraction):2	
			mg/m3;STEL(respirable	

			fraction):10 mg/m3	
Titanium dioxide	13463-67-7	ACGIH	TWA:10 mg/m ³	A4: Not class. as human
				carcin
Heptane	142-82-5	ACGIH	TWA:400 ppm;STEL:500 ppm	
Aluminum, insoluble compounds	21645-51-2	ACGIH	TWA(respirable fraction):1	A4: Not class. as human
_			mg/m3	carcin

ACGIH: American Conference of Governmental Industrial Hygienists

AIHA: American Industrial Hygiene Association

CMRG: Chemical Manufacturer's Recommended Guidelines

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

None required.

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

information on basic physical and chemical properties			
Physical state	Liquid.		
Specific Physical Form:	Paste		
Color	White		
Odor	Slight Urethane		
Odour threshold	No data available.		
pH	Not applicable.		
Melting point/Freezing point: NA	Not applicable.		

Boiling point/Initial boiling point/Boiling range	Not applicable.	
Flash point	No flash point	
Evaporation rate	No data available.	
Flammability (solid, gas)	Not applicable.	
Flammable Limits(LEL)	Not applicable.	
Flammable Limits(UEL)	Not applicable.	
Vapour pressure	No data available.	
Vapor Density and/or Relative Vapor Density	No data available.	
Density	1.3 g/ml	
Relative density	1.3 [Ref Std:WATER=1]	
Water solubility	Nil	
Solubility- non-water	No data available.	
Partition coefficient: n-octanol/water	No data available.	
Autoignition temperature	No data available.	
Decomposition temperature	No data available.	
Viscosity/Kinematic Viscosity	100,000 - 500,000 mPa-s	
Volatile organic compounds (VOC)	38 g/l [Test Method:tested per EPA method 24] [Details:EU	
	VOC content]	
Percent volatile	2.83 % weight	
VOC less H2O & exempt solvents	38 g/l [Test Method:tested per EPA method 24]	
Molecular weight	No data available.	

SECTION 10: Stability and reactivity

10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

None known.

10.5 Incompatible materials

Amines.

Alcohols.

Water

10.6 Hazardous decomposition products

Substance

Condition

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be

relevant to the material as a whole.

11.1 Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. Allergic respiratory reaction: Signs/symptoms may include difficulty breathing, wheezing, cough, and tightness of chest. May cause additional health effects (see below).

Skin contact

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye contact

Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea. May cause additional health effects (see below).

Additional Health Effects:

Prolonged or repeated exposure may cause target organ effects:

Respiratory effects: Signs/symptoms may include cough, shortness of breath, chest tightness, wheezing, increased heart rate, bluish coloured skin (cyanosis), sputum production, changes in lung function tests, and respiratory failure.

Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

Additional information:

Persons previously sensitised to isocyanates may develop a cross-sensitisation reaction to other isocyanates.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Inhalation- Vapor(4 hr)		No data available; calculated ATE >50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Urethane Polymer	Dermal		LD50 estimated to be > 5,000 mg/kg
Urethane Polymer	Ingestion	Rat	LD50 > 5,000 mg/kg
Titanium dioxide	Dermal	Rabbit	LD50 > 10,000 mg/kg
Titanium dioxide	Inhalation-	Rat	LC50 > 6.82 mg/l
	Dust/Mist (4 hours)		
Titanium dioxide	Ingestion	Rat	LD50 > 10,000 mg/kg
Synthetic Amorphous Silica	Dermal	Rabbit	LD50 > 5,000 mg/kg
Synthetic Amorphous Silica	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Synthetic Amorphous Silica	Ingestion	Rat	LD50 > 5,110 mg/kg
4,4'-methylenediphenyl diisocyanate	Dermal	Rabbit	LD50 > 5,000 mg/kg

4,4'-methylenediphenyl diisocyanate	Inhalation- Dust/Mist (4 hours)	Rat	LC50 0.368 mg/l
4,4'-methylenediphenyl diisocyanate	Ingestion	Rat	LD50 31,600 mg/kg
Zinc oxide	Dermal		LD50 estimated to be > 5,000 mg/kg
Zinc oxide	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 5.7 mg/l
Zinc oxide	Ingestion	Rat	LD50 > 5,000 mg/kg
2-(2-Ethoxyethoxy)ethyl acetate	Dermal	Rabbit	LD50 15,000 mg/kg
2-(2-Ethoxyethoxy)ethyl acetate	Ingestion	Rat	LD50 11,000 mg/kg
Fumed silica	Dermal	Rabbit	LD50 > 5,000 mg/kg
Fumed silica	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Fumed silica	Ingestion	Rat	LD50 > 5,110 mg/kg
Aluminium hydroxide	Dermal		LD50 estimated to be > 5,000 mg/kg
Aluminium hydroxide	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 2.3 mg/l
Aluminium hydroxide	Ingestion	Rat	LD50 > 5,000 mg/kg
Toluene	Dermal	Rat	LD50 12,000 mg/kg
Toluene	Inhalation- Vapor (4 hours)	Rat	LC50 30 mg/l
Toluene	Ingestion	Rat	LD50 5,550 mg/kg
Heptane	Dermal	Rabbit	LD50 3,000 mg/kg
Heptane	Inhalation- Vapor (4 hours)	Rat	LC50 103 mg/l
Heptane	Ingestion	Rat	LD50 > 15,000 mg/kg
(Gamma-mercaptopropyl)trimethoxysilane	Dermal	Rabbit	LD50 2,270 mg/kg
(Gamma-mercaptopropyl)trimethoxysilane	Ingestion	Rat	LD50 770 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Titanium dioxide	Rabbit	No significant irritation
Synthetic Amorphous Silica	Rabbit	No significant irritation
4,4'-methylenediphenyl diisocyanate	official	Irritant
	classificat	
	ion	
Zinc oxide	Human	No significant irritation
	and	
	animal	
2-(2-Ethoxyethoxy)ethyl acetate	Human	Minimal irritation
	and	
	animal	
Fumed silica	Rabbit	No significant irritation
Aluminium hydroxide	Rabbit	No significant irritation
Toluene	Rabbit	Irritant
Heptane	Human	Mild irritant
(Gamma-mercaptopropyl)trimethoxysilane	Rabbit	No significant irritation

Serious Eve Damage/Irritation

Name	Species	Value
Titanium dioxide	Rabbit	No significant irritation
Synthetic Amorphous Silica	Rabbit	No significant irritation
4,4'-methylenediphenyl diisocyanate	official classificat	Severe irritant
	ion	
Zinc oxide	Rabbit	Mild irritant

Page: 8 of 18

2-(2-Ethoxyethoxy)ethyl acetate	Rabbit	Severe irritant
Fumed silica	Rabbit	No significant irritation
Aluminium hydroxide	Rabbit	No significant irritation
Toluene	Rabbit	Moderate irritant
Heptane	Professio	Moderate irritant
	nal	
	judgemen	
	t	
(Gamma-mercaptopropyl)trimethoxysilane	Rabbit	No significant irritation

Sensitization:

Skin Sensitisation

Name	Species	Value
Tune	Species	, and
Titanium dioxide	Human	Not classified
	and	
	animal	
Synthetic Amorphous Silica	Human	Not classified
	and	
	animal	
4,4'-methylenediphenyl diisocyanate	official	Sensitising
	classificat	
	ion	
Zinc oxide	Guinea	Not classified
	pig	
2-(2-Ethoxyethoxy)ethyl acetate	Human	Not classified
	and	
	animal	
Fumed silica	Human	Not classified
	and	
	animal	
Aluminium hydroxide	Guinea	Not classified
·	pig	
Toluene	Guinea	Not classified
	pig	
(Gamma-mercaptopropyl)trimethoxysilane	Guinea	Sensitising
	pig	

Respiratory Sensitisation

Tree pri wood y semination								
Name	Species	Value						
4 4'-methylenediphenyl diisocyanate	Human	Sensitising						

Germ Cell Mutagenicity

Name	Route	Value
Titanium dioxide	In Vitro	Not mutagenic
Titanium dioxide	In vivo	Not mutagenic
Synthetic Amorphous Silica	In Vitro	Not mutagenic
4,4'-methylenediphenyl diisocyanate	In Vitro	Some positive data exist, but the data are not sufficient for classification
Zinc oxide	In Vitro	Some positive data exist, but the data are not sufficient for classification
Zinc oxide	In vivo	Some positive data exist, but the data are not sufficient for classification
2-(2-Ethoxyethoxy)ethyl acetate	In Vitro	Not mutagenic
Fumed silica	In Vitro	Not mutagenic
Toluene	In Vitro	Not mutagenic
Toluene	In vivo	Not mutagenic
Heptane	In Vitro	Not mutagenic
(Gamma-mercaptopropyl)trimethoxysilane	In Vitro	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
Titanium dioxide	Ingestion	Multiple animal species	Not carcinogenic
Titanium dioxide	Inhalation	Rat	Carcinogenic.
Synthetic Amorphous Silica	Not specified.	Mouse	Some positive data exist, but the data are not sufficient for classification
4,4'-methylenediphenyl diisocyanate	Inhalation	Rat	Some positive data exist, but the data are not sufficient for classification
Fumed silica	Not specified.	Mouse	Some positive data exist, but the data are not sufficient for classification
Aluminium hydroxide	Not specified.	Multiple animal species	Not carcinogenic
Toluene	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Toluene	Ingestion	Rat	Some positive data exist, but the data are not sufficient for classification
Toluene	Inhalation	Mouse	Some positive data exist, but the data are not sufficient for classification

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
Synthetic Amorphous Silica	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Synthetic Amorphous Silica	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Synthetic Amorphous Silica	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis
4,4'-methylenediphenyl diisocyanate	Inhalation	Not classified for development	Rat	NOAEL 0.004 mg/l	during organogenesis
Zinc oxide	Ingestion	Not classified for reproduction and/or development	Multiple animal species	NOAEL 125 mg/kg/day	premating & during gestation
Fumed silica	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Fumed silica	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Fumed silica	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis
Aluminium hydroxide	Ingestion	Not classified for development	Rat	NOAEL 768 mg/kg/day	during organogenesis
Toluene	Inhalation	Not classified for female reproduction	Human	NOAEL Not available	occupational exposure
Toluene	Inhalation	Not classified for male reproduction	Rat	NOAEL 2.3 mg/l	1 generation
Toluene	Ingestion	Toxic to development	Rat	LOAEL 520 mg/kg/day	during gestation
Toluene	Inhalation	Toxic to development	Human	NOAEL Not available	poisoning and/or abuse

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Specific Target Organ Toxicity - single exposure								
Name	Route	Target Organ(s)	Value	Species	Test result	Exposure		
						Duration		
4,4'-methylenediphenyl	Inhalation	respiratory irritation	May cause respiratory irritation	official	NOAEL Not			
diisocyanate				classifica	available			
				tion				
2-(2-Ethoxyethoxy)ethyl	Inhalation	central nervous	May cause drowsiness or	Human	NOAEL Not	not applicable		

acetate		system depression	dizziness	and	available	
2-(2-Ethoxyethoxy)ethyl acetate	Ingestion	central nervous system depression	May cause drowsiness or dizziness	multiple animal species	NOAEL Not available	not applicable
Toluene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Toluene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Toluene	Inhalation	immune system	Not classified	Mouse	NOAEL 0.004 mg/l	3 hours
Toluene	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse
Heptane	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Heptane	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Heptane	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Titanium dioxide	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 0.01 mg/l	2 years
Titanium dioxide	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not available	occupational exposure
Synthetic Amorphous Silica	Inhalation	respiratory system silicosis	Not classified	Human	NOAEL Not available	occupational exposure
4,4'-methylenediphenyl diisocyanate	Inhalation	respiratory system	Causes damage to organs through prolonged or repeated exposure	Rat	LOAEL 0.004 mg/l	13 weeks
Zinc oxide	Ingestion	nervous system	Not classified	Rat	NOAEL 600 mg/kg/day	10 days
Zinc oxide	Ingestion	endocrine system hematopoietic system kidney and/or bladder	Not classified	Other	NOAEL 500 mg/kg/day	6 months
2-(2-Ethoxyethoxy)ethyl acetate	Inhalation	respiratory system liver immune system kidney and/or bladder	Not classified	Rat	NOAEL 0.48 mg/l	2 weeks
Fumed silica	Inhalation	respiratory system silicosis	Not classified	Human	NOAEL Not available	occupational exposure
Toluene	Inhalation	auditory system eyes olfactory system	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	poisoning and/or abuse
Toluene	Inhalation	nervous system	May cause damage to organs though prolonged or repeated exposure	Human	NOAEL Not available	poisoning and/or abuse
Toluene	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 2.3 mg/l	15 months
Toluene	Inhalation	heart liver kidney and/or bladder	Not classified	Rat	NOAEL 11.3 mg/l	15 weeks
Toluene	Inhalation	endocrine system	Not classified	Rat	NOAEL 1.1 mg/l	4 weeks
Toluene	Inhalation	immune system	Not classified	Mouse	NOAEL Not available	20 days
Toluene	Inhalation	bone, teeth, nails, and/or hair	Not classified	Mouse	NOAEL 1.1 mg/l	8 weeks
Toluene	Inhalation	hematopoietic system vascular system	Not classified	Human	NOAEL Not available	occupational exposure
Toluene	Inhalation	gastrointestinal tract	Not classified	Multiple	NOAEL 11.3	15 weeks

				animal species	mg/l	
Toluene	Ingestion	nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 625 mg/kg/day	13 weeks
Toluene	Ingestion	heart	Not classified	Rat	NOAEL 2,500 mg/kg/day	13 weeks
Toluene	Ingestion	liver kidney and/or bladder	Not classified	Multiple animal species	NOAEL 2,500 mg/kg/day	13 weeks
Toluene	Ingestion	hematopoietic system	Not classified	Mouse	NOAEL 600 mg/kg/day	14 days
Toluene	Ingestion	endocrine system	Not classified	Mouse	NOAEL 105 mg/kg/day	28 days
Toluene	Ingestion	immune system	Not classified	Mouse	NOAEL 105 mg/kg/day	4 weeks
Heptane	Inhalation	liver nervous system kidney and/or bladder	Not classified	Rat	NOAEL 12 mg/l	26 weeks

Aspiration Hazard

Name	Value
Toluene	Aspiration hazard
Heptane	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labelling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

12.1. Toxicity

Acute aquatic hazard:

GHS Acute 2: Toxic to aquatic life.

Chronic aquatic hazard:

GHS Chronic 2: Toxic to aquatic life with long lasting effects.

No product test data available.

Material	CAS Nbr	Organism	Type	Exposure	Test endpoint	Test result
Urethane Polymer	51447-37-1		Data not available or insufficient for classification			N/A
Titanium dioxide	13463-67-7	Activated sludge	Experimental	3 hours	NOEC	>=1,000 mg/l
Titanium dioxide	13463-67-7	Diatom	Experimental	72 hours	EC50	>10,000 mg/l
Titanium dioxide	13463-67-7	Fathead minnow	Experimental	96 hours	LC50	>100 mg/l
Titanium	13463-67-7	Water flea	Experimental	48 hours	EC50	>100 mg/l

dioxide						
Titanium	13463-67-7	Diatom	Experimental	72 hours	NOEC	5,600 mg/l
dioxide						
Synthetic	112945-52-5	Green algae	Experimental	72 hours	EC50	>100 mg/l
Amorphous						
Silica	112045 52 5	XX / O	E 1	241	EG50	. 100 //
Synthetic	112945-52-5	Water flea	Experimental	24 hours	EC50	>100 mg/l
Amorphous Silica						
Synthetic	112945-52-5	Zebra Fish	Experimental	96 hours	LC50	>100 mg/l
Amorphous	112945-32-3	Zeora Pisii	Experimental	90 Hours	LC30	100 mg/1
Silica						
Synthetic	112945-52-5	Green algae	Experimental	72 hours	NOEC	60 mg/l
Amorphous			r · · · · · ·			
Silica						
4,4'-	101-68-8	Activated	Estimated	3 hours	EC50	>100 mg/l
methylenediph		sludge				
enyl						
diisocyanate						
4,4'-	101-68-8	Green algae	Estimated	72 hours	EC50	>1,640 mg/l
methylenediph						
enyl						
diisocyanate	101-68-8	Water flea	Estimated	24 h	EC50	> 1 000 m ~/1
4,4'- methylenediph	101-08-8	w ater riea	Estimated	24 hours	EC30	>1,000 mg/l
enyl						
diisocyanate						
4,4'-	101-68-8	Zebra Fish	Estimated	96 hours	LC50	>1,000 mg/l
methylenediph	101 00 0	2014 1 1511	Estimated	yo nours		1,000 mg/1
enyl						
diisocyanate						
4,4'-	101-68-8	Green algae	Estimated	72 hours	NOEC	1,640 mg/l
methylenediph						
enyl						
diisocyanate						
4,4'-	101-68-8	Water flea	Estimated	21 days	NOEC	10 mg/l
methylenediph						
enyl						
diisocyanate Zinc oxide	1314-13-2	Activated	Estimated	3 hours	EC50	6.5 mg/l
Zific oxide	1314-13-2	sludge	Estimated	3 Hours	ECSU	0.3 mg/1
Zinc oxide	1314-13-2	Green algae	Estimated	72 hours	EC50	0.052 mg/l
Zinc oxide	1314-13-2	Rainbow trout	Estimated	96 hours	LC50	0.21 mg/l
Zinc oxide	1314-13-2	Water flea	Estimated	48 hours	EC50	0.07 mg/l
Zinc oxide	1314-13-2	Green algae	Estimated	72 hours	NOEC	0.006 mg/l
Zinc oxide	1314-13-2	Water flea	Estimated	7 days	NOEC	0.02 mg/l
Alkyl	85702-90-5		Data not			N/A
Isocyanate			available or			
Silane			insufficient for			
			classification			
Aluminium	21645-51-2	Fish	Experimental	96 hours	No tox obs at	>100 mg/l
hydroxide					lmt of water sol	
Aluminium	21645-51-2	Green algae	Experimental	72 hours	No tox obs at	>100 mg/l
hydroxide					lmt of water sol	

Aluminium	21645-51-2	Water flea	Experimental	48 hours	No tox obs at	>100 mg/l
hydroxide	210.3312	, ater free	Emperimentar	lo nouis	lmt of water sol	
Aluminium	21645-51-2	Green algae	Experimental	72 hours	No tox obs at	100 mg/l
hydroxide			F		lmt of water sol	
2-(2-	112-15-2	Fathead	Experimental	96 hours	LC50	110 mg/l
Ethoxyethoxy)		minnow	1			
ethyl acetate						
2-(2-	112-15-2	Green algae	Experimental	72 hours	EC50	>100 mg/l
Ethoxyethoxy)						
ethyl acetate						
2-(2-	112-15-2	Water flea	Experimental	48 hours	EC50	>100 mg/l
Ethoxyethoxy)						
ethyl acetate						
2-(2-	112-15-2	Green algae	Experimental	72 hours	NOEC	100 mg/l
Ethoxyethoxy)						
ethyl acetate						
Fumed silica	7631-86-9		Data not			N/A
		1	available or			
			insufficient for			
			classification			
Toluene	108-88-3	Coho Salmon	Experimental	96 hours	LC50	5.5 mg/l
Toluene	108-88-3	Grass Shrimp	Experimental	96 hours	LC50	9.5 mg/l
Toluene	108-88-3	Green algae	Experimental	72 hours	EC50	12.5 mg/l
Toluene	108-88-3	Leopard frog	Experimental	9 days	LC50	0.39 mg/l
Toluene	108-88-3	Pink Salmon	Experimental	96 hours	LC50	6.41 mg/l
Toluene	108-88-3	Water flea	Experimental	48 hours	EC50	3.78 mg/l
Toluene	108-88-3	Coho Salmon	Experimental	40 days	NOEC	1.39 mg/l
Toluene	108-88-3	Diatom	Experimental	72 hours	NOEC	10 mg/l
Toluene	108-88-3	Water flea	Experimental	7 days	NOEC	0.74 mg/l
Toluene	108-88-3	Activated sludge	Experimental	12 hours	IC50	292 mg/l
Toluene	108-88-3	Bacteria	Experimental	16 hours	NOEC	29 mg/l
Toluene	108-88-3	Bacteria	Experimental	24 hours	EC50	84 mg/l
Toluene	108-88-3	Redworm	Experimental	28 days	LC50	>150 mg per kg of
						bodyweight
Toluene	108-88-3	Soil microbes	Experimental	28 days	NOEC	<26 mg/kg (Dry
						Weight)
Heptane	142-82-5	Water flea	Experimental	48 hours	EC50	1.5 mg/l
Heptane	142-82-5	Water flea	Estimated	21 days	NOEC	0.17 mg/l
(Gamma-	4420-74-0	Green algae	Experimental	72 hours	EC50	267 mg/l
mercaptopropyl		1				
)trimethoxysila						
ne						
(Gamma-	4420-74-0	Water flea	Experimental	48 hours	EC50	6.7 mg/l
mercaptopropyl						
)trimethoxysila		1				
ne						
(Gamma-	4420-74-0	Zebra Fish	Experimental	96 hours	LC50	439 mg/l
mercaptopropyl						
)trimethoxysila						
ne	1					

12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Urethane Polymer	51447-37-1	Data not available-insufficient	N/A	N/A	N/A	N/A
Titanium dioxide	13463-67-7	Data not available-insufficient	N/A	N/A	N/A	N/A
Synthetic Amorphous Silica	112945-52-5	Data not available-insufficient	N/A	N/A	N/A	N/A
4,4'- methylenediph enyl diisocyanate	101-68-8	Estimated Hydrolysis		Hydrolytic half-life	20 hours (t 1/2)	Non-standard method
Zinc oxide	1314-13-2	Data not available-insufficient	N/A	N/A	N/A	N/A
Alkyl Isocyanate Silane	85702-90-5	Data not available-insufficient	N/A	N/A	N/A	N/A
Aluminium hydroxide	21645-51-2	Data not available-insufficient	N/A	N/A	N/A	N/A
2-(2- Ethoxyethoxy) ethyl acetate	112-15-2	Experimental Biodegradation	28 days	BOD	100 %BOD/Th BOD	OECD 301C - MITI test (I)
Fumed silica	7631-86-9	Data not available-insufficient	N/A	N/A	N/A	N/A
Toluene	108-88-3	Experimental Photolysis		Photolytic half- life (in air)	5.2 days (t 1/2)	
Toluene	108-88-3	Experimental Biodegradation	20 days	BOD	80 %BOD/ThB OD	APHA Std Meth Water/Wastewater
Heptane	142-82-5	Experimental Photolysis		Photolytic half- life (in air)	4.24 days (t 1/2)	Non-standard method
Heptane	142-82-5	Experimental Biodegradation	28 days	BOD	101 %BOD/Th BOD	OECD 301C - MITI test (I)
(Gamma- mercaptopropyl)trimethoxysila ne	4420-74-0	Estimated Hydrolysis		Hydrolytic half-life	53.3 minutes (t 1/2)	Non-standard method

12.3 : Bioaccumulative potential

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Urethane	51447-37-1	Data not	N/A	N/A	N/A	N/A
Polymer		available or				
		insufficient for				
		classification				
Titanium	13463-67-7	Experimental	42 days	Bioaccumulatio	9.6	Non-standard method
dioxide		BCF - Carp		n factor		
Synthetic	112945-52-5	Data not	N/A	N/A	N/A	N/A
Amorphous		available or				
Silica		insufficient for				

		classification				
4,4'- methylenediph enyl diisocyanate	101-68-8	Experimental BCF - Carp	28 days	Bioaccumulatio n factor	200	OECD 305E - Bioaccumulation flow- through fish test
Zinc oxide	1314-13-2	Experimental BCF - Carp	56 days	Bioaccumulatio n factor	≤217	OECD 305E - Bioaccumulation flow- through fish test
Alkyl Isocyanate Silane	85702-90-5	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Aluminium hydroxide	21645-51-2	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
2-(2- Ethoxyethoxy) ethyl acetate	112-15-2	Experimental Bioconcentrati on		Log Kow	0.74	Non-standard method
Fumed silica	7631-86-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Toluene	108-88-3	Experimental BCF - Other	72 hours	Bioaccumulatio n factor	90	
Toluene	108-88-3	Experimental Bioconcentrati on		Log Kow	2.73	
Heptane	142-82-5	Estimated Bioconcentrati on		Bioaccumulatio n factor	105	Estimated: Bioconcentration factor
(Gamma- mercaptopropyl)trimethoxysila ne	4420-74-0	Estimated Bioconcentrati on		Log Kow	0.25	Estimated: Octanol- water partition coefficient

12.4. Mobility in soil

Please contact manufacturer for more details

12.5 Other Adverse effects

Material	CAS Nbr	Ozone Depletion Potential	Global Warming Potential
(gamma-	4420-74-0	0	
mercaptopropyl)trimethoxy			
silane			

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerised) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals

(chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

SECTION 14: Transport Information

Air Transport (IATA)Regulations

UN No UN3077

Proper Shipping Name ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (HEPTANE; ZINC

OXIDE)

Hazard Classs/Division 9 Subsidiary Risk Not applicable

Packing Group: III

Marine Transport (IMDG)

UN No UN3077

Proper Shipping Name ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (HEPTANE; ZINC

OXIDE)

Hazard Classs/Division 9 Subsidiary Risk Not applicable

Packing Group: III

Environmental Hazards: Marine Pollutant: Yes

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

Applicable Environmental, Health and Safety Regulations

The Manufacture, Storage and Import of Hazardous Chemical Rules, 1989 Hazardous Waste(Management, Handling & Transboundary) Rules, 2008 Hazardous Chemicals (Classification, Packaging and Labelling Draft Rules), 2011

The following ingredients are listed as hazardous on Part II of Schedule I of the India Manufacture, Storage and Import of Hazardous Chemicals (MSIHC) rules

Benzene, 1,1'-methylenebis[4-isocyanato-

4,4'-methylenediphenyl diisocyanate

Toluene

The following ingredients are classified as hazardous based on the criteria listed under Part I of Schedule I of the India Manufacture, Storage and Import of Hazardous Chemicals (MSIHC) rules:

The product is classified as Non-Hazardous as per MSIHC Rules, 1989.

SECTION 16: Other information

NFPA Hazard Classification

Health: 2 Flammability: 1 Instability: 1 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Revision information:

Label: GHS Classification information was modified.

Label: GHS Precautionary - Prevention information was modified.

Label: GHS Precautionary - Response information was modified.

Label: GHS Precautionary - Storage information was added.

Section 2: Ingredient table information was modified.

Section 7: Precautions safe handling information information was modified.

Section 8: Occupational exposure limit table information was modified.

Section 09: Nanoparticle information was deleted.

Section 11: Acute Toxicity table information was modified.

Section 11: Aspiration Hazard Table information was modified.

Section 11: Carcinogenicity Table information was modified.

Section 11: Germ Cell Mutagenicity Table information was modified.

Section 11: Reproductive Hazards information information was added.

Section 11: Reproductive Toxicity Table information was modified.

Section 11: Serious Eye Damage/Irritation Table information was modified.

Section 11: Skin Corrosion/Irritation Table information was modified.

Section 11: Skin Sensitization Table information was modified.

Section 11: Target Organs - Repeated Table information was modified.

Section 11: Target Organs - Single Table information was modified.

Section 12: Component ecotoxicity information information was modified.

Section 12: Persistence and Degradability information information was modified.

Section 12:Bioccumulative potential information information was modified.

Section 15: MSIHC Ingredients information was modified.

DISCLAIMER: The information in this Safety Data Sheet (SDS) is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this SDS or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own evaluation to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into India, you are responsible to comply with all applicable regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration/notification.

3M India SDSs are available at http://solutions.3mindia.co.in