



Safety Data Sheet

Copyright,2014,3M India Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	33-5980-9	Version number:	1.01
Issue Date:	22/05/2014	Supersedes date:	20/05/2014

This Safety Data Sheet has been prepared in accordance with the GHS guidelines & India Hazardous substances (Classification, Labeling & Packaging) Draft Rules 2011.

IDENTIFICATION

1.1. Product identifier

RPM resin KIT

Product Identification Numbers

IE-5101-6405-6

1.2. Recommended use and restrictions on use

1.3. Supplier's details

Address: 3M India Limited, plot-48-51, Electronic city, Hosur road, Bangalore-560100
Telephone: 080-39143000, contact Product EHS team
E Mail: productehs.in@mmm.com
Website: <http://solutions.3mindia.co.in>

1.4. Emergency telephone number

080-39143000 (Contact hours: 8:00 AM to 5:00 PM)

This product is a kit or a multipart product which consists of multiple, independently packaged components. A Safety Data Sheet for each of these components is included. Please do not separate the component Safety Data Sheets from this cover page. The document numbers of the MSDSs for components of this product are:

10-2789-5, 29-8372-4, 29-8389-8, 26-0759-6

TRANSPORT INFORMATION

Air Transport (IATA) Regulations

UN No Not applicable

Proper Shipping Name Not applicable

Hazard Classes/Division Not applicable

Subsidiary Risk Not applicable

Packing Group: Not applicable

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the

product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

3M India SDSs are available at <http://solutions.3mindia.co.in>



Safety Data Sheet

Copyright,2020, 3M India Limited.All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	29-8389-8	Version number:	2.00
Issue Date:	19/08/2020	Supersedes date:	29/05/2020

This Safety Data Sheet has been prepared in accordance with the GHS guidelines & India Hazardous substances (Classification, Labeling & Packaging) Draft Rules 2011.

SECTION 1: Identification

1.1. Product identifier

3M AFP Resin Kit Component - Hardener

Product Identification Numbers

IS-5101-2222-6

1.2. Recommended use and restrictions on use

Recommended use

Adhesive, Component of two part epoxy system used for edge sealing of aluminum backed flexible reflective sheeting.

1.3. Supplier's details

Address: 3M India Limited, plot-48-51, Electronic city, Hosur road, Bangalore-560100
Telephone: 080-45543000, contact Product EHS team
E Mail: productehs.in@mmm.com
Website: <http://solutions.3mindia.co.in>

1.4. Emergency telephone number

080-45543000 (Contact hours: 8:00 AM to 5:00 PM)

SECTION 2: Hazard identification

Under MSIHC Rules, information is noted below on flammability, acute toxicity and explosivity relevant to this product. In line with international standards, information on other hazard classes and associated precautionary statements relevant to this product are included as well.

2.1. Classification of the substance or mixture

Acute Toxicity (dermal): Category 4.
Serious Eye Damage/Irritation: Category 1.
Skin Corrosion/Irritation: Category 1B.
Skin Sensitizer: Category 1.

2.2. Label elements

Signal Word
DANGER!

Symbols

Corrosion | Exclamation mark |

Pictograms



HAZARD STATEMENTS:

H312 Harmful in contact with skin.
H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.

PRECAUTIONARY STATEMENTS

Prevention:

P260 Do not breathe dust/fume/gas/mist/vapours/spray.
P280D Wear protective gloves, protective clothing, and eye/face protection.
P264 Wash thoroughly after handling.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a POISON CENTER or doctor/physician.
P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.
P312 Call a POISON CENTRE or doctor/physician if you feel unwell.

Disposal:

P501 Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

2.3. Other hazards

Persons previously sensitised to amines may develop a cross-sensitisation reaction to certain other amines. - May cause chemical gastrointestinal burns.

SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	CAS Nbr	% by Wt
Polyamine-fatty acids copolymer	68410-23-1	70 - 100
Triethylenetetramine	112-24-3	5 - 10

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

3M AFP Resin Kit Component - Hardener

Immediately flush with large amounts of water for at least 15 minutes. Remove contaminated clothing. Get immediate medical attention. Wash clothing before reuse.

Eye contact

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

If swallowed

Rinse mouth. Do not induce vomiting. Get immediate medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1 Information on toxicological effects

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable Extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

5.3. Special protective actions for fire-fighters

No special protective actions for fire-fighters are anticipated.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage including any incompatibilities

Store away from heat.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
Triethylenetetramine	112-24-3	AIHA	TWA:6 mg/m ³ (1 ppm)	SKIN

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Full face shield.

Indirect vented goggles.

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended: Butyl rubber.

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Boot covers - Disposable Apron – Butyl rubber

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid.
----------------	---------

Color	Colorless
Odor	Slight Odor
Odour threshold	<i>No data available.</i>
pH	11
Melting point/Freezing point: NA	<i>Not applicable.</i>
Boiling point/Initial boiling point/Boiling range	200 °C
Flash point	145 °C
Evaporation rate	<i>No data available.</i>
Flammability (solid, gas)	Not applicable.
Flammable Limits(LEL)	<i>Not applicable.</i>
Flammable Limits(UEL)	<i>Not applicable.</i>
Vapour pressure	0 Pa
Vapor Density and/or Relative Vapor Density	<i>No data available.</i>
Density	0.98 g/cm ³
Relative density	0.98 [Ref Std: WATER=1]
Water solubility	100 g/l
Solubility- non-water	<i>No data available.</i>
Partition coefficient: n-octanol/water	<i>No data available.</i>
Autoignition temperature	<i>Not applicable.</i>
Decomposition temperature	<i>No data available.</i>
Viscosity/Kinematic Viscosity	<i>No data available.</i>
Volatile organic compounds (VOC)	
Percent volatile	
VOC less H₂O & exempt solvents	

Nanoparticles

This material does not contain nanoparticles.

SECTION 10: Stability and reactivity**10.1 Reactivity**

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

Heat.

Sparks and/or flames.

10.5 Incompatible materials

None known.

10.6 Hazardous decomposition products**Substance**

Carbon monoxide.
Carbon dioxide.
Oxides of nitrogen.

Condition

Not specified.
Not specified.
Not specified.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1 Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Skin contact

Harmful in contact with skin. Corrosive (skin burns): Signs/symptoms may include localised redness, swelling, itching, intense pain, blistering, ulceration, and tissue destruction. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye contact

Corrosive (eye burns): Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision.

Ingestion

Gastrointestinal corrosion: Signs/symptoms may include severe mouth, throat and abdominal pain, nausea, vomiting, and diarrhea; blood in the faeces and/or vomitus may also be seen.

Additional information:

Persons previously sensitised to amines may develop a cross-sensitisation reaction to certain other amines.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE 1,000 - 2,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Polyamine-fatty acids copolymer	Dermal	Rat	LD50 > 2,000 mg/kg
Polyamine-fatty acids copolymer	Ingestion	Rat	LD50 > 2,000 mg/kg
Triethylenetetramine	Dermal	Rabbit	LD50 550 mg/kg
Triethylenetetramine	Ingestion	Rat	LD50 2,500 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Polyamine-fatty acids copolymer	In vitro data	Irritant
Triethylenetetramine	Rabbit	Corrosive

Serious Eye Damage/Irritation

Name	Species	Value
------	---------	-------

3M AFP Resin Kit Component - Hardener

Polyamine-fatty acids copolymer	Rabbit	Corrosive
Triethylenetetramine	Rabbit	Corrosive

Sensitization:**Skin Sensitisation**

Name	Species	Value
Polyamine-fatty acids copolymer	Mouse	Sensitising
Triethylenetetramine	Guinea pig	Sensitising

Respiratory Sensitisation

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Polyamine-fatty acids copolymer	In Vitro	Not mutagenic

Carcinogenicity

For the component/components, either no data are currently available or the data are not sufficient for classification.

Reproductive Toxicity**Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test result	Exposure Duration
Polyamine-fatty acids copolymer	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	premating into lactation
Polyamine-fatty acids copolymer	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	6 weeks
Polyamine-fatty acids copolymer	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	premating into lactation

Target Organ(s)**Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Polyamine-fatty acids copolymer	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Polyamine-fatty acids copolymer	Ingestion	heart liver immune system endocrine system gastrointestinal tract bone, teeth, nails, and/or hair hematopoietic system nervous system kidney and/or bladder respiratory system vascular system	Not classified	Rat	NOAEL 1,000 mg/kg/day	6 weeks

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labelling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

12.1. Toxicity**Acute aquatic hazard:**

Not acutely toxic to aquatic life by GHS criteria.

Chronic aquatic hazard:

Not chronically toxic to aquatic life by GHS criteria.

No product test data available.

Material	CAS Nbr	Organism	Type	Exposure	Test endpoint	Test result
Polyamine-fatty acids copolymer	68410-23-1	Water flea	Estimated	48 hours	EC50	5.18 mg/l
Polyamine-fatty acids copolymer	68410-23-1	Zebra Fish	Estimated	96 hours	LC50	7.07 mg/l
Polyamine-fatty acids copolymer	68410-23-1	Green algae	Experimental	72 hours	EC50	4.11 mg/l
Polyamine-fatty acids copolymer	68410-23-1	Green algae	Experimental	72 hours	NOEC	1.25 mg/l
Triethylenetetramine	112-24-3	Green Algae	Experimental	72 hours	EC50	27.4 mg/l
Triethylenetetramine	112-24-3	Guppy	Experimental	96 hours	LC50	570 mg/l
Triethylenetetramine	112-24-3	Water flea	Experimental	48 hours	EC50	37.4 mg/l
Triethylenetetramine	112-24-3	Green Algae	Experimental	72 hours	NOEC	0.468 mg/l
Triethylenetetramine	112-24-3	Water flea	Experimental	21 days	NOEC	2.86 mg/l

12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Polyamine-fatty acids copolymer	68410-23-1	Experimental Biodegradation	28 days	BOD	15 % BOD/ThBOD	OECD 301D - Closed bottle test

3M AFP Resin Kit Component - Hardener

Triethylenetetramine	112-24-3	Experimental Biodegradation	20 days	BOD	0 % BOD/ThBOD	OECD 301D - Closed bottle test
----------------------	----------	-----------------------------	---------	-----	---------------	--------------------------------

12.3 : Bioaccumulative potential

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Polyamine-fatty acids copolymer	68410-23-1	Estimated Bioconcentration		Bioaccumulation factor	6.8	Estimated: Bioconcentration factor
Triethylenetetramine	112-24-3	Experimental BCF-Carp	42 days	Bioaccumulation factor	<5.0	OECD 305E - Bioaccumulation flow-through fish test

12.4. Mobility in soil

Please contact manufacturer for more details

12.5 Other Adverse effects

No information available.

SECTION 13: Disposal considerations**13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

SECTION 14: Transport Information**Air Transport (IATA) Regulations**

UN No UN2735

Proper Shipping Name AMINES, LIQUID, CORROSIVE, N.O.S. (contains triethylene tetraamine)

Hazard Class/Division 8

Subsidiary Risk Not applicable

Packing Group: II

Marine Transport (IMDG)

UN No UN2735

Proper Shipping Name AMINES, LIQUID, CORROSIVE, N.O.S. (contains triethylene tetraamine)

Hazard Class/Division 8

Subsidiary Risk Not applicable

Packing Group: II

Environmental Hazards: Not applicable

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****Global inventory status**

Contact 3M for more information.

Applicable Environmental, Health and Safety Regulations

The Manufacture, Storage and Import of Hazardous Chemical Rules, 1989
Hazardous Waste(Management , Handling & Transboundary) Rules, 2008
Hazardous Chemicals (Classification, Packaging and Labelling Draft Rules), 2011

The following ingredients are listed as hazardous on Part II of Schedule I of the India Manufacture, Storage and Import of Hazardous Chemicals (MSIHC) rules

None.

The following ingredients are classified as hazardous based on the criteria listed under Part I of Schedule I of the India Manufacture, Storage and Import of Hazardous Chemicals (MSIHC) rules:

The product is classified as Toxic (Corrosive) as per MSIHC Rules, 1989.

SECTION 16: Other information

NFPA Hazard Classification

Health: 3 **Flammability:** 1 **Instability:** 0 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Revision information:

Section 1: Product name information was modified.
Section 09: Nanoparticle information was added.
Section 09: Percent Volatile information was added.
Section 09: Vapor Density Value information was added.
Section 9: Vapour density value information was deleted.
Section 9: Viscosity information information was deleted.
Section 09: Viscosity information was added.
Section 09: VOC Less H2O & Exempt Solvents information was added.
Section 09: Volatile Organic Compounds information was added.
Section 12: Component ecotoxicity information information was modified.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

3M India SDSs are available at <http://solutions.3mindia.co.in>



Safety Data Sheet

Copyright,2024, 3M India Limited.All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	29-8372-4	Version number:	2.01
Issue Date:	23/10/2024	Supersedes date:	19/08/2020

This Safety Data Sheet has been prepared in accordance with the GHS guidelines & India Hazardous substances (Classification, Labeling & Packaging) Draft Rules 2011.

SECTION 1: Identification

1.1. Product identifier

3M AFP Resin Kit Component - Resin

Product Identification Numbers

IS-5101-2223-4

1.2. Recommended use and restrictions on use

Recommended use

Resin for reflective sheeting application, Resin

1.3. Supplier's details

Address: 3M India Limited, plot-48-51, Electronic city, Hosur road, Bangalore-560100
Telephone: 080-45543000, contact Product EHS team
E Mail: productehs.in@mmm.com
Website: <http://solutions.3mindia.co.in>

1.4. Emergency telephone number

080-45543000 (Contact hours: 8:00 AM to 5:00 PM)

SECTION 2: Hazard identification

Under MSIHC Rules, information is noted below on flammability, acute toxicity and explosivity relevant to this product. In line with international standards, information on other hazard classes and associated precautionary statements relevant to this product are included as well.

2.1. Classification of the substance or mixture

Skin Corrosion/Irritation: Category 3.
Serious Eye Damage/Irritation: Category 2B.
Skin Sensitizer: Category 1.
Acute Aquatic Toxicity: Category 2.
Chronic Aquatic Toxicity: Category 3.

2.2. Label elements

Signal Word

Warning

Symbols

Exclamation mark |

Pictograms



HAZARD STATEMENTS:

- H316 Causes mild skin irritation.
- H320 Causes eye irritation.
- H317 May cause an allergic skin reaction.

- H401 Toxic to aquatic life.
- H412 Harmful to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENTS

Prevention:

P280E Wear protective gloves.

Response:

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

Disposal:

P501 Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

2.3. Other hazards

None known.

SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	CAS Nbr	% by Wt
Epoxy Resin	25068-38-6	100

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye contact

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

No critical symptoms or effects. See Section 11.1, information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable Extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

5.3. Special protective actions for fire-fighters

No special protective actions for fire-fighters are anticipated.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid eye contact. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage including any incompatibilities

Store away from heat.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

No occupational exposure limit values exist for any of the components listed in Section 3 of this Safety Data Sheet.

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect vented goggles.

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Boot covers - Disposable
Apron - polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid.
Color	Light Yellow
Odor	Slight Odor
Odour threshold	<i>No data available.</i>
pH	7
Melting point/Freezing point: NA	<i>Not applicable.</i>
Boiling point/Initial boiling point/Boiling range	200 °C
Flash point	200 °C
Evaporation rate	<i>No data available.</i>
Flammability	Not applicable.
Flammable Limits(LEL)	<i>Not applicable.</i>
Flammable Limits(UEL)	<i>Not applicable.</i>
Vapour pressure	0 Pa
Vapor Density and/or Relative Vapor Density	<i>No data available.</i>

Density	1.15 - 1.2 g/cm ³
Relative density	1.15 - 1.2 [Ref Std: WATER=1]
Water solubility	<i>Not applicable.</i>
Solubility- non-water	<i>No data available.</i>
Partition coefficient: n-octanol/water	<i>No data available.</i>
Autoignition temperature	<i>Not applicable.</i>
Decomposition temperature	<i>No data available.</i>
Kinematic Viscosity	<i>No data available.</i>
Volatile organic compounds (VOC)	<i>No data available.</i>
Percent volatile	<i>No data available.</i>
VOC less H ₂ O & exempt solvents	<i>No data available.</i>

Particle Characteristics	<i>Not applicable.</i>
--------------------------	------------------------

SECTION 10: Stability and reactivity

10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

Heat.

Sparks and/or flames.

10.5 Incompatible materials

None known.

10.6 Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
Aldehydes.	Not specified.
Carbon monoxide.	Not specified.
Carbon dioxide.	Not specified.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1 Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

No known health effects.

Skin contact

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye contact

Moderate eye irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Epoxy Resin	Dermal	Rat	LD50 > 1,600 mg/kg
Epoxy Resin	Ingestion	Rat	LD50 > 1,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Epoxy Resin	Rabbit	Mild irritant

Serious Eye Damage/Irritation

Name	Species	Value
Epoxy Resin	Rabbit	Moderate irritant

Sensitization:**Skin Sensitisation**

Name	Species	Value
Epoxy Resin	Human and animal	Sensitising

Respiratory Sensitisation

Name	Species	Value
Epoxy Resin	Human	Not classified

Germ Cell Mutagenicity

Name	Route	Value
Epoxy Resin	In vivo	Not mutagenic
Epoxy Resin	In Vitro	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

Name	Route	Species	Value
Epoxy Resin	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification

Reproductive Toxicity**Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test result	Exposure Duration
Epoxy Resin	Ingestion	Not classified for female reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
Epoxy Resin	Ingestion	Not classified for male reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
Epoxy Resin	Dermal	Not classified for development	Rabbit	NOAEL 300 mg/kg/day	during organogenesis
Epoxy Resin	Ingestion	Not classified for development	Rat	NOAEL 750 mg/kg/day	2 generation

Target Organ(s)**Specific Target Organ Toxicity - single exposure**

For the component/components, either no data are currently available or the data are not sufficient for classification.

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Epoxy Resin	Dermal	liver	Not classified	Rat	NOAEL 1,000 mg/kg/day	2 years
Epoxy Resin	Dermal	nervous system	Not classified	Rat	NOAEL 1,000 mg/kg/day	13 weeks
Epoxy Resin	Ingestion	auditory system heart endocrine system hematopoietic system liver eyes kidney and/or bladder	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labelling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

12.1. Toxicity**Acute aquatic hazard:**

GHS Acute 2: Toxic to aquatic life.

Chronic aquatic hazard:

GHS Chronic 3: Harmful to aquatic life with long lasting effects.

No product test data available.

3M AFP Resin Kit Component - Resin

Material	CAS Nbr	Organism	Type	Exposure	Test endpoint	Test result
Epoxy Resin	25068-38-6	Rainbow trout	Estimated	96 hours	LC50	2 mg/l
Epoxy Resin	25068-38-6	Water flea	Estimated	48 hours	LC50	1.8 mg/l
Epoxy Resin	25068-38-6	Activated sludge	Experimental	3 hours	IC50	>100 mg/l
Epoxy Resin	25068-38-6	Green algae	Experimental	72 hours	EC50	>11 mg/l
Epoxy Resin	25068-38-6	Green algae	Experimental	72 hours	NOEC	4.2 mg/l
Epoxy Resin	25068-38-6	Water flea	Experimental	21 days	NOEC	0.3 mg/l

12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Epoxy Resin	25068-38-6	Experimental Biodegradation	28 days	BOD	5 %BOD/COD	OECD 301F - Manometric respirometry
Epoxy Resin	25068-38-6	Experimental Hydrolysis		Hydrolytic half-life	117 hours (t 1/2)	

12.3 : Bioaccumulative potential

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Epoxy Resin	25068-38-6	Experimental Bioconcentration		Log Kow	3.242	

12.4. Mobility in soil

Please contact manufacturer for more details

12.5 Other Adverse effects

No information available.

SECTION 13: Disposal considerations**13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

SECTION 14: Transport Information

Not hazardous for transportation.

Air Transport (IATA) Regulations

UN No Not applicable

Proper Shipping Name Not applicable

Hazard Class/Division Not applicable

Subsidiary Risk Not applicable

Packing Group: Not applicable

Marine Transport (IMDG)

UN No Not applicable

Proper Shipping Name Not applicable

Hazard Class/Division Not applicable

Subsidiary Risk Not applicable

Packing Group: Not applicable

Environmental Hazards: Marine Pollutant: Yes

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status

Contact 3M for more information.

Applicable Environmental, Health and Safety Regulations

The Manufacture, Storage and Import of Hazardous Chemical Rules, 1989

Hazardous Waste(Management , Handling & Transboundary) Rules, 2008

Hazardous Chemicals (Classification, Packaging and Labelling Draft Rules), 2011

The following ingredients are listed as hazardous on Part II of Schedule I of the India Manufacture, Storage and Import of Hazardous Chemicals (MSIHC) rules

None.

The following ingredients are classified as hazardous based on the criteria listed under Part I of Schedule I of the India Manufacture, Storage and Import of Hazardous Chemicals (MSIHC) rules:

The product is classified as Non-Hazardous as per MSIHC Rules, 1989.

SECTION 16: Other information

NFPA Hazard Classification

Health: 2 Flammability: 1 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Revision information:

Section 14: Packing group (IMO) information was modified.

US Section 01 Product Use - Recommended Use information was modified.

Label: GHS Classification information was modified.

Label: Signal Word information was modified.

Label: Symbol information was modified.

Section 04: Information on toxicological effects information was deleted.

Section 9: Flammability (solid, gas) information information was deleted.

Section 09: Flammability information information was added.

Section 09: Kinematic Viscosity information information was added.

Section 09: Nanoparticle information was deleted.

Section 09: Particle Characteristics N/A information was added.

Section 09: Percent Volatile information was modified.

Section 09: Viscosity information was deleted.

Section 09: VOC Less H2O & Exempt Solvents information was modified.

Section 09: Volatile Organic Compounds information was modified.

Section 11: Reproductive Toxicity Table information was modified.

Section 12: Component ecotoxicity information information was modified.

Section 12: Persistence and Degradability information information was modified.

Section 12: Bioaccumulative potential information information was modified.

Section 14: IATA transport hazard classes information was modified.

Section 14: IMO transport hazard classes information was modified.

Section 14: Packing group (IATA) information was modified.

Section 14: Proper Shipping Name (IATA) information was modified.

Section 14: Proper Shipping Name (IMO) information was modified.

Section 14: Proper Shipping Name n.o.s. ingredients information was deleted.

Section 14: Transportation Information information was added.

Section 14: UN Number (IATA) information was modified.

Section 14: UN Number (IMO) information was modified.

DISCLAIMER: The information in this Safety Data Sheet (SDS) is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this SDS or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own evaluation to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into India, you are responsible to comply with all applicable regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration/notification.

3M India SDSs are available at <http://solutions.3mindia.co.in>



Safety Data Sheet

Copyright, 2023, 3M India Limited. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

This product is defined as an article as per the Occupational Safety and Health Administration's Hazard Communication Standard (29 CFR 1910.1200(b)(6)(v)). As defined in this Standard:

'Article' means a manufactured item other than a fluid or particle: (i) which is formed to a specific shape or design during manufacture; (ii) which has end use function(s) dependent in whole or in part upon its shape or design during end use; and (iii) which under normal conditions of use does not release more than very small quantities, e.g., minute or trace amounts of a hazardous chemical, and which does not pose a physical hazard or health risk to employees.

When used under reasonable conditions and in accordance with the directions for use, the product should not present a health and safety hazard. However, use or processing of the product in a manner not in accordance with the directions for use may affect its performance and present potential health and safety hazards.

Document group:	26-0759-6	Version number:	1.01
Issue Date:	31/07/2023	Supersedes date:	19/05/2014

This Safety Data Sheet has been prepared in accordance with the GHS guidelines & India Hazardous substances (Classification, Labeling & Packaging) Draft Rules 2011.

SECTION 1: Identification

1.1. Product identifier

3M™ 235 Masking Tape

Product Identification Numbers

IS-2600-4629-4

1.2. Recommended use and restrictions on use

Recommended use

Masking, Industrial use.

1.3. Supplier's details

Address: 3M India Limited, plot-48-51, Electronic city, Hosur road, Bangalore-560100
Telephone: 080-45543000, contact Product EHS team
E Mail: productehs.in@mmm.com
Website: <http://solutions.3mindia.co.in>

1.4. Emergency telephone number

080-45543000 (Contact hours: 8:00 AM to 5:00 PM)

3M™ Value Masking Tape 101+3M™ Value Masking Tape 101+3M™ Paper Tape 2003M™ General Use Masking Tape 201+Scotch® Crepe Masking Tape 2023M™ General Purpose Masking Tape 203Scotch® High Performance Masking Tape 213Scotch® High Performance Masking Tape 214Scotch® Weather Resistant Masking Tape 225Scotch® Solvent Resistant Masking Tape 226Scotch® Paint Masking Tape 231 /231AScotch® High Performance Masking Tape 232Scotch® General Purpose Masking Tape 234Scotch® Photographic Tape 235Scotch® Flatback Masking Tape 250Scotch® Printable Flatback

Paper Tape 2563M™ Performance Yellow Masking Tape 301+3M™ High Performance Green Masking Tape 401+/233+3M™ Specialty High Temperature Masking Tape 501+3M™ Specialty High Temperature Masking Tape 501+Purple3M™ Paper Masking Tape 22093M™ Paper Masking Tape 22143M™ Masking Tape 2307Scotch® Masking Tape 2308Scotch® Performance Masking Tape 2364Scotch® Performance Masking Tape 2380Scotch® Premium High Temperature Masking Tape 23933M™ Masking Tape 2450Scotch(R) Sealer Tape 2510Tartan™ Flat Back Paper Masking Tape 2515Scotch® Flatback Tape 2517Scotch® Performance Flatback Tape 2525Scotch® Textile Flatback Tape 2526Scotch® High Performance Masking Tape 2693ScotchBlue™ Industrial Masking Tape 2750

SECTION 2: Hazard identification

Under MSIHC Rules, information is noted below on flammability, acute toxicity and explosivity relevant to this product. In line with international standards, information on other hazard classes and associated precautionary statements relevant to this product are included as well.

2.1. Classification of the substance or mixture

This product is considered to be an article and is exempt from GHS classification.

2.2. Label elements

Signal Word

Not applicable.

Symbols

Not applicable

Pictograms

Not applicable

2.3. Other hazards

None known.

SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	CAS Nbr	% by Wt
Paper Backing	None	51 - 99
Rubber Adhesive	Trade Secret	1 - 49

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

No need for first aid is anticipated. If symptoms develop, remove the affected person to fresh air. Get medical attention.

Skin contact

If exposed, wash with soap and water. If signs/symptoms develop, get medical attention.

Eye contact

If exposed, flush eyes with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms develop, get medical attention.

If swallowed

Do not induce vomiting. Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

No critical symptoms or effects. See Section 11.1, information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable Extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

5.3. Special protective actions for fire-fighters

No special protective actions for fire-fighters are anticipated.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Not applicable.

6.2. Environmental precautions

Not applicable.

6.3. Methods and material for containment and cleaning up

Not applicable.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

This product is considered to be an article which does not release or otherwise result in exposure to a hazardous chemical under normal use conditions.

7.2. Conditions for safe storage including any incompatibilities

Not applicable.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

No occupational exposure limit values exist for any of the components listed in Section 3 of this Safety Data Sheet.

8.2. Exposure controls

8.2.1. Engineering controls

Not applicable.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Eye protection not required.

Skin/hand protection

PPE No chemical protective gloves are required.

Respiratory protection

Respiratory protection is not required.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Solid.
Color	Multicolor
Odor	Rubber
Odour threshold	<i>Not applicable.</i>
pH	<i>Not applicable.</i>
Melting point/Freezing point: NA	<i>Not applicable.</i>
Boiling point/Initial boiling point/Boiling range	<i>Not applicable.</i>
Flash point	<i>Not applicable.</i>
Evaporation rate	<i>Not applicable.</i>
Flammability (solid, gas)	Not classified
Flammable Limits(LEL)	<i>Not applicable.</i>
Flammable Limits(UEL)	<i>Not applicable.</i>
Vapour pressure	<i>Not applicable.</i>
Vapor Density and/or Relative Vapor Density	<i>Not applicable.</i>
Density	<i>Not applicable.</i>
Relative density	<i>Not applicable.</i>
Water solubility	Nil
Solubility- non-water	<i>Not applicable.</i>
Partition coefficient: n-octanol/water	<i>Not applicable.</i>
Autoignition temperature	<i>Not applicable.</i>
Decomposition temperature	<i>Not applicable.</i>
Viscosity/Kinematic Viscosity	<i>Not applicable.</i>
Volatile organic compounds (VOC)	<i>Not applicable.</i>
Percent volatile	<i>Not applicable.</i>
VOC less H ₂ O & exempt solvents	<i>Not applicable.</i>
Molecular weight	<i>No data available.</i>

SECTION 10: Stability and reactivity

10.1 Reactivity

This material is considered to be non reactive under normal use conditions

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

None known.

10.5 Incompatible materials

None known.

10.6 Hazardous decomposition products**Substance**

None known.

Condition

Under recommended usage conditions, hazardous decomposition products are not expected. Hazardous decomposition products may occur as a result of oxidation, heating, or reaction with another material.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1 Information on Toxicological effects**Signs and Symptoms of Exposure**

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

This product may have a characteristic odour; however, no adverse health effects are anticipated.

Skin contact

No health effects are expected.

Eye contact

No health effects are expected.

Ingestion

No health effects are expected.

Additional information:

This product, when used under reasonable conditions and in accordance with the 3M directions for use, should not present a health hazard. However, use or processing of the product in a manner not in accordance with the product's directions for use may affect the performance of the product and may present potential health and safety hazards

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

For the component/components, either no data are currently available or the data are not sufficient for classification.

Serious Eye Damage/Irritation

For the component/components, either no data are currently available or the data are not sufficient for classification.

Sensitization:

Skin Sensitisation

For the component/components, either no data are currently available or the data are not sufficient for classification.

Respiratory Sensitisation

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

For the component/components, either no data are currently available or the data are not sufficient for classification.

Carcinogenicity

For the component/components, either no data are currently available or the data are not sufficient for classification.

Reproductive Toxicity

Reproductive and/or Developmental Effects

For the component/components, either no data are currently available or the data are not sufficient for classification.

Target Organ(s)

Specific Target Organ Toxicity - single exposure

For the component/components, either no data are currently available or the data are not sufficient for classification.

Specific Target Organ Toxicity - repeated exposure

For the component/components, either no data are currently available or the data are not sufficient for classification.

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labelling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

12.1. Toxicity

Acute aquatic hazard:

Not acutely toxic to aquatic life by GHS criteria.

Chronic aquatic hazard:

Not chronically toxic to aquatic life by GHS criteria.

No product test data available.

12.2. Persistence and degradability

No test data available.

12.3 : Bioaccumulative potential

No test data available.

12.4. Mobility in soil

Please contact manufacturer for more details

12.5 Other Adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Prior to disposal, consult all applicable authorities and regulations to insure proper classification. Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. If no other disposal options are available, waste product may be placed in a landfill properly designed for industrial waste.

SECTION 14: Transport Information

Not hazardous for transportation.

Air Transport (IATA) Regulations

UN No Not applicable

Proper Shipping Name Not applicable

Hazard Class/Division Not applicable

Subsidiary Risk Not applicable

Packing Group: Not applicable

Marine Transport (IMDG)

UN No Not applicable

Proper Shipping Name Not applicable

Hazard Class/Division Not applicable

Subsidiary Risk Not applicable

Packing Group: Not applicable

Environmental Hazards: Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status

Contact 3M for more information.

Applicable Environmental, Health and Safety Regulations

Not applicable

The following ingredients are listed as hazardous on Part II of Schedule I of the India Manufacture, Storage and Import of Hazardous Chemicals (MSIHC) rules

None.

SECTION 16: Other information

NFPA Hazard Classification

Health: 0 **Flammability:** 1 **Instability:** 0 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address

the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Revision information:

Section 14: Packing group (IMO) information was added.
Company Telephone information was modified.
Section 1: Emergency telephone information was modified.
Section 1: Product identification numbers information was added.
Section 1: Product name information was modified.
Section 02: GHS Classification Statements information was added.
Section 02: GHS Pictogram Not Applicable information was added.
Label: GHS Classification information was deleted.
Label: Graphic information was deleted.
Label: Signal Word information was deleted.
Label: Symbol information was deleted.
Section 2: Product identification comment information was modified.
Section 2: Ingredient table information was modified.
Section 03: Material is a mixture standard phrase information was modified.
Section 4: First aid for eye contact information information was modified.
Section 4: First aid for ingestion (swallowing) information information was modified.
Section 4: First aid for inhalation information information was modified.
Section 4: First aid for skin contact information information was modified.
Section 04: Information on toxicological effects information was deleted.
Section 5: Fire - Advice for fire fighters information information was modified.
Section 6: Accidental release environmental information information was modified.
Section 6: Accidental release personal information information was modified.
Section 8: Personal Protection - Respiratory Information information was modified.
Section 09: Color information was added.
Section 09: Odor information was added.
Sections 3 and 9: Odour, colour, grade information information was deleted.
Section 09: Percent Volatile information was added.
Section 9: Property description for optional properties information was added.
Section 9: Property description for optional properties information was deleted.
Section 09: Vapor Density Value information was added.
Section 9: Vapour density value information was deleted.
Section 9: Viscosity information information was deleted.
Section 09: Viscosity information was added.
Section 09: VOC Less H₂O & Exempt Solvents information was added.
Section 09: Volatile Organic Compounds information was added.
Section 11: Aspiration Hazard text information was added.
Section 11: Carcinogenicity text information was added.
Section 11: Germ Cell Mutagenicity text information was added.
Section 11: Health Effects - Additional Information information was added.
Section 11: Health Effects - Eye information information was modified.
Section 11: Health Effects - Inhalation information information was modified.
Section 11: Health Effects - Skin information information was modified.
Section 11: Respiratory Sensitization text information was added.
Section 11: Serious Eye Damage/Irritation text information was added.
Section 11: Skin Corrosion/Irritation text information was added.
Section 11: Skin Sensitization text information was added.
Section 11: Specific Target Organ Toxicity - repeated exposure text information was added.
Section 11: Specific Target Organ Toxicity - single exposure text information was added.
Prints No Data if Component ecotoxicity information is not present information was deleted.
Section 13: 13.1. Waste disposal note information was modified.
Section 13: Standard Phrase Category Waste GHS information was modified.

Section 14: Environmental hazards information was added.

Section 14: IMO Subsidiary Risk information was added.

Section 14: IMO transport hazard classes information was added.

Section 14: Proper Shipping Name (IMO) information was added.

Section 14: UN Number (IMO) information was added.

Section 16: UK disclaimer information was deleted.

Section 2: GHS Signal Word - Not applicable information was added.

Section 2: GHS Symbol Text - Not applicable information was added.

DISCLAIMER: The information in this Safety Data Sheet (SDS) is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this SDS or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own evaluation to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into India, you are responsible to comply with all applicable regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration/notification.

3M India SDSs are available at <http://solutions.3mindia.co.in>



Safety Data Sheet

Copyright,2021, 3M India Limited.All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	10-2789-5	Version number:	1.06
Issue Date:	31/12/2021	Supersedes date:	31/12/2021

This Safety Data Sheet has been prepared in accordance with the GHS guidelines & India Hazardous substances (Classification, Labeling & Packaging) Draft Rules 2011.

SECTION 1: Identification

1.1. Product identifier

3M™ Neoprene High Performance Contact Adhesive 1357

1.2. Recommended use and restrictions on use

Recommended use

Adhesive, Industrial use.

1.3. Supplier's details

Address: 3M India Limited, plot-48-51, Electronic city, Hosur road, Bangalore-560100
Telephone: 080-45543000, contact Product EHS team
E Mail: productehs.in@mmm.com
Website: <http://solutions.3mindia.co.in>

1.4. Emergency telephone number

080-45543000 (Contact hours: 8:00 AM to 5:00 PM)

SECTION 2: Hazard identification

Under MSIHC Rules, information is noted below on flammability, acute toxicity and explosivity relevant to this product. In line with international standards, information on other hazard classes and associated precautionary statements relevant to this product are included as well.

2.1. Classification of the substance or mixture

Flammable Liquid: Category 2.
Skin Corrosion/Irritation: Category 2.
Serious Eye Damage/Irritation: Category 2A
Skin Sensitizer: Category 1.
Carcinogenicity: Category 2.
Reproductive Toxicity: Category 1B.
Specific Target Organ Toxicity (repeated exposure): Category 1.
Specific Target Organ Toxicity (single exposure): Category 3.
Acute Aquatic Toxicity: Category 2.
Chronic Aquatic Toxicity: Category 2.

2.2. Label elements

Signal Word

Danger

Symbols

Flame | Exclamation mark | Health Hazard | Environment |

Pictograms



HAZARD STATEMENTS:

- H225 Highly flammable liquid and vapour.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H317 May cause an allergic skin reaction.
- H351 Suspected of causing cancer.
- H360 May damage fertility or the unborn child.
- H336 May cause drowsiness or dizziness.

- H372 Causes damage to organs through prolonged or repeated exposure: nervous system | sensory organs.

- H411 Toxic to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENTS

Prevention:

- P201 Obtain special instructions before use.
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P260 Do not breathe dust/fume/gas/mist/vapours/spray.
- P273 Avoid release to the environment.
- P280E Wear protective gloves.

Response:

- P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P308 + P313 IF exposed or concerned: Get medical advice/attention.
- P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.
- P370 + P378 In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

Disposal:

- P501 Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

2.3. Other hazards

Aspiration classification does not apply due to the viscosity of the product.

SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	CAS Nbr	% by Wt
C10-13-iso-Alkanes	64741-84-0	20 - 50
Acetone	67-64-1	10 - 30
n-hexane	110-54-3	10 - 25
Heptane	142-82-5	3 - 15
Butanone	78-93-3	7 - 13
Polychloroprene	9010-98-4	7 - 13
2-Methylpentane	107-83-5	1 - 10
3-Methylpentane	96-14-0	1 - 10
Magnesium Resinate	68037-42-3	5 - 10
Toluene	108-88-3	< 10
Cyclohexane	110-82-7	< 5
Ethylbenzene	100-41-4	< 1
Rosin	8050-09-7	< 1
Styrenated Phenol	61788-44-1	< 1
Xylene	1330-20-7	< 1
Zinc oxide	1314-13-2	< 1

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye contact

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Allergic skin reaction (redness, swelling, blistering, and itching). Central nervous system depression (headache, dizziness, drowsiness, incoordination, nausea, slurred speech, giddiness, and unconsciousness). Target organ effects following prolonged or repeated exposure. See Section 11 for additional details.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable Extinguishing media

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products

Substance

Aldehydes.

Condition

During combustion.

Hydrocarbons.
Carbon monoxide.
Carbon dioxide.
Hydrogen Chloride
Irritant vapours or gases.

During combustion.
During combustion.
During combustion.
During combustion.
During combustion.

5.3. Special protective actions for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. When fire fighting conditions are severe and total thermal decomposition of the product is possible, wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, tunic and trousers (leggings), bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Cover spill area with a fire-extinguishing foam. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

For industrial/occupational use only. Not for consumer sale or use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.) Wear low static or properly grounded shoes. Use personal protective equipment (eg. gloves, respirators...) as required. To minimize the risk of ignition, determine applicable electrical classifications for the process using this product and select specific local exhaust ventilation equipment to avoid flammable vapor accumulation. Ground/bond container and receiving equipment if there is potential for static electricity accumulation during transfer.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store away from heat. Store away from acids. Store away from oxidising agents.

SECTION 8: Exposure controls/personal protection**8.1 Control parameters****Occupational exposure limits**

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
Ethylbenzene	100-41-4	ACGIH	TWA:20 ppm	A3: Confirmed animal carcin.
2-Methylpentane	107-83-5	ACGIH	TWA:500 ppm;STEL:1000 ppm	
Toluene	108-88-3	ACGIH	TWA:20 ppm	A4: Not class. as human carcin, Ototoxicant
n-hexane	110-54-3	ACGIH	TWA:50 ppm	Danger of cutaneous absorption
HEXANE (ISOMERS OTHER THAN N-HEXANE)	110-54-3	ACGIH	TWA:500 ppm;STEL:1000 ppm	
Cyclohexane	110-82-7	ACGIH	TWA:100 ppm	
Zinc oxide	1314-13-2	ACGIH	TWA(respirable fraction):2 mg/m ³ ;STEL(respirable fraction):10 mg/m ³	
Xylene	1330-20-7	ACGIH	TWA:100 ppm;STEL:150 ppm	A4: Not class. as human carcin
Heptane	142-82-5	ACGIH	TWA:400 ppm;STEL:500 ppm	
Acetone	67-64-1	ACGIH	TWA:250 ppm;STEL:500 ppm	A4: Not class. as human carcin
Butanone	78-93-3	ACGIH	TWA:200 ppm;STEL:300 ppm	
Rosin	8050-09-7	ACGIH	TWA(as Resin, inhalable fraction):0.001 mg/m ³	Dermal/Respiratory Sensitizer
3-Methylpentane	96-14-0	ACGIH	TWA:500 ppm;STEL:1000 ppm	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls**8.2.1. Engineering controls**

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment. Use explosion-proof ventilation equipment.

8.2.2. Personal protective equipment (PPE)**Eye/face protection**

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Full face shield.

Indirect vented goggles.

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates
Organic vapor respirators may have short service life.

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid.
Color	Gray, Green
Odor	Strong Petroleum
Odour threshold	<i>No data available.</i>
pH	<i>Not applicable.</i>
Melting point/Freezing point: NA	<i>Not applicable.</i>
Boiling point/Initial boiling point/Boiling range	>=56 °C [<i>Details:Acetone</i>]
Flash point	-21.7 °C [<i>Test Method:Closed Cup</i>] [<i>Details:n-Hexane</i>]
Evaporation rate	>=2 [<i>Ref Std:WATER=1</i>]
Flammability (solid, gas)	Not applicable.
Flammable Limits(LEL)	1 % volume
Flammable Limits(UEL)	12.8 % volume
Vapour pressure	<=24,664.6 Pa [<i>@ 20 °C</i>]
Vapor Density and/or Relative Vapor Density	2 [<i>Ref Std:AIR=1</i>]
Density	0.815 g/ml
Relative density	0.815 [<i>Ref Std:WATER=1</i>]
Water solubility	Slight (less than 10%)
Solubility- non-water	<i>No data available.</i>
Partition coefficient: n-octanol/water	<i>No data available.</i>
Autoignition temperature	<i>No data available.</i>
Decomposition temperature	<i>No data available.</i>
Viscosity/Kinematic Viscosity	200 - 450 mPa-s [<i>@ 27 °C</i>]
Volatile organic compounds (VOC)	<=658 g/l [<i>Details:EU VOC content</i>]
Percent volatile	70 - 80 %
VOC less H2O & exempt solvents	<=630 g/l [<i>Test Method:calculated SCAQMD rule 443.1</i>]
Molecular weight	<i>No data available.</i>
Solids content	12 - 25 %

Nanoparticles

This material does not contain nanoparticles.

SECTION 10: Stability and reactivity

10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

Heat.

Sparks and/or flames.

10.5 Incompatible materials

Strong oxidising agents.

10.6 Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1 Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

Skin contact

Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye contact

Severe eye irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea. May cause additional health effects (see below).

Additional Health Effects:**Single exposure may cause target organ effects:**

Central nervous system (CNS) depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

Prolonged or repeated exposure may cause target organ effects:

Ocular effects: Signs/symptoms may include blurred or significantly impaired vision. Auditory effects: Signs/symptoms may include hearing impairment, balance dysfunction and ringing in the ears. Peripheral neuropathy: Signs/symptoms may include tingling or numbness of the extremities, incoordination, weakness of the hands and feet, tremors and muscle atrophy. Olfactory effects: Signs/symptoms may include decreased ability to detect odours and complete loss of smell. Neurological effects: Signs/symptoms may include personality changes, lack of coordination, sensory loss, tingling or numbness of the extremities, weakness, tremors, and changes in blood pressure and heart rate.

Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation-Vapor(4 hr)		No data available; calculated ATE >50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
C10-13-iso-Alkanes	Dermal	Rat	LD50 > 2,800 mg/kg
C10-13-iso-Alkanes	Inhalation-Vapor (4 hours)	Rat	LC50 > 25.2 mg/l
C10-13-iso-Alkanes	Ingestion	Rat	LD50 > 5,840 mg/kg
n-hexane	Dermal	Rabbit	LD50 > 2,000 mg/kg
n-hexane	Inhalation-Vapor (4 hours)	Rat	LC50 170 mg/l
n-hexane	Ingestion	Rat	LD50 > 28,700 mg/kg
Acetone	Dermal	Rabbit	LD50 > 15,688 mg/kg
Acetone	Inhalation-Vapor (4 hours)	Rat	LC50 76 mg/l
Acetone	Ingestion	Rat	LD50 5,800 mg/kg
Heptane	Dermal	Rabbit	LD50 3,000 mg/kg
Heptane	Inhalation-Vapor (4 hours)	Rat	LC50 103 mg/l
Heptane	Ingestion	Rat	LD50 > 15,000 mg/kg
Butanone	Dermal	Rabbit	LD50 > 8,050 mg/kg
Butanone	Inhalation-Vapor (4 hours)	Rat	LC50 34.5 mg/l
Butanone	Ingestion	Rat	LD50 2,737 mg/kg
Polychloroprene	Dermal		LD50 estimated to be > 5,000 mg/kg
Polychloroprene	Ingestion	Rat	LD50 > 20,000 mg/kg
Magnesium Resinate	Dermal		LD50 estimated to be 2,000 - 5,000 mg/kg
Magnesium Resinate	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg

3M™ Neoprene High Performance Contact Adhesive 1357

2-Methylpentane	Dermal		LD50 estimated to be > 5,000 mg/kg
2-Methylpentane	Inhalation-Vapor		LC50 estimated to be > 50 mg/l
2-Methylpentane	Ingestion		LD50 estimated to be > 5,000 mg/kg
3-Methylpentane	Dermal		LD50 estimated to be > 5,000 mg/kg
3-Methylpentane	Inhalation-Vapor		LC50 estimated to be > 50 mg/l
3-Methylpentane	Ingestion		LD50 estimated to be > 5,000 mg/kg
Toluene	Dermal	Rat	LD50 12,000 mg/kg
Toluene	Inhalation-Vapor (4 hours)	Rat	LC50 30 mg/l
Toluene	Ingestion	Rat	LD50 5,550 mg/kg
Cyclohexane	Dermal	Rat	LD50 > 2,000 mg/kg
Cyclohexane	Inhalation-Vapor (4 hours)	Rat	LC50 > 32.9 mg/l
Cyclohexane	Ingestion	Rat	LD50 6,200 mg/kg
Zinc oxide	Dermal		LD50 estimated to be > 5,000 mg/kg
Zinc oxide	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 5.7 mg/l
Zinc oxide	Ingestion	Rat	LD50 > 5,000 mg/kg
Rosin	Dermal	Rabbit	LD50 > 2,500 mg/kg
Rosin	Ingestion	Rat	LD50 7,600 mg/kg
Ethylbenzene	Dermal	Rabbit	LD50 15,433 mg/kg
Ethylbenzene	Inhalation-Vapor (4 hours)	Rat	LC50 17.4 mg/l
Ethylbenzene	Ingestion	Rat	LD50 4,769 mg/kg
Styrenated Phenol	Dermal	Rat	LD50 > 2,000 mg/kg
Styrenated Phenol	Ingestion	Rat	LD50 > 2,000 mg/kg
Xylene	Dermal	Rabbit	LD50 > 4,200 mg/kg
Xylene	Inhalation-Vapor (4 hours)	Rat	LC50 29 mg/l
Xylene	Ingestion	Rat	LD50 3,523 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
C10-13-iso-Alkanes	Rabbit	Irritant
n-hexane	Human and animal	Mild irritant
Acetone	Mouse	Minimal irritation
Heptane	Human	Mild irritant
Butanone	Rabbit	Minimal irritation
Polychloroprene	Human	No significant irritation
2-Methylpentane	Professional judgement	Mild irritant
3-Methylpentane	Professional judgement	Mild irritant
Toluene	Rabbit	Irritant
Cyclohexane	Rabbit	Mild irritant
Zinc oxide	Human and animal	No significant irritation
Rosin	Rabbit	No significant irritation

Ethylbenzene	Rabbit	Mild irritant
Styrenated Phenol	Rabbit	No significant irritation
Xylene	Rabbit	Mild irritant

Serious Eye Damage/Irritation

Name	Species	Value
C10-13-iso-Alkanes	Rabbit	Mild irritant
n-hexane	Rabbit	Mild irritant
Acetone	Rabbit	Severe irritant
Heptane	Professional judgement	Moderate irritant
Butanone	Rabbit	Severe irritant
Polychloroprene	Professional judgement	No significant irritation
2-Methylpentane	Professional judgement	Moderate irritant
3-Methylpentane	Professional judgement	Moderate irritant
Toluene	Rabbit	Moderate irritant
Cyclohexane	Rabbit	Mild irritant
Zinc oxide	Rabbit	Mild irritant
Rosin	Rabbit	Mild irritant
Ethylbenzene	Rabbit	Moderate irritant
Styrenated Phenol	Rabbit	Mild irritant
Xylene	Rabbit	Mild irritant

Sensitization:

Skin Sensitisation

Name	Species	Value
C10-13-iso-Alkanes	Guinea pig	Not classified
n-hexane	Human	Not classified
Toluene	Guinea pig	Not classified
Zinc oxide	Guinea pig	Not classified
Rosin	Guinea pig	Sensitising
Ethylbenzene	Human	Not classified
Styrenated Phenol	Mouse	Sensitising

Respiratory Sensitisation

Name	Species	Value
Rosin	Human	Not classified

Germ Cell Mutagenicity

Name	Route	Value
n-hexane	In Vitro	Not mutagenic
n-hexane	In vivo	Not mutagenic
Acetone	In vivo	Not mutagenic

Acetone	In Vitro	Some positive data exist, but the data are not sufficient for classification
Heptane	In Vitro	Not mutagenic
Butanone	In Vitro	Not mutagenic
Toluene	In Vitro	Not mutagenic
Toluene	In vivo	Not mutagenic
Cyclohexane	In Vitro	Not mutagenic
Cyclohexane	In vivo	Some positive data exist, but the data are not sufficient for classification
Zinc oxide	In Vitro	Some positive data exist, but the data are not sufficient for classification
Zinc oxide	In vivo	Some positive data exist, but the data are not sufficient for classification
Ethylbenzene	In vivo	Not mutagenic
Ethylbenzene	In Vitro	Some positive data exist, but the data are not sufficient for classification
Xylene	In Vitro	Not mutagenic
Xylene	In vivo	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
n-hexane	Dermal	Mouse	Not carcinogenic
n-hexane	Inhalation	Mouse	Some positive data exist, but the data are not sufficient for classification
Acetone	Not specified.	Multiple animal species	Not carcinogenic
Butanone	Inhalation	Human	Not carcinogenic
Toluene	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Toluene	Ingestion	Rat	Some positive data exist, but the data are not sufficient for classification
Toluene	Inhalation	Mouse	Some positive data exist, but the data are not sufficient for classification
Ethylbenzene	Inhalation	Multiple animal species	Carcinogenic.
Xylene	Dermal	Rat	Not carcinogenic
Xylene	Ingestion	Multiple animal species	Not carcinogenic
Xylene	Inhalation	Human	Some positive data exist, but the data are not sufficient for classification

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
C10-13-iso-Alkanes	Ingestion	Toxic to male reproduction	similar compounds	NOAEL not available	not available
C10-13-iso-Alkanes	Inhalation	Toxic to male reproduction	similar compounds	NOAEL not available	not available
n-hexane	Ingestion	Not classified for development	Mouse	NOAEL 2,200 mg/kg/day	during organogenesis
n-hexane	Inhalation	Not classified for development	Rat	NOAEL 0.7 mg/l	during gestation
n-hexane	Ingestion	Toxic to male reproduction	Rat	NOAEL 1,140 mg/kg/day	90 days
n-hexane	Inhalation	Toxic to male reproduction	Rat	LOAEL 3.52 mg/l	28 days
Acetone	Ingestion	Not classified for male reproduction	Rat	NOAEL	13 weeks

				1,700 mg/kg/day	
Acetone	Inhalation	Not classified for development	Rat	NOAEL 5.2 mg/l	during organogenesis
Butanone	Inhalation	Not classified for development	Rat	LOAEL 8.8 mg/l	during gestation
Toluene	Inhalation	Not classified for female reproduction	Human	NOAEL Not available	occupational exposure
Toluene	Inhalation	Not classified for male reproduction	Rat	NOAEL 2.3 mg/l	1 generation
Toluene	Ingestion	Toxic to development	Rat	LOAEL 520 mg/kg/day	during gestation
Toluene	Inhalation	Toxic to development	Human	NOAEL Not available	poisoning and/or abuse
Cyclohexane	Inhalation	Not classified for female reproduction	Rat	NOAEL 24 mg/l	2 generation
Cyclohexane	Inhalation	Not classified for male reproduction	Rat	NOAEL 24 mg/l	2 generation
Cyclohexane	Inhalation	Not classified for development	Rat	NOAEL 6.9 mg/l	2 generation
Zinc oxide	Ingestion	Not classified for reproduction and/or development	Multiple animal species	NOAEL 125 mg/kg/day	premating & during gestation
Ethylbenzene	Inhalation	Not classified for development	Rat	NOAEL 4.3 mg/l	premating & during gestation
Xylene	Inhalation	Not classified for female reproduction	Human	NOAEL Not available	occupational exposure
Xylene	Ingestion	Not classified for development	Mouse	NOAEL Not available	during organogenesis
Xylene	Inhalation	Not classified for development	Multiple animal species	NOAEL Not available	during gestation

Lactation

Name	Route	Species	Value
Xylene	Ingestion	Mouse	Not classified for effects on or via lactation

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
C10-13-iso-Alkanes	Inhalation	central nervous system depression	May cause drowsiness or dizziness	similar compounds	NOAEL not available	not available
C10-13-iso-Alkanes	Ingestion	central nervous system depression	May cause drowsiness or dizziness	similar compounds	NOAEL not available	not available
n-hexane	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	not available
n-hexane	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Rabbit	NOAEL Not available	8 hours
n-hexane	Inhalation	respiratory system	Not classified	Rat	NOAEL 24.6 mg/l	8 hours
Acetone	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Acetone	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Acetone	Inhalation	immune system	Not classified	Human	NOAEL 1.19 mg/l	6 hours
Acetone	Inhalation	liver	Not classified	Guinea pig	NOAEL Not available	

3M™ Neoprene High Performance Contact Adhesive 1357

Acetone	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse
Heptane	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Heptane	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Heptane	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Butanone	Inhalation	central nervous system depression	May cause drowsiness or dizziness	official classification	NOAEL Not available	
Butanone	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Butanone	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	
Butanone	Ingestion	liver	Not classified	Rat	NOAEL Not available	not applicable
Butanone	Ingestion	kidney and/or bladder	Not classified	Rat	LOAEL 1,080 mg/kg	not applicable
2-Methylpentane	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	
2-Methylpentane	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
2-Methylpentane	Inhalation	cardiac sensitization	Not classified	Dog	NOAEL Not available	
2-Methylpentane	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	
3-Methylpentane	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	
3-Methylpentane	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
3-Methylpentane	Inhalation	cardiac sensitization	Not classified	Dog	NOAEL Not available	
3-Methylpentane	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	
Toluene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Toluene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Toluene	Inhalation	immune system	Not classified	Mouse	NOAEL 0.004 mg/l	3 hours
Toluene	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse
Cyclohexane	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
Cyclohexane	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human and animal	NOAEL Not available	
Cyclohexane	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	

Ethylbenzene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Ethylbenzene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human and animal	NOAEL Not available	
Ethylbenzene	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	
Xylene	Inhalation	auditory system	Causes damage to organs	Rat	LOAEL 6.3 mg/l	8 hours
Xylene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Xylene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Xylene	Inhalation	eyes	Not classified	Rat	NOAEL 3.5 mg/l	not available
Xylene	Inhalation	liver	Not classified	Multiple animal species	NOAEL Not available	
Xylene	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Multiple animal species	NOAEL Not available	
Xylene	Ingestion	eyes	Not classified	Rat	NOAEL 250 mg/kg	not applicable

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
C10-13-iso-Alkanes	Inhalation	peripheral nervous system	May cause damage to organs though prolonged or repeated exposure	similar compounds	NOAEL not available	not available
n-hexane	Inhalation	peripheral nervous system	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure
n-hexane	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Mouse	LOAEL 1.76 mg/l	13 weeks
n-hexane	Inhalation	liver	Not classified	Rat	NOAEL Not available	6 months
n-hexane	Inhalation	kidney and/or bladder	Not classified	Rat	LOAEL 1.76 mg/l	6 months
n-hexane	Inhalation	hematopoietic system	Not classified	Mouse	NOAEL 35.2 mg/l	13 weeks
n-hexane	Inhalation	auditory system immune system eyes	Not classified	Human	NOAEL Not available	occupational exposure
n-hexane	Inhalation	heart skin endocrine system	Not classified	Rat	NOAEL 1.76 mg/l	6 months
n-hexane	Ingestion	peripheral nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1,140 mg/kg/day	90 days
n-hexane	Ingestion	endocrine system hematopoietic system liver immune system kidney and/or bladder	Not classified	Rat	NOAEL Not available	13 weeks
Acetone	Dermal	eyes	Not classified	Guinea pig	NOAEL Not available	3 weeks
Acetone	Inhalation	hematopoietic system	Not classified	Human	NOAEL 3 mg/l	6 weeks
Acetone	Inhalation	immune system	Not classified	Human	NOAEL 1.19 mg/l	6 days
Acetone	Inhalation	kidney and/or bladder	Not classified	Guinea pig	NOAEL 119 mg/l	not available
Acetone	Inhalation	heart liver	Not classified	Rat	NOAEL 45	8 weeks

3M™ Neoprene High Performance Contact Adhesive 1357

					mg/l	
Acetone	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 900 mg/kg/day	13 weeks
Acetone	Ingestion	heart	Not classified	Rat	NOAEL 2,500 mg/kg/day	13 weeks
Acetone	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 200 mg/kg/day	13 weeks
Acetone	Ingestion	liver	Not classified	Mouse	NOAEL 3,896 mg/kg/day	14 days
Acetone	Ingestion	eyes	Not classified	Rat	NOAEL 3,400 mg/kg/day	13 weeks
Acetone	Ingestion	respiratory system	Not classified	Rat	NOAEL 2,500 mg/kg/day	13 weeks
Acetone	Ingestion	muscles	Not classified	Rat	NOAEL 2,500 mg/kg	13 weeks
Acetone	Ingestion	skin bone, teeth, nails, and/or hair	Not classified	Mouse	NOAEL 11,298 mg/kg/day	13 weeks
Heptane	Inhalation	liver nervous system kidney and/or bladder	Not classified	Rat	NOAEL 12 mg/l	26 weeks
Butanone	Dermal	nervous system	Not classified	Guinea pig	NOAEL Not available	31 weeks
Butanone	Inhalation	liver kidney and/or bladder heart endocrine system gastrointestinal tract bone, teeth, nails, and/or hair hematopoietic system immune system muscles	Not classified	Rat	NOAEL 14.7 mg/l	90 days
Butanone	Ingestion	liver	Not classified	Rat	NOAEL Not available	7 days
Butanone	Ingestion	nervous system	Not classified	Rat	NOAEL 173 mg/kg/day	90 days
2-Methylpentane	Inhalation	peripheral nervous system	Not classified	Rat	NOAEL 5.3 mg/l	14 weeks
2-Methylpentane	Ingestion	peripheral nervous system	Not classified	Rat	NOAEL Not available	8 weeks
2-Methylpentane	Ingestion	kidney and/or bladder	Not classified	Rat	LOAEL 2,000 mg/kg	28 days
3-Methylpentane	Inhalation	peripheral nervous system	Not classified	Rat	NOAEL 5.3 mg/l	14 weeks
3-Methylpentane	Ingestion	peripheral nervous system	Not classified	Rat	NOAEL Not available	8 weeks
3-Methylpentane	Ingestion	kidney and/or bladder	Not classified	Rat	LOAEL 2,000 mg/kg	28 days
Toluene	Inhalation	auditory system eyes olfactory system	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	poisoning and/or abuse
Toluene	Inhalation	nervous system	May cause damage to organs though prolonged or repeated exposure	Human	NOAEL Not available	poisoning and/or abuse
Toluene	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 2.3 mg/l	15 months
Toluene	Inhalation	heart liver kidney and/or bladder	Not classified	Rat	NOAEL 11.3 mg/l	15 weeks
Toluene	Inhalation	endocrine system	Not classified	Rat	NOAEL 1.1 mg/l	4 weeks
Toluene	Inhalation	immune system	Not classified	Mouse	NOAEL Not available	20 days
Toluene	Inhalation	bone, teeth, nails,	Not classified	Mouse	NOAEL 1.1	8 weeks

		and/or hair			mg/l	
Toluene	Inhalation	hematopoietic system vascular system	Not classified	Human	NOAEL Not available	occupational exposure
Toluene	Inhalation	gastrointestinal tract	Not classified	Multiple animal species	NOAEL 11.3 mg/l	15 weeks
Toluene	Ingestion	nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 625 mg/kg/day	13 weeks
Toluene	Ingestion	heart	Not classified	Rat	NOAEL 2,500 mg/kg/day	13 weeks
Toluene	Ingestion	liver kidney and/or bladder	Not classified	Multiple animal species	NOAEL 2,500 mg/kg/day	13 weeks
Toluene	Ingestion	hematopoietic system	Not classified	Mouse	NOAEL 600 mg/kg/day	14 days
Toluene	Ingestion	endocrine system	Not classified	Mouse	NOAEL 105 mg/kg/day	28 days
Toluene	Ingestion	immune system	Not classified	Mouse	NOAEL 105 mg/kg/day	4 weeks
Cyclohexane	Inhalation	liver	Not classified	Rat	NOAEL 24 mg/l	90 days
Cyclohexane	Inhalation	auditory system	Not classified	Rat	NOAEL 1.7 mg/l	90 days
Cyclohexane	Inhalation	kidney and/or bladder	Not classified	Rabbit	NOAEL 2.7 mg/l	10 weeks
Cyclohexane	Inhalation	hematopoietic system	Not classified	Mouse	NOAEL 24 mg/l	14 weeks
Cyclohexane	Inhalation	peripheral nervous system	Not classified	Rat	NOAEL 8.6 mg/l	30 weeks
Zinc oxide	Ingestion	nervous system	Not classified	Rat	NOAEL 600 mg/kg/day	10 days
Zinc oxide	Ingestion	endocrine system hematopoietic system kidney and/or bladder	Not classified	Other	NOAEL 500 mg/kg/day	6 months
Ethylbenzene	Inhalation	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1.1 mg/l	2 years
Ethylbenzene	Inhalation	liver	Some positive data exist, but the data are not sufficient for classification	Mouse	NOAEL 1.1 mg/l	103 weeks
Ethylbenzene	Inhalation	hematopoietic system	Not classified	Rat	NOAEL 3.4 mg/l	28 days
Ethylbenzene	Inhalation	auditory system	Not classified	Rat	NOAEL 2.4 mg/l	5 days
Ethylbenzene	Inhalation	endocrine system	Not classified	Mouse	NOAEL 3.3 mg/l	103 weeks
Ethylbenzene	Inhalation	gastrointestinal tract	Not classified	Rat	NOAEL 3.3 mg/l	2 years
Ethylbenzene	Inhalation	bone, teeth, nails, and/or hair muscles	Not classified	Multiple animal species	NOAEL 4.2 mg/l	90 days
Ethylbenzene	Inhalation	heart immune system respiratory system	Not classified	Multiple animal species	NOAEL 3.3 mg/l	2 years
Ethylbenzene	Ingestion	liver kidney and/or bladder	Not classified	Rat	NOAEL 680 mg/kg/day	6 months
Xylene	Inhalation	nervous system	Causes damage to organs through prolonged or repeated exposure	Rat	LOAEL 0.4 mg/l	4 weeks
Xylene	Inhalation	auditory system	May cause damage to organs through prolonged or repeated exposure	Rat	LOAEL 7.8 mg/l	5 days
Xylene	Inhalation	liver	Not classified	Multiple animal species	NOAEL Not available	

Xylene	Inhalation	heart endocrine system gastrointestinal tract hematopoietic system muscles kidney and/or bladder respiratory system	Not classified	Multiple animal species	NOAEL 3.5 mg/l	13 weeks
Xylene	Ingestion	auditory system	Not classified	Rat	NOAEL 900 mg/kg/day	2 weeks
Xylene	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 1,500 mg/kg/day	90 days
Xylene	Ingestion	liver	Not classified	Multiple animal species	NOAEL Not available	
Xylene	Ingestion	heart skin endocrine system bone, teeth, nails, and/or hair hematopoietic system immune system nervous system respiratory system	Not classified	Mouse	NOAEL 1,000 mg/kg/day	103 weeks

Aspiration Hazard

Name	Value
C10-13-iso-Alkanes	Aspiration hazard
n-hexane	Aspiration hazard
Heptane	Aspiration hazard
2-Methylpentane	Aspiration hazard
3-Methylpentane	Aspiration hazard
Toluene	Aspiration hazard
Cyclohexane	Aspiration hazard
Ethylbenzene	Aspiration hazard
Xylene	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labelling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

12.1. Toxicity

Acute aquatic hazard:

GHS Acute 2: Toxic to aquatic life.

Chronic aquatic hazard:

GHS Chronic 2: Toxic to aquatic life with long lasting effects.

No product test data available.

Material	CAS Nbr	Organism	Type	Exposure	Test endpoint	Test result
C10-13-iso-	64741-84-0	Green Algae	Estimated	72 hours	EC50	30 mg/l

Alkanes						
C10-13-iso-Alkanes	64741-84-0	Rainbow trout	Estimated	96 hours	LL50	11.4 mg/l
C10-13-iso-Alkanes	64741-84-0	Water flea	Estimated	48 hours	EL50	3 mg/l
C10-13-iso-Alkanes	64741-84-0	Green Algae	Estimated	72 hours	NOEL	3 mg/l
C10-13-iso-Alkanes	64741-84-0	Water flea	Estimated	21 days	NOEL	1 mg/l
Acetone	67-64-1	Algae other	Experimental	96 hours	EC50	11,493 mg/l
Acetone	67-64-1	Crustacea other	Experimental	24 hours	LC50	2,100 mg/l
Acetone	67-64-1	Rainbow trout	Experimental	96 hours	LC50	5,540 mg/l
Acetone	67-64-1	Water flea	Experimental	21 days	NOEC	1,000 mg/l
Acetone	67-64-1	Bacteria	Experimental	16 hours	NOEC	1,700 mg/l
Acetone	67-64-1	Redworm	Experimental	48 hours	LC50	>100
n-hexane	110-54-3	Fathead minnow	Experimental	96 hours	LC50	2.5 mg/l
n-hexane	110-54-3	Water flea	Experimental	48 hours	LC50	3.9 mg/l
Heptane	142-82-5	Water flea	Experimental	48 hours	EC50	1.5 mg/l
Heptane	142-82-5	Water flea	Estimated	21 days	NOEC	0.17 mg/l
Butanone	78-93-3	Fathead minnow	Experimental	96 hours	LC50	2,993 mg/l
Butanone	78-93-3	Green algae	Experimental	96 hours	ErC50	2,029 mg/l
Butanone	78-93-3	Water flea	Experimental	48 hours	EC50	308 mg/l
Butanone	78-93-3	Green Algae	Experimental	96 hours	ErC10	1,289 mg/l
Butanone	78-93-3	Water flea	Experimental	21 days	NOEC	100 mg/l
Butanone	78-93-3	Bacteria	Experimental	16 hours	LOEC	1,150 mg/l
Polychloroprene	9010-98-4		Data not available or insufficient for classification			N/A
2-Methylpentane	107-83-5		Data not available or insufficient for classification			N/A
3-Methylpentane	96-14-0		Data not available or insufficient for classification			N/A
Magnesium Resinate	68037-42-3		Data not available or insufficient for classification			n/a
Toluene	108-88-3	Coho Salmon	Experimental	96 hours	LC50	5.5 mg/l
Toluene	108-88-3	Grass Shrimp	Experimental	96 hours	LC50	9.5 mg/l
Toluene	108-88-3	Green Algae	Experimental	72 hours	EC50	12.5 mg/l
Toluene	108-88-3	Leopard frog	Experimental	9 days	LC50	0.39 mg/l
Toluene	108-88-3	Pink Salmon	Experimental	96 hours	LC50	6.41 mg/l
Toluene	108-88-3	Water flea	Experimental	48 hours	EC50	3.78 mg/l
Toluene	108-88-3	Coho Salmon	Experimental	40 days	NOEC	1.39 mg/l
Toluene	108-88-3	Diatom	Experimental	72 hours	NOEC	10 mg/l
Toluene	108-88-3	Water flea	Experimental	7 days	NOEC	0.74 mg/l
Toluene	108-88-3	Activated sludge	Experimental	12 hours	IC50	292 mg/l

Toluene	108-88-3	Bacteria	Experimental	16 hours	NOEC	29 mg/l
Toluene	108-88-3	Bacteria	Experimental	24 hours	EC50	84 mg/l
Toluene	108-88-3	Redworm	Experimental	28 days	LC50	>150 mg per kg of bodyweight
Toluene	108-88-3	Soil microbes	Experimental	28 days	NOEC	<26 mg/kg (Dry Weight)
Cyclohexane	110-82-7	Bacteria	Experimental	24 hours	IC50	97 mg/l
Cyclohexane	110-82-7	Fathead minnow	Experimental	96 hours	LC50	4.53 mg/l
Cyclohexane	110-82-7	Water flea	Experimental	48 hours	EC50	0.9 mg/l
Ethylbenzene	100-41-4	Activated sludge	Experimental	49 hours	EC50	130 mg/l
Ethylbenzene	100-41-4	Atlantic Silverside	Experimental	96 hours	LC50	5.1 mg/l
Ethylbenzene	100-41-4	Green Algae	Experimental	96 hours	EC50	3.6 mg/l
Ethylbenzene	100-41-4	Mysid Shrimp	Experimental	96 hours	LC50	2.6 mg/l
Ethylbenzene	100-41-4	Rainbow trout	Experimental	96 hours	LC50	4.2 mg/l
Ethylbenzene	100-41-4	Water flea	Experimental	48 hours	EC50	1.8 mg/l
Ethylbenzene	100-41-4	Water flea	Experimental	7 days	NOEC	0.96 mg/l
Rosin	8050-09-7	Bacteria	Experimental		EC50	76.1 mg/l
Rosin	8050-09-7	Green Algae	Experimental	72 hours	EL50	>100 mg/l
Rosin	8050-09-7	Water flea	Experimental	48 hours	EL50	911 mg/l
Rosin	8050-09-7	Zebra Fish	Experimental	96 hours	LL50	>1 mg/l
Rosin	8050-09-7	Green Algae	Experimental	72 hours	NOEL	100 mg/l
Styrenated Phenol	61788-44-1	Activated sludge	Experimental	3 hours	EC50	362 mg/l
Styrenated Phenol	61788-44-1	Green algae	Experimental	72 hours	EC50	1.35 mg/l
Styrenated Phenol	61788-44-1	Medaka	Experimental	96 hours	LC50	5.6 mg/l
Styrenated Phenol	61788-44-1	Water flea	Experimental	48 hours	EC50	4.6 mg/l
Styrenated Phenol	61788-44-1	Green Algae	Experimental	72 hours	NOEC	0.42 mg/l
Styrenated Phenol	61788-44-1	Water flea	Experimental	21 days	NOEC	0.2 mg/l
Xylene	1330-20-7	Activated sludge	Estimated	3 hours	NOEC	157 mg/l
Xylene	1330-20-7	Green Algae	Estimated	72 hours	EC50	4.36 mg/l
Xylene	1330-20-7	Rainbow trout	Estimated	96 hours	LC50	2.6 mg/l
Xylene	1330-20-7	Water flea	Estimated	48 hours	EC50	3.82 mg/l
Xylene	1330-20-7	Green Algae	Estimated	72 hours	NOEC	0.44 mg/l
Xylene	1330-20-7	Water flea	Estimated	7 days	NOEC	0.96 mg/l
Xylene	1330-20-7	Rainbow trout	Experimental	56 days	NOEC	>1.3 mg/l
Zinc oxide	1314-13-2	Activated sludge	Estimated	3 hours	EC50	6.5 mg/l
Zinc oxide	1314-13-2	Green Algae	Estimated	72 hours	EC50	0.052 mg/l
Zinc oxide	1314-13-2	Rainbow trout	Estimated	96 hours	LC50	0.21 mg/l
Zinc oxide	1314-13-2	Water flea	Estimated	48 hours	EC50	0.07 mg/l
Zinc oxide	1314-13-2	Green Algae	Estimated	72 hours	NOEC	0.006 mg/l
Zinc oxide	1314-13-2	Water flea	Estimated	7 days	NOEC	0.02 mg/l

12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
C10-13-iso-Alkanes	64741-84-0	Estimated Biodegradation	28 days	BOD	98 % BOD/ThBOD	OECD 301F - Manometric respirometry
Acetone	67-64-1	Experimental Photolysis		Photolytic half-life (in air)	147 days (t 1/2)	
Acetone	67-64-1	Experimental Biodegradation	28 days	BOD	78 % BOD/ThBOD	OECD 301D - Closed bottle test
n-hexane	110-54-3	Experimental Photolysis		Photolytic half-life (in air)	5.4 days (t 1/2)	Non-standard method
n-hexane	110-54-3	Experimental Bioconcentration	28 days	BOD	100 % weight	OECD 301C - MITI test (I)
Heptane	142-82-5	Experimental Photolysis		Photolytic half-life (in air)	4.24 days (t 1/2)	Non-standard method
Heptane	142-82-5	Experimental Biodegradation	28 days	BOD	101 % BOD/ThBOD	OECD 301C - MITI test (I)
Butanone	78-93-3	Experimental Biodegradation	28 days	BOD	98 % BOD/ThBOD	OECD 301D - Closed bottle test
Polychloroprene	9010-98-4	Data not available-insufficient			N/A	
2-Methylpentane	107-83-5	Experimental Photolysis		Photolytic half-life (in air)	5.4 days (t 1/2)	Non-standard method
2-Methylpentane	107-83-5	Experimental Biodegradation	28 days	BOD	93 % BOD/ThBOD	OECD 301C - MITI test (I)
3-Methylpentane	96-14-0	Experimental Photolysis		Photolytic half-life (in air)	5.3 days (t 1/2)	Non-standard method
3-Methylpentane	96-14-0	Estimated Biodegradation	28 days	BOD	93 % BOD/ThBOD	OECD 301C - MITI test (I)
Magnesium Resinate	68037-42-3	Data not available-insufficient			N/A	
Toluene	108-88-3	Experimental Photolysis		Photolytic half-life (in air)	5.2 days (t 1/2)	
Toluene	108-88-3	Experimental Biodegradation	20 days	BOD	80 % BOD/ThBOD	APHA Std Meth Water/Wastewater
Cyclohexane	110-82-7	Experimental Photolysis		Photolytic half-life (in air)	4.14 days (t 1/2)	Non-standard method
Cyclohexane	110-82-7	Experimental Biodegradation	28 days	BOD	77 % BOD/ThBOD	OECD 301F - Manometric respirometry
Ethylbenzene	100-41-4	Experimental Photolysis		Photolytic half-life (in air)	4.26 days (t 1/2)	Non-standard method
Ethylbenzene	100-41-4	Experimental Biodegradation	28 days	CO2 evolution	70-80 %CO2 evolution/THC O2 evolution	ISO 14593 Inorg C Headspace
Rosin	8050-09-7	Experimental Biodegradation	28 days	CO2 evolution	64 % weight	OECD 301B - Modified sturm or CO2
Styrenated Phenol	61788-44-1	Experimental Biodegradation	28 days	BOD	7 % BOD/ThBOD	OECD 301F - Manometric respirometry
Xylene	1330-20-7	Experimental		Photolytic half-	1.4 days (t 1/2)	

		Photolysis		life (in air)		
Xylene	1330-20-7	Experimental Biodegradation	28 days	BOD	90-98 % BOD/ThBOD	OECD 301F - Manometric respirometry
Zinc oxide	1314-13-2	Data not available-insufficient			N/A	

12.3 : Bioaccumulative potential

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
C10-13-iso-Alkanes	64741-84-0	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Acetone	67-64-1	Experimental BCF - Other		Bioaccumulation factor	0.65	
Acetone	67-64-1	Experimental Bioconcentration		Log Kow	-0.24	
n-hexane	110-54-3	Estimated Bioconcentration		Bioaccumulation factor	50	Estimated: Bioconcentration factor
Heptane	142-82-5	Estimated Bioconcentration		Bioaccumulation factor	105	Estimated: Bioconcentration factor
Butanone	78-93-3	Experimental Bioconcentration		Log Kow	0.3	OECD 117 log Kow HPLC method
Polychloroprene	9010-98-4	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
2-Methylpentane	107-83-5	Estimated Bioconcentration		Bioaccumulation factor	63	Non-standard method
3-Methylpentane	96-14-0	Estimated Bioconcentration		Bioaccumulation factor	150	Estimated: Bioconcentration factor
Magnesium Resinate	68037-42-3	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Toluene	108-88-3	Experimental BCF - Other	72 hours	Bioaccumulation factor	90	
Toluene	108-88-3	Experimental Bioconcentration		Log Kow	2.73	
Cyclohexane	110-82-7	Experimental BCF-Carp	56 days	Bioaccumulation factor	129	OECD 305E - Bioaccumulation flow-through fish test
Ethylbenzene	100-41-4	Experimental BCF - Salmon	42 days	Bioaccumulation factor	1	Non-standard method
Rosin	8050-09-7	Estimated BCF	20 days	Bioaccumulation factor	129	Non-standard method

		- Rainbow Trout		n factor		
Styrenated Phenol	61788-44-1	Experimental BCF - Rainbow Trout	10 days	Bioaccumulation factor	10395	
Xylene	1330-20-7	Experimental BCF - Rainbow Trout	56 days	Bioaccumulation factor	25.9	
Zinc oxide	1314-13-2	Experimental BCF-Carp	56 days	Bioaccumulation factor	≤217	OECD 305E - Bioaccumulation flow-through fish test

12.4. Mobility in soil

Please contact manufacturer for more details

12.5 Other Adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. Combustion products will include halogen acid (HCl/HF/HBr). Facility must be capable of handling halogenated materials. As a disposal alternative, utilize an acceptable permitted waste disposal facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

SECTION 14: Transport Information

Air Transport (IATA) Regulations

UN No UN1133

Proper Shipping Name Adhesives

Hazard Class/Division 3

Subsidiary Risk Not applicable

Packing Group: II

Marine Transport (IMDG)

UN No UN1133

Proper Shipping Name Adhesives

Hazard Class/Division 3

Subsidiary Risk Not applicable

Packing Group: II

Environmental Hazards: Marine Pollutant: Yes

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The

components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

Applicable Environmental, Health and Safety Regulations

The Manufacture, Storage and Import of Hazardous Chemical Rules, 1989

Hazardous Waste(Management , Handling & Transboundary) Rules, 2008

Hazardous Chemicals (Classification, Packaging and Labelling Draft Rules), 2011

The following ingredients are listed as hazardous on Part II of Schedule I of the India Manufacture, Storage and Import of Hazardous Chemicals (MSIHC) rules

2-Butanone

Acetone

Cyclohexane

Ethylbenzene

n-hexane

Hexane, all isomers

Butanone

Naphtha

Toluene

The following ingredients are classified as hazardous based on the criteria listed under Part I of Schedule I of the India Manufacture, Storage and Import of Hazardous Chemicals (MSIHC) rules:

The product is classified as Very Highly Flammable liquid as per MSIHC Rules, 1989.

SECTION 16: Other information**NFPA Hazard Classification**

Health: 2 **Flammability:** 3 **Instability:** 0 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Revision information:

Label: GHS Classification information was modified.

Label: GHS Precautionary - Prevention information was modified.

Label: GHS Precautionary - Response information was modified.

Label: GHS Target Organ Hazard Statement information was modified.

Label: Signal Word information was modified.

Label: Symbol information was modified.

Section 1: Product identification numbers information was deleted.

Section 09: Percent Volatile information was modified.

Section 09: VOC Less H₂O & Exempt Solvents information was modified.

Section 09: Volatile Organic Compounds information was modified.

Section 11: Acute Toxicity table information was modified.

Section 11: Carcinogenicity Table information was modified.

Section 11: Germ Cell Mutagenicity Table information was modified.

Section 11: Reproductive Toxicity Table information was modified.

Section 11: Respiratory Sensitization Table information was added.
Section 11: Respiratory Sensitization text information was deleted.
Section 11: Serious Eye Damage/Irritation Table information was modified.
Section 11: Skin Corrosion/Irritation Table information was modified.
Section 11: Skin Sensitization Table information was modified.
Section 11: Target Organs - Repeated Table information was modified.
Section 11: Target Organs - Single Table information was modified.
Section 12: Component ecotoxicity information information was modified.
Section 12: Persistence and Degradability information information was modified.
Section 12: Biocumulative potential information information was modified.
Section 14: Environmental hazards information was modified.
Section 15: MSIHC Ingredients information was modified.
Section 2: Ingredient table information was modified.
Section 5: Hazardous combustion products table information was modified.
Section 8: Occupational exposure limit table information was modified.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

3M India SDSs are available at <http://solutions.3mindia.co.in>