



## Safety Data Sheet

Copyright, 2017, 3M India Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

<b>Document group:</b>	33-7187-9	<b>Version number:</b>	1.00
<b>Issue Date:</b>	13/02/2017	<b>Supersedes date:</b>	Initial issue.

This Safety Data Sheet has been prepared in accordance with the GHS guidelines & India Hazardous substances (Classification, Labeling & Packaging) Draft Rules 2011.

### SECTION 1: Identification

#### 1.1. Product identifier

3M(TM) Scotch-Weld(TM) Acrylic Adhesive DP8425NS Green and Acrylic Adhesive 8425NS Green, Part B

#### Product Identification Numbers

62-2862-8530-9      62-2862-9530-8

#### 1.2. Recommended use and restrictions on use

##### Recommended use

Structural adhesive.

#### 1.3. Supplier's details

**Address:** 3M India Limited, plot-48-51, Electronic city, Hosur road, Bangalore-560100  
**Telephone:** 080-39143000, contact Product EHS team  
**E Mail:** productehs.in@mmm.com  
**Website:** <http://solutions.3mindia.co.in>

#### 1.4. Emergency telephone number

080-39143000 (Contact hours: 8:00 AM to 5:00 PM)

### SECTION 2: Hazard identification

Under MSIHC Rules, information is noted below on flammability, acute toxicity and explosivity relevant to this product. In line with international standards, information on other hazard classes and associated precautionary statements relevant to this product are included as well.

#### 2.1. Classification of the substance or mixture

Flammable Liquid: Category 2.  
Acute Toxicity (inhalation): Category 5.  
Serious Eye Damage/Irritation: Category 2A  
Skin Corrosion/Irritation: Category 3.  
Skin Sensitizer: Category 1.  
Specific Target Organ Toxicity (single exposure): Category 3.  
Specific Target Organ Toxicity (repeated exposure): Category 1.  
Acute Aquatic Toxicity: Category 1.  
Chronic Aquatic Toxicity: Category 1.

## 2.2. Label elements

### Signal Word

DANGER!

### Symbols

Flame | Exclamation mark | Health Hazard | Environment |

### Pictograms



### HAZARD STATEMENTS:

H225	Highly flammable liquid and vapour.
H333	May be harmful if inhaled.
H319	Causes serious eye irritation.
H316	Causes mild skin irritation.
H317	May cause an allergic skin reaction.
H335	May cause respiratory irritation.
H372	Causes damage to organs through prolonged or repeated exposure: sensory organs
H410	Very toxic to aquatic life with long lasting effects.

### PRECAUTIONARY STATEMENTS

#### Prevention:

P210	Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P233	Keep container tightly closed.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P271	Use only outdoors or in a well-ventilated area.
P280E	Wear protective gloves.
P273	Avoid release to the environment.

#### Response:

P304 + P312	IF INHALED: Call a POISON CENTER or doctor/physician if you feel unwell.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
P332 + P313	If skin irritation occurs: Get medical advice/attention.
P370 + P378G	In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

#### Storage:

P403 + P235	Store in a well-ventilated place. Keep cool.
-------------	--

#### Disposal:

P501	Dispose of contents/container in accordance with applicable local/regional/national/international regulations.
------	--

## 2.3. Other hazards

**3M(TM) Scotch-Weld(TM) Acrylic Adhesive DP8425NS Green and Acrylic Adhesive 8425NS Green, Part B**

None known.

**SECTION 3: Composition/information on ingredients**

This material is a mixture.

<b>Ingredient</b>	<b>CAS Nbr</b>	<b>% by Wt</b>
Methyl methacrylate	80-62-6	40 - 65
Acrylonitrile-Butadiene Polymer	9003-18-3	1 - 25
Fillers (NJTS Reg. No. 04499600-6923)	Trade Secret	5 - 25
Bisphenol A Polyethylene Glycol Diether Dimethacrylate	41637-38-1	0.1 - 10
Hydroxyethyl Methacrylate	868-77-9	0.1 - 10
Hydrotreated light paraffinic distillates (petroleum)	64742-55-8	<= 5
Phosphate Esters of PPG Methacrylate (NJTS Reg. No. 04499600-6924)	Trade Secret	0.1 - 5
Naphthenic acids, copper salts	1338-02-9	<= 0.2

**SECTION 4: First aid measures****4.1. Description of first aid measures****Inhalation**

Remove person to fresh air. If you feel unwell, get medical attention.

**Skin contact**

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

**Eye contact**

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

**If swallowed**

Rinse mouth. If you feel unwell, get medical attention.

**4.2. Most important symptoms and effects, both acute and delayed**

See Section 11.1 Information on toxicological effects

**4.3. Indication of any immediate medical attention and special treatment required**

Not applicable

**SECTION 5: Fire-fighting measures****5.1. Suitable Extinguishing media**

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

**5.2. Special hazards arising from the substance or mixture**

Closed containers exposed to heat from fire may build pressure and explode.

**Hazardous Decomposition or By-Products****Substance**

Carbon monoxide.

**Condition**

During combustion.

### 3M(TM) Scotch-Weld(TM) Acrylic Adhesive DP8425NS Green and Acrylic Adhesive 8425NS Green, Part B

Carbon dioxide.  
Oxides of nitrogen.

During combustion.  
During combustion.

#### 5.3. Special protective actions for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture.

## SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

#### 6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

#### 6.3. Methods and material for containment and cleaning up

Contain spill. Cover spill area with a fire-extinguishing foam. An appropriate aqueous film forming foam (AFFF) is recommended. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible.

## SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

For industrial or professional use only. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.) Wear low static or properly grounded shoes. To minimize the risk of ignition, determine applicable electrical classifications for the process using this product and select specific local exhaust ventilation equipment to avoid flammable vapor accumulation. Ground/bond container and receiving equipment if there is potential for static electricity accumulation during transfer.

#### 7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store away from heat. Store away from acids. Store away from strong bases. Store away from oxidising agents. Store away from amines.

## SECTION 8: Exposure controls/personal protection

#### 8.1 Control parameters

##### Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available

**3M(TM) Scotch-Weld(TM) Acrylic Adhesive DP8425NS Green and Acrylic Adhesive 8425NS Green, Part B**

for the component.

<b>Ingredient</b>	<b>CAS Nbr</b>	<b>Agency</b>	<b>Limit type</b>	<b>Additional comments</b>
COPPER COMPOUNDS	1338-02-9	ACGIH	TWA(as Cu dust or mist):1 mg/m <sup>3</sup> ;TWA(as Cu, fume):0.2 mg/m <sup>3</sup>	
Methyl methacrylate	80-62-6	ACGIH	TWA:50 ppm;STEL:100 ppm	Dermal Sensitizer, A4: Not class. as human carcin
Fillers (NJTS Reg. No. 04499600-6923)	Trade Secret	ACGIH	TWA(respirable fraction):2 mg/m <sup>3</sup>	A4: Not class. as human carcin

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

## **8.2. Exposure controls**

### **8.2.1. Engineering controls**

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment. Use explosion-proof ventilation equipment.

### **8.2.2. Personal protective equipment (PPE)**

#### **Eye/face protection**

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect vented goggles.

#### **Skin/hand protection**

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

#### **Respiratory protection**

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

## **SECTION 9: Physical and chemical properties**

### **9.1. Information on basic physical and chemical properties**

**Physical state**

Liquid.

**Specific Physical Form:**

Paste

**Appearance/Odour**

White methacrylate odour

**Odour threshold**

*No data available.*

pH	<i>Not applicable.</i>
Melting point/Freezing point: NA	<i>Not applicable.</i>
Boiling point/Initial boiling point/Boiling range	$\geq 37.8$ °C
Flash point	$\geq 10$ °C [ <i>Test Method</i> :Closed Cup]
Evaporation rate	<i>No data available.</i>
Flammability (solid, gas)	Not applicable.
Flammable Limits(LEL)	<i>No data available.</i>
Flammable Limits(UEL)	<i>No data available.</i>
Vapour pressure	<i>No data available.</i>
Density	1.15 g/ml
Relative density	1.15 [ <i>Ref Std</i> :WATER=1]
Water solubility	Nil
Solubility- non-water	<i>No data available.</i>
Partition coefficient: n-octanol/water	<i>No data available.</i>
Autoignition temperature	<i>No data available.</i>
Decomposition temperature	<i>No data available.</i>
Viscosity	85,000 mPa-s
VOC less H <sub>2</sub> O & exempt solvents	21.8 g/l [ <i>Details</i> :when used as intended with Part A]
VOC less H <sub>2</sub> O & exempt solvents	1.9 % [ <i>Details</i> :when used as intended with Part A]

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

### 10.2 Chemical stability

Stable.

### 10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

### 10.4 Conditions to avoid

Heat.

Sparks and/or flames.

### 10.5 Incompatible materials

Amines.

Strong acids.

Strong bases.

Strong oxidising agents.

### 10.6 Hazardous decomposition products

#### Substance

None known.

#### Condition

Refer to section 5.2 for hazardous decomposition products during combustion.

## SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be

relevant to the material as a whole.

## 11.1 Information on Toxicological effects

### Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### Inhalation

May be harmful if inhaled. Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

#### Skin contact

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

#### Eye contact

Severe eye irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

#### Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.

### Additional Health Effects:

#### Prolonged or repeated exposure may cause target organ effects:

Olfactory effects: Signs/symptoms may include decreased ability to detect odours and complete loss of smell.

### Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

#### Acute Toxicity

Name	Route	Species	Value
Overall product	Inhalation-Vapor(4 hr)		No data available; calculated ATE20 - 50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Methyl methacrylate	Dermal	Rabbit	LD50 > 5,000 mg/kg
Methyl methacrylate	Inhalation-Vapor (4 hours)	Rat	LC50 29 mg/l
Methyl methacrylate	Ingestion	Rat	LD50 7,900 mg/kg
Acrylonitrile-Butadiene Polymer	Dermal	Rabbit	LD50 > 15,000 mg/kg
Acrylonitrile-Butadiene Polymer	Ingestion	Rat	LD50 > 30,000 mg/kg
Bisphenol A Polyethylene Glycol Diether Dimethacrylate	Dermal	Professional judgment	LD50 estimated to be > 5,000 mg/kg
Bisphenol A Polyethylene Glycol Diether Dimethacrylate	Ingestion	Rat	LD50 > 2,000 mg/kg
Fillers (NJTS Reg. No. 04499600-6923)	Dermal		LD50 estimated to be > 5,000 mg/kg
Fillers (NJTS Reg. No. 04499600-6923)	Ingestion	Human	LD50 > 15,000 mg/kg
Hydroxyethyl Methacrylate	Dermal	Rabbit	LD50 > 5,000 mg/kg
Hydroxyethyl Methacrylate	Ingestion	Rat	LD50 5,564 mg/kg
Naphthenic acids, copper salts	Dermal		estimated to be > 5,000 mg/kg
Naphthenic acids, copper salts	Inhalation-Dust/Mist		estimated to be > 12.5 mg/l
Naphthenic acids, copper salts	Inhalation-Vapor		estimated to be > 50 mg/l
Naphthenic acids, copper salts	Ingestion		estimated to be 300 - 2,000 mg/kg

**3M(TM) Scotch-Weld(TM) Acrylic Adhesive DP8425NS Green and Acrylic Adhesive 8425NS Green, Part B**

ATE = acute toxicity estimate

**Skin Corrosion/Irritation**

Name	Species	Value
Methyl methacrylate	Human and animal	Mild irritant
Acrylonitrile-Butadiene Polymer	Professional judgement	No significant irritation
Fillers (NJTS Reg. No. 04499600-6923)	Professional judgement	No significant irritation
Hydroxyethyl Methacrylate	Rabbit	Minimal irritation

**Serious Eye Damage/Irritation**

Name	Species	Value
Methyl methacrylate	Rabbit	Moderate irritant
Acrylonitrile-Butadiene Polymer	Professional judgement	No significant irritation
Fillers (NJTS Reg. No. 04499600-6923)	Professional judgement	No significant irritation
Hydroxyethyl Methacrylate	Rabbit	Moderate irritant

**Skin Sensitisation**

Name	Species	Value
Methyl methacrylate	Human and animal	Sensitising
Bisphenol A Polyethylene Glycol Diether Dimethacrylate	Guinea pig	Not sensitizing
Hydroxyethyl Methacrylate	Human and animal	Sensitising

**Respiratory Sensitisation**

Name	Species	Value
Methyl methacrylate	Human	Some positive data exist, but the data are not sufficient for classification

**Germ Cell Mutagenicity**

Name	Route	Value
Methyl methacrylate	In vivo	Not mutagenic
Methyl methacrylate	In Vitro	Some positive data exist, but the data are not sufficient for classification
Bisphenol A Polyethylene Glycol Diether Dimethacrylate	In Vitro	Not mutagenic
Hydroxyethyl Methacrylate	In vivo	Not mutagenic
Hydroxyethyl Methacrylate	In Vitro	Some positive data exist, but the data are not sufficient for classification

**Carcinogenicity**

Name	Route	Species	Value
------	-------	---------	-------



**3M(TM) Scotch-Weld(TM) Acrylic Adhesive DP8425NS Green and Acrylic Adhesive 8425NS Green, Part B**

Methyl methacrylate	Ingestion	Rat	Not carcinogenic
Methyl methacrylate	Inhalation	Human and animal	Not carcinogenic
Fillers (NJTS Reg. No. 04499600-6923)	Inhalation	Multiple animal species	Not carcinogenic

**Reproductive Toxicity****Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test result	Exposure Duration
Methyl methacrylate	Inhalation	Not toxic to male reproduction	Mouse	NOAEL 36.9 mg/l	
Methyl methacrylate	Inhalation	Not toxic to development	Rat	NOAEL 8.3 mg/l	during organogenesis
Hydroxyethyl Methacrylate	Ingestion	Not toxic to female reproduction	Rat	NOAEL 1,000 mg/kg/day	premating & during gestation
Hydroxyethyl Methacrylate	Ingestion	Not toxic to male reproduction	Rat	NOAEL 1,000 mg/kg/day	49 days
Hydroxyethyl Methacrylate	Ingestion	Not toxic to development	Rat	NOAEL 1,000 mg/kg/day	premating & during gestation

**Target Organ(s)****Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Methyl methacrylate	Inhalation	respiratory irritation	May cause respiratory irritation	Human	NOAEL Not available	occupational exposure

**Specific Target Organ Toxicity - repeated exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Methyl methacrylate	Dermal	peripheral nervous system	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure
Methyl methacrylate	Inhalation	olfactory system	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure
Methyl methacrylate	Inhalation	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Multiple animal species	NOAEL Not available	14 weeks
Methyl methacrylate	Inhalation	liver	Some positive data exist, but the data are not sufficient for classification	Mouse	NOAEL 12.3 mg/l	14 weeks
Methyl methacrylate	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure
Fillers (NJTS Reg. No. 04499600-6923)	Inhalation	pneumoconiosis	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL NA	occupational exposure
Fillers (NJTS Reg. No. 04499600-6923)	Inhalation	pulmonary fibrosis	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL Not available	

**Aspiration Hazard**

For the component/components, either no data are currently available or the data are not sufficient for classification.

**Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.**

## SECTION 12: Ecological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labelling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

### 12.1. Toxicity

#### Acute aquatic hazard:

GHS Acute 1: Very toxic to aquatic life.

#### Chronic aquatic hazard:

GHS Chronic 1: Very toxic to aquatic life with long lasting effects.

No product test data available.

Material	CAS Nbr	Organism	Type	Exposure	Test endpoint	Test result
Hydrotreated light paraffinic distillates (petroleum)	64742-55-8	Rainbow trout	Experimental	96 hours	LC50	>100 mg/l
Hydrotreated light paraffinic distillates (petroleum)	64742-55-8	Green algae	Experimental	96 hours	EC50	>100 mg/l
Hydrotreated light paraffinic distillates (petroleum)	64742-55-8	Water flea	Experimental	21 days	NOEC	1,000 mg/l
Naphthenic acids, copper salts	1338-02-9	Water flea	Experimental	48 hours	EC50	0.34 mg/l
Naphthenic acids, copper salts	1338-02-9	Fish	Experimental	96 hours	LC50	0.00034 mg/l
Methyl methacrylate	80-62-6	Water flea	Experimental	48 hours	EC50	69 mg/l
Methyl methacrylate	80-62-6	Green algae	Experimental	96 hours	EC50	170 mg/l
Methyl methacrylate	80-62-6	Bluegill	Experimental	96 hours	LC50	191 mg/l
Methyl methacrylate	80-62-6	Water flea	Experimental	21 days	NOEC	37 mg/l
Fillers (NJTS Reg. No. 04499600-6923)	Trade Secret		Data not available or insufficient for classification			
Hydroxyethyl Methacrylate	868-77-9	Fathead minnow	Experimental	96 hours	LC50	227 mg/l
Hydroxyethyl Methacrylate	868-77-9	Water flea	Experimental	48 hours	EC50	380 mg/l
Hydroxyethyl Methacrylate	868-77-9	Green Algae	Experimental	72 hours	EC50	345 mg/l

**3M(TM) Scotch-Weld(TM) Acrylic Adhesive DP8425NS Green and Acrylic Adhesive 8425NS Green, Part B**

Hydroxyethyl Methacrylate	868-77-9	Green Algae	Experimental	72 hours	NOEC	160 mg/l
Hydroxyethyl Methacrylate	868-77-9	Water flea	Experimental	21 days	NOEC	24.1 mg/l
Bisphenol A Polyethylene Glycol Diether Dimethacrylate	41637-38-1		Data not available or insufficient for classification			
Acrylonitrile-Butadiene Polymer	9003-18-3		Data not available or insufficient for classification			

**12.2. Persistence and degradability**

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Methyl methacrylate	80-62-6	Estimated Photolysis		Photolytic half-life (in air)	1.23 days (t <sub>1/2</sub> )	Other methods
Hydroxyethyl Methacrylate	868-77-9	Experimental Hydrolysis		Hydrolytic half-life	10.9 days (t <sub>1/2</sub> )	Other methods
Naphthenic acids, copper salts	1338-02-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Acrylonitrile-Butadiene Polymer	9003-18-3	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Fillers (NJTS Reg. No. 04499600-6923)	Trade Secret	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Methyl methacrylate	80-62-6	Experimental Biodegradation	28 days	BOD	88 % weight	OECD 301D - Closed bottle test
Hydrotreated light paraffinic distillates (petroleum)	64742-55-8	Experimental Biodegradation	28 days	CO <sub>2</sub> evolution	22 % weight	OECD 301B - Modified sturm or CO <sub>2</sub>
Bisphenol A Polyethylene Glycol Diether Dimethacrylate	41637-38-1	Calculated Biodegradation	28 days	BOD	38 % weight	OECD 301C - MITI test (I)
Hydroxyethyl Methacrylate	868-77-9	Experimental Biodegradation	14 days	BOD	95 % weight	OECD 301C - MITI test (I)

**12.3 : Bioaccumulative potential**

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Fillers (NJTS Reg. No. 04499600-6923)	Trade Secret	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Hydrotreated light paraffinic distillates	64742-55-8	Data not available or insufficient for	N/A	N/A	N/A	N/A

**3M(TM) Scotch-Weld(TM) Acrylic Adhesive DP8425NS Green and Acrylic Adhesive 8425NS Green, Part B**

(petroleum)		classification				
Acrylonitrile-Butadiene Polymer	9003-18-3	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Bisphenol A Polyethylene Glycol Diether Dimethacrylate	41637-38-1	Calculated Bioconcentration		Bioaccumulation factor	6.7	Estimated: Bioconcentration factor
Hydroxyethyl Methacrylate	868-77-9	Experimental Bioconcentration		Log Kow	0.47	Other methods
Naphthenic acids, copper salts	1338-02-9	Experimental Bioconcentration		Log Kow	4.1	Other methods
Methyl methacrylate	80-62-6	Experimental Bioconcentration		Log Kow	1.38	Other methods

**12.4. Mobility in soil**

Please contact manufacturer for more details

**12.5 Other Adverse effects**

No information available.

**SECTION 13: Disposal considerations****13.1. Disposal methods**

See Section 11.1 Information on toxicological effects

Dispose of completely cured (or polymerised) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

**SECTION 14: Transport Information****Air Transport (IATA) Regulations**

UN No UN1133

Proper Shipping Name Adhesives

Hazard Class/Division 3

Subsidiary Risk Not applicable

Packing Group: II

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****Global inventory status**

All applicable chemical ingredients in this material are listed on the European Inventory of Existing Chemical Substances

## 3M(TM) Scotch-Weld(TM) Acrylic Adhesive DP8425NS Green and Acrylic Adhesive 8425NS Green, Part B

(EINECS), or are exempt polymers whose monomers are listed on EINECS. Contact 3M for more information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the chemical notification requirements of TSCA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory.

### Applicable Environmental, Health and Safety Regulations

Manufacture, Storage and Import of Hazardous Chemical Rules, 1989  
Hazardous Waste(Management , Handling & Transboundary) Rules, 2008  
Hazardous Chemicals (Classification, Packaging and Label Rules), 2001  
Central Motor Vehicle Rules, 1989

The following ingredients are listed as hazardous on Part II of Schedule I of the India Manufacture, Storage and Import of Hazardous Chemicals (MSIHC) rules

COPPER COMPOUNDS

Methyl methacrylate

The following ingredients are classified as hazardous based on the criteria listed under Part I of Schedule I of the India Manufacture, Storage and Import of Hazardous Chemicals (MSIHC) rules:

Product is classified as very highly flammable liquid

## SECTION 16: Other information

### NFPA Hazard Classification

**Health:** 2    **Flammability:** 3    **Instability:** 0    **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

### Revision information:

No revision information

**DISCLAIMER:** The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

**3M India SDSs are available at <http://solutions.3mindia.co.in>**