

# Safety Data Sheet

Copyright, 2024, 3M India Limited. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

**Document group:** 34-5178-8 **Version number:** 1.01

**Issue Date:** 07/03/2024 **Supersedes date:** 28/11/2020

This Safety Data Sheet has been prepared in accordance with the GHS guidelines & India Hazardous substances (Classification, Labeling & Packaging) Draft Rules 2011.

# **SECTION 1: Identification**

#### 1.1. Product identifier

3M<sup>TM</sup> Perfect-It<sup>TM</sup> EX Machine Polish, 06093, 06094, 06095, 06096, 36093

#### **Product Identification Numbers**

60-4550-8470-1 IA-2601-0438-4

#### 1.2. Recommended use and restrictions on use

#### Recommended use

Automotive., Rubbing Compound

## 1.3. Supplier's details

Address: 3M India Limited, plot-48-51, Electronic city, Hosur road, Bangalore-560100

**Telephone:** 080-45543000, contact Product EHS team

E Mail: productehs.in@mmm.com
Website: http://solutions.3mindia.co.in

## 1.4. Emergency telephone number

080-45543000 (Contact hours: 8:00 AM to 5:00 PM)

## **SECTION 2: Hazard identification**

Under MSIHC Rules, information is noted below on flammability, acute toxicity and explosivity relevant to this product. In line with international standards, information on other hazard classes and associated precautionary statements relevant to this product are included as well.

## 2.1. Classification of the substance or mixture

Skin Corrosion/Irritation: Category 3. Skin Sensitizer: Category 1B. Acute Aquatic Toxicity: Category 3. Chronic Aquatic Toxicity: Category 3.

#### 2.2. Label elements

## Signal Word

Warning

## **Symbols**

Exclamation mark |

#### **Pictograms**



#### **HAZARD STATEMENTS:**

H316 Causes mild skin irritation.

H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

#### PRECAUTIONARY STATEMENTS

General:

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

**Prevention:** 

P280E Wear protective gloves.

**Response:** 

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

Disposal:

P501 Dispose of contents/container in accordance with applicable

local/regional/national/international regulations.

#### 2.3. Other hazards

Persons previously sensitised to amines may develop a cross-sensitisation reaction to certain other amines.

# **SECTION 3: Composition/information on ingredients**

This material is a mixture.

Ingredient	CAS Nbr	% by Wt
Water	7732-18-5	45 - 70
Distillates (petroleum), hydrotreated light	64742-47-8	10 - 30
Aluminum Oxide (non-fibrous)	1344-28-1	7 - 13
Dodecamethylcyclohexasiloxane	540-97-6	1 - 5
White Mineral Oil (Petroleum)	8042-47-5	1 - 5
Ethylenediamine, ethoxylated and	26316-40-5	0.5 - 1.5
propoxylated		

# **SECTION 4: First aid measures**

## 4.1. Description of first aid measures

#### Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

## 3M<sup>™</sup> Perfect-It<sup>™</sup> EX Machine Polish, 06093, 06094, 06095, 06096, 36093

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

#### Eye contact

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

#### If swallowed

Rinse mouth. If you feel unwell, get medical attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

Allergic skin reaction (redness, swelling, blistering, and itching).

#### 4.3. Indication of any immediate medical attention and special treatment required

Not applicable

# **SECTION 5: Fire-fighting measures**

#### 5.1. Suitable Extinguishing media

Use a fire fighting agent suitable for the surrounding fire.

### 5.2. Special hazards arising from the substance or mixture

None inherent in this product.

## **Hazardous Decomposition or By-Products**

#### **Substance**

Hydrocarbons.

Carbon monoxide.

Carbon dioxide.

Oxides of nitrogen.

#### Condition

During combustion.

During combustion.

During combustion.

During combustion.

## 5.3. Special protective actions for fire-fighters

No special protective actions for fire-fighters are anticipated.

## **SECTION 6: Accidental release measures**

## 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

## 6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

## 6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

# **SECTION 7: Handling and storage**

## 7.1. Precautions for safe handling

Keep out of reach of children. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse.

#### 7.2. Conditions for safe storage including any incompatibilities

No special storage requirements.

# **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

## Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

TOT THE COMPONENT.				
Ingredient	CAS Nbr	Agency	Limit type	<b>Additional comments</b>
Aluminum, insoluble compounds	1344-28-1	ACGIH	TWA(respirable fraction):1	A4: Not class. as human
			mg/m3	carcin
Kerosine (petroleum)	64742-47-8	ACGIH	TWA(as total hydrocarbon	A3: Confirmed animal
			vapor, non-aerosol):200	carcin., SKIN
			mg/m3	
MINERAL OILS, HIGHLY-	8042-47-5	ACGIH	TWA(inhalable fraction):5	A4: Not class. as human
REFINED OILS			mg/m3	carcin

ACGIH: American Conference of Governmental Industrial Hygienists

AIHA: American Industrial Hygiene Association

CMRG: Chemical Manufacturer's Recommended Guidelines

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

## 8.2. Exposure controls

#### 8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

#### 8.2.2. Personal protective equipment (PPE)

#### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety glasses with side shields.

#### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an

exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

## Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

# **SECTION 9: Physical and chemical properties**

9.1. Information on basic physical and chemical properties

Physical stateLiquid.ColorGrayOdorMild Odor	
J	
Oden Mild Oden	
Odor Willa Odor	
Odour threshold No data available.	
<b>pH</b> 7.5 - 9	
Melting point/Freezing point: NA  No data available.	
Boiling point/Initial boiling point/Boiling range  No data available.	
Flash point No flash point	
<b>Evaporation rate</b> No data available.	
Flammability (solid, gas) Not applicable.	
Flammable Limits(LEL)  No data available.	
Flammable Limits(UEL)  No data available.	
Vapour pressure No data available.	
Vapor Density and/or Relative Vapor Density  No data available.	
<b>Density</b> 1 - 1.02 g/ml	
<b>Relative density</b> 1 - 1.02 [ <i>Ref Std</i> :WATER=1]	
Water solubility No data available.	
Solubility- non-water No data available.	
Partition coefficient: n-octanol/water No data available.	
Autoignition temperature No data available.	
<b>Decomposition temperature</b> No data available.	
Viscosity/Kinematic Viscosity 22,000 - 28,000 mPa-s	
Volatile organic compounds (VOC) 167 g/l [Test Method:calculated SCAQMD rule 443.1]	
Volatile organic compounds (VOC) 16 % weight [Test Method:calculated per CARB title 2]	
Percent volatile 81.5 % weight	
VOC less H2O & exempt solvents 487 g/l [Test Method:calculated SCAQMD rule 443.1]	
Molecular weight Not applicable.	

# **SECTION 10: Stability and reactivity**

### 10.1 Reactivity

This material is considered to be non reactive under normal use conditions

## 10.2 Chemical stability

Stable.

### 10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

#### 10.4 Conditions to avoid

None known.

#### 10.5 Incompatible materials

None known.

#### 10.6 Hazardous decomposition products

**Substance** 

**Condition** 

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

# **SECTION 11: Toxicological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

### 11.1 Information on Toxicological effects

### Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

#### Skin contact

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

#### Eve contact

Dust created by cutting, grinding, sanding, or machining may cause eye irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

#### Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.

#### Additional information:

Persons previously sensitised to amines may develop a cross-sensitisation reaction to certain other amines.

# **Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

**Acute Toxicity** 

Name	Route	Species	Value
Overall product	Inhalation- Vapor(4 hr)		No data available; calculated ATE >50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Distillates (petroleum), hydrotreated light	Ingestion	Rat	LD50 > 15,000 mg/kg
Distillates (petroleum), hydrotreated light	Dermal	similar compoun	LD50 > 5,000 mg/kg

		ds	
Aluminum Oxide (non-fibrous)	Dermal		LD50 estimated to be > 5,000 mg/kg
Aluminum Oxide (non-fibrous)	Inhalation-	Rat	LC50 > 2.3 mg/l
	Dust/Mist		
	(4 hours)		
Aluminum Oxide (non-fibrous)	Ingestion	Rat	LD50 > 5,000 mg/kg
Dodecamethylcyclohexasiloxane	Dermal	Rat	LD50 > 2,000  mg/kg
Dodecamethylcyclohexasiloxane	Ingestion	Rat	LD50 > 50,000 mg/kg
White Mineral Oil (Petroleum)	Dermal	Rabbit	LD50 > 2,000  mg/kg
White Mineral Oil (Petroleum)	Ingestion	Rat	LD50 > 5,000 mg/kg
Ethylenediamine, ethoxylated and propoxylated	Dermal	Rabbit	LD50 > 5,000  mg/kg
Ethylenediamine, ethoxylated and propoxylated	Ingestion	Rat	LD50 > 5,000 mg/kg

ATE = acute toxicity estimate

## Skin Corrosion/Irritation

Name	Species	Value
Distillates (petroleum), hydrotreated light	similar	Mild irritant
	compoun	
	ds	
Aluminum Oxide (non-fibrous)	Rabbit	No significant irritation
Dodecamethylcyclohexasiloxane	Rabbit	No significant irritation
White Mineral Oil (Petroleum)	Rabbit	No significant irritation
Ethylenediamine, ethoxylated and propoxylated	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Serious Lye Duminger Illienteron		
Name	Species	Value
Distillates (petroleum), hydrotreated light	similar compoun ds	No significant irritation
Aluminum Oxide (non-fibrous)	Rabbit	No significant irritation
Dodecamethylcyclohexasiloxane	Rabbit	No significant irritation
White Mineral Oil (Petroleum)	Rabbit	Mild irritant
Ethylenediamine, ethoxylated and propoxylated	Rabbit	Moderate irritant

## **Sensitization:**

## **Skin Sensitisation**

Skiii Schsitisation		
Name	Species	Value
Distillates (petroleum), hydrotreated light	similar compoun ds	Not classified
White Mineral Oil (Petroleum)	Guinea pig	Not classified
Ethylenediamine, ethoxylated and propoxylated	Mouse	Sensitising

# **Respiratory Sensitisation**

For the component/components, either no data are currently available or the data are not sufficient for classification.

**Germ Cell Mutagenicity** 

Name	Route	Value
Distillates (petroleum), hydrotreated light	In Vitro	Not mutagenic
Aluminum Oxide (non-fibrous)	In Vitro	Not mutagenic
White Mineral Oil (Petroleum)	In Vitro	Not mutagenic
Ethylenediamine, ethoxylated and propoxylated	In Vitro	Not mutagenic

Carcinogenicity

Name Route Species Value
--------------------------

Page: 7 of 13

Aluminum Oxide (non-fibrous)	Inhalation	Rat	Not carcinogenic
White Mineral Oil (Petroleum)	Dermal	Mouse	Not carcinogenic
White Mineral Oil (Petroleum)	Inhalation	Multiple	Not carcinogenic
		animal	
		species	

# Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
Dodecamethylcyclohexasiloxane	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	premating & during gestation
Dodecamethylcyclohexasiloxane	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	28 days
Dodecamethylcyclohexasiloxane	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	premating & during gestation
White Mineral Oil (Petroleum)	Ingestion	Not classified for female reproduction	Rat	NOAEL 4,350 mg/kg/day	13 weeks
White Mineral Oil (Petroleum)	Ingestion	Not classified for male reproduction	Rat	NOAEL 4,350 mg/kg/day	13 weeks
White Mineral Oil (Petroleum)	Ingestion	Not classified for development	Rat	NOAEL 4,350 mg/kg/day	during gestation
Ethylenediamine, ethoxylated and propoxylated	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	premating into lactation
Ethylenediamine, ethoxylated and propoxylated	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	40 days
Ethylenediamine, ethoxylated and propoxylated	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	during gestation

# Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Distillates (petroleum), hydrotreated light	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
Ethylenediamine, ethoxylated and propoxylated	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Distillates (petroleum), hydrotreated light	Inhalation	liver	Not classified	Rat	NOAEL 6 mg/l	13 weeks
Distillates (petroleum), hydrotreated light	Inhalation	kidney and/or bladder	Not classified	Rat	LOAEL 1.5 mg/l	13 weeks
Distillates (petroleum), hydrotreated light	Inhalation	hematopoietic system	Not classified	Rat	NOAEL 6 mg/l	13 weeks
Distillates (petroleum), hydrotreated light	Ingestion	liver	Not classified	Rat	NOAEL 1,000 mg/kg/day	13 weeks
Distillates (petroleum), hydrotreated light	Ingestion	kidney and/or bladder	Not classified	Rat	LOAEL 100 mg/kg/day	13 weeks

Distillates (petroleum), hydrotreated light	Ingestion	hematopoietic system   eyes	Not classified	Rat	NOAEL 1,000 mg/kg/day	13 weeks
Aluminum Oxide (non-fibrous)	Inhalation	pneumoconiosis	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure
Aluminum Oxide (non- fibrous)	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not available	occupational exposure
Dodecamethylcyclohexasil oxane	Ingestion	endocrine system   liver   respiratory system   nervous system	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
White Mineral Oil (Petroleum)	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 1,381 mg/kg/day	90 days
White Mineral Oil (Petroleum)	Ingestion	liver   immune system	Not classified	Rat	NOAEL 1,336 mg/kg/day	90 days
Ethylenediamine, ethoxylated and propoxylated	Ingestion	gastrointestinal tract   hematopoietic   system   respiratory   system	Not classified	Rat	NOAEL 1,000 mg/kg/day	90 days
Ethylenediamine, ethoxylated and propoxylated	Ingestion	endocrine system	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
Ethylenediamine, ethoxylated and propoxylated	Ingestion	eyes   kidney and/or bladder	Not classified	Rat	NOAEL 1,000 mg/kg/day	90 days
Ethylenediamine, ethoxylated and propoxylated	Ingestion	heart   skin   bone, teeth, nails, and/or hair   liver   immune system   muscles   nervous system   vascular system	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days

**Aspiration Hazard** 

Name	Value
Distillates (petroleum), hydrotreated light	Aspiration hazard
White Mineral Oil (Petroleum)	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

# **SECTION 12: Ecological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labelling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

## 12.1. Toxicity

### Acute aquatic hazard:

GHS Acute 3: Harmful to aquatic life.

#### Chronic aquatic hazard:

GHS Chronic 3: Harmful to aquatic life with long lasting effects.

No product test data available.

Material	CAS Nbr	Organism	Туре	Exposure	Test endpoint	Test result

Page: 9 of 13

Distillates (petroleum), hydrotreated light	64742-47-8	Green algae	Experimental	72 hours	EL50	>1,000 mg/l
Distillates (petroleum), hydrotreated light	64742-47-8	Rainbow trout	Experimental	96 hours	LL50	>1,000 mg/l
Distillates (petroleum), hydrotreated light	64742-47-8	Water flea	Experimental	48 hours	EL50	>1,000 mg/l
Distillates (petroleum), hydrotreated light	64742-47-8	Green algae	Experimental	72 hours	NOEL	1,000 mg/l
Aluminum Oxide (non-fibrous)	1344-28-1	N/A	Experimental	96 hours	LC50	>100 mg/l
Aluminum Oxide (non-fibrous)	1344-28-1	Green algae	Experimental	72 hours	EC50	>100 mg/l
Aluminum Oxide (non-fibrous)	1344-28-1	Water flea	Experimental	48 hours	LC50	>100 mg/l
Aluminum Oxide (non-fibrous)	1344-28-1	Green algae	Experimental	72 hours	NOEC	>100 mg/l
Dodecamethylcycl ohexasiloxane	540-97-6	Activated sludge	Experimental	3 hours	EC50	>100 mg/l
Dodecamethylcycl ohexasiloxane	540-97-6	Green algae	Experimental	72 hours	EC50	>100 mg/l
Dodecamethylcycl ohexasiloxane	540-97-6	Fathead minnow	Experimental	49 days	NOEC	100 mg/l
Dodecamethylcycl ohexasiloxane	540-97-6	Green algae	Experimental	72 hours	NOEC	100 mg/l
Dodecamethylcycl ohexasiloxane	540-97-6	Water flea	Experimental	21 days	NOEC	100 mg/l
White Mineral Oil (Petroleum)	8042-47-5	Water flea	Analogous Compound	48 hours	EL50	>100 mg/l
White Mineral Oil (Petroleum)	8042-47-5	Bluegill	Experimental	96 hours	LL50	>100 mg/l
White Mineral Oil (Petroleum)	8042-47-5	Green algae	Analogous Compound	72 hours	NOEL	100 mg/l
White Mineral Oil (Petroleum)	8042-47-5	Water flea	Analogous Compound	21 days	NOEL	>100 mg/l
Ethylenediamine, ethoxylated and propoxylated	26316-40-5	N/A	Data not available or insufficient for classification	N/A	N/A	N/A

# 12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Distillates (petroleum), hydrotreated light	64742-47-8	Estimated Biodegradation	28 days	BOD	69 %BOD/ThOD	OECD 301F - Manometric respirometry
Aluminum Oxide (non-fibrous)	1344-28-1	Data not available-insufficient	N/A	N/A	N/A	N/A
Dodecamethylcycl ohexasiloxane	540-97-6	Experimental Biodegradation	28 days	CO2 evolution	4.47 %CO2 evolution/THCO2 evolution	OECD 310 CO2 Headspace
White Mineral Oil (Petroleum)	8042-47-5	Experimental Biodegradation	28 days	CO2 evolution	0 %CO2 evolution/THCO2 evolution	OECD 301B - Modified sturm or CO2
Ethylenediamine, ethoxylated and propoxylated	26316-40-5	Data not available- insufficient	N/A	N/A	N/A	N/A

# 12.3 : Bioaccumulative potential

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Distillates	64742-47-8	Data not available	N/A	N/A	N/A	N/A
(petroleum),		or insufficient for				
hydrotreated light		classification				
Aluminum Oxide	1344-28-1	Data not available	N/A	N/A	N/A	N/A
(non-fibrous)		or insufficient for				
		classification				
Dodecamethylcycl	540-97-6	Experimental BCF	49 days	Bioaccumulation	1160	OECD305-Bioconcentration
ohexasiloxane		- Fish		factor		
White Mineral Oil	8042-47-5	Data not available	N/A	N/A	N/A	N/A
(Petroleum)		or insufficient for				
		classification				
Ethylenediamine,	26316-40-5	Data not available	N/A	N/A	N/A	N/A
ethoxylated and		or insufficient for				
propoxylated		classification				

#### 12.4. Mobility in soil

Please contact manufacturer for more details

#### 12.5 Other Adverse effects

No information available.

# **SECTION 13: Disposal considerations**

#### 13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

# **SECTION 14: Transport Information**

Not hazardous for transportation.

#### Air Transport (IATA)Regulations

UN No Not applicable

Proper Shipping NameNot applicableHazard Classs/DivisionNot applicableSubsidiary RiskNot applicable

Packing Group: Not applicable

#### Marine Transport (IMDG)

UN No Not applicable

Proper Shipping Name Not applicable Hazard Classs/Division Not applicable Subsidiary Risk Not applicable Packing Group: Not applicable

Environmental Hazards: Not applicable

# **SECTION 15: Regulatory information**

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Japan Chemical Substance Control Law. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

# Applicable Environmental, Health and Safety Regulations

The Manufacture, Storage and Import of Hazardous Chemical Rules, 1989 Hazardous Waste(Management , Handling & Transboundary) Rules, 2008 Hazardous Chemicals (Classification, Packaging and Labelling Draft Rules), 2011

The following ingredients are listed as hazardous on Part II of Schedule I of the India Manufacture, Storage and Import of Hazardous Chemicals (MSIHC) rules None.

The following ingredients are classified as hazardous based on the criteria listed under Part I of Schedule I of the India Manufacture, Storage and Import of Hazardous Chemicals (MSIHC) rules:

The product is classified as Non-Hazardous as per MSIHC Rules, 1989.

## **SECTION 16: Other information**

### NFPA Hazard Classification

Health: 2 Flammability: 1 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

#### **Revision information:**

Section 1: Product identification numbers information was modified.

Section 1: Product name information was modified.

Label: GHS Classification information was modified.

Label: GHS Precautionary - General information was modified.

Label: Signal Word information was modified.

Label: Symbol information was modified.

Section 04: First Aid - Symptoms and Effects (GHS) information was added.

Section 04: Information on toxicological effects information was deleted.

Section 5: Fire - Extinguishing media information information was modified.

Section 6: Accidental release clean-up information information was modified.

Section 8: Eye protection information information was deleted.

Section 8: Eye/face protection information information was added.

Section 8: Personal Protection - Eye information information was added.

Section 09: Nanoparticle information was deleted.

Section 11: Acute Toxicity table information was modified.

Section 11: Carcinogenicity Table information was modified.

Section 11: Germ Cell Mutagenicity Table information was modified.

#### 3M<sup>TM</sup> Perfect-It<sup>TM</sup> EX Machine Polish, 06093, 06094, 06095, 06096, 36093

- Section 11: Health Effects Skin information information was modified.
- Section 11: Reproductive Toxicity Table information was modified.
- Section 11: Serious Eye Damage/Irritation Table information was modified.
- Section 11: Skin Corrosion/Irritation Table information was modified.
- Section 11: Skin Sensitization Table information was modified.
- Section 11: Specific Target Organ Toxicity single exposure text information was deleted.
- Section 11: Target Organs Repeated Table information was modified.
- Section 11: Target Organs Single Table information was added.
- Section 12: Acute aquatic hazard information information was modified.
- Section 12: Component ecotoxicity information information was modified.
- Section 12: Persistence and Degradability information information was modified.
- Section 12:Bioccumulative potential information information was modified.
- Section 15: Regulations Inventories information was modified.
- Section 16: NFPA hazard classification for flammability information was modified.

DISCLAIMER: The information in this Safety Data Sheet (SDS) is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this SDS or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own evaluation to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into India, you are responsible to comply with all applicable regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration/notification.

3M India SDSs are available at http://solutions.3mindia.co.in