



Safety Data Sheet

Copyright,2024, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group: 35-4036-6
Revision date: 08/04/2024
Transportation version number:

Version number: 4.00
Supersedes date: 19/03/2024

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

3M™Scotch-Weld™ DP-190 Grey : Kit

Product Identification Numbers

UU-0101-3322-9 UU-0101-3323-7

7100200489 7100200490

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Industrial use.

1.3. Details of the supplier of the safety data sheet

Address: 3M Ireland Limited, The Iveagh Building, The Park, Carrickmines, Dublin 18.
Telephone: +353 1 280 3555
E Mail: tox.uk@mmm.com

Website: www.3M.com

1.4. Emergency telephone number

Emergency medical information: 8am-10pm (seven days) contact National Poisons Information Centre, Beaumont Hospital, Dublin 9 DOV2NO, Ireland. Telephone Number: +353 (0)1 809 2166

This product is a kit or a multipart product which consists of multiple, independently packaged components. A Safety Data Sheet for each of these components is included. Please do not separate the component Safety Data Sheets from this cover page. The document numbers of the MSDSs for components of this product are:

35-4033-3, 24-4380-2

TRANSPORTATION INFORMATION

Refer to section 14 of the kit components for transport information.

KIT LABEL

2.1. Classification of the substance or mixture CLP REGULATION (EC) No 1272/2008

CLASSIFICATION:

Skin Corrosion/Irritation, Category 2 - Skin Irrit. 2; H315

Serious Eye Damage/Eye Irritation, Category 2 - Eye Irrit. 2; H319

Skin Sensitization, Category 1 - Skin Sens. 1; H317

Specific Target Organ Toxicity-Single Exposure, Category 3 - STOT SE 3; H336

Hazardous to the Aquatic Environment (Acute), Category 1 - Aquatic Acute 1; H400

Hazardous to the Aquatic Environment (Chronic), Category 1 - Aquatic Chronic 1; H410

For full text of H phrases, see Section 16.

2.2. Label elements CLP REGULATION (EC) No 1272/2008

SIGNAL WORD

WARNING.

Symbols

GHS07 (Exclamation mark) |GHS09 (Environment) |

Pictograms



Contains:

bis-[4-(2,3-epoxipropoxy)phenyl]propane; Reaction products of fatty acids, C18-unsaturated, dimers and trimers with 3,3'-[oxybis(ethane-2,1-diylloxy)]dipropan-1-amine .

HAZARD STATEMENTS:

H315	Causes skin irritation.
H319	Causes serious eye irritation.
H317	May cause an allergic skin reaction.
H336	May cause drowsiness or dizziness.
H410	Very toxic to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENTS

Prevention:

P261A	Avoid breathing vapours.
P273	Avoid release to the environment.
P280E	Wear protective gloves.

Response:

P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
--------------------	--

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.
P391 Collect spillage.

For containers not exceeding 125 ml the following Hazard and Precautionary statements may be used:

<=125 ml Hazard statements

H317 May cause an allergic skin reaction.

<=125 ml Precautionary statements

Prevention:

P280E Wear protective gloves.

Response:

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

Revision information:

No revision information



Safety Data Sheet

Copyright, 2024, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	24-4380-2	Version number:	13.01
Revision date:	08/04/2024	Supersedes date:	19/03/2024

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

3M(tm) Scotch-Weld(tm) Epoxy Structural Adhesive DP-190 Grey : Part B

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Structural adhesive.

1.3. Details of the supplier of the safety data sheet

Address: 3M Ireland Limited, The Iveagh Building, The Park, Carrickmines, Dublin 18.
Telephone: +353 1 280 3555
E Mail: tox.uk@mmm.com
Website: www.3M.com

1.4. Emergency telephone number

Emergency medical information: 8am-10pm (seven days) contact National Poisons Information Centre, Beaumont Hospital, Dublin 9 DOV2NO, Ireland. Telephone Number: +353 (0)1 809 2166

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

CLP REGULATION (EC) No 1272/2008

The health and environmental classifications of this material have been derived using the calculation method, except in cases where test data are available or the physical form impacts classification. Classification(s) based on test data or physical form are noted below, if applicable.

CLASSIFICATION:

Skin Corrosion/Irritation, Category 2 - Skin Irrit. 2; H315
Serious Eye Damage/Eye Irritation, Category 2 - Eye Irrit. 2; H319
Skin Sensitization, Category 1 - Skin Sens. 1; H317
Hazardous to the Aquatic Environment (Chronic), Category 2 - Aquatic Chronic 2; H411

For full text of H phrases, see Section 16.

2.2. Label elements

CLP REGULATION (EC) No 1272/2008**SIGNAL WORD**

WARNING.

Symbols

GHS07 (Exclamation mark) | GHS09 (Environment) |

Pictograms**Ingredients:**

Ingredient	CAS Nbr	EC No.	% by Wt
bis-[4-(2,3-epoxipropoxy)phenyl]propane	1675-54-3	216-823-5	60 - 90

HAZARD STATEMENTS:

H315	Causes skin irritation.
H319	Causes serious eye irritation.
H317	May cause an allergic skin reaction.
H411	Toxic to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENTS**Prevention:**

P273	Avoid release to the environment.
P280E	Wear protective gloves.

Response:

P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
P391	Collect spillage.

For containers not exceeding 125 ml the following Hazard and Precautionary statements may be used:**<=125 ml Hazard statements**

H317	May cause an allergic skin reaction.
------	--------------------------------------

<=125 ml Precautionary statements**Prevention:**

P280E	Wear protective gloves.
-------	-------------------------

Response:

P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
-------------	--

2.3. Other hazards

None known.

This material does not contain any substances that are assessed to be a PBT or vPvB

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Ingredient	Identifier(s)	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
bis-[4-(2,3-epoxipropoxy)phenyl]propane	(CAS-No.) 1675-54-3 (EC-No.) 216-823-5 (REACH-No.) 01-2119456619-26	60 - 90	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411
Kaolin	(CAS-No.) 1332-58-7 (EC-No.) 310-194-1	20 - 30	Substance with a national occupational exposure limit
Titanium dioxide	(CAS-No.) 13463-67-7 (EC-No.) 236-675-5	< 1	Carc. 2, H351 (inhalation)

Please see section 16 for the full text of any H statements referred to in this section

Specific Concentration Limits

Ingredient	Identifier(s)	Specific Concentration Limits
bis-[4-(2,3-epoxipropoxy)phenyl]propane	(CAS-No.) 1675-54-3 (EC-No.) 216-823-5	(C >= 5%) Skin Irrit. 2, H315 (C >= 5%) Eye Irrit. 2, H319

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye contact

If exposed, flush eyes with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms develop, get medical attention.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

The most important symptoms and effects based on the CLP classification include:

Irritation to the skin (localized redness, swelling, itching, and dryness). Allergic skin reaction (redness, swelling, blistering,

and itching). Serious irritation to the eyes (significant redness, swelling, pain, tearing, and impaired vision).

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

5.3. Advice for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Clean up residue. Seal the container. Dispose of collected material as soon as possible.

6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid breathing dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.)

7.2. Conditions for safe storage including any incompatibilities

Protect from sunlight. Store away from heat. Store away from acids. Store away from strong bases. Store away from oxidising agents. Store away from amines.

7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
Kaolin	1332-58-7	Ireland OELs	TWA(as respirable dust)(8 hours):2 mg/m ³	
Titanium dioxide	13463-67-7	Ireland OELs	TWA(Total inhalable dust)(8 hours):10 mg/m ³ ;TWA(as respirable dust)(8 hours):4 mg/m ³	

Ireland OELs : Ireland. OELs
TWA: Time-Weighted-Average
STEL: Short Term Exposure Limit
CEIL: Ceiling

Biological limit values

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

Derived no effect level (DNEL)

Ingredient	Degradation Product	Population	Human exposure pattern	DNEL
bis-[4-(2,3-epoxipropoxy)phenyl]propane		Worker	Dermal, Long-term exposure (8 hours), Systemic effects	8.3 mg/kg bw/d
bis-[4-(2,3-epoxipropoxy)phenyl]propane		Worker	Dermal, Short-term exposure, Systemic effects	8.3 mg/kg bw/d
bis-[4-(2,3-epoxipropoxy)phenyl]propane		Worker	Inhalation, Long-term exposure (8 hours), Systemic effects	12.3 mg/m ³
bis-[4-(2,3-epoxipropoxy)phenyl]propane		Worker	Inhalation, Short-term exposure, Systemic effects	12.3 mg/m ³

Predicted no effect concentrations (PNEC)

Ingredient	Degradation Product	Compartment	PNEC
bis-[4-(2,3-epoxipropoxy)phenyl]propane		Freshwater	0.003 mg/l
bis-[4-(2,3-epoxipropoxy)phenyl]propane		Freshwater sediments	0.5 mg/kg d.w.
bis-[4-(2,3-epoxipropoxy)phenyl]propane		Intermittent releases to water	0.013 mg/l
bis-[4-(2,3-epoxipropoxy)phenyl]propane		Marine water	0.0003 mg/l
bis-[4-(2,3-epoxipropoxy)phenyl]propane		Marine water sediments	0.5 mg/kg d.w.
bis-[4-(2,3-epoxipropoxy)phenyl]propane		Sewage Treatment Plant	10 mg/l

ne			
----	--	--	--

Recommended monitoring procedures:Information on recommended monitoring procedures can be obtained from Indust. Inspect./Ministry (IE)

8.2. Exposure controls

In addition, refer to the annex for more information.

8.2.1. Engineering controls

Provide ventilated enclosure for heat curing. Curing enclosures must be exhausted to outdoors or to a suitable emission control device. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:
Safety glasses with side shields.
Indirect vented goggles.

Applicable Norms/Standards

Use eye protection conforming to EN 166

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.
Gloves made from the following material(s) are recommended:

Material	Thickness (mm)	Breakthrough Time
Butyl rubber.	No data available	No data available
Polymer laminate	No data available	No data available

Applicable Norms/Standards

Use gloves tested to EN 374

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron – Butyl rubber
Apron - polymer laminate

Respiratory protection

None required.

8.2.3. Environmental exposure controls

Refer to Annex

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Solid.
Specific Physical Form:	Paste
Colour	Beige
Odor	Epoxy
Odour threshold	No data available.
Melting point/freezing point	No data available.
Boiling point/boiling range	>=200 °C
Flammability (solid, gas)	Not classified
Flammable Limits(LEL)	Not applicable.
Flammable Limits(UEL)	Not applicable.
Flash point	150 °C
Autoignition temperature	No data available.
Decomposition temperature	No data available.
pH	substance/mixture is non-soluble (in water)
Kinematic Viscosity	No data available.
Water solubility	No data available.
Solubility- non-water	No data available.
Partition coefficient: n-octanol/water	No data available.
Vapour pressure	Not applicable.
Density	No data available.
Relative density	1.31 - 1.39
Relative Vapour Density	Not applicable.
Particle Characteristics	Not applicable.

9.2. Other information

9.2.2 Other safety characteristics

EU Volatile Organic Compounds

No data available.

Evaporation rate

No data available.

Percent volatile

<=1 %

SECTION 10: Stability and reactivity

10.1 Reactivity

This material is considered to be non reactive under normal use conditions

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

Heat is generated during cure. Do not cure a mass larger than 50 grams in a confined space to prevent a premature exothermic reaction with production of intense heat and smoke.

10.5 Incompatible materials

Amines.

Strong acids.

Strong bases.

Strong oxidising agents.

10.6 Hazardous decomposition products**Substance**

Aldehydes.
Carbon monoxide
Carbon dioxide.

Condition

Not specified.
Not specified.
Not specified.

SECTION 11: Toxicological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from internal hazard assessments.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008**Signs and Symptoms of Exposure**

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

No health effects are expected.

Skin contact

Mild Skin Irritation: Signs/symptoms may include localised redness, swelling, itching, and dryness. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye contact

Moderate eye irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
bis-[4-(2,3-epoxipropoxy)phenyl]propane	Dermal	Rat	LD50 > 1,600 mg/kg
bis-[4-(2,3-epoxipropoxy)phenyl]propane	Ingestion	Rat	LD50 > 1,000 mg/kg
Kaolin	Dermal		LD50 estimated to be > 5,000 mg/kg
Kaolin	Ingestion	Human	LD50 > 15,000 mg/kg
Titanium dioxide	Dermal	Rabbit	LD50 > 10,000 mg/kg
Titanium dioxide	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 6.82 mg/l
Titanium dioxide	Ingestion	Rat	LD50 > 10,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value

3M(tm) Scotch-Weld(tm) Epoxy Structural Adhesive DP-190 Grey : Part B

bis-[4-(2,3-epoxipropoxy)phenyl]propane	Rabbit	Mild irritant
Kaolin	Professional judgement	No significant irritation
Titanium dioxide	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
bis-[4-(2,3-epoxipropoxy)phenyl]propane	Rabbit	Moderate irritant
Kaolin	Professional judgement	No significant irritation
Titanium dioxide	Rabbit	No significant irritation

Skin Sensitisation

Name	Species	Value
bis-[4-(2,3-epoxipropoxy)phenyl]propane	Human and animal	Sensitising
Titanium dioxide	Human and animal	Not classified

Respiratory Sensitisation

Name	Species	Value
bis-[4-(2,3-epoxipropoxy)phenyl]propane	Human	Not classified

Germ Cell Mutagenicity

Name	Route	Value
bis-[4-(2,3-epoxipropoxy)phenyl]propane	In vivo	Not mutagenic
bis-[4-(2,3-epoxipropoxy)phenyl]propane	In Vitro	Some positive data exist, but the data are not sufficient for classification
Titanium dioxide	In Vitro	Not mutagenic
Titanium dioxide	In vivo	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
bis-[4-(2,3-epoxipropoxy)phenyl]propane	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Kaolin	Inhalation	Multiple animal species	Not carcinogenic
Titanium dioxide	Ingestion	Multiple animal species	Not carcinogenic
Titanium dioxide	Inhalation	Rat	Carcinogenic.

Reproductive Toxicity**Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test result	Exposure Duration
bis-[4-(2,3-epoxipropoxy)phenyl]propane	Ingestion	Not classified for female reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
bis-[4-(2,3-epoxipropoxy)phenyl]propane	Ingestion	Not classified for male reproduction	Rat	NOAEL 750	2 generation

3M(tm) Scotch-Weld(tm) Epoxy Structural Adhesive DP-190 Grey : Part B

				mg/kg/day	
bis-[4-(2,3-epoxipropoxy)phenyl]propane	Dermal	Not classified for development	Rabbit	NOAEL 300 mg/kg/day	during organogenesis
bis-[4-(2,3-epoxipropoxy)phenyl]propane	Ingestion	Not classified for development	Rat	NOAEL 750 mg/kg/day	2 generation

Target Organ(s)**Specific Target Organ Toxicity - single exposure**

For the component/components, either no data is currently available or the data is not sufficient for classification.

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
bis-[4-(2,3-epoxipropoxy)phenyl]propane	Dermal	liver	Not classified	Rat	NOAEL 1,000 mg/kg/day	2 years
bis-[4-(2,3-epoxipropoxy)phenyl]propane	Dermal	nervous system	Not classified	Rat	NOAEL 1,000 mg/kg/day	13 weeks
bis-[4-(2,3-epoxipropoxy)phenyl]propane	Ingestion	auditory system heart endocrine system hematopoietic system liver eyes kidney and/or bladder	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
Kaolin	Inhalation	pneumoconiosis	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL NA	occupational exposure
Kaolin	Inhalation	pulmonary fibrosis	Not classified	Rat	NOAEL Not available	
Titanium dioxide	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 0.01 mg/l	2 years
Titanium dioxide	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not available	occupational exposure

Aspiration Hazard

For the component/components, either no data is currently available or the data is not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

11.2. Information on other hazards

This material does not contain any substances that are assessed to be an endocrine disruptor for human health.

SECTION 12: Ecological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

12.1. Toxicity

No product test data available.

Material	CAS #	Organism	Type	Exposure	Test endpoint	Test result
----------	-------	----------	------	----------	---------------	-------------

3M(tm) Scotch-Weld(tm) Epoxy Structural Adhesive DP-190 Grey : Part B

bis-[4-(2,3-epoxipropoxy)phenyl]propane	1675-54-3	Activated sludge	Analogous Compound	3 hours	IC50	>100 mg/l
bis-[4-(2,3-epoxipropoxy)phenyl]propane	1675-54-3	Rainbow trout	Estimated	96 hours	LC50	2 mg/l
bis-[4-(2,3-epoxipropoxy)phenyl]propane	1675-54-3	Water flea	Estimated	48 hours	EC50	1.8 mg/l
bis-[4-(2,3-epoxipropoxy)phenyl]propane	1675-54-3	Green algae	Experimental	72 hours	ErC50	>11 mg/l
bis-[4-(2,3-epoxipropoxy)phenyl]propane	1675-54-3	Green algae	Experimental	72 hours	NOEC	4.2 mg/l
bis-[4-(2,3-epoxipropoxy)phenyl]propane	1675-54-3	Water flea	Experimental	21 days	NOEC	0.3 mg/l
Kaolin	1332-58-7	Water flea	Experimental	48 hours	LC50	>1,100 mg/l
Titanium dioxide	13463-67-7	Activated sludge	Experimental	3 hours	NOEC	>=1,000 mg/l
Titanium dioxide	13463-67-7	Diatom	Experimental	72 hours	EC50	>10,000 mg/l
Titanium dioxide	13463-67-7	Fathead minnow	Experimental	96 hours	LC50	>100 mg/l
Titanium dioxide	13463-67-7	Water flea	Experimental	48 hours	EC50	>100 mg/l
Titanium dioxide	13463-67-7	Diatom	Experimental	72 hours	NOEC	5,600 mg/l

12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
bis-[4-(2,3-epoxipropoxy)phenyl]propane	1675-54-3	Experimental Biodegradation	28 days	BOD	5 %BOD/COD	OECD 301F - Manometric respirometry
bis-[4-(2,3-epoxipropoxy)phenyl]propane	1675-54-3	Experimental Hydrolysis		Hydrolytic half-life (pH 7)	117 hours (t 1/2)	OECD 111 Hydrolysis func of pH
Kaolin	1332-58-7	Data not available or insufficient	N/A	N/A	N/A	N/A
Titanium dioxide	13463-67-7	Data not available or insufficient	N/A	N/A	N/A	N/A

12.3 : Bioaccumulative potential

Material	Cas No.	Test type	Duration	Study Type	Test result	Protocol
bis-[4-(2,3-epoxipropoxy)phenyl]propane	1675-54-3	Experimental Bioconcentration		Log Kow	3.242	OECD 117 log Kow HPLC method
Kaolin	1332-58-7	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Titanium dioxide	13463-67-7	Experimental BCF - Fish	42 days	Bioaccumulation factor	9.6	

12.4. Mobility in soil

Material	Cas No.	Test type	Study Type	Test result	Protocol
bis-[4-(2,3-epoxipropoxy)phenyl]propane	1675-54-3	Modeled Mobility in Soil	Koc	450 l/kg	Episuite™

12.5. Results of the PBT and vPvB assessment

This material does not contain any substances that are assessed to be a PBT or vPvB

12.6. Endocrine disrupting properties

This material does not contain any substances that are assessed to be an endocrine disruptor for environmental effects

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

EU waste code (product as sold)

08 04 09* Waste adhesives and sealants containing organic solvents or other dangerous substances
20 01 27* Paint, inks, adhesives and resins containing dangerous substances

SECTION 14: Transportation information

	Ground Transport (ADR)	Air Transport (IATA)	Marine Transport (IMDG)
14.1 UN number or ID number	UN3077	UN3077	UN3077
14.2 UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.(SOLID EPOXY RESIN)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.(SOLID EPOXY RESIN)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.(SOLID EPOXY RESIN)
14.3 Transport hazard class(es)	9	9	9
14.4 Packing group	III	III	III

14.5 Environmental hazards	Environmentally Hazardous	Not applicable	Marine Pollutant
14.6 Special precautions for user	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.
14.7 Marine Transport in bulk according to IMO instruments	No data available.	No data available.	No data available.
Control Temperature	No data available.	No data available.	No data available.
Emergency Temperature	No data available.	No data available.	No data available.
ADR Classification Code	M7	Not applicable.	Not applicable.
IMDG Segregation Code	Not applicable.	Not applicable.	NONE

Please contact the address or phone number listed on the first page of the SDS for additional information on the transport/shipment of the material by rail (RID) or inland waterways (ADN).

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Carcinogenicity

<u>Ingredient</u>	<u>CAS Nbr</u>	<u>Classification</u>	<u>Regulation</u>
bis-[4-(2,3-epoxipropoxy)phenyl]propane	1675-54-3	Gr. 3: Not classifiable	International Agency for Research on Cancer
Titanium dioxide	13463-67-7	Grp. 2B: Possible human carc.	International Agency for Research on Cancer

Restrictions on the manufacture, placing on the market and use:

The following substance(s) contained in this product is/are subject through Annex XVII of REACH regulation to restrictions on the manufacture, placing on the market and use when present in certain dangerous substances, mixtures and articles. Users of this product are required to comply with the restrictions placed upon it by the aforementioned provision.

bis-[4-(2,3-epoxipropoxy)phenyl]propane	1675-54-3
---	-----------

Global inventory status

Contact 3M for more information. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

DIRECTIVE 2012/18/EU

Seveso hazard categories, Annex 1, Part 1

Hazard Categories	Qualifying quantity (tonnes) for the application of	
	Lower-tier requirements	Upper-tier requirements
E2 Hazardous to the Aquatic	200	500

environment		
-------------	--	--

Seveso named dangerous substances, Annex 1, Part 2

None

Regulation (EU) No 649/2012

No chemicals listed

15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out for this mixture. Chemical safety assessments for the contained substances may have been carried out by the registrants of the substances in accordance with Regulation (EC) No 1907/2006, as amended.

SECTION 16: Other information

List of relevant H statements

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H351i	Suspected of causing cancer by inhalation.
H411	Toxic to aquatic life with long lasting effects.

Revision information:

CLP: Ingredient table information was modified.

Section 3: Composition/ Information of ingredients table information was modified.

Section 4: First aid for eye contact information information was modified.

Section 7: Precautions safe handling information information was modified.

Section 8: Personal Protection - Respiratory Information information was deleted.

Section 8: Respiratory protection - recommended respirators guide information was deleted.

Section 8: Respiratory protection - recommended respirators information information was deleted.

Section 8: Respiratory protection information information was added.

Section 11: Cancer Hazards information information was deleted.

Section 11: Health Effects - Inhalation information information was modified.

Section 11: Prolonged or repeated exposure may cause standard phrases information was deleted.

Annex

1. Title	
Substance identification	bis-[4-(2,3-epoxipropoxy)phenyl]propane; EC No. 216-823-5; CAS Nbr 1675-54-3;
Exposure Scenario Name	Formulation
Lifecycle Stage	Formulation or re-packing
Contributing activities	PROC 09 -Transfer of substance or mixture into small containers (dedicated filling line, including weighing) ERC 02 -Formulation into mixture
Processes, tasks and activities covered	Batch manufacture of a chemical substance or formulation (including polymerisation reactions).
2. Operational conditions and risk management measures	
Operating Conditions	Physical state: Liquid. General operating conditions: Duration of use: 8 hours/day; Emission days per year: <= 225 days per year;

Risk management measures	Under the operational conditions described above the following risk management measures apply: General risk management measures: Human health: Protective Gloves - Chemical resistant. Refer to Section 8 of the SDS for specific glove material.; Environmental: Waste Water treatment - Incineration;
Waste management measures	Do not apply industrial sludge to natural soils; Prevent leaks and prevent soil / water pollution caused by leaks;
3. Prediction of exposure	
Prediction of exposure	Human and environmental exposures are not expected to exceed the DNELs and PNECs when the identified risk management measures are adopted.

1. Title	
Substance identification	bis-[4-(2,3-epoxipropoxy)phenyl]propane; EC No. 216-823-5; CAS Nbr 1675-54-3;
Exposure Scenario Name	Professional Use of Adhesives
Lifecycle Stage	Widespread use by professional workers
Contributing activities	PROC 13 -Treatment of articles by dipping and pouring ERC 08c -Widespread use leading to inclusion into/onto article (indoor) ERC 08f -Widespread use leading to inclusion into/onto article (outdoor)
Processes, tasks and activities covered	Application of product with applicator gun.
2. Operational conditions and risk management measures	
Operating Conditions	Physical state: Liquid. General operating conditions: Application Temperature:: <= 40 degree Celsius; Duration of use: 8 hours/day; Indoors with good general ventilation;
Risk management measures	Under the operational conditions described above the following risk management measures apply: General risk management measures: Human health: Goggles - Chemical resistant; Protective Gloves - Chemical resistant. Refer to Section 8 of the SDS for specific glove material.; Environmental: Industrial Sewage Treatment Plant;
Waste management measures	No use-specific waste management measures are required for this product. Refer to Section 13 of main SDS for disposal instructions:
3. Prediction of exposure	
Prediction of exposure	Human and environmental exposures are not expected to exceed the DNELs and PNECs when the identified risk management measures are adopted.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into the European Union, you are responsible for all regulatory requirements, including, but not limited to, product registrations/notifications, substance

volume tracking, and potential substance registration.

3M Ireland MSDSs are available at www.3M.com



Safety Data Sheet

Copyright, 2023, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	35-4033-3	Version number:	5.00
Revision date:	01/06/2023	Supersedes date:	20/12/2022

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

3M™Scotch-Weld™ DP-190 Grey : Part A

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Industrial use.

1.3. Details of the supplier of the safety data sheet

Address:	3M Ireland Limited, The Iveagh Building, The Park, Carrickmines, Dublin 18.
Telephone:	+353 1 280 3555
E Mail:	tox.uk@mmm.com
Website:	www.3M.com

1.4. Emergency telephone number

Emergency medical information: 8am-10pm (seven days) contact National Poisons Information Centre, Beaumont Hospital, Dublin 9 DOV2NO, Ireland. Telephone Number: +353 (0)1 809 2166

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

CLP REGULATION (EC) No 1272/2008

The health and environmental classifications of this material have been derived using the calculation method, except in cases where test data are available or the physical form impacts classification. Classification(s) based on test data or physical form are noted below, if applicable.

CLASSIFICATION:

Skin Corrosion/Irritation, Category 2 - Skin Irrit. 2; H315
Serious Eye Damage/Eye Irritation, Category 2 - Eye Irrit. 2; H319
Skin Sensitization, Category 1 - Skin Sens. 1; H317
Specific Target Organ Toxicity-Single Exposure, Category 3 - STOT SE 3; H336
Hazardous to the Aquatic Environment (Acute), Category 1 - Aquatic Acute 1; H400
Hazardous to the Aquatic Environment (Chronic), Category 1 - Aquatic Chronic 1; H410

For full text of H phrases, see Section 16.

2.2. Label elements**CLP REGULATION (EC) No 1272/2008****SIGNAL WORD**

WARNING.

Symbols

GHS07 (Exclamation mark) | GHS09 (Environment) |

Pictograms**Ingredients:**

Ingredient	CAS Nbr	EC No.	% by Wt
Reaction products of fatty acids, C18-unsaturated, dimers and trimers with 3,3'-[oxybis(ethane-2,1-diyl oxy)]dipropan-1-amine		701-270-9	55 - 65

HAZARD STATEMENTS:

H315	Causes skin irritation.
H319	Causes serious eye irritation.
H317	May cause an allergic skin reaction.
H336	May cause drowsiness or dizziness.
H410	Very toxic to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENTS**Prevention:**

P261A	Avoid breathing vapours.
P273	Avoid release to the environment.
P280E	Wear protective gloves.

Response:

P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
P391	Collect spillage.

For containers not exceeding 125 ml the following Hazard and Precautionary statements may be used:

<=125 ml Hazard statements

H317	May cause an allergic skin reaction.
------	--------------------------------------

<=125 ml Precautionary statements**Prevention:**

P280E	Wear protective gloves.
-------	-------------------------

Response:

P333 + P313

If skin irritation or rash occurs: Get medical advice/attention.

2.3. Other hazards

Persons previously sensitised to amines may develop a cross-sensitisation reaction to certain other amines.
This material does not contain any substances that are assessed to be a PBT or vPvB

SECTION 3: Composition/information on ingredients**3.1. Substances**

Not applicable

3.2. Mixtures

Ingredient	Identifier(s)	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Reaction products of fatty acids, C18-unsaturated, dimers and trimers with 3,3'-[oxybis(ethane-2,1-diyloxy)]dipropylamine	(EC-No.) 701-270-9	55 - 65	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1A, H317 STOT SE 3, H336 Aquatic Acute 1, H400,M=1 Aquatic Chronic 1, H410,M=1
Kaolin	(CAS-No.) 1332-58-7 (EC-No.) 310-194-1	35 - 45	Substance with a national occupational exposure limit
Titanium dioxide	(CAS-No.) 13463-67-7 (EC-No.) 236-675-5	< 1	Carc. 2, H351 (inhalation)

Any entry in the Identifier(s) column that begins with the numbers 6, 7, 8, or 9 are a Provisional List Number provided by ECHA pending publication of the official EC Inventory Number for the substance.
Please see section 16 for the full text of any H statements referred to in this section

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

SECTION 4: First aid measures**4.1. Description of first aid measures****Inhalation**

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye contact

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

The most important symptoms and effects based on the CLP classification include:

Irritation to the skin (localized redness, swelling, itching, and dryness). Allergic skin reaction (redness, swelling, blistering, and itching). Serious irritation to the eyes (significant redness, swelling, pain, tearing, and impaired vision). Central nervous system depression (headache, dizziness, drowsiness, incoordination, nausea, slurred speech, giddiness, and unconsciousness).

4.3. Indication of any immediate medical attention and special treatment required

Not applicable.

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

<u>Substance</u>	<u>Condition</u>
Carbon monoxide	During combustion.
Carbon dioxide.	During combustion.
Oxides of nitrogen.	During combustion.

5.3. Advice for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Contain spill. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible.

6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

SECTION 7: Handling and storage

7.1. Precautions for safe handling

For industrial/occupational use only. Not for consumer sale or use. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.)

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Store away from acids. Store away from oxidising agents.

7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
Kaolin	1332-58-7	Ireland OELs	TWA(as respirable dust)(8 hours):2 mg/m ³	
Titanium dioxide	13463-67-7	Ireland OELs	TWA(Total inhalable dust)(8 hours):10 mg/m ³ ;TWA(as respirable dust)(8 hours):4 mg/m ³	

Ireland OELs : Ireland. OELs

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

Biological limit values

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

Recommended monitoring procedures:Information on recommended monitoring procedures can be obtained from Indust. Inspect./Ministry (IE)

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety glasses with side shields.

Indirect vented goggles.

Applicable Norms/Standards

Use eye protection conforming to EN 166

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended:

Material	Thickness (mm)	Breakthrough Time
Polymer laminate	No data available	No data available

Applicable Norms/Standards

Use gloves tested to EN 374

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

Applicable Norms/Standards

Use a respirator conforming to EN 140 or EN 136: filter types A & P

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Solid.
Specific Physical Form:	Paste
Colour	Dark Gray
Odor	Amine
Odour threshold	No data available.
Melting point/freezing point	No data available.
Boiling point/boiling range	>=152.2 °C
Flammability (solid, gas)	Not classified
Flammable Limits(LEL)	No data available.
Flammable Limits(UEL)	No data available.
Flash point	>=151.7 °C [Test Method:Closed Cup]
Autoignition temperature	No data available.
Decomposition temperature	No data available.
pH	substance/mixture is non-soluble (in water)
Kinematic Viscosity	No data available.
Water solubility	No data available.
Solubility- non-water	No data available.
Partition coefficient: n-octanol/water	No data available.
Vapour pressure	No data available.
Density	No data available.
Relative density	1.24 - 1.32 [Ref Std:WATER=1]
Relative Vapour Density	No data available.

9.2. Other information

9.2.2 Other safety characteristics

EU Volatile Organic Compounds	No data available.
Evaporation rate	No data available.
Molecular weight	Not applicable.
Percent volatile	No data available.

SECTION 10: Stability and reactivity

10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

None known.

10.5 Incompatible materials

Strong acids.

Strong oxidising agents.

10.6 Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from internal hazard assessments.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Skin contact

Skin Irritation: Signs/symptoms may include localised redness, swelling, itching, dryness, cracking, blistering, and pain.
Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye contact

Severe eye irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

Ingestion

May be harmful if swallowed.

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.
May cause additional health effects (see below).

Additional Health Effects:**Single exposure may cause target organ effects:**

Central nervous system (CNS) depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

Additional information:

Persons previously sensitised to amines may develop a cross-sensitisation reaction to certain other amines.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE >2,000 - =5,000 mg/kg
Reaction products of fatty acids, C18-unsaturated, dimers and trimers with 3,3'-[oxybis(ethane-2,1-diylloxy)]dipropylamine	Dermal	Rat	LD50 > 2,000 mg/kg
Reaction products of fatty acids, C18-unsaturated, dimers and trimers with 3,3'-[oxybis(ethane-2,1-diylloxy)]dipropylamine	Ingestion	Rat	LD50 > 2,000 mg/kg
Kaolin	Dermal		LD50 estimated to be > 5,000 mg/kg
Kaolin	Ingestion	Human	LD50 > 15,000 mg/kg
Titanium dioxide	Dermal	Rabbit	LD50 > 10,000 mg/kg
Titanium dioxide	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 6.82 mg/l
Titanium dioxide	Ingestion	Rat	LD50 > 10,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Reaction products of fatty acids, C18-unsaturated, dimers and trimers with 3,3'-[oxybis(ethane-2,1-diylloxy)]dipropylamine	Rat	Irritant
Kaolin	Professional judgement	No significant irritation
Titanium dioxide	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
Reaction products of fatty acids, C18-unsaturated, dimers and trimers with 3,3'-[oxybis(ethane-2,1-diylloxy)]dipropylamine	In vitro data	Severe irritant
Kaolin	Professional judgement	No significant irritation
Titanium dioxide	Rabbit	No significant irritation

Skin Sensitisation

Name	Species	Value
Reaction products of fatty acids, C18-unsaturated, dimers and trimers with 3,3'-[oxybis(ethane-2,1-diylloxy)]dipropylamine	Guinea pig	Sensitising
Titanium dioxide	Human and	Not classified

animal

Respiratory Sensitisation

For the component/components, either no data is currently available or the data is not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Reaction products of fatty acids, C18-unsaturated, dimers and trimers with 3,3'-[oxybis(ethane-2,1-diylloxy)]dipropylamine	In Vitro	Not mutagenic
Titanium dioxide	In Vitro	Not mutagenic
Titanium dioxide	In vivo	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
Kaolin	Inhalation	Multiple animal species	Not carcinogenic
Titanium dioxide	Ingestion	Multiple animal species	Not carcinogenic
Titanium dioxide	Inhalation	Rat	Carcinogenic.

Reproductive Toxicity**Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test result	Exposure Duration
Reaction products of fatty acids, C18-unsaturated, dimers and trimers with 3,3'-[oxybis(ethane-2,1-diylloxy)]dipropylamine	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	premating into lactation
Reaction products of fatty acids, C18-unsaturated, dimers and trimers with 3,3'-[oxybis(ethane-2,1-diylloxy)]dipropylamine	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	29 days
Reaction products of fatty acids, C18-unsaturated, dimers and trimers with 3,3'-[oxybis(ethane-2,1-diylloxy)]dipropylamine	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	premating into lactation

Target Organ(s)**Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Reaction products of fatty acids, C18-unsaturated, dimers and trimers with 3,3'-[oxybis(ethane-2,1-diylloxy)]dipropylamine	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	Irritation Positive	
Reaction products of fatty acids, C18-unsaturated, dimers and trimers with 3,3'-[oxybis(ethane-2,1-diylloxy)]dipropylamine	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Rat	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Reaction products of fatty acids, C18-unsaturated, dimers and trimers with	Ingestion	heart skin endocrine system gastrointestinal tract	Not classified	Rat	NOAEL 1,000 mg/kg/day	29 days

3,3'-[oxybis(ethane-2,1-diyloxy)]dipropylamine		bone, teeth, nails, and/or hair hematopoietic system liver immune system muscles nervous system eyes kidney and/or bladder respiratory system vascular system				
Kaolin	Inhalation	pneumoconiosis	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL NA	occupational exposure
Kaolin	Inhalation	pulmonary fibrosis	Not classified	Rat	NOAEL Not available	
Titanium dioxide	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 0.01 mg/l	2 years
Titanium dioxide	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not available	occupational exposure

Aspiration Hazard

For the component/components, either no data is currently available or the data is not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

11.2. Information on other hazards

This material does not contain any substances that are assessed to be an endocrine disruptor for human health.

SECTION 12: Ecological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

12.1. Toxicity

No product test data available.

Material	CAS #	Organism	Type	Exposure	Test endpoint	Test result
Reaction products of fatty acids, C18-unsaturated, dimers and trimers with 3,3'-[oxybis(ethane-2,1-diyloxy)]dipropylamine	701-270-9	Fathead minnow	Experimental	96 hours	LL50	2.16 mg/l
Reaction products of fatty acids, C18-unsaturated, dimers and trimers with 3,3'-[oxybis(ethane-2,1-diyloxy)]dipropylamine	701-270-9	Green algae	Experimental	72 hours	EL50	0.43 mg/l
Reaction products of fatty acids, C18-unsaturated, dimers and trimers with 3,3'-[oxybis(ethane-2,1-diyloxy)]dipropylamine	701-270-9	Water flea	Experimental	48 hours	EL50	0.57 mg/l

amine						
Reaction products of fatty acids, C18-unsaturated, dimers and trimers with 3,3'-[oxybis(ethane-2,1-diylloxy)]dipropyl-amine	701-270-9	Green algae	Experimental	72 hours	NOEL	0.28 mg/l
Reaction products of fatty acids, C18-unsaturated, dimers and trimers with 3,3'-[oxybis(ethane-2,1-diylloxy)]dipropyl-amine	701-270-9	Activated sludge	Experimental	3 hours	EC50	410.3 mg/l
Kaolin	1332-58-7	Water flea	Experimental	48 hours	LC50	>1,100 mg/l
Titanium dioxide	13463-67-7	Activated sludge	Experimental	3 hours	NOEC	>=1,000 mg/l
Titanium dioxide	13463-67-7	Diatom	Experimental	72 hours	EC50	>10,000 mg/l
Titanium dioxide	13463-67-7	Fathead minnow	Experimental	96 hours	LC50	>100 mg/l
Titanium dioxide	13463-67-7	Water flea	Experimental	48 hours	EC50	>100 mg/l
Titanium dioxide	13463-67-7	Diatom	Experimental	72 hours	NOEC	5,600 mg/l

12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Reaction products of fatty acids, C18-unsaturated, dimers and trimers with 3,3'-[oxybis(ethane-2,1-diylloxy)]dipropyl-amine	701-270-9	Experimental Biodegradation	28 days	BOD	0 %BOD/ThO D	OECD 301F - Manometric respirometry
Kaolin	1332-58-7	Data not available - insufficient	N/A	N/A	N/A	N/A
Titanium dioxide	13463-67-7	Data not available - insufficient	N/A	N/A	N/A	N/A

12.3 : Bioaccumulative potential

Material	Cas No.	Test type	Duration	Study Type	Test result	Protocol
Reaction products of fatty acids, C18-unsaturated, dimers and trimers with 3,3'-[oxybis(ethane-2,1-diylloxy)]dipropyl-amine	701-270-9	Modeled Bioconcentration		Bioaccumulation factor	42	Catalogic™
Reaction products of fatty acids, C18-unsaturated, dimers and trimers with 3,3'-[oxybis(ethane-2,1-diylloxy)]dipropyl-amine	701-270-9	Modeled Bioconcentration		Log Kow	11.7	Episuite™
Kaolin	1332-58-7	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Titanium dioxide	13463-67-7	Experimental BCF - Fish	42 days	Bioaccumulation factor	9.6	

12.4. Mobility in soil

Material	Cas No.	Test type	Study Type	Test result	Protocol
----------	---------	-----------	------------	-------------	----------

Reaction products of fatty acids, C18-unsaturated, dimers and trimers with 3,3'-[oxybis(ethane-2,1-diylloxy)]dipropyl-amine	701-270-9	Modeled Mobility in Soil	Koc	3,780,000,000 l/kg	
---	-----------	--------------------------	-----	--------------------	--

12.5. Results of the PBT and vPvB assessment

This material does not contain any substances that are assessed to be a PBT or vPvB

12.6. Endocrine disrupting properties

This material does not contain any substances that are assessed to be an endocrine disruptor for environmental effects

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

EU waste code (product as sold)

08 04 09* Waste adhesives and sealants containing organic solvents or other dangerous substances

SECTION 14: Transportation information

	Ground Transport (ADR)	Air Transport (IATA)	Marine Transport (IMDG)
14.1 UN number or ID number	UN3077	UN3077	UN3077
14.2 UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.(ALIPHATIC POLYMER DIAMINE)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.(ALIPHATIC POLYMER DIAMINE)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.(ALIPHATIC POLYMER DIAMINE)
14.3 Transport hazard class(es)	9	9	9

14.4 Packing group	III	III	III
14.5 Environmental hazards	Environmentally Hazardous	Not applicable	Marine Pollutant
14.6 Special precautions for user	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.
14.7 Marine Transport in bulk according to IMO instruments	No data available.	No data available.	No data available.
Control Temperature	No data available.	No data available.	No data available.
Emergency Temperature	No data available.	No data available.	No data available.
ADR Classification Code	M7	Not applicable.	Not applicable.
IMDG Segregation Code	Not applicable.	Not applicable.	NONE

Please contact the address or phone number listed on the first page of the SDS for additional information on the transport/shipment of the material by rail (RID) or inland waterways (ADN).

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Carcinogenicity

Ingredient

Titanium dioxide

CAS Nbr

13463-67-7

Classification

Grp. 2B: Possible human carc.

Regulation

International Agency for Research on Cancer

Global inventory status

Contact 3M for more information. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

DIRECTIVE 2012/18/EU

Seveso hazard categories, Annex 1, Part 1

Hazard Categories	Qualifying quantity (tonnes) for the application of	
	Lower-tier requirements	Upper-tier requirements
E1 Hazardous to the Aquatic environment	100	200

Seveso named dangerous substances, Annex 1, Part 2

None

Regulation (EU) No 649/2012

No chemicals listed

15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out for this substance/mixture in accordance with Regulation (EC) No 1907/2006, as amended.

SECTION 16: Other information**List of relevant H statements**

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H351i	Suspected of causing cancer by inhalation.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

Revision information:

Section 8: Eye/face protection information information was modified.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into the European Union, you are responsible for all regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration.

3M Ireland MSDSs are available at www.3M.com