



Safety Data Sheet

Copyright, 2023, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	05-6784-2	Version number:	20.00
Revision date:	13/01/2023	Supersedes date:	12/07/2019
Transportation version number:			

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

3M Scotch-Weld Epoxy Adhesive DP105 Clear

Product Identification Numbers

UU-0101-3127-2

7100200485

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Structural adhesive.

1.3. Details of the supplier of the safety data sheet

Address: 3M Ireland Limited, The Iveagh Building, The Park, Carrickmines, Dublin 18.
Telephone: +353 1 280 3555
E Mail: tox.uk@mmm.com

Website: www.3M.com

1.4. Emergency telephone number

Emergency medical information: 8am-10pm (seven days) contact National Poisons Information Centre, Beaumont Hospital, Dublin 9 DOV2NO, Ireland. Telephone Number: +353 (0)1 809 2166

This product is a kit or a multipart product which consists of multiple, independently packaged components. A Safety Data Sheet for each of these components is included. Please do not separate the component Safety Data Sheets from this cover page. The document numbers of the MSDSs for components of this product are:

05-6781-8, 05-6783-4

TRANSPORTATION INFORMATION

Refer to section 14 of the kit components for transport information.

KIT LABEL

2.1. Classification of the substance or mixture CLP REGULATION (EC) No 1272/2008

CLASSIFICATION:

Skin Corrosion/Irritation, Category 2 - Skin Irrit. 2; H315

Serious Eye Damage/Eye Irritation, Category 2 - Eye Irrit. 2; H319

Skin Sensitization, Category 1 - Skin Sens. 1; H317

Hazardous to the Aquatic Environment (Chronic), Category 3 - Aquatic Chronic 3; H412

For full text of H phrases, see Section 16.

2.2. Label elements

CLP REGULATION (EC) No 1272/2008

SIGNAL WORD

WARNING.

Symbols

GHS07 (Exclamation mark) |

Pictograms



Contains:

3,6-diazaoctanethylenediamin; bis-[4-(2,3-epoxypropoxy)phenyl]propane; Triethylenetetramine, propoxylated; 4,4'-Isopropylidenedicyclohexanol, oligomeric reaction products with 1-chloro-2,3-epoxypropane; Reaction products of pentaerythritol, propoxylated and 1-chloro-2,3-epoxypropane with hydrogen sulphide

HAZARD STATEMENTS:

H315 Causes skin irritation.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENTS

Prevention:

P280E Wear protective gloves.

Response:

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

For containers not exceeding 125 ml the following Hazard and Precautionary statements may be used:

<=125 ml Hazard statements

H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

<=125 ml Precautionary statements

Prevention:

P280E Wear protective gloves.

Response:

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

Refer to Safety Data Sheet for component % unknown values (www.3M.com/msds).

Revision information:

Label: CLP Percent Unknown - Kit information was added.

Label: CLP Ingredients - kit components information was modified.

Section 1: Emergency telephone information was modified.

Label: CLP Classification information was modified.

Label: CLP Precautionary - Disposal information was deleted.



Safety Data Sheet

Copyright, 2023, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	05-6783-4	Version number:	21.01
Revision date:	21/02/2023	Supersedes date:	13/01/2023

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

3M Scotch-Weld Epoxy Adhesive DP105 Clear, Part A

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Structural adhesive.

1.3. Details of the supplier of the safety data sheet

Address: 3M Ireland Limited, The Iveagh Building, The Park, Carrickmines, Dublin 18.
Telephone: +353 1 280 3555
E Mail: tox.uk@mmm.com
Website: www.3M.com

1.4. Emergency telephone number

Emergency medical information: 8am-10pm (seven days) contact National Poisons Information Centre, Beaumont Hospital, Dublin 9 DOV2NO, Ireland. Telephone Number: +353 (0)1 809 2166

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

CLP REGULATION (EC) No 1272/2008

The health and environmental classifications of this material have been derived using the calculation method, except in cases where test data are available or the physical form impacts classification. Classification(s) based on test data or physical form are noted below, if applicable.

A similar mixture has been tested for eye damage/irritation and the test results do not meet the criteria for classification.

A similar mixture has been tested for skin corrosion/irritation and the test results do not meet the criteria for classification.

CLASSIFICATION:

Skin Sensitization, Category 1 - Skin Sens. 1; H317

Hazardous to the Aquatic Environment (Chronic), Category 3 - Aquatic Chronic 3; H412

For full text of H phrases, see Section 16.

2.2. Label elements

CLP REGULATION (EC) No 1272/2008

SIGNAL WORD

WARNING.

Symbols

GHS07 (Exclamation mark) |

Pictograms



Ingredients:

Ingredient	CAS Nbr	EC No.	% by Wt
alpha-Hydro-omega-hydroxy-poly[oxy(methyl-1,2-ethanediyl)], ether with 2,2-bis(hydroxymethyl)-1,3-propanediol (4:1), 2-hydroxy-3-mercaptoethyl ether	72244-98-5	701-196-7	85 - 100
Triethylenetetramine, propoxylated	26950-63-0	500-055-5	1 - 10
3,6-diazaoctanethylenediamin	112-24-3	203-950-6	< 3

HAZARD STATEMENTS:

- H317 May cause an allergic skin reaction.
- H412 Harmful to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENTS

Prevention:

P280E Wear protective gloves.

Response:

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

For containers not exceeding 125 ml the following Hazard and Precautionary statements may be used:

<=125 ml Hazard statements

- H317 May cause an allergic skin reaction.
- H412 Harmful to aquatic life with long lasting effects.

<=125 ml Precautionary statements

Prevention:

P280E Wear protective gloves.

Response:

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

10% of the mixture consists of components of unknown acute inhalation toxicity.

2.3. Other hazards

Persons previously sensitised to amines may develop a cross-sensitisation reaction to certain other amines.
This material does not contain any substances that are assessed to be a PBT or vPvB

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Ingredient	Identifier(s)	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
alpha-Hydro-omega-hydroxy-poly[oxy(methyl-1,2-ethanediyl)], ether with 2,2-bis(hydroxymethyl)-1,3-propanediol (4:1), 2-hydroxy-3-mercaptopropyl ether	(CAS-No.) 72244-98-5 (EC-No.) 701-196-7	85 - 100	Aquatic Chronic 3, H412 Skin Sens. 1B, H317
Triethylenetetramine, propoxylated	(CAS-No.) 26950-63-0 (EC-No.) 500-055-5	1 - 10	Eye Irrit. 2, H319 Skin Sens. 1B, H317
N,N,N',N'-tetramethyl-2,2'-oxybis(ethylamine)	(CAS-No.) 3033-62-3 (EC-No.) 221-220-5	< 5	EUH071 Acute Tox. 3, H311 Acute Tox. 4, H332 Acute Tox. 4, H332 Acute Tox. 4, H302 Skin Corr. 1B, H314 Eye Dam. 1, H318
1,8-Diazabicyclo[5.4.0]undec-7-ene	(CAS-No.) 6674-22-2 (EC-No.) 229-713-7	< 3	Acute Tox. 4, H312 Acute Tox. 4, H302 Skin Corr. 1B, H314 Eye Dam. 1, H318
3,6-diazaoctanethylenediamin	(CAS-No.) 112-24-3 (EC-No.) 203-950-6	< 3	Acute Tox. 3, H311 Skin Corr. 1B, H314 Skin Sens. 1A, H317 Aquatic Chronic 3, H412

Please see section 16 for the full text of any H statements referred to in this section

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye contact

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist,

get medical attention.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

The most important symptoms and effects based on the CLP classification include:

Allergic skin reaction (redness, swelling, blistering, and itching).

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products

Substance

Carbon monoxide

Carbon dioxide.

Oxides of sulphur.

Toxic vapour, gas, particulate.

Condition

During combustion.

During combustion.

During combustion.

During combustion.

5.3. Advice for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible.

6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

Avoid breathing dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage including any incompatibilities

No special storage requirements.

7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

SECTION 8: Exposure controls/personal protection**8.1 Control parameters****Occupational exposure limits**

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
N,N,N',N'-tetramethyl-2,2'-oxybis(ethylamine)	3033-62-3	Ireland OELs	TWA(8 hours):0.05 ppm;STEL(15 minutes):0.15 ppm	

Ireland OELs : Ireland. OELs

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

Biological limit values

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

Recommended monitoring procedures:Information on recommended monitoring procedures can be obtained from Indust. Inspect./Ministry (IE)

8.2. Exposure controls**8.2.1. Engineering controls**

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)**Eye/face protection**

None required.

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended:

Material	Thickness (mm)	Breakthrough Time
-----------------	-----------------------	--------------------------

Polymer laminate

No data available

No data available

Applicable Norms/Standards

Use gloves tested to EN 374

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

Applicable Norms/Standards

Use a respirator conforming to EN 140 or EN 136: filter types A & P

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties****Physical state**

Liquid.

Colour

Colourless

Odor

Mercaptan

Odour threshold*No data available.***Melting point/freezing point***Not applicable.***Boiling point/boiling range** ≥ 93.3 °C**Flammability (solid, gas)**

Not applicable.

Flammable Limits(LEL)*No data available.***Flammable Limits(UEL)***No data available.***Flash point** ≥ 93.3 °C [*Test Method: Closed Cup*]**Autoignition temperature***No data available.***Decomposition temperature***No data available.***pH***substance/mixture is non-soluble (in water)***Kinematic Viscosity**10,435 mm²/sec**Water solubility**

Nil

Solubility- non-water*No data available.***Partition coefficient: n-octanol/water***No data available.***Vapour pressure** ≤ 13.3 Pa**Density**

1.15 g/ml

Relative density1.15 [*Ref Std: WATER=1*]**Relative Vapour Density***No data available.***9.2. Other information****9.2.2 Other safety characteristics****EU Volatile Organic Compounds***No data available.***Evaporation rate***No data available.***Molecular weight***No data available.***SECTION 10: Stability and reactivity**

10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

Heat is generated during cure. Do not cure a mass larger than 50 grams in a confined space to prevent a premature exothermic reaction with production of intense heat and smoke.

10.5 Incompatible materials

None known.

10.6 Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
------------------	------------------

None known.	
-------------	--

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from internal hazard assessments.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Skin contact

May be harmful in contact with skin. Mild Skin Irritation: Signs/symptoms may include localised redness, swelling, itching, and dryness. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye contact

Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion

Harmful if swallowed.

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.

Additional information:

Persons previously sensitised to amines may develop a cross-sensitisation reaction to certain other amines.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >2,000 - =5,000 mg/kg
Overall product	Inhalation-Vapour(4 hr)		No data available; calculated ATE >50 mg/l
Overall product	Ingestion		No data available; calculated ATE >300 - =2,000 mg/kg
alpha-Hydro-omega-hydroxy-poly[oxy(methyl-1,2-ethanediyl)], ether with 2,2-bis(hydroxymethyl)-1,3-propanediol (4:1), 2-hydroxy-3-mercaptopropyl ether	Dermal	Rabbit	LD50 > 10,200 mg/kg
alpha-Hydro-omega-hydroxy-poly[oxy(methyl-1,2-ethanediyl)], ether with 2,2-bis(hydroxymethyl)-1,3-propanediol (4:1), 2-hydroxy-3-mercaptopropyl ether	Ingestion	Rat	LD50 2,600 mg/kg
Triethylenetetramine, propoxylated	Dermal		LD50 estimated to be 2,000 - 5,000 mg/kg
Triethylenetetramine, propoxylated	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
N,N,N',N'-tetramethyl-2,2'-oxybis(ethylamine)	Dermal	Rabbit	LD50 311 mg/kg
N,N,N',N'-tetramethyl-2,2'-oxybis(ethylamine)	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 3.4 mg/l
N,N,N',N'-tetramethyl-2,2'-oxybis(ethylamine)	Inhalation-Vapour (4 hours)	Rat	LC50 > 2.2 mg/l
N,N,N',N'-tetramethyl-2,2'-oxybis(ethylamine)	Ingestion	Rat	LD50 571 mg/kg
3,6-diazaoctanethylenediamin	Dermal	Rabbit	LD50 550 mg/kg
3,6-diazaoctanethylenediamin	Ingestion	Rat	LD50 2,500 mg/kg
1,8-Diazabicyclo[5.4.0]undec-7-ene	Dermal	Rabbit	LD50 1,233 mg/kg
1,8-Diazabicyclo[5.4.0]undec-7-ene	Ingestion	Rat	LD50 > 300, < 681 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Overall product	Rabbit	Mild irritant
alpha-Hydro-omega-hydroxy-poly[oxy(methyl-1,2-ethanediyl)], ether with 2,2-bis(hydroxymethyl)-1,3-propanediol (4:1), 2-hydroxy-3-mercaptopropyl ether	Rabbit	No significant irritation
N,N,N',N'-tetramethyl-2,2'-oxybis(ethylamine)	Rabbit	Corrosive
3,6-diazaoctanethylenediamin	Rabbit	Corrosive
1,8-Diazabicyclo[5.4.0]undec-7-ene	In vitro data	Corrosive

Serious Eye Damage/Irritation

Name	Species	Value
Overall product	Rabbit	Mild irritant
alpha-Hydro-omega-hydroxy-poly[oxy(methyl-1,2-ethanediyl)], ether with 2,2-bis(hydroxymethyl)-1,3-propanediol (4:1), 2-hydroxy-3-mercaptopropyl ether	Rabbit	Mild irritant
Triethylenetetramine, propoxylated	Rabbit	Severe irritant
N,N,N',N'-tetramethyl-2,2'-oxybis(ethylamine)	Rabbit	Corrosive
3,6-diazaoctanethylenediamin	Rabbit	Corrosive
1,8-Diazabicyclo[5.4.0]undec-7-ene	similar health hazards	Corrosive

Skin Sensitisation

Name	Species	Value
------	---------	-------

3M Scotch-Weld Epoxy Adhesive DP105 Clear, Part A

alpha-Hydro-omega-hydroxy-poly[oxy(methyl-1,2-ethanediyl)], ether with 2,2-bis(hydroxymethyl)-1,3-propanediol (4:1), 2-hydroxy-3-mercaptopropyl ether	Mouse	Sensitising
Triethylenetetramine, propoxylated	Mouse	Sensitising
N,N,N',N'-tetramethyl-2,2'-oxybis(ethylamine)	Multiple animal species	Not classified
3,6-diazaoctanethylenediamin	Guinea pig	Sensitising

Respiratory Sensitisation

For the component/components, either no data is currently available or the data is not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
alpha-Hydro-omega-hydroxy-poly[oxy(methyl-1,2-ethanediyl)], ether with 2,2-bis(hydroxymethyl)-1,3-propanediol (4:1), 2-hydroxy-3-mercaptopropyl ether	In Vitro	Not mutagenic
Triethylenetetramine, propoxylated	In Vitro	Some positive data exist, but the data are not sufficient for classification
N,N,N',N'-tetramethyl-2,2'-oxybis(ethylamine)	In Vitro	Not mutagenic
N,N,N',N'-tetramethyl-2,2'-oxybis(ethylamine)	In vivo	Not mutagenic
1,8-Diazabicyclo[5.4.0]undec-7-ene	In Vitro	Not mutagenic

Carcinogenicity

For the component/components, either no data is currently available or the data is not sufficient for classification.

Reproductive Toxicity
Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
Triethylenetetramine, propoxylated	Ingestion	Not classified for female reproduction	Rat	NOAEL 750 mg/kg/day	prematuring into lactation
Triethylenetetramine, propoxylated	Ingestion	Not classified for male reproduction	Rat	NOAEL 750 mg/kg/day	43 days
Triethylenetetramine, propoxylated	Ingestion	Not classified for development	Rat	NOAEL 750 mg/kg/day	prematuring into lactation
N,N,N',N'-tetramethyl-2,2'-oxybis(ethylamine)	Dermal	Not classified for development	Rabbit	NOAEL 12 mg/kg/day	during organogenesis
1,8-Diazabicyclo[5.4.0]undec-7-ene	Ingestion	Not classified for female reproduction	Rat	NOAEL 150 mg/kg/day	prematuring into lactation
1,8-Diazabicyclo[5.4.0]undec-7-ene	Ingestion	Not classified for male reproduction	Rat	NOAEL 150 mg/kg/day	29 days
1,8-Diazabicyclo[5.4.0]undec-7-ene	Ingestion	Not classified for development	Rat	NOAEL 150 mg/kg/day	during gestation

Target Organ(s)
Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Triethylenetetramine, propoxylated	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL not available	
N,N,N',N'-tetramethyl-2,2'-oxybis(ethylamine)	Inhalation	respiratory irritation	May cause respiratory irritation	similar health hazards	NOAEL Not available	
1,8-Diazabicyclo[5.4.0]undec-7-ene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
alpha-Hydro-omega-hydroxy-poly[oxy(methyl-1,2-ethanediyl)], ether with 2,2-bis(hydroxymethyl)-1,3-propanediol (4:1), 2-hydroxy-3-mercaptopropyl ether	Ingestion	hematopoietic system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 75 mg/kg/day	90 days
alpha-Hydro-omega-hydroxy-poly[oxy(methyl-1,2-ethanediyl)], ether with 2,2-bis(hydroxymethyl)-1,3-propanediol (4:1), 2-hydroxy-3-mercaptopropyl ether	Ingestion	liver	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 250 mg/kg/day	90 days
alpha-Hydro-omega-hydroxy-poly[oxy(methyl-1,2-ethanediyl)], ether with 2,2-bis(hydroxymethyl)-1,3-propanediol (4:1), 2-hydroxy-3-mercaptopropyl ether	Ingestion	endocrine system heart skin immune system nervous system eyes kidney and/or bladder respiratory system vascular system	Not classified	Rat	NOAEL 1,000 mg/kg/day	90 days
Triethylenetetramine, propoxylated	Ingestion	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 300 mg/kg/day	43 days
N,N,N',N'-tetramethyl-2,2'-oxybis(ethylamine)	Dermal	skin heart endocrine system gastrointestinal tract hematopoietic system liver immune system muscles nervous system kidney and/or bladder respiratory system vascular system	Not classified	Rabbit	NOAEL 8 mg/kg/day	90 days
N,N,N',N'-tetramethyl-2,2'-oxybis(ethylamine)	Inhalation	skin endocrine system eyes respiratory system heart hematopoietic system liver immune system nervous system kidney and/or bladder	Not classified	Rat	NOAEL 0.038 mg/l	14 weeks
N,N,N',N'-tetramethyl-2,2'-oxybis(ethylamine)	Ingestion	gastrointestinal tract liver kidney and/or bladder respiratory system	Not classified	Rat	NOAEL 150 mg/kg/day	7 days
N,N,N',N'-tetramethyl-2,2'-oxybis(ethylamine)	Ingestion	heart endocrine system hematopoietic system nervous system	Not classified	Rat	NOAEL 220 mg/kg/day	7 days
1,8-Diazabicyclo[5.4.0]undec-7-ene	Ingestion	heart skin endocrine system gastrointestinal tract bone, teeth, nails, and/or hair hematopoietic system liver immune system muscles nervous system eyes kidney and/or	Not classified	Rat	NOAEL 120 mg/kg/day	90 days

3M Scotch-Weld Epoxy Adhesive DP105 Clear, Part A

		bladder respiratory system vascular system				
--	--	--	--	--	--	--

Aspiration Hazard

For the component/components, either no data is currently available or the data is not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

11.2. Information on other hazards

This material does not contain any substances that are assessed to be an endocrine disruptor for human health.

SECTION 12: Ecological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

12.1. Toxicity

No product test data available.

Material	CAS #	Organism	Type	Exposure	Test endpoint	Test result
alpha-Hydro-omega-hydroxy-poly[oxy(methyl-1,2-ethanediyl)], ether with 2,2-bis(hydroxymethyl)-1,3-propanediol (4:1), 2-hydroxy-3-mercaptopropyl ether	72244-98-5	Activated sludge	Experimental	3 hours	EC50	>1,000 mg/l
alpha-Hydro-omega-hydroxy-poly[oxy(methyl-1,2-ethanediyl)], ether with 2,2-bis(hydroxymethyl)-1,3-propanediol (4:1), 2-hydroxy-3-mercaptopropyl ether	72244-98-5	Green algae	Experimental	72 hours	EC50	>733 mg/l
alpha-Hydro-omega-hydroxy-poly[oxy(methyl-1,2-ethanediyl)], ether with 2,2-bis(hydroxymethyl)-1,3-propanediol (4:1), 2-hydroxy-3-mercaptopropyl ether	72244-98-5	Water flea	Experimental	48 hours	EC50	12 mg/l
alpha-Hydro-omega-hydroxy-poly[oxy(methyl-1,2-ethanediyl)], ether with 2,2-bis(hydroxymethyl)-1,3-propanediol (4:1), 2-hydroxy-3-mercaptopropyl ether	72244-98-5	Zebra Fish	Experimental	96 hours	LC50	87 mg/l

3M Scotch-Weld Epoxy Adhesive DP105 Clear, Part A

alpha-Hydro-omega-hydroxy-poly[oxy(methyl-1,2-ethanediy)], ether with 2,2-bis(hydroxymethyl)-1,3-propanediol (4:1), 2-hydroxy-3-mercaptopropyl ether	72244-98-5	Green algae	Experimental	72 hours	NOEC	338 mg/l
alpha-Hydro-omega-hydroxy-poly[oxy(methyl-1,2-ethanediy)], ether with 2,2-bis(hydroxymethyl)-1,3-propanediol (4:1), 2-hydroxy-3-mercaptopropyl ether	72244-98-5	Water flea	Experimental	21 days	NOEC	3.5 mg/l
Triethylenetetramine, propoxylated	26950-63-0	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
N,N,N',N'-tetramethyl-2,2'-oxybis(ethylamine)	3033-62-3	Activated sludge	Experimental	30 minutes	EC20	>720 mg/l
N,N,N',N'-tetramethyl-2,2'-oxybis(ethylamine)	3033-62-3	Green algae	Experimental	72 hours	ErC50	24 mg/l
N,N,N',N'-tetramethyl-2,2'-oxybis(ethylamine)	3033-62-3	Water flea	Experimental	48 hours	EC50	102 mg/l
N,N,N',N'-tetramethyl-2,2'-oxybis(ethylamine)	3033-62-3	Zebra Fish	Experimental	96 hours	LC50	131.2 mg/l
N,N,N',N'-tetramethyl-2,2'-oxybis(ethylamine)	3033-62-3	Green algae	Experimental	72 hours	ErC10	5 mg/l
1,8-Diazabicyclo[5.4.0]undec-7-ene	6674-22-2	Activated sludge	Experimental	30 minutes	EC20	650 mg/l
1,8-Diazabicyclo[5.4.0]undec-7-ene	6674-22-2	Bacteria	Experimental	17 hours	EC10	210 mg/l
1,8-Diazabicyclo[5.4.0]undec-7-ene	6674-22-2	Golden Orfe	Experimental	96 hours	LC50	>=146.6 mg/l
1,8-Diazabicyclo[5.4.0]undec-7-ene	6674-22-2	Green algae	Experimental	72 hours	EC50	>100 mg/l
1,8-Diazabicyclo[5.4.0]undec-7-ene	6674-22-2	Water flea	Experimental	48 hours	EC50	50 mg/l
1,8-Diazabicyclo[5.4.0]undec-7-ene	6674-22-2	Green algae	Experimental	72 hours	EC10	>100 mg/l
1,8-Diazabicyclo[5.4.0]undec-7-ene	6674-22-2	Water flea	Experimental	21 days	NOEC	12 mg/l
3,6-diazaoctanethylenediamin	112-24-3	Green algae	Experimental	72 hours	EC50	27.4 mg/l
3,6-diazaoctanethylenediamin	112-24-3	Guppy	Experimental	96 hours	LC50	570 mg/l
3,6-diazaoctanethylenediamin	112-24-3	Water flea	Experimental	48 hours	EC50	37.4 mg/l
3,6-diazaoctanethylenediamin	112-24-3	Green algae	Experimental	72 hours	NOEC	0.468 mg/l
3,6-diazaoctanethylenediamin	112-24-3	Water flea	Experimental	21 days	NOEC	2.86 mg/l

12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
alpha-Hydro-omega-hydroxy-poly[oxy(methyl-1,2-ethanediyl)], ether with 2,2-bis(hydroxymethyl)-1,3-propanediol (4:1), 2-hydroxy-3-mercaptopropyl ether	72244-98-5	Experimental Biodegradation	28 days	CO2 evolution	5 %CO2 evolution/THC O2 evolution	OECD 301B - Modified sturm or CO2
Triethylenetetramine, propoxylated	26950-63-0	Data not availbl-insufficient	N/A	N/A	N/A	N/A
N,N,N',N'-tetramethyl-2,2'-oxybis(ethylamine)	3033-62-3	Experimental Biodegradation	28 days	BOD	0 %BOD/ThoD	OECD 301C - MITI test (I)
1,8-Diazabicyclo[5.4.0]undec-7-ene	6674-22-2	Experimental Biodegradation	28 days	BOD	0 %BOD/ThoD	OECD 301C - MITI test (I)
3,6-diazaoctanethylenediamin	112-24-3	Experimental Biodegradation	20 days	BOD	0 %BOD/ThoD	OECD 301D - Closed bottle test

12.3 : Bioaccumulative potential

Material	Cas No.	Test type	Duration	Study Type	Test result	Protocol
alpha-Hydro-omega-hydroxy-poly[oxy(methyl-1,2-ethanediyl)], ether with 2,2-bis(hydroxymethyl)-1,3-propanediol (4:1), 2-hydroxy-3-mercaptopropyl ether	72244-98-5	Estimated Bioconcentration		Log Kow	>1.2	
Triethylenetetramine, propoxylated	26950-63-0	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
N,N,N',N'-tetramethyl-2,2'-oxybis(ethylamine)	3033-62-3	Experimental Bioconcentration		Log Kow	-0.339	OECD 107 log Kow shke flask mtd
1,8-Diazabicyclo[5.4.0]undec-7-ene	6674-22-2	Experimental BCF - Fish	42 days	Bioaccumulation factor	<3.6	OECD305-Bioconcentration
3,6-diazaoctanethylenediamin	112-24-3	Experimental BCF - Fish	42 days	Bioaccumulation factor	<5.0	OECD305-Bioconcentration

12.4. Mobility in soil

Material	Cas No.	Test type	Study Type	Test result	Protocol
N,N,N',N'-tetramethyl-2,2'-oxybis(ethylamine)	3033-62-3	Modeled Mobility in Soil	Koc	13 l/kg	Episuite™
1,8-Diazabicyclo[5.4.0]undec-7-ene	6674-22-2	Estimated Mobility in Soil	Koc	1 l/kg	ACD/Labs ChemSketch™

12.5. Results of the PBT and vPvB assessment

This material does not contain any substances that are assessed to be a PBT or vPvB

12.6. Endocrine disrupting properties

This material does not contain any substances that are assessed to be an endocrine disruptor for environmental effects

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

EU waste code (product as sold)

- 08 04 09* Waste adhesives and sealants containing organic solvents or other dangerous substances
- 20 01 27* Paint, inks, adhesives and resins containing dangerous substances

SECTION 14: Transportation information

Not hazardous for transportation.

	Ground Transport (ADR)	Air Transport (IATA)	Marine Transport (IMDG)
14.1 UN number or ID number	No data available.	No data available.	No data available.
14.2 UN proper shipping name	No data available.	No data available.	No data available.
14.3 Transport hazard class(es)	No data available.	No data available.	No data available.
14.4 Packing group	No data available.	No data available.	No data available.
14.5 Environmental hazards	No data available.	No data available.	No data available.
14.6 Special precautions for user	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.
14.7 Marine Transport in bulk according to IMO instruments	No data available.	No data available.	No data available.
Control Temperature	No data available.	No data available.	No data available.

Emergency Temperature	No data available.	No data available.	No data available.
ADR Classification Code	No data available.	No data available.	No data available.
IMDG Segregation Code	No data available.	No data available.	No data available.

Please contact the address or phone number listed on the first page of the SDS for additional information on the transport/shipment of the material by rail (RID) or inland waterways (ADN).

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Japan Chemical Substance Control Law. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

DIRECTIVE 2012/18/EU

Seveso hazard categories, Annex 1, Part 1
None

Seveso named dangerous substances, Annex 1, Part 2
None

Regulation (EU) No 649/2012

No chemicals listed

15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out for this substance/mixture in accordance with Regulation (EC) No 1907/2006, as amended.

SECTION 16: Other information

List of relevant H statements

EUH071	Corrosive to the respiratory tract.
H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H312	Harmful in contact with skin.

H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H412	Harmful to aquatic life with long lasting effects.

Revision information:

CLP: Ingredient table information was modified.

Section 3: Composition/ Information of ingredients table information was modified.

Section 8: Occupational exposure limit table information was modified.

Section 11: Acute Toxicity table information was modified.

Section 11: Germ Cell Mutagenicity Table information was modified.

Section 11: Reproductive Toxicity Table information was modified.

Section 11: Serious Eye Damage/Irritation Table information was modified.

Section 11: Skin Corrosion/Irritation Table information was modified.

Section 11: Skin Sensitization Table information was modified.

Section 11: Target Organs - Repeated Table information was modified.

Section 11: Target Organs - Single Table information was modified.

Section 12: Component ecotoxicity information information was modified.

Section 12: Mobility in soil information information was modified.

Section 12: Persistence and Degradability information information was modified.

Section 12: Bioaccumulative potential information information was modified.

Two-column table displaying the unique list of H Codes and statements (std phrases) for all components of the given material. information was modified.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into the European Union, you are responsible for all regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration.

3M Ireland MSDSs are available at www.3M.com



Safety Data Sheet

Copyright, 2023, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	05-6781-8	Version number:	19.01
Revision date:	29/06/2023	Supersedes date:	08/02/2023

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

3M Scotch-Weld Epoxy Adhesive DP105 Clear, Part B

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Structural adhesive.

1.3. Details of the supplier of the safety data sheet

Address: 3M Ireland Limited, The Iveagh Building, The Park, Carrickmines, Dublin 18.
Telephone: +353 1 280 3555
E Mail: tox.uk@mmm.com
Website: www.3M.com

1.4. Emergency telephone number

Emergency medical information: 8am-10pm (seven days) contact National Poisons Information Centre, Beaumont Hospital, Dublin 9 DOV2NO, Ireland. Telephone Number: +353 (0)1 809 2166

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

CLP REGULATION (EC) No 1272/2008

The health and environmental classifications of this material have been derived using the calculation method, except in cases where test data are available or the physical form impacts classification. Classification(s) based on test data or physical form are noted below, if applicable.

CLASSIFICATION:

Skin Corrosion/Irritation, Category 2 - Skin Irrit. 2; H315
Serious Eye Damage/Eye Irritation, Category 2 - Eye Irrit. 2; H319
Skin Sensitization, Category 1 - Skin Sens. 1; H317
Hazardous to the Aquatic Environment (Chronic), Category 3 - Aquatic Chronic 3; H412

For full text of H phrases, see Section 16.

2.2. Label elements

CLP REGULATION (EC) No 1272/2008

SIGNAL WORD

WARNING.

Symbols

GHS07 (Exclamation mark) |

Pictograms



Ingredients:

Ingredient	CAS Nbr	EC No.	% by Wt
4,4'-Isopropylidenedicyclohexanol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	30583-72-3	500-070-7	70 - 80
bis-[4-(2,3-epoxipropoxy)phenyl]propane	1675-54-3	216-823-5	20 - 24

HAZARD STATEMENTS:

H315	Causes skin irritation.
H319	Causes serious eye irritation.
H317	May cause an allergic skin reaction.
H412	Harmful to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENTS

Prevention:

P280E Wear protective gloves.

Response:

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

For containers not exceeding 125 ml the following Hazard and Precautionary statements may be used:

<=125 ml Hazard statements

H317	May cause an allergic skin reaction.
H412	Harmful to aquatic life with long lasting effects.

<=125 ml Precautionary statements

Prevention:

P280E Wear protective gloves.

Response:

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

2.3. Other hazards

None known.

This material does not contain any substances that are assessed to be a PBT or vPvB

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Ingredient	Identifier(s)	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
4,4'-Isopropylidenedicyclohexanol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	(CAS-No.) 30583-72-3 (EC-No.) 500-070-7	70 - 80	Skin Sens. 1, H317 Aquatic Chronic 3, H412
bis-[4-(2,3-epoxipropoxy)phenyl]propane	(CAS-No.) 1675-54-3 (EC-No.) 216-823-5 (REACH-No.) 01-2119456619-26	20 - 24	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	(CAS-No.) 2530-83-8 (EC-No.) 219-784-2 (REACH-No.) 01-2119513212-58	0.5 - 1.5	Eye Dam. 1, H318 Aquatic Chronic 3, H412

Please see section 16 for the full text of any H statements referred to in this section

Specific Concentration Limits

Ingredient	Identifier(s)	Specific Concentration Limits
bis-[4-(2,3-epoxipropoxy)phenyl]propane	(CAS-No.) 1675-54-3 (EC-No.) 216-823-5	(C >= 5%) Skin Irrit. 2, H315 (C >= 5%) Eye Irrit. 2, H319

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye contact

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

The most important symptoms and effects based on the CLP classification include:
Irritation to the skin (localized redness, swelling, itching, and dryness). Allergic skin reaction (redness, swelling, blistering, and itching). Serious irritation to the eyes (significant redness, swelling, pain, tearing, and impaired vision).

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

<u>Substance</u>	<u>Condition</u>
Aldehydes.	During combustion.
Hydrocarbons.	During combustion.
Carbon monoxide	During combustion.
Carbon dioxide.	During combustion.
Hydrogen Chloride	During combustion.
Ketones.	During combustion.
Toxic vapour, gas, particulate.	During combustion.

5.3. Advice for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible.

6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

SECTION 7: Handling and storage

7.1. Precautions for safe handling

3M Scotch-Weld Epoxy Adhesive DP105 Clear, Part B

Avoid breathing dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.)

7.2. Conditions for safe storage including any incompatibilities

Store away from acids. Store away from oxidising agents.

7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

SECTION 8: Exposure controls/personal protection**8.1 Control parameters****Occupational exposure limits**

No occupational exposure limit values exist for any of the components listed in Section 3 of this Safety Data Sheet.

Biological limit values

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

Derived no effect level (DNEL)

Ingredient	Degradation Product	Population	Human exposure pattern	DNEL
bis-[4-(2,3-epoxipropoxy)phenyl]propane		Worker	Dermal, Long-term exposure (8 hours), Systemic effects	8.3 mg/kg bw/d
bis-[4-(2,3-epoxipropoxy)phenyl]propane		Worker	Dermal, Short-term exposure, Systemic effects	8.3 mg/kg bw/d
bis-[4-(2,3-epoxipropoxy)phenyl]propane		Worker	Inhalation, Long-term exposure (8 hours), Systemic effects	12.3 mg/m ³
bis-[4-(2,3-epoxipropoxy)phenyl]propane		Worker	Inhalation, Short-term exposure, Systemic effects	12.3 mg/m ³
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane		Worker	Dermal, Long-term exposure (8 hours), Systemic effects	21 mg/kg bw/d
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane		Worker	Dermal, Short-term exposure, Systemic effects	21 mg/kg bw/d
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane		Worker	Inhalation, Long-term exposure (8 hours), Systemic effects	147 mg/m ³
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane		Worker	Inhalation, Short-term exposure, Systemic effects	147 mg/m ³

Predicted no effect concentrations (PNEC)

Ingredient	Degradation Product	Compartment	PNEC
bis-[4-(2,3-epoxipropoxy)phenyl]propane		Freshwater	0.003 mg/l

ne			
bis-[4-(2,3-epoxipropoxy)phenyl]propane		Freshwater sediments	0.5 mg/kg d.w.
bis-[4-(2,3-epoxipropoxy)phenyl]propane		Intermittent releases to water	0.013 mg/l
bis-[4-(2,3-epoxipropoxy)phenyl]propane		Marine water	0.0003 mg/l
bis-[4-(2,3-epoxipropoxy)phenyl]propane		Marine water sediments	0.5 mg/kg d.w.
bis-[4-(2,3-epoxipropoxy)phenyl]propane		Sewage Treatment Plant	10 mg/l
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane		Agricultural soil	0.13 mg/kg d.w.
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane		Freshwater	1 mg/l
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane		Freshwater sediments	0.79 mg/kg d.w.
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane		Intermittent releases to water	1 mg/l
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane		Marine water	0.1 mg/l
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane		Sewage Treatment Plant	10 mg/l

Recommended monitoring procedures: Information on recommended monitoring procedures can be obtained from Indust. Inspect./Ministry (IE)

8.2. Exposure controls

In addition, refer to the annex for more information.

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect vented goggles.

Applicable Norms/Standards

Use eye protection conforming to EN 166

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended:

Material	Thickness (mm)	Breakthrough Time
Polymer laminate	No data available	No data available

Applicable Norms/Standards

Use gloves tested to EN 374

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

Applicable Norms/Standards

Use a respirator conforming to EN 140 or EN 136: filter types A & P

8.2.3. Environmental exposure controls

Refer to Annex

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid.
Specific Physical Form:	Viscous Liquid
Colour	Colourless
Odor	Slight Epoxy
Odour threshold	<i>No data available.</i>
Melting point/freezing point	<i>Not applicable.</i>
Boiling point/boiling range	>=115.6 °C
Flammability (solid, gas)	Not applicable.
Flammable Limits(LEL)	<i>No data available.</i>
Flammable Limits(UEL)	<i>No data available.</i>
Flash point	>=115.6 °C [<i>Test Method:</i> Pensky-Martens Closed Cup]
Autoignition temperature	<i>No data available.</i>
Decomposition temperature	<i>No data available.</i>
pH	<i>substance/mixture is non-soluble (in water)</i>
Kinematic Viscosity	4,505 mm ² /sec
Water solubility	Nil
Solubility- non-water	<i>No data available.</i>
Partition coefficient: n-octanol/water	<i>No data available.</i>
Vapour pressure	<=186,158.4 Pa [<i>@ 55 °C</i>]
Density	1.11 g/ml
Relative density	1.11 [<i>Ref Std:</i> WATER=1]

Relative Vapour Density

No data available.

9.2. Other information

9.2.2 Other safety characteristics

EU Volatile Organic Compounds

No data available.

Evaporation rate

No data available.

Molecular weight

No data available.

SECTION 10: Stability and reactivity

10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

Heat is generated during cure. Do not cure a mass larger than 50 grams in a confined space to prevent a premature exothermic reaction with production of intense heat and smoke.

10.5 Incompatible materials

Strong acids.

Strong oxidising agents.

10.6 Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
------------------	------------------

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from internal hazard assessments.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Skin contact

Mild Skin Irritation: Signs/symptoms may include localised redness, swelling, itching, and dryness. Allergic skin reaction

3M Scotch-Weld Epoxy Adhesive DP105 Clear, Part B

(non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye contact

Severe eye irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

Ingestion

May be harmful if swallowed.

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE >2,000 - =5,000 mg/kg
4,4'-Isopropylidenedicyclohexanol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	Dermal	Rat	LD50 > 2,000 mg/kg
4,4'-Isopropylidenedicyclohexanol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	Ingestion	Rat	LD50 > 2,000 mg/kg
bis-[4-(2,3-epoxipropoxy)phenyl]propane	Dermal	Rat	LD50 > 1,600 mg/kg
bis-[4-(2,3-epoxipropoxy)phenyl]propane	Ingestion	Rat	LD50 > 1,000 mg/kg
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Dermal	Rabbit	LD50 4,000 mg/kg
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 5.3 mg/l
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Ingestion	Rat	LD50 7,010 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
4,4'-Isopropylidenedicyclohexanol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	Rabbit	Minimal irritation
bis-[4-(2,3-epoxipropoxy)phenyl]propane	Rabbit	Mild irritant
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Rabbit	Mild irritant

Serious Eye Damage/Irritation

Name	Species	Value
4,4'-Isopropylidenedicyclohexanol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	Rabbit	Mild irritant
bis-[4-(2,3-epoxipropoxy)phenyl]propane	Rabbit	Moderate irritant
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Rabbit	Corrosive

Skin Sensitisation

Name	Species	Value
4,4'-Isopropylidenedicyclohexanol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	Mouse	Sensitising
bis-[4-(2,3-epoxipropoxy)phenyl]propane	Human and animal	Sensitising
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Guinea pig	Not classified

Respiratory Sensitisation

Name	Species	Value
bis-[4-(2,3-epoxipropoxy)phenyl]propane	Human	Not classified

Germ Cell Mutagenicity

Name	Route	Value
4,4'-Isopropylidenedicyclohexanol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	In vivo	Not mutagenic
4,4'-Isopropylidenedicyclohexanol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	In Vitro	Some positive data exist, but the data are not sufficient for classification
bis-[4-(2,3-epoxipropoxy)phenyl]propane	In vivo	Not mutagenic
bis-[4-(2,3-epoxipropoxy)phenyl]propane	In Vitro	Some positive data exist, but the data are not sufficient for classification
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	In vivo	Not mutagenic
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	In Vitro	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

Name	Route	Species	Value
bis-[4-(2,3-epoxipropoxy)phenyl]propane	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Dermal	Mouse	Not carcinogenic

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
4,4'-Isopropylidenedicyclohexanol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	Ingestion	Not classified for development	Rat	NOAEL 300 mg/kg/day	during gestation
bis-[4-(2,3-epoxipropoxy)phenyl]propane	Ingestion	Not classified for female reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
bis-[4-(2,3-epoxipropoxy)phenyl]propane	Ingestion	Not classified for male reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
bis-[4-(2,3-epoxipropoxy)phenyl]propane	Dermal	Not classified for development	Rabbit	NOAEL 300 mg/kg/day	during organogenesis
bis-[4-(2,3-epoxipropoxy)phenyl]propane	Ingestion	Not classified for development	Rat	NOAEL 750 mg/kg/day	2 generation
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	1 generation
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	1 generation
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Ingestion	Not classified for development	Rat	NOAEL 3,000 mg/kg/day	during organogenesis

Target Organ(s)

Specific Target Organ Toxicity - single exposure

For the component/components, either no data is currently available or the data is not sufficient for classification.

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
4,4'-Isopropylidenedicyclohexanol, oligomeric reaction	Ingestion	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 100 mg/kg/day	90 days

3M Scotch-Weld Epoxy Adhesive DP105 Clear, Part B

products with 1-chloro-2,3-epoxypropane						
4,4'-Isopropylidenedicyclohexanol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	Ingestion	heart endocrine system gastrointestinal tract bone, teeth, nails, and/or hair hematopoietic system liver immune system nervous system vascular system skin muscles eyes respiratory system	Not classified	Rat	NOAEL 600 mg/kg/day	90 days
bis-[4-(2,3-epoxipropoxy)phenyl]propane	Dermal	liver	Not classified	Rat	NOAEL 1,000 mg/kg/day	2 years
bis-[4-(2,3-epoxipropoxy)phenyl]propane	Dermal	nervous system	Not classified	Rat	NOAEL 1,000 mg/kg/day	13 weeks
bis-[4-(2,3-epoxipropoxy)phenyl]propane	Ingestion	auditory system heart endocrine system hematopoietic system liver eyes kidney and/or bladder	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Ingestion	heart endocrine system bone, teeth, nails, and/or hair hematopoietic system liver immune system nervous system kidney and/or bladder respiratory system	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days

Aspiration Hazard

For the component/components, either no data is currently available or the data is not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

11.2. Information on other hazards

This material does not contain any substances that are assessed to be an endocrine disruptor for human health.

SECTION 12: Ecological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

12.1. Toxicity

No product test data available.

Material	CAS #	Organism	Type	Exposure	Test endpoint	Test result
4,4'-Isopropylidenedicyclohexanol, oligomeric	30583-72-3	Activated sludge	Experimental	3 hours	NOEC	1,000 mg/l

3M Scotch-Weld Epoxy Adhesive DP105 Clear, Part B

reaction products with 1-chloro-2,3-epoxypropane						
4,4'-Isopropylidenedicyclohexanol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	30583-72-3	Green algae	Experimental	72 hours	EC50	>100 mg/l
4,4'-Isopropylidenedicyclohexanol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	30583-72-3	Rainbow trout	Experimental	96 hours	LC50	11.5 mg/l
bis-[4-(2,3-epoxipropoxy)phenyl]propane	1675-54-3	Activated sludge	Analogous Compound	3 hours	IC50	>100 mg/l
bis-[4-(2,3-epoxipropoxy)phenyl]propane	1675-54-3	Rainbow trout	Estimated	96 hours	LC50	2 mg/l
bis-[4-(2,3-epoxipropoxy)phenyl]propane	1675-54-3	Water flea	Estimated	48 hours	EC50	1.8 mg/l
bis-[4-(2,3-epoxipropoxy)phenyl]propane	1675-54-3	Green algae	Experimental	72 hours	ErC50	>11 mg/l
bis-[4-(2,3-epoxipropoxy)phenyl]propane	1675-54-3	Green algae	Experimental	72 hours	NOEC	4.2 mg/l
bis-[4-(2,3-epoxipropoxy)phenyl]propane	1675-54-3	Water flea	Experimental	21 days	NOEC	0.3 mg/l
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	2530-83-8	Common Carp	Experimental	96 hours	LC50	55 mg/l
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	2530-83-8	Green algae	Experimental	96 hours	ErC50	350 mg/l
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	2530-83-8	Invertebrate	Experimental	48 hours	LC50	324 mg/l
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	2530-83-8	Green algae	Experimental	96 hours	NOEC	130 mg/l
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	2530-83-8	Water flea	Experimental	21 days	NOEC	100 mg/l
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	2530-83-8	Activated sludge	Experimental	3 hours	EC50	>100 mg/l

12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
4,4'-Isopropylidenedicyclohexanol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	30583-72-3	Experimental Biodegradation	28 days	BOD	0.1 %BOD/Th OD	OECD 301D - Closed bottle test
bis-[4-(2,3-epoxipropoxy)phenyl]propane	1675-54-3	Experimental Biodegradation	28 days	BOD	5 %BOD/COD	OECD 301F - Manometric respirometry
bis-[4-(2,3-epoxipropoxy)phenyl]propane	1675-54-3	Experimental Hydrolysis		Hydrolytic half-life (pH 7)	117 hours (t 1/2)	OECD 111 Hydrolysis func of pH
[3-(2,3-	2530-83-8	Experimental	28 days	Dissolv. Organic	37 %removal	EC C.4.A. DOC Die-Away

3M Scotch-Weld Epoxy Adhesive DP105 Clear, Part B

epoxypropoxy)propyl]trimethoxysilane		Biodegradation		Carbon Deplet	of DOC	Test
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	2530-83-8	Experimental Hydrolysis		Hydrolytic half-life (pH 7)	6.5 hours (t 1/2)	OECD 111 Hydrolysis func of pH

12.3 : Bioaccumulative potential

Material	Cas No.	Test type	Duration	Study Type	Test result	Protocol
4,4'-Isopropylidenedicyclohexanol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	30583-72-3	Experimental Bioconcentration		Log Kow	3.84	
bis-[4-(2,3-epoxypropoxy)phenyl]propane	1675-54-3	Experimental Bioconcentration		Log Kow	3.242	OECD 117 log Kow HPLC method
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	2530-83-8	Experimental Bioconcentration		Log Kow	0.5	Episuite™

12.4. Mobility in soil

Material	Cas No.	Test type	Study Type	Test result	Protocol
bis-[4-(2,3-epoxypropoxy)phenyl]propane	1675-54-3	Modeled Mobility in Soil	Koc	450 l/kg	Episuite™
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	2530-83-8	Modeled Mobility in Soil	Koc	10 l/kg	Episuite™

12.5. Results of the PBT and vPvB assessment

This material does not contain any substances that are assessed to be a PBT or vPvB

12.6. Endocrine disrupting properties

This material does not contain any substances that are assessed to be an endocrine disruptor for environmental effects

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations**13.1 Waste treatment methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Combustion products will include halogen acid (HCl/HF/HBr). Facility must be capable of handling halogenated materials. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

EU waste code (product as sold)

08 04 09* Waste adhesives and sealants containing organic solvents or other dangerous substances

20 01 27* Paint, inks, adhesives and resins containing dangerous substances

SECTION 14: Transportation information

Not hazardous for transportation.

	Ground Transport (ADR)	Air Transport (IATA)	Marine Transport (IMDG)
14.1 UN number or ID number	No data available.	No data available.	No data available.
14.2 UN proper shipping name	No data available.	No data available.	No data available.
14.3 Transport hazard class(es)	No data available.	No data available.	No data available.
14.4 Packing group	No data available.	No data available.	No data available.
14.5 Environmental hazards	No data available.	No data available.	No data available.
14.6 Special precautions for user	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.
14.7 Marine Transport in bulk according to IMO instruments	No data available.	No data available.	No data available.
Control Temperature	No data available.	No data available.	No data available.
Emergency Temperature	No data available.	No data available.	No data available.
ADR Classification Code	No data available.	No data available.	No data available.
IMDG Segregation Code	No data available.	No data available.	No data available.

Please contact the address or phone number listed on the first page of the SDS for additional information on the transport/shipment of the material by rail (RID) or inland waterways (ADN).

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Carcinogenicity

<u>Ingredient</u>	<u>CAS Nbr</u>	<u>Classification</u>	<u>Regulation</u>
bis-[4-(2,3-epoxipropoxy)phenyl]propane	1675-54-3	Gr. 3: Not classifiable	International Agency for Research on Cancer

Restrictions on the manufacture, placing on the market and use:

The following substance(s) contained in this product is/are subject through Annex XVII of REACH regulation to restrictions on the manufacture, placing on the market and use when present in certain dangerous substances, mixtures and articles. Users of this product are required to comply with the restrictions placed upon it by the aforementioned provision.

<u>Ingredient</u>	<u>CAS Nbr</u>
bis-[4-(2,3-epoxipropoxy)phenyl]propane	1675-54-3

Restriction status: listed in REACH Annex XVII

Restricted uses: See Annex XVII to Regulation (EC) No 1907/2006 for Conditions of Restriction

Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Japan Chemical Substance Control Law. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

DIRECTIVE 2012/18/EU

Seveso hazard categories, Annex 1, Part 1
None

Seveso named dangerous substances, Annex 1, Part 2
None

Regulation (EU) No 649/2012

No chemicals listed

15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out for this mixture. Chemical safety assessments for the contained substances may have been carried out by the registrants of the substances in accordance with Regulation (EC) No 1907/2006, as amended.

SECTION 16: Other information**List of relevant H statements**

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Revision information:

Industrial Use of Adhesives: Section 16: Annex information was modified.

Annex

1. Title	
Substance identification	[3-(2,3-epoxypropoxy)propyl]trimethoxysilane; EC No. 219-784-2; CAS Nbr 2530-83-8;
Exposure Scenario Name	Formulation
Lifecycle Stage	Use at industrial sites
Contributing activities	PROC 05 -Mixing or blending in batch processes PROC 08b -Transfer of substance or mixture (charging and discharging) at dedicated facilities PROC 09 -Transfer of substance or mixture into small containers (dedicated filling line, including weighing) ERC 02 -Formulation into mixture
Processes, tasks and activities covered	Mixing or blending of solid or liquid materials. Transfer of substance/mixture with dedicated engineering controls.
2. Operational conditions and risk management measures	
Operating Conditions	Physical state: Liquid. General operating conditions: Duration of use: 8 hours/day; Emission days per year: <= 200 days per year; Indoor use;
Risk management measures	Under the operational conditions described above the following risk management measures apply: General risk management measures: Human health: Face shield; Goggles - Chemical resistant; Local exhaust ventilation; Protective Clothing - Apron; Protective Gloves - Butyl Rubber; Protective Gloves - Fluoroelastomer (Viton); Protective Gloves - Polyvinyl Alcohol (PVA); Environmental: None needed;
Waste management measures	No use-specific waste management measures are required for this product. Refer to Section 13 of main SDS for disposal instructions:
3. Prediction of exposure	
Prediction of exposure	Human and environmental exposures are not expected to exceed the DNELs and PNECs when the identified risk management measures are adopted.

1. Title	
Substance identification	[3-(2,3-epoxypropoxy)propyl]trimethoxysilane; EC No. 219-784-2; CAS Nbr 2530-83-8;
Exposure Scenario Name	Industrial Mixing and Application
Lifecycle Stage	Use at industrial sites
Contributing activities	PROC 08b -Transfer of substance or mixture (charging and discharging) at dedicated facilities

	PROC 13 -Treatment of articles by dipping and pouring ERC 05 -Use at industrial site leading to inclusion into/onto article
Processes, tasks and activities covered	Application of product. Transfer of substance/mixture with dedicated engineering controls. Transfer of substances/mixtures into small containers e.g. tubes , bottles or small reservoirs.
2. Operational conditions and risk management measures	
Operating Conditions	Physical state: Liquid. General operating conditions: Duration of use: 8 hours/day; Emission days per year: <= 200 days per year; Indoor use; Task: Transferring Material; Duration of use: 4 hours/day;
Risk management measures	Under the operational conditions described above the following risk management measures apply: General risk management measures: Human health: Face shield; Goggles - Chemical resistant; Protective Clothing - Apron; Protective Gloves - Butyl Rubber; Protective Gloves - Fluoroelastomer (Viton); Protective Gloves - Polyvinyl Alcohol (PVA); Environmental: None needed;
Waste management measures	Send to a municipal sewage treatment plant;
3. Prediction of exposure	
Prediction of exposure	Human and environmental exposures are not expected to exceed the DNELs and PNECs when the identified risk management measures are adopted.

1. Title	
Substance identification	bis-[4-(2,3-epoxipropoxy)phenyl]propane; EC No. 216-823-5; CAS Nbr 1675-54-3;
Exposure Scenario Name	Industrial Use of Adhesives
Lifecycle Stage	Use at industrial sites
Contributing activities	PROC 08a -Transfer of substance or mixture (charging and discharging) at non-dedicated facilities PROC 13 -Treatment of articles by dipping and pouring ERC 05 -Use at industrial site leading to inclusion into/onto article
Processes, tasks and activities covered	Application of product with a roller or brush. Application of product with applicator gun. Application with a wipe. Transfers without dedicated controls, including loading, filling, dumping, bagging.
2. Operational conditions and risk management measures	
Operating Conditions	Physical state: Liquid. General operating conditions: Duration of use: 8 hours/day; Emission days per year: 220 days/year; Frequency of exposure at workplace [for one worker]: 5 days/week;
Risk management measures	Under the operational conditions described above the following risk management measures apply: General risk management measures: Human health: Protective Gloves - Chemical resistant. Refer to Section 8 of the SDS for

	specific glove material.; Environmental: None needed;
Waste management measures	Do not apply industrial sludge to natural soils; Prevent discharge of undissolved substance to or recover from wastewater;
3. Prediction of exposure	
Prediction of exposure	Human and environmental exposures are not expected to exceed the DNELs and PNECs when the identified risk management measures are adopted.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into the European Union, you are responsible for all regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration.

3M Ireland MSDSs are available at www.3M.com