



Safety Data Sheet

Copyright,2023, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	07-1664-7	Version number:	10.00
Revision date:	24/05/2023	Supersedes date:	04/01/2023
Transportation version number:			

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

3M™ Panel Bonding Adhesive PN 08115

Product Identification Numbers

UU-0089-1498-6

7100137215

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Automotive.

1.3. Details of the supplier of the safety data sheet

Address: 3M Ireland Limited, The Iveagh Building, The Park, Carrickmines, Dublin 18.
Telephone: +353 1 280 3555
E Mail: tox.uk@mmm.com

Website: www.3M.com

1.4. Emergency telephone number

Emergency medical information: 8am-10pm (seven days) contact National Poisons Information Centre, Beaumont Hospital, Dublin 9 DOV2NO, Ireland. Telephone Number: +353 (0)1 809 2166

This product is a kit or a multipart product which consists of multiple, independently packaged components. A Safety Data Sheet for each of these components is included. Please do not separate the component Safety Data Sheets from this cover page. The document numbers of the MSDSs for components of this product are:

09-3599-9, 32-4327-6

TRANSPORTATION INFORMATION

Refer to section 14 of the kit components for transport information.

KIT LABEL

2.1. Classification of the substance or mixture CLP REGULATION (EC) No 1272/2008

CLASSIFICATION:

Skin Corrosion/Irritation, Category 1B - Skin Corr. 1B; H314
Serious Eye Damage/Eye Irritation, Category 1 - Eye Dam. 1; H318
Skin Sensitization, Category 1 - Skin Sens. 1; H317
Germ Cell Mutagenicity, Category 2 - Muta. 2; H341
Reproductive Toxicity, Category 1B - Repr. 1B; H360D
Specific Target Organ Toxicity-Single Exposure, Category 3 - STOT SE 3; H336
Hazardous to the Aquatic Environment (Acute), Category 1 - Aquatic Acute 1; H400
Hazardous to the Aquatic Environment (Chronic), Category 1 - Aquatic Chronic 1; H410

For full text of H phrases, see Section 16.

2.2. Label elements CLP REGULATION (EC) No 1272/2008

SIGNAL WORD

DANGER.

Symbols

GHS05 (Corrosion) | GHS07 (Exclamation mark) | GHS08 (Health Hazard) | GHS09 (Environment) |

Pictograms



Contains:

2,4,6-tris(dimethylaminomethyl)phenol.; Rxn mass: 2-([[1-chloro-3-([4-[methoxy(oxiran-2-yl)methyl]cyclohexyl)methoxy]propan-2-yl]oxy)methyl]oxirane & 2,2'-[cis-cyclohexane-1,4-diylbis(methyleneoxymethylene)]bisoxirane & 2,2'-[trans-cyclohexane-1,4-diylbis(methyleneoxymethylene)]bisoxirane; Reaction products of fatty acids, C18-unsaturated, dimers and trimers with 3,3'-[oxybis(ethane-2,1-diyloxy)]dipropan-1-amine ; 2-piperazin-1-ylethylamine; bis-[4-(2,3-epoxipropoxy)phenyl]propane; 3,3'-Oxybis(ethyleneoxy)bis(propylamine); 2-Propenenitrile, polymer with 1,3-butadiene, 1-cyano-1-methyl-4-oxo-4-[[2-(1-piperazinyl)ethyl]amino]butyl-terminated; imidazole

HAZARD STATEMENTS:

H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H341	Suspected of causing genetic defects.
H360D	May damage the unborn child.
H336	May cause drowsiness or dizziness.
H410	Very toxic to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENTS

Prevention:

P201	Obtain special instructions before use.
P260A	Do not breathe vapours.
P280J	Wear protective gloves, protective clothing, respiratory protection, and eye/face protection.

Response:

P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTRE or doctor/physician.

SUPPLEMENTAL INFORMATION:

Supplemental Precautionary Statements:

Restricted to professional users.

Refer to Safety Data Sheet for component % unknown values (www.3M.com/msds).

Revision information:

Kit: Component document group number(s) information was modified.

Label: CLP Ingredients - kit components information was modified.



Safety Data Sheet

Copyright, 2023, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	09-3599-9	Version number:	8.02
Revision date:	02/11/2023	Supersedes date:	24/05/2023

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

3M™ Panel Bonding (90 Minutes) Adhesive Part A (Accelerator) PN 08115, 38315, 38515, 58115

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Automotive.

1.3. Details of the supplier of the safety data sheet

Address: 3M Ireland Limited, The Iveagh Building, The Park, Carrickmines, Dublin 18.
Telephone: +353 1 280 3555
E Mail: tox.uk@mmm.com
Website: www.3M.com

1.4. Emergency telephone number

Emergency medical information: 8am-10pm (seven days) contact National Poisons Information Centre, Beaumont Hospital, Dublin 9 DOV2NO, Ireland. Telephone Number: +353 (0)1 809 2166

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

CLP REGULATION (EC) No 1272/2008

The health and environmental classifications of this material have been derived using the calculation method, except in cases where test data are available or the physical form impacts classification. Classification(s) based on test data or physical form are noted below, if applicable.

This material has been tested for eye damage/irritation and the test results are reflected in the assigned classification.

This material has been tested for skin corrosion/irritation and the test results are reflected in the assigned classification.

This material has been tested for skin sensitization and the test results are reflected in the assigned classification.

CLASSIFICATION:

Skin Corrosion/Irritation, Category 1B - Skin Corr. 1B; H314

Serious Eye Damage/Eye Irritation, Category 1 - Eye Dam. 1; H318

Skin Sensitization, Category 1B - Skin Sens. 1B; H317

Reproductive Toxicity, Category 1B - Repr. 1B; H360D

Specific Target Organ Toxicity-Single Exposure, Category 3 - STOT SE 3; H336

Hazardous to the Aquatic Environment (Acute), Category 1 - Aquatic Acute 1; H400
 Hazardous to the Aquatic Environment (Chronic), Category 1 - Aquatic Chronic 1; H410

For full text of H phrases, see Section 16.

2.2. Label elements

CLP REGULATION (EC) No 1272/2008

SIGNAL WORD

DANGER.

Symbols

GHS05 (Corrosion) |GHS07 (Exclamation mark) |GHS08 (Health Hazard) |GHS09 (Environment) |

Pictograms



Ingredients:

Ingredient	CAS Nbr	EC No.	% by Wt
Reaction products of fatty acids, C18-unsaturated, dimers and trimers with 3,3'-[oxybis(ethane-2,1-diylxy)]dipropan-1-amine		701-270-9	35 - 45
2-Propenenitrile, polymer with 1,3-butadiene, 1-cyano-1-methyl-4-oxo-4-[[2-(1-piperazinyl)ethyl]amino]butyl-terminated	68683-29-4		10 - 30
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	4246-51-9	224-207-2	< 10
2,4,6-tris(dimethylaminomethyl)phenol imidazole	90-72-2	202-013-9	5 - 10
	288-32-4	206-019-2	1 - 5
2-piperazin-1-ylethylamine	140-31-8	205-411-0	0.1 - 1

HAZARD STATEMENTS:

H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H360D	May damage the unborn child.
H336	May cause drowsiness or dizziness.
H410	Very toxic to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENTS

Prevention:

P201	Obtain special instructions before use.
P260A	Do not breathe vapours.
P280J	Wear protective gloves, protective clothing, respiratory protection, and eye/face protection.

Response:

P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTRE or doctor/physician.

SUPPLEMENTAL INFORMATION:

Supplemental Precautionary Statements:

Restricted to professional users.

1% of the mixture consists of components of unknown acute dermal toxicity.

Contains 4% of components with unknown hazards to the aquatic environment.

2.3. Other hazards

Persons previously sensitised to amines may develop a cross-sensitisation reaction to certain other amines.

This material does not contain any substances that are assessed to be a PBT or vPvB

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Ingredient	Identifier(s)	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Reaction products of fatty acids, C18-unsaturated, dimers and trimers with 3,3'-[oxybis(ethane-2,1-diyloxy)]dipropan-1-amine	(EC-No.) 701-270-9	35 - 45	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1A, H317 STOT SE 3, H336 Aquatic Acute 1, H400,M=1 Aquatic Chronic 1, H410,M=1
2-Propenenitrile, polymer with 1,3-butadiene, 1-cyano-1-methyl-4-oxo-4-[[2-(1-piperaziny)ethyl]amino]butyl-terminated	(CAS-No.) 68683-29-4	10 - 30	Skin Irrit. 2, H315 Skin Sens. 1A, H317
Silica, vitreous	(CAS-No.) 60676-86-0 (EC-No.) 262-373-8	10 - 30	Substance with a national occupational exposure limit
Bis[(dimethylamino)methyl]phenol	(CAS-No.) 71074-89-0 (EC-No.) 275-162-0	0.1 - 1.5	Acute Tox. 4, H302 Skin Corr. 1C, H314
2,4,6-tris(dimethylaminomethyl)phenol	(CAS-No.) 90-72-2 (EC-No.) 202-013-9 (REACH-No.) 01-2119560597-27	5 - 10	Acute Tox. 4, H302 Skin Corr. 1C, H314 Eye Dam. 1, H318
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	(CAS-No.) 4246-51-9 (EC-No.) 224-207-2 (REACH-No.) 01-2119963377-26	< 10	Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1, H317
Nitric acid, ammonium calcium salt	(CAS-No.) 15245-12-2 (EC-No.) 239-289-5	1 - 5	Acute Tox. 4, H302 Eye Dam. 1, H318
imidazole	(CAS-No.) 288-32-4 (EC-No.) 206-019-2	1 - 5	Acute Tox. 4, H302 Skin Corr. 1C, H314

			Repr. 1B, H360D Acute Tox. 3, H311
toluene	(CAS-No.) 108-88-3 (EC-No.) 203-625-9	< 0.5	Flam. Liq. 2, H225 Asp. Tox. 1, H304 Skin Irrit. 2, H315 Repr. 2, H361d STOT SE 3, H336 STOT RE 2, H373 Aquatic Chronic 3, H412
Siloxanes and Silicones, di-Me, reaction products with silica	(CAS-No.) 67762-90-7	1 - 5	Substance with a national occupational exposure limit
2-piperazin-1-ylethylamine	(CAS-No.) 140-31-8 (EC-No.) 205-411-0	0.1 - 1	Acute Tox. 3, H311 Acute Tox. 4, H302 Skin Corr. 1B, H314 Skin Sens. 1B, H317 Aquatic Chronic 3, H412 Repr. 2, H361d STOT RE 1, H372

Any entry in the Identifier(s) column that begins with the numbers 6, 7, 8, or 9 are a Provisional List Number provided by ECHA pending publication of the official EC Inventory Number for the substance. Please see section 16 for the full text of any H statements referred to in this section

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Immediately flush with large amounts of water for at least 15 minutes. Remove contaminated clothing. Get immediate medical attention. Wash clothing before reuse.

Eye contact

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

If swallowed

Rinse mouth. Do not induce vomiting. Get immediate medical attention.

4.2. Most important symptoms and effects, both acute and delayed

The most important symptoms and effects based on the CLP classification include:

Skin burns (localized redness, swelling, itching, intense pain, blistering, and tissue destruction). Allergic skin reaction (redness, swelling, blistering, and itching). Serious damage to the eyes (corneal cloudiness, severe pain, tearing, ulcerations, and significantly impaired or loss of vision). Central nervous system depression (headache, dizziness, drowsiness, incoordination, nausea, slurred speech, giddiness, and unconsciousness).

4.3. Indication of any immediate medical attention and special treatment required

Overexposure to this product may result in methemoglobinemia. Methemoglobinemia may be clinically suspected by the presence of clinical "cyanosis" in the presence of a normal PaO₂ (as obtained by arterial blood gases). Routine pulse oximetry may be inaccurate for monitoring oxygen saturation in the presence of methemoglobinemia, and should not be used to make the diagnosis of this disorder. If the patient is symptomatic or if the methemoglobin level is >20%, specific therapy with methylene blue should be considered as part of the medical management.

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

<u>Substance</u>	<u>Condition</u>
Carbon monoxide	During combustion.
Carbon dioxide.	During combustion.

5.3. Advice for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible.

6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not use in a confined area with minimal air exchange. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (eg. gloves, respirators...) as required.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Store away from acids. Store away from oxidising agents.

7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
toluene	108-88-3	Ireland OELs	TWA(8 hours):192 mg/m ³ (50 ppm);TWA(8 hours):50 ppm(192 mg/m ³);STEL(15 minutes):384 mg/m ³ (100 ppm);STEL(15 minutes):100 ppm(384 mg/m ³)	SKIN
Silica, vitreous	60676-86-0	Ireland OELs	TWA(as respirable dust)(8 hours):0.08 mg/m ³	
Silicon dioxide	67762-90-7	Ireland OELs	TWA(Total inhalable dust)(8 hours):6 mg/m ³ ;TWA(as respirable dust)(8 hours):2.4 mg/m ³	

Ireland OELs : Ireland. OELs
 TWA: Time-Weighted-Average
 STEL: Short Term Exposure Limit
 CEIL: Ceiling

Biological limit values

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

Derived no effect level (DNEL)

Ingredient	Degradation Product	Population	Human exposure pattern	DNEL
2,4,6-tris(dimethylaminomethyl)phenol		Worker	Inhalation, Long-term exposure (8 hours), Systemic effects	0.31 mg/m ³
3,3'-Oxybis(ethyleneoxy)bis(propylamine)		Worker	Dermal, Long-term exposure (8 hours), Systemic effects	8.3 mg/kg bw/d
3,3'-Oxybis(ethyleneoxy)bis(propylamine)		Worker	Inhalation, Long-term exposure (8 hours), Local effects	1 mg/m ³
3,3'-Oxybis(ethyleneoxy)bis(propylamine)		Worker	Inhalation, Long-term exposure (8 hours), Systemic effects	59 mg/m ³
3,3'-Oxybis(ethyleneoxy)bis(propylamine)		Worker	Inhalation, Short-term exposure, Local effects	13 mg/m ³
3,3'-Oxybis(ethyleneoxy)bis(propylamine)		Worker	Inhalation, Short-term exposure, Systemic effects	176 mg/m ³

Predicted no effect concentrations (PNEC)

Ingredient	Degradation Product	Compartment	PNEC

2,4,6-tris(dimethylaminomethyl)phenol		Freshwater	0.084 mg/l
2,4,6-tris(dimethylaminomethyl)phenol		Intermittent releases to water	0.84 mg/l
2,4,6-tris(dimethylaminomethyl)phenol		Marine water	0.0084 mg/l
2,4,6-tris(dimethylaminomethyl)phenol		Sewage Treatment Plant	0.2 mg/l
3,3'-Oxybis(ethyleneoxy)bis(propylamine)		Freshwater	0.22 mg/l
3,3'-Oxybis(ethyleneoxy)bis(propylamine)		Freshwater sediments	0.809 mg/kg d.w.
3,3'-Oxybis(ethyleneoxy)bis(propylamine)		Intermittent releases to water	2.2 mg/l
3,3'-Oxybis(ethyleneoxy)bis(propylamine)		Marine water	0.022 mg/l
3,3'-Oxybis(ethyleneoxy)bis(propylamine)		Marine water sediments	0.0809 mg/kg d.w.
3,3'-Oxybis(ethyleneoxy)bis(propylamine)		Sewage Treatment Plant	125 mg/l

Recommended monitoring procedures: Information on recommended monitoring procedures can be obtained from Indust. Inspect./Ministry (IE)

8.2. Exposure controls

In addition, refer to the annex for more information.

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Full face shield.

Indirect vented goggles.

Applicable Norms/Standards

Use eye/face protection conforming to EN 166

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended:

Material	Thickness (mm)	Breakthrough Time
Polymer laminate	No data available	No data available

Applicable Norms/Standards
Use gloves tested to EN 374

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:
Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

Applicable Norms/Standards
Use a respirator conforming to EN 140 or EN 136: filter types A & P

8.2.3. Environmental exposure controls

Refer to Annex

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid.
Specific Physical Form:	Viscous liquid
Colour	Tan
Odor	Slight Amine
Odour threshold	<i>No data available.</i>
Melting point/freezing point	<i>Not applicable.</i>
Boiling point/boiling range	>=110 °C
Flammability (solid, gas)	Not applicable.
Flammable Limits(LEL)	<i>No data available.</i>
Flammable Limits(UEL)	<i>No data available.</i>
Flash point	110 °C [<i>Test Method: Closed Cup</i>]
Autoignition temperature	<i>No data available.</i>
Decomposition temperature	<i>No data available.</i>
pH	<i>substance/mixture is non-soluble (in water)</i>
Kinematic Viscosity	187,500 mm ² /sec
Water solubility	<i>No data available.</i>
Solubility- non-water	<i>No data available.</i>
Partition coefficient: n-octanol/water	<i>No data available.</i>
Vapour pressure	<=26,664.4 Pa [<i>@ 20 °C</i>]
Density	1.2 g/ml

Density	1.2 kg/l
Relative density	1.2 [Ref Std:WATER=1]
Relative Vapour Density	No data available.

9.2. Other information

9.2.2 Other safety characteristics

EU Volatile Organic Compounds	No data available.
Evaporation rate	<=1 [Ref Std:BUOAC=1]
Molecular weight	No data available.
Percent volatile	0.4 % weight

SECTION 10: Stability and reactivity

10.1 Reactivity

This material is considered to be non reactive under normal use conditions

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

None known.

10.5 Incompatible materials

Strong oxidising agents.

10.6 Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from internal hazard assessments.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

Skin contact

May be harmful in contact with skin. Corrosive (skin burns): Signs/symptoms may include localised redness, swelling, itching, intense pain, blistering, ulceration, and tissue destruction. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye contact

Corrosive (eye burns): Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision.

Ingestion

May be harmful if swallowed.

Gastrointestinal corrosion: Signs/symptoms may include severe mouth, throat and abdominal pain, nausea, vomiting, and diarrhea; blood in the faeces and/or vomitus may also be seen. May cause additional health effects (see below).

Additional Health Effects:

Single exposure may cause target organ effects:

Methemoglobinemia: Signs/symptoms may include headache, dizziness, nausea, difficulty breathing, and generalised weakness. Central nervous system (CNS) depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

Additional information:

Persons previously sensitised to amines may develop a cross-sensitisation reaction to certain other amines.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >2,000 - =5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE >2,000 - =5,000 mg/kg
Reaction products of fatty acids, C18-unsaturated, dimers and trimers with 3,3'-[oxybis(ethane-2,1-diyloxy)]dipropan-1-amine	Dermal	Rat	LD50 > 2,000 mg/kg
Reaction products of fatty acids, C18-unsaturated, dimers and trimers with 3,3'-[oxybis(ethane-2,1-diyloxy)]dipropan-1-amine	Ingestion	Rat	LD50 > 2,000 mg/kg
Silica, vitreous	Dermal	Rabbit	LD50 > 5,000 mg/kg
Silica, vitreous	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Silica, vitreous	Ingestion	Rat	LD50 > 5,110 mg/kg
2-Propenenitrile, polymer with 1,3-butadiene, 1-cyano-1-methyl-4-oxo-4-[[2-(1-piperazinyl)ethyl]amino]butyl-terminated	Dermal	Rabbit	LD50 > 3,000 mg/kg
2-Propenenitrile, polymer with 1,3-butadiene, 1-cyano-1-methyl-4-oxo-4-[[2-(1-piperazinyl)ethyl]amino]butyl-terminated	Ingestion	Rat	LD50 > 15,300 mg/kg
2,4,6-tris(dimethylaminomethyl)phenol	Dermal	Rat	LD50 1,280 mg/kg
2,4,6-tris(dimethylaminomethyl)phenol	Ingestion	Rat	LD50 1,000 mg/kg
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	Dermal	Rabbit	LD50 2,525 mg/kg
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	Ingestion	Rat	LD50 2,850 mg/kg
Siloxanes and Silicones, di-Me, reaction products with silica	Dermal	Rabbit	LD50 > 5,000 mg/kg
Siloxanes and Silicones, di-Me, reaction products with silica	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Siloxanes and Silicones, di-Me, reaction products with silica	Ingestion	Rat	LD50 > 5,110 mg/kg
imidazole	Ingestion	Rat	LD50 970 mg/kg
imidazole	Dermal	similar	LD50 400 mg/kg

		compound s	
Nitric acid, ammonium calcium salt	Ingestion	Rat	LD50 >300, <2000 mg/kg
Nitric acid, ammonium calcium salt	Dermal	similar compound s	LD50 > 2,000 mg/kg
Bis[(dimethylamino)methyl]phenol	Ingestion		LD50 estimated to be 300 - 2,000 mg/kg
2-piperazin-1-ylethylamine	Dermal	Rabbit	LD50 865 mg/kg
2-piperazin-1-ylethylamine	Ingestion	Rat	LD50 1,470 mg/kg
toluene	Dermal	Rat	LD50 12,000 mg/kg
toluene	Inhalation-Vapour (4 hours)	Rat	LC50 30 mg/l
toluene	Ingestion	Rat	LD50 5,550 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Overall product	Rabbit	Corrosive
Reaction products of fatty acids, C18-unsaturated, dimers and trimers with 3,3'-[oxybis(ethane-2,1-diyloxy)]dipropan-1-amine	Rat	Irritant
Silica, vitreous	Rabbit	No significant irritation
2-Propenenitrile, polymer with 1,3-butadiene, 1-cyano-1-methyl-4-oxo-4-[[2-(1-piperazinyl)ethyl]amino]butyl-terminated	Rabbit	Irritant
2,4,6-tris(dimethylaminomethyl)phenol	Rabbit	Corrosive
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	Rabbit	Corrosive
Siloxanes and Silicones, di-Me, reaction products with silica	Rabbit	No significant irritation
imidazole	Rabbit	Corrosive
Nitric acid, ammonium calcium salt	similar compound s	No significant irritation
Bis[(dimethylamino)methyl]phenol	similar compound s	Corrosive
2-piperazin-1-ylethylamine	Rabbit	Corrosive
toluene	Rabbit	Irritant

Serious Eye Damage/Irritation

Name	Species	Value
Overall product	similar health hazards	Corrosive
Reaction products of fatty acids, C18-unsaturated, dimers and trimers with 3,3'-[oxybis(ethane-2,1-diyloxy)]dipropan-1-amine	In vitro data	Severe irritant
Silica, vitreous	Rabbit	No significant irritation
2-Propenenitrile, polymer with 1,3-butadiene, 1-cyano-1-methyl-4-oxo-4-[[2-(1-piperazinyl)ethyl]amino]butyl-terminated	Rabbit	Mild irritant
2,4,6-tris(dimethylaminomethyl)phenol	Rabbit	Corrosive
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	Rabbit	Corrosive
Siloxanes and Silicones, di-Me, reaction products with silica	Rabbit	No significant irritation
imidazole	Rabbit	Corrosive
Nitric acid, ammonium calcium salt	Rabbit	Corrosive
Bis[(dimethylamino)methyl]phenol	similar compound s	Corrosive
2-piperazin-1-ylethylamine	Rabbit	Corrosive
toluene	Rabbit	Moderate irritant

Skin Sensitisation

Name	Species	Value

Overall product	Guinea pig	Sensitising
Reaction products of fatty acids, C18-unsaturated, dimers and trimers with 3,3'-[oxybis(ethane-2,1-diyloxy)]dipropan-1-amine	Guinea pig	Sensitising
Silica, vitreous	Human and animal	Not classified
2-Propenenitrile, polymer with 1,3-butadiene, 1-cyano-1-methyl-4-oxo-4-[[2-(1-piperazinyl)ethyl]amino]butyl-terminated	Guinea pig	Sensitising
2,4,6-tris(dimethylaminomethyl)phenol	Guinea pig	Not classified
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	Professional judgement	Sensitising
Siloxanes and Silicones, di-Me, reaction products with silica	Human and animal	Not classified
Nitric acid, ammonium calcium salt	Mouse	Not classified
2-piperazin-1-ylethylamine	Guinea pig	Sensitising
toluene	Guinea pig	Not classified

Respiratory Sensitisation

For the component/components, either no data is currently available or the data is not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Reaction products of fatty acids, C18-unsaturated, dimers and trimers with 3,3'-[oxybis(ethane-2,1-diyloxy)]dipropan-1-amine	In Vitro	Not mutagenic
Silica, vitreous	In Vitro	Not mutagenic
2,4,6-tris(dimethylaminomethyl)phenol	In Vitro	Not mutagenic
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	In Vitro	Not mutagenic
Siloxanes and Silicones, di-Me, reaction products with silica	In Vitro	Not mutagenic
imidazole	In Vitro	Not mutagenic
imidazole	In vivo	Not mutagenic
Nitric acid, ammonium calcium salt	In Vitro	Not mutagenic
2-piperazin-1-ylethylamine	In vivo	Not mutagenic
2-piperazin-1-ylethylamine	In Vitro	Some positive data exist, but the data are not sufficient for classification
toluene	In Vitro	Not mutagenic
toluene	In vivo	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
Silica, vitreous	Not specified.	Mouse	Some positive data exist, but the data are not sufficient for classification
Siloxanes and Silicones, di-Me, reaction products with silica	Not specified.	Mouse	Some positive data exist, but the data are not sufficient for classification
toluene	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
toluene	Ingestion	Rat	Some positive data exist, but the data are not sufficient for classification
toluene	Inhalation	Mouse	Some positive data exist, but the data are not sufficient for classification

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
Reaction products of fatty acids, C18-	Ingestion	Not classified for female reproduction	Rat	NOAEL	pre mating

unsaturated, dimers and trimers with 3,3'-[oxybis(ethane-2,1-diyloxy)]dipropan-1-amine				1,000 mg/kg/day	into lactation
Reaction products of fatty acids, C18-unsaturated, dimers and trimers with 3,3'-[oxybis(ethane-2,1-diyloxy)]dipropan-1-amine	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	29 days
Reaction products of fatty acids, C18-unsaturated, dimers and trimers with 3,3'-[oxybis(ethane-2,1-diyloxy)]dipropan-1-amine	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	prematuring into lactation
Silica, vitreous	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Silica, vitreous	Inhalation	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Silica, vitreous	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	Ingestion	Not classified for female reproduction	Rat	NOAEL 600 mg/kg/day	prematuring into lactation
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	Ingestion	Not classified for male reproduction	Rat	NOAEL 600 mg/kg/day	59 days
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	Ingestion	Not classified for development	Rat	NOAEL 600 mg/kg/day	prematuring into lactation
Siloxanes and Silicones, di-Me, reaction products with silica	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Siloxanes and Silicones, di-Me, reaction products with silica	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Siloxanes and Silicones, di-Me, reaction products with silica	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis
imidazole	Ingestion	Toxic to development	Rat	NOAEL 60 mg/kg/day	during organogenesis
2-piperazin-1-ylethylamine	Ingestion	Not classified for female reproduction	Rat	NOAEL 598 mg/kg/day	prematuring & during gestation
2-piperazin-1-ylethylamine	Ingestion	Not classified for male reproduction	Rat	NOAEL 409 mg/kg/day	32 days
2-piperazin-1-ylethylamine	Ingestion	Toxic to development	Rabbit	NOAEL 75 mg/kg/day	during gestation
toluene	Inhalation	Not classified for female reproduction	Human	NOAEL Not available	occupational exposure
toluene	Inhalation	Not classified for male reproduction	Rat	NOAEL 2.3 mg/l	1 generation
toluene	Ingestion	Toxic to development	Rat	LOAEL 520 mg/kg/day	during gestation
toluene	Inhalation	Toxic to development	Human	NOAEL Not available	poisoning and/or abuse

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Reaction products of fatty acids, C18-unsaturated, dimers and trimers with 3,3'-[oxybis(ethane-2,1-diyloxy)]dipropan-1-amine	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	Irritation Positive	
Reaction products of fatty acids, C18-unsaturated, dimers and trimers with 3,3'-[oxybis(ethane-2,1-diyloxy)]dipropan-1-amine	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Rat	NOAEL Not available	
2-Propenenitrile, polymer with 1,3-butadiene, 1-cyano-1-methyl-4-oxo-4-	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL not available	

[[2-(1-piperazinyl)ethyl]amino]butyl-terminated						
2,4,6-tris(dimethylaminomethyl)phenol	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
3,3'-Oxybis(ethyleneoxy)bis(propylamine)imidazole	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
Nitric acid, ammonium calcium salt	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
Nitric acid, ammonium calcium salt	Ingestion	methemoglobinemia	Causes damage to organs	similar compounds	NOAEL Not available	
2-piperazin-1-ylethylamine	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
toluene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
toluene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
toluene	Inhalation	immune system	Not classified	Mouse	NOAEL 0.004 mg/l	3 hours
toluene	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Reaction products of fatty acids, C18-unsaturated, dimers and trimers with 3,3'-[oxybis(ethane-2,1-diyloxy)]dipropan-1-amine	Ingestion	heart skin endocrine system gastrointestinal tract bone, teeth, nails, and/or hair hematopoietic system liver immune system muscles nervous system eyes kidney and/or bladder respiratory system vascular system	Not classified	Rat	NOAEL 1,000 mg/kg/day	29 days
Silica, vitreous	Inhalation	respiratory system silicosis	Not classified	Human	NOAEL Not available	occupational exposure
2,4,6-tris(dimethylaminomethyl)phenol	Dermal	skin liver nervous system auditory system hematopoietic system eyes	Not classified	Rat	NOAEL 125 mg/kg/day	28 days
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	Ingestion	gastrointestinal tract heart endocrine system bone, teeth, nails, and/or hair hematopoietic system liver immune system muscles nervous system eyes kidney and/or bladder respiratory system vascular system	Not classified	Rat	NOAEL 600 mg/kg/day	59 days

Siloxanes and Silicones, di-Me, reaction products with silica	Inhalation	respiratory system silicosis	Not classified	Human	NOAEL Not available	occupational exposure
imidazole	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 60 mg/kg/day	90 days
imidazole	Ingestion	heart liver blood nervous system eyes	Not classified	Rat	NOAEL 180 mg/kg/day	90 days
2-piperazin-1-ylethylamine	Dermal	skin	Not classified	Rat	NOAEL 100 mg/kg/day	29 days
2-piperazin-1-ylethylamine	Dermal	hematopoietic system nervous system kidney and/or bladder	Not classified	Rat	NOAEL 1,000 mg/kg/day	29 days
2-piperazin-1-ylethylamine	Inhalation	respiratory system	Causes damage to organs through prolonged or repeated exposure	Rat	NOAEL 0.2 mg/m ³	13 weeks
2-piperazin-1-ylethylamine	Inhalation	hematopoietic system eyes kidney and/or bladder	Not classified	Rat	NOAEL 53.8 mg/m ³	13 weeks
2-piperazin-1-ylethylamine	Ingestion	heart endocrine system hematopoietic system liver nervous system kidney and/or bladder	Not classified	Rat	NOAEL 598 mg/kg/day	28 days
toluene	Inhalation	auditory system nervous system eyes olfactory system	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	poisoning and/or abuse
toluene	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 2.3 mg/l	15 months
toluene	Inhalation	heart liver kidney and/or bladder	Not classified	Rat	NOAEL 11.3 mg/l	15 weeks
toluene	Inhalation	endocrine system	Not classified	Rat	NOAEL 1.1 mg/l	4 weeks
toluene	Inhalation	immune system	Not classified	Mouse	NOAEL Not available	20 days
toluene	Inhalation	bone, teeth, nails, and/or hair	Not classified	Mouse	NOAEL 1.1 mg/l	8 weeks
toluene	Inhalation	hematopoietic system vascular system	Not classified	Human	NOAEL Not available	occupational exposure
toluene	Inhalation	gastrointestinal tract	Not classified	Multiple animal species	NOAEL 11.3 mg/l	15 weeks
toluene	Ingestion	nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 625 mg/kg/day	13 weeks
toluene	Ingestion	heart	Not classified	Rat	NOAEL 2,500 mg/kg/day	13 weeks
toluene	Ingestion	liver kidney and/or bladder	Not classified	Multiple animal species	NOAEL 2,500 mg/kg/day	13 weeks
toluene	Ingestion	hematopoietic system	Not classified	Mouse	NOAEL 600 mg/kg/day	14 days
toluene	Ingestion	endocrine system	Not classified	Mouse	NOAEL 105 mg/kg/day	28 days
toluene	Ingestion	immune system	Not classified	Mouse	NOAEL 105 mg/kg/day	4 weeks

Aspiration Hazard

Name	Value
toluene	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

11.2. Information on other hazards

This material does not contain any substances that are assessed to be an endocrine disruptor for human health.

SECTION 12: Ecological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

12.1. Toxicity

No product test data available.

Material	CAS #	Organism	Type	Exposure	Test endpoint	Test result
Reaction products of fatty acids, C18-unsaturated, dimers and trimers with 3,3'-[oxybis(ethane-2,1-diylloxy)]dipropan-1-amine	701-270-9	Fathead minnow	Experimental	96 hours	LL50	2.16 mg/l
Reaction products of fatty acids, C18-unsaturated, dimers and trimers with 3,3'-[oxybis(ethane-2,1-diylloxy)]dipropan-1-amine	701-270-9	Green algae	Experimental	72 hours	EL50	0.43 mg/l
Reaction products of fatty acids, C18-unsaturated, dimers and trimers with 3,3'-[oxybis(ethane-2,1-diylloxy)]dipropan-1-amine	701-270-9	Water flea	Experimental	48 hours	EL50	0.57 mg/l
Reaction products of fatty acids, C18-unsaturated, dimers and trimers with 3,3'-[oxybis(ethane-2,1-diylloxy)]dipropan-1-amine	701-270-9	Green algae	Experimental	72 hours	NOEL	0.28 mg/l
Reaction products of fatty acids, C18-unsaturated, dimers and trimers with 3,3'-[oxybis(ethane-2,1-diylloxy)]dipropan-1-amine	701-270-9	Activated sludge	Experimental	3 hours	EC50	410.3 mg/l
2-Propenenitrile, polymer with 1,3-butadiene, 1-cyano-1-methyl-4-oxo-4-[[2-(1-piperazinyl)ethyl]amino]butyl-terminated	68683-29-4	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Silica, vitreous	60676-86-0	Common Carp	Experimental	72 hours	LC50	>10,000 mg/l

3M™ Panel Bonding (90 Minutes) Adhesive Part A (Accelerator) PN 08115, 38315, 38515, 58115

Bis[(dimethylamino)methyl]phenol	71074-89-0	N/A	Data not available or insufficient for classification	N/A	N/A	NA
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	4246-51-9	Bacteria	Experimental	17 hours	EC50	4,000 mg/l
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	4246-51-9	Golden Orfe	Experimental	96 hours	LC50	>1,000 mg/l
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	4246-51-9	Green algae	Experimental	72 hours	EC50	>500 mg/l
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	4246-51-9	Water flea	Experimental	48 hours	EC50	218.16 mg/l
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	4246-51-9	Green algae	Experimental	72 hours	EC10	5.4 mg/l
2,4,6-tris(dimethylaminomethyl)phenol	90-72-2	N/A	Experimental	96 hours	LC50	718 mg/l
2,4,6-tris(dimethylaminomethyl)phenol	90-72-2	Common Carp	Experimental	96 hours	LC50	>100 mg/l
2,4,6-tris(dimethylaminomethyl)phenol	90-72-2	Green algae	Experimental	72 hours	EC50	46.7 mg/l
2,4,6-tris(dimethylaminomethyl)phenol	90-72-2	Water flea	Experimental	48 hours	EC50	>100 mg/l
2,4,6-tris(dimethylaminomethyl)phenol	90-72-2	Green algae	Experimental	72 hours	NOEC	6.44 mg/l
imidazole	288-32-4	Green algae	Experimental	72 hours	ErC50	133 mg/l
imidazole	288-32-4	Water flea	Experimental	48 hours	EC50	341.5 mg/l
imidazole	288-32-4	Green algae	Experimental	72 hours	NOEC	25 mg/l
imidazole	288-32-4	Activated sludge	Experimental	30 minutes	EC50	>1,000 mg/l
Nitric acid, ammonium calcium salt	15245-12-2	Green algae	Experimental	72 hours	EC50	>100 mg/l
Nitric acid, ammonium calcium salt	15245-12-2	Water flea	Experimental	48 hours	EC50	>100 mg/l
Nitric acid, ammonium calcium salt	15245-12-2	Fathead minnow	Estimated	32 days	NOEC	157 mg/l
Nitric acid, ammonium calcium salt	15245-12-2	Green algae	Experimental	72 hours	NOEC	100 mg/l
Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
toluene	108-88-3	Coho Salmon	Experimental	96 hours	LC50	5.5 mg/l
toluene	108-88-3	Grass Shrimp	Experimental	96 hours	LC50	9.5 mg/l
toluene	108-88-3	Green algae	Experimental	72 hours	EC50	12.5 mg/l
toluene	108-88-3	Leopard frog	Experimental	9 days	LC50	0.39 mg/l
toluene	108-88-3	Pink Salmon	Experimental	96 hours	LC50	6.41 mg/l
toluene	108-88-3	Water flea	Experimental	48 hours	EC50	3.78 mg/l
toluene	108-88-3	Coho Salmon	Experimental	40 days	NOEC	1.39 mg/l

toluene	108-88-3	Diatom	Experimental	72 hours	NOEC	10 mg/l
toluene	108-88-3	Water flea	Experimental	7 days	NOEC	0.74 mg/l
toluene	108-88-3	Activated sludge	Experimental	12 hours	IC50	292 mg/l
toluene	108-88-3	Bacteria	Experimental	16 hours	NOEC	29 mg/l
toluene	108-88-3	Bacteria	Experimental	24 hours	EC50	84 mg/l
toluene	108-88-3	Redworm	Experimental	28 days	LC50	>150 mg per kg of bodyweight
toluene	108-88-3	Soil microbes	Experimental	28 days	NOEC	<26 mg/kg (Dry Weight)
2-piperazin-1-ylethylamine	140-31-8	Bacteria	Experimental	17 hours	EC10	100 mg/l
2-piperazin-1-ylethylamine	140-31-8	Golden Orfe	Experimental	96 hours	LC50	368 mg/l
2-piperazin-1-ylethylamine	140-31-8	Green algae	Experimental	72 hours	EC50	>1,000 mg/l
2-piperazin-1-ylethylamine	140-31-8	Water flea	Experimental	48 hours	EC50	58 mg/l
2-piperazin-1-ylethylamine	140-31-8	Green algae	Experimental	72 hours	NOEC	31 mg/l

12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Reaction products of fatty acids, C18-unsaturated, dimers and trimers with 3,3'-[oxybis(ethane-2,1-diyloxy)]dipropan-1-amine	701-270-9	Experimental Biodegradation	28 days	BOD	0 %BOD/ThO D	OECD 301F - Manometric respirometry
2-Propenenitrile, polymer with 1,3-butadiene, 1-cyano-1-methyl-4-oxo-4-[[2-(1-piperazinyl)ethyl]amino]butyl-terminated	68683-29-4	Data not available - insufficient	N/A	N/A	N/A	N/A
Silica, vitreous	60676-86-0	Data not available - insufficient	N/A	N/A	N/A	N/A
Bis[(dimethylamino)methyl]phenol	71074-89-0	Modeled Biodegradation	28 days	BOD	41 %CO2 evolution/THC O2 evolution	Catalytic™
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	4246-51-9	Experimental Biodegradation	25 days	CO2 evolution	-8 %CO2 evolution/THC O2 evolution	OECD 301B - Modified sturm or CO2
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	4246-51-9	Estimated Photolysis		Photolytic half-life (in air)	2.96 hours (t 1/2)	
2,4,6-tris(dimethylaminomethyl)phenol	90-72-2	Experimental Biodegradation	28 days	BOD	4 %BOD/ThO D	OECD 301D - Closed bottle test
imidazole	288-32-4	Experimental Biodegradation	18 days	Dissolv. Organic Carbon Deplet	98 %removal of DOC	OECD 301A - DOC Die Away Test
imidazole	288-32-4	Experimental Aquatic Inherent Biodegrad.	8 days	CO2 evolution	83 %removal of DOC	OECD 302B Zahn-Wellens/EVPA
imidazole	288-32-4	Experimental Biodegradation	19 days	Percent degraded	86 %removal of DOC	OECD 303A - Simulated Aerobic
Nitric acid, ammonium calcium salt	15245-12-2	Data not available - insufficient	N/A	N/A	N/A	N/A
Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	Data not available - insufficient	N/A	N/A	N/A	N/A
toluene	108-88-3	Experimental Biodegradation	20 days	BOD	80 %BOD/ThO D	APHA Std Meth Water/Wastewater

toluene	108-88-3	Experimental Photolysis		Photolytic half-life (in air)	5.2 days (t 1/2)	
2-piperazin-1-ylethylamine	140-31-8	Experimental Biodegradation	28 days	BOD	0 %BOD/ThO D	OECD 301C - MITI test (I)

12.3 : Bioaccumulative potential

Material	Cas No.	Test type	Duration	Study Type	Test result	Protocol
Reaction products of fatty acids, C18-unsaturated, dimers and trimers with 3,3'-[oxybis(ethane-2,1-diyloxy)]dipropan-1-amine	701-270-9	Modeled Bioconcentration		Bioaccumulation factor	42	Catalogic™
Reaction products of fatty acids, C18-unsaturated, dimers and trimers with 3,3'-[oxybis(ethane-2,1-diyloxy)]dipropan-1-amine	701-270-9	Modeled Bioconcentration		Log Kow	11.7	Episuite™
2-Propenenitrile, polymer with 1,3-butadiene, 1-cyano-1-methyl-4-oxo-4-[[2-(1-piperazinyl)ethyl]amino]butyl-terminated	68683-29-4	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Silica, vitreous	60676-86-0	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Bis[(dimethylamino)methyl]phenol	71074-89-0	Modeled Bioconcentration		Log Kow	-2.34	ACD/Labs ChemSketch™
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	4246-51-9	Experimental Bioconcentration		Log Kow	-1.25	
2,4,6-tris(dimethylaminomethyl)phenol	90-72-2	Experimental Bioconcentration		Log Kow	-0.66	830.7550 Part.Coef Shake Flask
imidazole	288-32-4	Experimental Bioconcentration		Log Kow	-0.02	OECD 107 log Kow shke flask mtd
Nitric acid, ammonium calcium salt	15245-12-2	Estimated Bioconcentration		Log Kow	-3.1	OECD 107 log Kow shke flask mtd
Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
toluene	108-88-3	Experimental BCF - Other	72 hours	Bioaccumulation factor	90	
toluene	108-88-3	Experimental Bioconcentration		Log Kow	2.73	
2-piperazin-1-ylethylamine	140-31-8	Experimental Bioconcentration		Log Kow	0.3	

12.4. Mobility in soil

Material	Cas No.	Test type	Study Type	Test result	Protocol
Reaction products of fatty acids, C18-unsaturated, dimers and trimers with 3,3'-[oxybis(ethane-2,1-diyloxy)]dipropan-1-amine	701-270-9	Modeled Mobility in Soil	Koc	3,780,000,000 l/kg	
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	4246-51-9	Modeled Mobility in Soil	Koc	1 l/kg	ACD/Labs ChemSketch™
imidazole	288-32-4	Experimental Mobility in Soil	Koc	23-207 l/kg	OECD 106 Adsp-Desb Batch Equil
toluene	108-88-3	Experimental Mobility in Soil	Koc	37-160 l/kg	

12.5. Results of the PBT and vPvB assessment

This material does not contain any substances that are assessed to be a PBT or vPvB

12.6. Endocrine disrupting properties

This material does not contain any substances that are assessed to be an endocrine disruptor for environmental effects

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

EU waste code (product as sold)

08 04 09* Waste adhesives and sealants containing organic solvents or other dangerous substances

SECTION 14: Transportation information

	Ground Transport (ADR)	Air Transport (IATA)	Marine Transport (IMDG)
14.1 UN number or ID number	UN3267	UN3267	UN3267
14.2 UN proper shipping name	CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S.(3,3'-OXYBIS(ETHYLENEOXY) BIS(PROPYLAMINE); TRIS(2,4,6-DIMETHYLAMINOMONOMETHYL)PHENOL)	CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S.(3,3'-OXYBIS(ETHYLENEOXY)BI S(PROPYLAMINE); TRIS(2,4,6-DIMETHYLAMINOMONOMETHYL)PHENOL)	CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S.(3,3'-OXYBIS(ETHYLENEOXY) BIS(PROPYLAMINE); TRIS(2,4,6-DIMETHYLAMINOMONOMETHYL)PHENOL)
14.3 Transport hazard class(es)	8	8	8
14.4 Packing group	II	II	II

14.5 Environmental hazards	Not Environmentally Hazardous	Not applicable	Not a Marine Pollutant
14.6 Special precautions for user	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.
14.7 Marine Transport in bulk according to IMO instruments	No data available.	No data available.	No data available.
Control Temperature	No data available.	No data available.	No data available.
Emergency Temperature	No data available.	No data available.	No data available.
ADR Classification Code	C7	Not applicable.	Not applicable.
IMDG Segregation Code	Not applicable.	Not applicable.	NONE

Please contact the address or phone number listed on the first page of the SDS for additional information on the transport/shipment of the material by rail (RID) or inland waterways (ADN).

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Carcinogenicity

Ingredient

toluene

CAS Nbr

108-88-3

Classification

Gr. 3: Not classifiable

Regulation

International Agency for Research on Cancer

Restrictions on the manufacture, placing on the market and use:

The following substance(s) contained in this product is/are subject through Annex XVII of REACH regulation to restrictions on the manufacture, placing on the market and use when present in certain dangerous substances, mixtures and articles. Users of this product are required to comply with the restrictions placed upon it by the aforementioned provision.

Ingredient

toluene

CAS Nbr

108-88-3

Restriction status: listed in REACH Annex XVII

Restricted uses: See Annex XVII to Regulation (EC) No 1907/2006 for Conditions of Restriction

Regulation (EU) 2019/1148 (marketing and use of explosive precursors)

This product is regulated by Regulation (EU) 2019/1148: all suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point. Please see your local legislation.

Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with

the new substance notification requirements of CEPA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

DIRECTIVE 2012/18/EU

Seveso hazard categories, Annex 1, Part 1

None

Seveso named dangerous substances, Annex 1, Part 2

Dangerous Substances	Identifier(s)	Qualifying quantity (tonnes) for the application of	
		Lower-tier requirements	Upper-tier requirements
toluene	108-88-3	10	50

Regulation (EU) No 649/2012

No chemicals listed

15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out for this mixture. Chemical safety assessments for the contained substances may have been carried out by the registrants of the substances in accordance with Regulation (EC) No 1907/2006, as amended.

SECTION 16: Other information

List of relevant H statements

H225	Highly flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H360D	May damage the unborn child.
H361d	Suspected of damaging the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Revision information:

CLP: Ingredient table information was modified.

Section 3: Composition/ Information of ingredients table information was modified.

Section 11: Target Organs - Repeated Table information was modified.

Section 12: Component ecotoxicity information information was modified.

Section 12: Persistence and Degradability information information was modified.

Section 12: Bioaccumulative potential information information was modified.

Section 14 Classification Code – Regulation Data information was modified.

Section 14 Hazard Class + Sub Risk – Regulation Data information was modified.

Section 14 Hazardous/Not Hazardous for Transportation information was modified.

Section 14 Other Dangerous Goods – Regulation Data information was modified.

Section 14 Packing Group – Regulation Data information was modified.

Section 14 Proper Shipping Name information was modified.

Section 14 Segregation – Regulation Data information was modified.

Section 14 UN Number Column data information was modified.

Section 14: Transportation classification information was deleted.

Annex

1. Title	
Substance identification	3,3'-Oxybis(ethyleneoxy)bis(propylamine); EC No. 224-207-2; CAS Nbr 4246-51-9;
Exposure Scenario Name	Formulation
Lifecycle Stage	Use at industrial sites
Contributing activities	PROC 05 -Mixing or blending in batch processes PROC 08a -Transfer of substance or mixture (charging and discharging) at non-dedicated facilities PROC 08b -Transfer of substance or mixture (charging and discharging) at dedicated facilities ERC 02 -Formulation into mixture
Processes, tasks and activities covered	Batch manufacture of a chemical substance or formulation (including polymerisation reactions). Transfers with dedicated controls, including loading, filling, dumping, bagging. Transfers without dedicated controls, including loading, filling, dumping, bagging.
2. Operational conditions and risk management measures	
Operating Conditions	Physical state: Liquid. General operating conditions: Duration of use: 5 days/week; Frequency of exposure at workplace [for one worker]: 8 hours/day; Indoor use;
Risk management measures	Under the operational conditions described above the following risk management measures apply: General risk management measures: Human health: Goggles - Chemical resistant; Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training. Refer to Section 8 of the SDS for specific glove material.; Environmental: None needed;
Waste management measures	No use-specific waste management measures are required for this product. Refer to Section 13 of main SDS for disposal instructions:
3. Prediction of exposure	
Prediction of exposure	Human and environmental exposures are not expected to exceed the DNELs and PNECs when the identified risk management measures are adopted.

1. Title	
Substance identification	3,3'-Oxybis(ethyleneoxy)bis(propylamine); EC No. 224-207-2; CAS Nbr 4246-51-9;
Exposure Scenario Name	Industrial Transfer
Lifecycle Stage	Use at industrial sites
Contributing activities	PROC 08a -Transfer of substance or mixture (charging and discharging) at non-

	dedicated facilities PROC 08b -Transfer of substance or mixture (charging and discharging) at dedicated facilities PROC 09 -Transfer of substance or mixture into small containers (dedicated filling line, including weighing) ERC 02 -Formulation into mixture
Processes, tasks and activities covered	Transfers with dedicated controls, including loading, filling, dumping, bagging.
2. Operational conditions and risk management measures	
Operating Conditions	Physical state: Liquid. General operating conditions: Duration of use: 8 hours/day; Frequency of exposure at workplace [for one worker]: 5 days/week; Indoor use; Outdoor use;
Risk management measures	Under the operational conditions described above the following risk management measures apply: General risk management measures: Human health: Face shield; Wear chemically resistant gloves (tested to EN374) in combination with ‘basic’ employee training. Refer to Section 8 of the SDS for specific glove material.; Environmental: None needed;
Waste management measures	No use-specific waste management measures are required for this product. Refer to Section 13 of main SDS for disposal instructions:
3. Prediction of exposure	
Prediction of exposure	Human and environmental exposures are not expected to exceed the DNELs and PNECs when the identified risk management measures are adopted.

1. Title	
Substance identification	2,4,6-tris(dimethylaminomethyl)phenol; EC No. 202-013-9; CAS Nbr 90-72-2;
Exposure Scenario Name	Industrial Use of panel bonding Adhesives
Lifecycle Stage	Use at industrial sites
Contributing activities	PROC 05 -Mixing or blending in batch processes PROC 08a -Transfer of substance or mixture (charging and discharging) at non-dedicated facilities PROC 08b -Transfer of substance or mixture (charging and discharging) at dedicated facilities PROC 09 -Transfer of substance or mixture into small containers (dedicated filling line, including weighing) PROC 10 -Roller application or brushing PROC 13 -Treatment of articles by dipping and pouring PROC 15 -Use a laboratory reagent ERC 05 -Use at industrial site leading to inclusion into/onto article ERC 06d -Use of reactive process regulators in polymerisation processes at industrial site (inclusion or not into/onto article)
Processes, tasks and activities covered	Application of product with a roller or brush. Application of product with applicator gun. Mixing or blending of solid or liquid materials. Transfer of substances/mixtures into small containers e.g. tubes , bottles or small reservoirs. Transfers with dedicated controls, including loading, filling, dumping, bagging. Transfers without dedicated controls, including loading, filling, dumping, bagging. Use as a laboratory reagent.
2. Operational conditions and risk management measures	
Operating Conditions	Physical state: Liquid.

	<p>General operating conditions: Emission days per year: 220 days/year; Indoors with good general ventilation; Processing Temperature:: <= 40 degree Celsius;</p> <p>Task: Transferring Material; Duration of use: 4 hours/day;</p> <p>Task: Mixing; Duration of use: 8 hours/day;</p> <p>Task: Laboratory use; Duration of use: <= 1 hour(s);</p>
Risk management measures	<p>Under the operational conditions described above the following risk management measures apply: General risk management measures: Human health: Face shield; Local exhaust ventilation; Protective clothing / Wear suitable protective clothing; Environmental: None needed; ; The following task-specific risk management measures apply in addition to those listed above: Task: Laboratory use; Human Health; Protective Gloves - Chemical resistant. Refer to Section 8 of the SDS for specific glove material.;</p>
Waste management measures	Send to a municipal sewage treatment plant;
3. Prediction of exposure	
Prediction of exposure	Human and environmental exposures are not expected to exceed the DNELs and PNECs when the identified risk management measures are adopted.

1. Title	
Substance identification	3,3'-Oxybis(ethyleneoxy)bis(propylamine); EC No. 224-207-2; CAS Nbr 4246-51-9;
Exposure Scenario Name	Industrial Use of Structural Adhesives
Lifecycle Stage	Use at industrial sites
Contributing activities	PROC 04 -Chemical production where opportunity for exposure arises PROC 05 -Mixing or blending in batch processes PROC 13 -Treatment of articles by dipping and pouring ERC 06d -Use of reactive process regulators in polymerisation processes at industrial site (inclusion or not into/onto article)
Processes, tasks and activities covered	Charging material in open systems where significant opportunity for exposure arises e.g. charging from open drum. Mixing or blending of solid or liquid materials.
2. Operational conditions and risk management measures	
Operating Conditions	Physical state: Liquid. General operating conditions: Duration of use: 8 hours/day; Frequency of exposure at workplace [for one worker]: 5 days/week; Indoor use;
Risk management measures	Under the operational conditions described above the following risk management measures apply: General risk management measures:

	<p>Human health: Goggles - Chemical resistant; Wear chemically resistant gloves (tested to EN374) in combination with ‘basic’ employee training. Refer to Section 8 of the SDS for specific glove material.;</p> <p>Environmental: None needed;</p>
Waste management measures	No use-specific waste management measures are required for this product. Refer to Section 13 of main SDS for disposal instructions:
3. Prediction of exposure	
Prediction of exposure	Human and environmental exposures are not expected to exceed the DNELs and PNECs when the identified risk management measures are adopted.

1. Title	
Substance identification	3,3'-Oxybis(ethyleneoxy)bis(propylamine); EC No. 224-207-2; CAS Nbr 4246-51-9;
Exposure Scenario Name	Professional Use of Adhesives and Sealants
Lifecycle Stage	Use at industrial sites
Contributing activities	PROC 13 -Treatment of articles by dipping and pouring ERC 08c -Widespread use leading to inclusion into/onto article (indoor) ERC 08f -Widespread use leading to inclusion into/onto article (outdoor)
Processes, tasks and activities covered	Application of product with applicator gun.
2. Operational conditions and risk management measures	
Operating Conditions	<p>Physical state:Liquid.</p> <p>General operating conditions: Duration of use: 8 hours/day; Frequency of exposure at workplace [for one worker]: 5 days/week; Indoor use;</p>
Risk management measures	<p>Under the operational conditions described above the following risk management measures apply:</p> <p>General risk management measures: Human health: Goggles - Chemical resistant; Wear chemically resistant gloves (tested to EN374) in combination with ‘basic’ employee training. Refer to Section 8 of the SDS for specific glove material.;</p> <p>Environmental: None needed;</p>
Waste management measures	No use-specific waste management measures are required for this product. Refer to Section 13 of main SDS for disposal instructions:
3. Prediction of exposure	
Prediction of exposure	Human and environmental exposures are not expected to exceed the DNELs and PNECs when the identified risk management measures are adopted.

1. Title	
Substance identification	
Exposure Scenario Name	Professional Use of Adhesives and Sealants
Lifecycle Stage	Use at industrial sites
Contributing activities	PROC 10 -Roller application or brushing PROC 13 -Treatment of articles by dipping and pouring ERC 08c -Widespread use leading to inclusion into/onto article (indoor)
Processes, tasks and activities covered	Application of product with applicator gun. Application of product.
2. Operational conditions and risk management measures	
Operating Conditions	<p>Physical state:Solid.</p> <p>General operating conditions:</p>

	Duration of use: 8 hours/day; Indoors with good general ventilation;
Risk management measures	Under the operational conditions described above the following risk management measures apply: General risk management measures: Human health: Protective Gloves - Chemical resistant. Refer to Section 8 of the SDS for specific glove material.; Environmental: None needed;
Waste management measures	No use-specific waste management measures are required for this product. Refer to Section 13 of main SDS for disposal instructions:
3. Prediction of exposure	
Prediction of exposure	Human and environmental exposures are not expected to exceed the DNELs and PNECs when the identified risk management measures are adopted.

1. Title	
Substance identification	2,4,6-tris(dimethylaminomethyl)phenol; EC No. 202-013-9; CAS Nbr 90-72-2;
Exposure Scenario Name	Professional Use of panel bonding Adhesives
Lifecycle Stage	Use at industrial sites
Contributing activities	PROC 05 -Mixing or blending in batch processes PROC 08a -Transfer of substance or mixture (charging and discharging) at non-dedicated facilities PROC 08b -Transfer of substance or mixture (charging and discharging) at dedicated facilities PROC 10 -Roller application or brushing PROC 13 -Treatment of articles by dipping and pouring ERC 08c -Widespread use leading to inclusion into/onto article (indoor)
Processes, tasks and activities covered	Application of product with a roller or brush. Application of product with applicator gun. Mixing or blending of solid or liquid materials. Transfers with dedicated controls, including loading, filling, dumping, bagging. Transfers without dedicated controls, including loading, filling, dumping, bagging.
2. Operational conditions and risk management measures	
Operating Conditions	Physical state: Liquid. General operating conditions: Duration of use: 8 hours/day; Emission days per year: 220 days/year; Indoors with good general ventilation; Processing Temperature:: <= 40 degree Celsius; Task: Transferring Material; Indoors with enhanced general ventilation; Duration of use: 4 hours/day;
Risk management measures	Under the operational conditions described above the following risk management measures apply: General risk management measures: Human health: Wear chemically resistant gloves (tested to EN374) in combination with ‘basic’ employee training. Refer to Section 8 of the SDS for specific glove material.; Environmental: Municipal Sewage Treatment Plant; ; The following task-specific risk management measures apply in addition to those listed above: Task: Transferring Material;

	<p>Human Health; Protective clothing / Wear suitable protective clothing; Face shield;</p> <p>Task: Mixing; Human Health; Protective clothing / Wear suitable protective clothing; Face shield; Local exhaust ventilation;</p>
Waste management measures	No use-specific waste management measures are required for this product. Refer to Section 13 of main SDS for disposal instructions:
3. Prediction of exposure	
Prediction of exposure	Human and environmental exposures are not expected to exceed the DNELs and PNECs when the identified risk management measures are adopted.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into the European Union, you are responsible for all regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration.

3M Ireland MSDSs are available at www.3M.com



Safety Data Sheet

Copyright, 2024, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	32-4327-6	Version number:	5.05
Revision date:	06/03/2024	Supersedes date:	25/01/2024

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

3M™ Panel Bonding Adhesive Part B PNs 08115, 38315, 38515, 58115

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Automotive.

1.3. Details of the supplier of the safety data sheet

Address: 3M Ireland Limited, The Iveagh Building, The Park, Carrickmines, Dublin 18.
Telephone: +353 1 280 3555
E Mail: tox.uk@mmm.com
Website: www.3M.com

1.4. Emergency telephone number

Emergency medical information: 8am-10pm (seven days) contact National Poisons Information Centre, Beaumont Hospital, Dublin 9 DOV2NO, Ireland. Telephone Number: +353 (0)1 809 2166

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

CLP REGULATION (EC) No 1272/2008

The health and environmental classifications of this material have been derived using the calculation method, except in cases where test data are available or the physical form impacts classification. Classification(s) based on test data or physical form are noted below, if applicable.

CLASSIFICATION:

Skin Corrosion/Irritation, Category 2 - Skin Irrit. 2; H315
Serious Eye Damage/Eye Irritation, Category 2 - Eye Irrit. 2; H319
Skin Sensitization, Category 1 - Skin Sens. 1; H317
Germ Cell Mutagenicity, Category 2 - Muta. 2; H341
Hazardous to the Aquatic Environment (Chronic), Category 2 - Aquatic Chronic 2; H411

For full text of H phrases, see Section 16.

2.2. Label elements

CLP REGULATION (EC) No 1272/2008

SIGNAL WORD

WARNING.

Symbols

GHS07 (Exclamation mark) |GHS08 (Health Hazard) |GHS09 (Environment) |

Pictograms



Ingredients:

Ingredient	CAS Nbr	EC No.	% by Wt
bis-[4-(2,3-epoxipropoxy)phenyl]propane	1675-54-3	216-823-5	30 - 60
Rxn mass: 2-(1-chloro-3-(4-[methoxy(oxiran-2-yl)methyl]cyclohexyl)methoxy)propan-2-yl)oxy)methyl)oxirane & 2,2'-[cis-cyclohexane-1,4-diylbis(methyleneoxymethylene)]bisoxirane & 2,2'-[trans-cyclohexane-1,4-diylbis(methyleneoxymethylene)]bisoxirane		946-427-4	7 - 13

HAZARD STATEMENTS:

H315	Causes skin irritation.
H319	Causes serious eye irritation.
H317	May cause an allergic skin reaction.
H341	Suspected of causing genetic defects.
H411	Toxic to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENTS

General:

P102 Keep out of reach of children.

Prevention:

P273 Avoid release to the environment.
 P280K Wear protective gloves and respiratory protection.

Response:

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

Contains 1% of components with unknown hazards to the aquatic environment.

2.3. Other hazards

None known.

This material does not contain any substances that are assessed to be a PBT or vPvB

SECTION 3: Composition/information on ingredients**3.1. Substances**

Not applicable

3.2. Mixtures

Ingredient	Identifier(s)	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
bis-[4-(2,3-epoxipropoxy)phenyl]propane	(CAS-No.) 1675-54-3 (EC-No.) 216-823-5 (REACH-No.) 01-2119456619-26	30 - 60	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411
Oxide glass chemicals	(CAS-No.) 65997-17-3 (EC-No.) 266-046-0	10 - 30	Substance with a national occupational exposure limit
Silica, vitreous	(CAS-No.) 60676-86-0 (EC-No.) 262-373-8	7 - 13	Substance with a national occupational exposure limit
Rxn mass: 2-(\{[1-chloro-3-(\{4-[methoxy(oxiran-2-yl)methyl]cyclohexyl\}methoxy)propan-2-yl]oxy\}methyl)oxirane & 2,2'-[cis-cyclohexane-1,4-diylbis(methyleneoxymethylene)]bisoxirane & 2,2'-[trans-cyclohexane-1,4-diylbis(methyleneoxymethylene)]bisoxirane	(EC-No.) 946-427-4 (REACH-No.) 01-2120803125-69	7 - 13	Acute Tox. 4, H302 Skin Irrit. 2, H315 Skin Sens. 1, H317 Muta. 2, H341 Aquatic Chronic 3, H412
Acrylate Polymer	Trade Secret	1 - 11	Substance not classified as hazardous
Silicon dioxide	(CAS-No.) 7631-86-9 (EC-No.) 231-545-4 (REACH-No.) 01-2119379499-16	1 - 5	Substance with a national occupational exposure limit
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	(CAS-No.) 2530-83-8 (EC-No.) 219-784-2 (REACH-No.) 01-2119513212-58	0.5 - 1.5	Eye Dam. 1, H318 Aquatic Chronic 3, H412
Siloxanes and Silicones, di-Me, reaction products with silica	(CAS-No.) 67762-90-7	0.5 - 1.5	Substance with a national occupational exposure limit
Carbon black	(CAS-No.) 1333-86-4 (EC-No.) 215-609-9 (REACH-No.) 01-2119384822-32	< 0.5	Substance with a national occupational exposure limit
toluene	(CAS-No.) 108-88-3 (EC-No.) 203-625-9 (REACH-No.) 01-2119471310-51	< 0.5	Flam. Liq. 2, H225 Asp. Tox. 1, H304 Skin Irrit. 2, H315 Repr. 2, H361d STOT SE 3, H336 STOT RE 2, H373 Aquatic Chronic 3, H412

Any entry in the Identifier(s) column that begins with the numbers 6, 7, 8, or 9 are a Provisional List Number provided by ECHA pending publication of the official EC Inventory Number for the substance.
Please see section 16 for the full text of any H statements referred to in this section

Specific Concentration Limits

Ingredient	Identifier(s)	Specific Concentration Limits
bis-[4-(2,3-epoxipropoxy)phenyl]propane	(CAS-No.) 1675-54-3 (EC-No.) 216-823-5	(C >= 5%) Skin Irrit. 2, H315 (C >= 5%) Eye Irrit. 2, H319

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

SECTION 4: First aid measures**4.1. Description of first aid measures****Inhalation**

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye contact

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

The most important symptoms and effects based on the CLP classification include:

Irritation to the skin (localized redness, swelling, itching, and dryness). Allergic skin reaction (redness, swelling, blistering, and itching). Serious irritation to the eyes (significant redness, swelling, pain, tearing, and impaired vision).

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures**5.1. Extinguishing media**

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

5.3. Advice for fire-fighters

When fire fighting conditions are severe and total thermal decomposition of the product is possible, wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, tunic and trousers (leggings), bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible.

6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

Keep out of reach of children. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (eg. gloves, respirators...) as required.

7.2. Conditions for safe storage including any incompatibilities

Store away from acids. Store away from strong bases. Store away from oxidising agents. Store away from amines.

7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

SECTION 8: Exposure controls/personal protection**8.1 Control parameters****Occupational exposure limits**

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
toluene	108-88-3	Ireland OELs	TWA(8 hours):192 mg/m ³ (50 ppm);TWA(8 hours):50 ppm(192 mg/m ³);STEL(15 minutes):384 mg/m ³ (100 ppm);STEL(15 minutes):100 ppm(384 mg/m ³)	SKIN
Carbon black	1333-86-4	Ireland OELs	TWA(inhalable fraction)(8 hours):3 mg/m ³	
Silica, vitreous	60676-86-0	Ireland OELs	TWA(as respirable dust)(8 hours):0.08 mg/m ³	

Mineral wool, with the exception of those specified elsewhere in this Annex	65997-17-3	Ireland OELs	TWA(8 hours):5 mg/m ³ (2 fiber/cc)
Oxide glass chemicals	65997-17-3	Manufacturer determined	TWA(as non-fibrous, respirable)(8 hours):3 mg/m ³ ;TWA(as non-fibrous, inhalable fraction)(8 hours):10 mg/m ³
Silicon dioxide	67762-90-7	Ireland OELs	TWA(Total inhalable dust)(8 hours):6 mg/m ³ ;TWA(as respirable dust)(8 hours):2.4 mg/m ³
Silicon dioxide	7631-86-9	Ireland OELs	TWA(Total inhalable dust)(8 hours):6 mg/m ³ ;TWA(as respirable dust)(8 hours):2.4 mg/m ³

Ireland OELs : Ireland. OELs
TWA: Time-Weighted-Average
STEL: Short Term Exposure Limit
CEIL: Ceiling

Biological limit values

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

Derived no effect level (DNEL)

Ingredient	Degradation Product	Population	Human exposure pattern	DNEL
bis-[4-(2,3-epoxipropoxy)phenyl]propane		Worker	Dermal, Long-term exposure (8 hours), Systemic effects	8.3 mg/kg bw/d
bis-[4-(2,3-epoxipropoxy)phenyl]propane		Worker	Dermal, Short-term exposure, Systemic effects	8.3 mg/kg bw/d
bis-[4-(2,3-epoxipropoxy)phenyl]propane		Worker	Inhalation, Long-term exposure (8 hours), Systemic effects	12.3 mg/m ³
bis-[4-(2,3-epoxipropoxy)phenyl]propane		Worker	Inhalation, Short-term exposure, Systemic effects	12.3 mg/m ³

Predicted no effect concentrations (PNEC)

Ingredient	Degradation Product	Compartment	PNEC
bis-[4-(2,3-epoxipropoxy)phenyl]propane		Freshwater	0.003 mg/l
bis-[4-(2,3-epoxipropoxy)phenyl]propane		Freshwater sediments	0.5 mg/kg d.w.
bis-[4-(2,3-epoxipropoxy)phenyl]propane		Intermittent releases to water	0.013 mg/l
bis-[4-(2,3-epoxipropoxy)phenyl]propane		Marine water	0.0003 mg/l
bis-[4-(2,3-		Marine water sediments	0.5 mg/kg d.w.

epoxipropoxi)phenyl]propa ne			
bis-[4-(2,3- epoxipropoxi)phenyl]propa ne		Sewage Treatment Plant	10 mg/l

Recommended monitoring procedures: Information on recommended monitoring procedures can be obtained from Indust. Inspect./Ministry (IE)

8.2. Exposure controls

In addition, refer to the annex for more information.

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:
Indirect vented goggles.

Applicable Norms/Standards

Use eye protection conforming to EN 166

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended:

Material	Thickness (mm)	Breakthrough Time
Polymer laminate	No data available	No data available

Applicable Norms/Standards

Use gloves tested to EN 374

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:
Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

Applicable Norms/Standards

Use a respirator conforming to EN 140 or EN 136: filter types A & P

8.2.3. Environmental exposure controls

Refer to Annex

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid.
Colour	Black
Odor	Acrylic
Odour threshold	<i>No data available.</i>
Melting point/freezing point	<i>No data available.</i>
Boiling point/boiling range	≥ 35 °C
Flammability (solid, gas)	Not applicable.
Flammable Limits(LEL)	<i>No data available.</i>
Flammable Limits(UEL)	<i>No data available.</i>
Flash point	≥ 104.4 °C [Test Method:Closed Cup]
Autoignition temperature	<i>No data available.</i>
Decomposition temperature	<i>No data available.</i>
pH	<i>substance/mixture is non-soluble (in water)</i>
Kinematic Viscosity	83,333 mm ² /sec
Water solubility	Negligible
Solubility- non-water	<i>No data available.</i>
Partition coefficient: n-octanol/water	<i>No data available.</i>
Vapour pressure	$\leq 186,158.4$ Pa
Density	1 kg/l
Density	0.96 g/ml
Relative density	0.96 [Ref Std:WATER=1]
Relative Vapour Density	<i>No data available.</i>
Particle Characteristics	<i>Not applicable.</i>

9.2. Other information

9.2.2 Other safety characteristics

EU Volatile Organic Compounds

No data available.

Evaporation rate

≤ 1 Units not available or not applicable. [Ref Std:BUOAC=1]

Molecular weight

No data available.

Percent volatile

1.6 % weight

SECTION 10: Stability and reactivity

10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

Sparks and/or flames.

10.5 Incompatible materials

Amines.
Strong acids.
Strong bases.
Strong oxidising agents.

10.6 Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
Aldehydes.	Not specified.
Carbon monoxide	Not specified.
Carbon dioxide.	Not specified.
Hydrogen Chloride	Not specified.

SECTION 11: Toxicological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from internal hazard assessments.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

May be harmful if inhaled. Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

Skin contact

Skin Irritation: Signs/symptoms may include localised redness, swelling, itching, dryness, cracking, blistering, and pain. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching. May cause additional health effects (see below).

Eye contact

Severe eye irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea. May cause additional health effects (see below).

Additional Health Effects:

Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

Genotoxicity:

Genotoxicity and Mutagenicity: May interact with genetic material and possibly alter gene expression.

Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation-Dust/Mist(4 hr)		No data available; calculated ATE >5 - =12.5 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
bis-[4-(2,3-epoxypropoxy)phenyl]propane	Dermal	Rat	LD50 > 1,600 mg/kg
bis-[4-(2,3-epoxypropoxy)phenyl]propane	Ingestion	Rat	LD50 > 1,000 mg/kg
Oxide glass chemicals	Dermal		LD50 estimated to be > 5,000 mg/kg
Oxide glass chemicals	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
Silica, vitreous	Dermal	Rabbit	LD50 > 5,000 mg/kg
Silica, vitreous	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Silica, vitreous	Ingestion	Rat	LD50 > 5,110 mg/kg
Rxn mass: 2-(\{1-chloro-3-(\{4-[methoxy(oxiran-2-yl)methyl]cyclohexyl\}methoxy)propan-2-yl]oxy\}methyl)oxirane & 2,2'-[cis-cyclohexane-1,4-diy]bis(methyleneoxymethylene)]bisoxirane & 2,2'-[trans-cyclohexane-1,4-diy]bis(methyleneoxymethylene)]bisoxirane	Ingestion	Rat	LD50 1,000 mg/kg
Acrylate Polymer	Dermal	Rabbit	LD50 > 5,000 mg/kg
Acrylate Polymer	Ingestion	Rat	LD50 > 5,000 mg/kg
Silicon dioxide	Dermal	Rabbit	LD50 > 5,000 mg/kg
Silicon dioxide	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Silicon dioxide	Ingestion	Rat	LD50 > 5,110 mg/kg
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Dermal	Rabbit	LD50 4,000 mg/kg
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 5.3 mg/l
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Ingestion	Rat	LD50 7,010 mg/kg
Siloxanes and Silicones, di-Me, reaction products with silica	Dermal	Rabbit	LD50 > 5,000 mg/kg
Siloxanes and Silicones, di-Me, reaction products with silica	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Siloxanes and Silicones, di-Me, reaction products with silica	Ingestion	Rat	LD50 > 5,110 mg/kg
Carbon black	Dermal	Rabbit	LD50 > 3,000 mg/kg
Carbon black	Ingestion	Rat	LD50 > 8,000 mg/kg
toluene	Dermal	Rat	LD50 12,000 mg/kg
toluene	Inhalation-Vapour (4 hours)	Rat	LC50 30 mg/l
toluene	Ingestion	Rat	LD50 5,550 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
bis-[4-(2,3-epoxypropoxy)phenyl]propane	Rabbit	Mild irritant
Oxide glass chemicals	Professional judgement	No significant irritation

Silica, vitreous	Rabbit	No significant irritation
Rxn mass: 2-(\{[1-chloro-3-(\{4-[methoxy(oxiran-2-yl)methyl]cyclohexyl\}methoxy)propan-2-yl]oxy\}methyl)oxirane & 2,2'-[cis-cyclohexane-1,4-diylbis(methyleneoxymethylene)]bisoxirane & 2,2'-[trans-cyclohexane-1,4-diylbis(methyleneoxymethylene)]bisoxirane	In vitro data	Irritant
Acrylate Polymer	Professional judgement	Minimal irritation
Silicon dioxide	Rabbit	No significant irritation
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Rabbit	Mild irritant
Siloxanes and Silicones, di-Me, reaction products with silica	Rabbit	No significant irritation
Carbon black	Rabbit	No significant irritation
toluene	Rabbit	Irritant

Serious Eye Damage/Irritation

Name	Species	Value
bis-[4-(2,3-epoxypropoxy)phenyl]propane	Rabbit	Moderate irritant
Oxide glass chemicals	Professional judgement	No significant irritation
Silica, vitreous	Rabbit	No significant irritation
Rxn mass: 2-(\{[1-chloro-3-(\{4-[methoxy(oxiran-2-yl)methyl]cyclohexyl\}methoxy)propan-2-yl]oxy\}methyl)oxirane & 2,2'-[cis-cyclohexane-1,4-diylbis(methyleneoxymethylene)]bisoxirane & 2,2'-[trans-cyclohexane-1,4-diylbis(methyleneoxymethylene)]bisoxirane	In vitro data	No significant irritation
Acrylate Polymer	Professional judgement	Mild irritant
Silicon dioxide	Rabbit	No significant irritation
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Rabbit	Corrosive
Siloxanes and Silicones, di-Me, reaction products with silica	Rabbit	No significant irritation
Carbon black	Rabbit	No significant irritation
toluene	Rabbit	Moderate irritant

Skin Sensitisation

Name	Species	Value
bis-[4-(2,3-epoxypropoxy)phenyl]propane	Human and animal	Sensitising
Silica, vitreous	Human and animal	Not classified
Rxn mass: 2-(\{[1-chloro-3-(\{4-[methoxy(oxiran-2-yl)methyl]cyclohexyl\}methoxy)propan-2-yl]oxy\}methyl)oxirane & 2,2'-[cis-cyclohexane-1,4-diylbis(methyleneoxymethylene)]bisoxirane & 2,2'-[trans-cyclohexane-1,4-diylbis(methyleneoxymethylene)]bisoxirane	similar compounds	Sensitising
Silicon dioxide	Human and animal	Not classified
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Guinea pig	Not classified
Siloxanes and Silicones, di-Me, reaction products with silica	Human and animal	Not classified
toluene	Guinea pig	Not classified

Respiratory Sensitisation

Name	Species	Value
------	---------	-------

bis-[4-(2,3-epoxipropoxy)phenyl]propane	Human	Not classified

Germ Cell Mutagenicity

Name	Route	Value
bis-[4-(2,3-epoxipropoxy)phenyl]propane	In vivo	Not mutagenic
bis-[4-(2,3-epoxipropoxy)phenyl]propane	In Vitro	Some positive data exist, but the data are not sufficient for classification
Oxide glass chemicals	In Vitro	Some positive data exist, but the data are not sufficient for classification
Silica, vitreous	In Vitro	Not mutagenic
Rxn mass: 2-(\{[1-chloro-3-(\{4-[methoxy(oxiran-2-yl)methyl]cyclohexyl\}methoxy)propan-2-yl]oxy\}methyl)oxirane & 2,2'-[cis-cyclohexane-1,4-diylbis(methyleneoxymethylene)]bisoxirane & 2,2'-[trans-cyclohexane-1,4-diylbis(methyleneoxymethylene)]bisoxirane	In Vitro	Mutagenic; structurally related to germ cell mutagens
Silicon dioxide	In Vitro	Not mutagenic
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	In vivo	Not mutagenic
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	In Vitro	Some positive data exist, but the data are not sufficient for classification
Siloxanes and Silicones, di-Me, reaction products with silica	In Vitro	Not mutagenic
Carbon black	In Vitro	Not mutagenic
Carbon black	In vivo	Some positive data exist, but the data are not sufficient for classification
toluene	In Vitro	Not mutagenic
toluene	In vivo	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
bis-[4-(2,3-epoxipropoxy)phenyl]propane	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Oxide glass chemicals	Inhalation	Multiple animal species	Some positive data exist, but the data are not sufficient for classification
Silica, vitreous	Not specified.	Mouse	Some positive data exist, but the data are not sufficient for classification
Silicon dioxide	Not specified.	Mouse	Some positive data exist, but the data are not sufficient for classification
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Dermal	Mouse	Not carcinogenic
Siloxanes and Silicones, di-Me, reaction products with silica	Not specified.	Mouse	Some positive data exist, but the data are not sufficient for classification
Carbon black	Dermal	Mouse	Not carcinogenic
Carbon black	Ingestion	Mouse	Not carcinogenic
Carbon black	Inhalation	Rat	Carcinogenic.
toluene	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
toluene	Ingestion	Rat	Some positive data exist, but the data are not sufficient for classification
toluene	Inhalation	Mouse	Some positive data exist, but the data are not sufficient for classification

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
bis-[4-(2,3-epoxipropoxy)phenyl]propane	Ingestion	Not classified for female reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
bis-[4-(2,3-epoxipropoxy)phenyl]propane	Ingestion	Not classified for male reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
bis-[4-(2,3-epoxipropoxy)phenyl]propane	Dermal	Not classified for development	Rabbit	NOAEL 300 mg/kg/day	during organogenesis
bis-[4-(2,3-epoxipropoxy)phenyl]propane	Ingestion	Not classified for development	Rat	NOAEL 750 mg/kg/day	2 generation

Silica, vitreous	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Silica, vitreous	Inhalation	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Silica, vitreous	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis
Silicon dioxide	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Silicon dioxide	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Silicon dioxide	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	1 generation
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	1 generation
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Ingestion	Not classified for development	Rat	NOAEL 3,000 mg/kg/day	during organogenesis
Siloxanes and Silicones, di-Me, reaction products with silica	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Siloxanes and Silicones, di-Me, reaction products with silica	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Siloxanes and Silicones, di-Me, reaction products with silica	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis
toluene	Inhalation	Not classified for female reproduction	Human	NOAEL Not available	occupational exposure
toluene	Inhalation	Not classified for male reproduction	Rat	NOAEL 2.3 mg/l	1 generation
toluene	Ingestion	Toxic to development	Rat	LOAEL 520 mg/kg/day	during gestation
toluene	Inhalation	Toxic to development	Human	NOAEL Not available	poisoning and/or abuse

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Rxn mass: 2-(\{1-chloro-3-(\{4-[methoxy(oxiran-2-yl)methyl]cyclohexyl\}methoxy)propan-2-yl\}oxy\}methyl)oxirane & 2,2'-[cis-cyclohexane-1,4-diylbis(methyleneoxymethylene)]bisoxirane & 2,2'-[trans-cyclohexane-1,4-diylbis(methyleneoxymethylene)]bisoxirane	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
toluene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
toluene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
toluene	Inhalation	immune system	Not classified	Mouse	NOAEL 0.004 mg/l	3 hours
toluene	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
bis-[4-(2,3-epoxipropoxy)phenyl]propane	Dermal	liver	Not classified	Rat	NOAEL 1,000 mg/kg/day	2 years
bis-[4-(2,3-epoxipropoxy)phenyl]propane	Dermal	nervous system	Not classified	Rat	NOAEL 1,000 mg/kg/day	13 weeks
bis-[4-(2,3-epoxipropoxy)phenyl]propane	Ingestion	auditory system heart endocrine system hematopoietic system liver eyes kidney and/or bladder	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
Oxide glass chemicals	Inhalation	respiratory system	Not classified	Human	NOAEL not available	occupational exposure
Silica, vitreous	Inhalation	respiratory system silicosis	Not classified	Human	NOAEL Not available	occupational exposure
Silicon dioxide	Inhalation	respiratory system silicosis	Not classified	Human	NOAEL Not available	occupational exposure
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Ingestion	heart endocrine system bone, teeth, nails, and/or hair hematopoietic system liver immune system nervous system kidney and/or bladder respiratory system	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
Siloxanes and Silicones, di-Me, reaction products with silica	Inhalation	respiratory system silicosis	Not classified	Human	NOAEL Not available	occupational exposure
Carbon black	Inhalation	pneumoconiosis	Not classified	Human	NOAEL Not available	occupational exposure
toluene	Inhalation	auditory system nervous system eyes olfactory system	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	poisoning and/or abuse
toluene	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 2.3 mg/l	15 months
toluene	Inhalation	heart liver kidney and/or bladder	Not classified	Rat	NOAEL 11.3 mg/l	15 weeks
toluene	Inhalation	endocrine system	Not classified	Rat	NOAEL 1.1 mg/l	4 weeks
toluene	Inhalation	immune system	Not classified	Mouse	NOAEL Not available	20 days
toluene	Inhalation	bone, teeth, nails, and/or hair	Not classified	Mouse	NOAEL 1.1 mg/l	8 weeks
toluene	Inhalation	hematopoietic system vascular system	Not classified	Human	NOAEL Not available	occupational exposure
toluene	Inhalation	gastrointestinal tract	Not classified	Multiple animal species	NOAEL 11.3 mg/l	15 weeks
toluene	Ingestion	nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 625 mg/kg/day	13 weeks
toluene	Ingestion	heart	Not classified	Rat	NOAEL 2,500 mg/kg/day	13 weeks
toluene	Ingestion	liver kidney and/or bladder	Not classified	Multiple animal species	NOAEL 2,500 mg/kg/day	13 weeks
toluene	Ingestion	hematopoietic system	Not classified	Mouse	NOAEL 600 mg/kg/day	14 days

toluene	Ingestion	endocrine system	Not classified	Mouse	NOAEL 105 mg/kg/day	28 days
toluene	Ingestion	immune system	Not classified	Mouse	NOAEL 105 mg/kg/day	4 weeks

Aspiration Hazard

Name	Value
toluene	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

11.2. Information on other hazards

This material does not contain any substances that are assessed to be an endocrine disruptor for human health.

SECTION 12: Ecological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

12.1. Toxicity

No product test data available.

Material	CAS #	Organism	Type	Exposure	Test endpoint	Test result
bis-[4-(2,3-epoxipropoxy)phenyl]propane	1675-54-3	Activated sludge	Analogous Compound	3 hours	IC50	>100 mg/l
bis-[4-(2,3-epoxipropoxy)phenyl]propane	1675-54-3	Rainbow trout	Estimated	96 hours	LC50	2 mg/l
bis-[4-(2,3-epoxipropoxy)phenyl]propane	1675-54-3	Water flea	Estimated	48 hours	EC50	1.8 mg/l
bis-[4-(2,3-epoxipropoxy)phenyl]propane	1675-54-3	Green algae	Experimental	72 hours	ErC50	>11 mg/l
bis-[4-(2,3-epoxipropoxy)phenyl]propane	1675-54-3	Green algae	Experimental	72 hours	NOEC	4.2 mg/l
bis-[4-(2,3-epoxipropoxy)phenyl]propane	1675-54-3	Water flea	Experimental	21 days	NOEC	0.3 mg/l
Oxide glass chemicals	65997-17-3	Green algae	Experimental	72 hours	EC50	>1,000 mg/l
Oxide glass chemicals	65997-17-3	Water flea	Experimental	72 hours	EC50	>1,000 mg/l
Oxide glass chemicals	65997-17-3	Zebra Fish	Experimental	96 hours	LC50	>1,000 mg/l
Oxide glass chemicals	65997-17-3	Green algae	Experimental	72 hours	NOEC	>=1,000 mg/l
Silica, vitreous	60676-86-0	Common Carp	Experimental	72 hours	LC50	>10,000 mg/l
Rxn mass: 2-(\{[1-chloro-3-(\{4-[methoxy(oxiran-2-yl)methyl]cyclohexyl\}methoxy)propan-2-yl]oxy\}methyl)oxirane	946-427-4	Green algae	Experimental	72 hours	EC50	38 mg/l

& 2,2'-[cis-cyclohexane-1,4-diylbis(methyleneoxymethylene)]bisoxirane & 2,2'-[trans-cyclohexane-1,4-diylbis(methyleneoxymethylene)]bisoxirane						
Rxn mass: 2-(\{[1-chloro-3-(\{4-[methoxy(oxiran-2-yl)methyl]cyclohexyl\}methoxy)propan-2-yl]oxy\}methyl)oxirane & 2,2'-[cis-cyclohexane-1,4-diylbis(methyleneoxymethylene)]bisoxirane & 2,2'-[trans-cyclohexane-1,4-diylbis(methyleneoxymethylene)]bisoxirane	946-427-4	Water flea	Experimental	72 hours	EC50	71 mg/l
Rxn mass: 2-(\{[1-chloro-3-(\{4-[methoxy(oxiran-2-yl)methyl]cyclohexyl\}methoxy)propan-2-yl]oxy\}methyl)oxirane & 2,2'-[cis-cyclohexane-1,4-diylbis(methyleneoxymethylene)]bisoxirane & 2,2'-[trans-cyclohexane-1,4-diylbis(methyleneoxymethylene)]bisoxirane	946-427-4	Green algae	Experimental	72 hours	EC10	18 mg/l
Acrylate Polymer	Trade Secret	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Silicon dioxide	7631-86-9	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	2530-83-8	Common Carp	Experimental	96 hours	LC50	55 mg/l
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	2530-83-8	Green algae	Experimental	96 hours	ErC50	350 mg/l
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	2530-83-8	Invertebrate	Experimental	48 hours	LC50	324 mg/l
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	2530-83-8	Green algae	Experimental	96 hours	NOEC	130 mg/l
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	2530-83-8	Water flea	Experimental	21 days	NOEC	100 mg/l
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	2530-83-8	Activated sludge	Experimental	3 hours	EC50	>100 mg/l
Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Carbon black	1333-86-4	Green algae	Experimental	72 hours	No tox obs at lmt of water sol	>100 mg/l
Carbon black	1333-86-4	Zebra Fish	Experimental	96 hours	No tox obs at lmt of water sol	>100 mg/l

Carbon black	1333-86-4	Green algae	Experimental	72 hours	No tox obs at lmt of water sol	100 mg/l
Carbon black	1333-86-4	Activated sludge	Experimental	3 hours	NOEC	>800 mg/l
toluene	108-88-3	Coho Salmon	Experimental	96 hours	LC50	5.5 mg/l
toluene	108-88-3	Grass Shrimp	Experimental	96 hours	LC50	9.5 mg/l
toluene	108-88-3	Green algae	Experimental	72 hours	EC50	12.5 mg/l
toluene	108-88-3	Leopard frog	Experimental	9 days	LC50	0.39 mg/l
toluene	108-88-3	Pink Salmon	Experimental	96 hours	LC50	6.41 mg/l
toluene	108-88-3	Water flea	Experimental	48 hours	EC50	3.78 mg/l
toluene	108-88-3	Coho Salmon	Experimental	40 days	NOEC	1.39 mg/l
toluene	108-88-3	Diatom	Experimental	72 hours	NOEC	10 mg/l
toluene	108-88-3	Water flea	Experimental	7 days	NOEC	0.74 mg/l
toluene	108-88-3	Activated sludge	Experimental	12 hours	IC50	292 mg/l
toluene	108-88-3	Bacteria	Experimental	16 hours	NOEC	29 mg/l
toluene	108-88-3	Bacteria	Experimental	24 hours	EC50	84 mg/l
toluene	108-88-3	Redworm	Experimental	28 days	LC50	>150 mg per kg of bodyweight
toluene	108-88-3	Soil microbes	Experimental	28 days	NOEC	<26 mg/kg (Dry Weight)

12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
bis-[4-(2,3-epoxipropoxy)phenyl]propane	1675-54-3	Experimental Biodegradation	28 days	BOD	5 %BOD/COD	OECD 301F - Manometric respirometry
bis-[4-(2,3-epoxipropoxy)phenyl]propane	1675-54-3	Experimental Hydrolysis		Hydrolytic half-life (pH 7)	117 hours (t 1/2)	OECD 111 Hydrolysis func of pH
Oxide glass chemicals	65997-17-3	Data not availbl-insufficient	N/A	N/A	N/A	N/A
Silica, vitreous	60676-86-0	Data not availbl-insufficient	N/A	N/A	N/A	N/A
Rxn mass: 2-(\{1-chloro-3-(\{4-[methoxy(oxiran-2-yl)methyl]cyclohexyl\}methoxy)propan-2-yl\}oxy\}methyl)oxirane & 2,2'-[cis-cyclohexane-1,4-diylbis(methyleneoxymethylene)]bisoxirane & 2,2'-[trans-cyclohexane-1,4-diylbis(methyleneoxymethylene)]bisoxirane	946-427-4	Experimental Biodegradation	28 days	CO2 evolution	1.3 %CO2 evolution/THC O2 evolution	OECD 301B - Modified sturm or CO2
Acrylate Polymer	Trade Secret	Data not availbl-insufficient	N/A	N/A	N/A	N/A
Silicon dioxide	7631-86-9	Data not availbl-insufficient	N/A	N/A	N/A	N/A
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	2530-83-8	Experimental Biodegradation	28 days	Dissolv. Organic Carbon Deplet	37 %removal of DOC	EC C.4.A. DOC Die-Away Test
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	2530-83-8	Experimental Hydrolysis		Hydrolytic half-life (pH 7)	6.5 hours (t 1/2)	OECD 111 Hydrolysis func of pH

Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	Data not available or insufficient	N/A	N/A	N/A	N/A
Carbon black	1333-86-4	Data not available or insufficient	N/A	N/A	N/A	N/A
toluene	108-88-3	Experimental Biodegradation	20 days	BOD	80 %BOD/ThOD	APHA Std Meth Water/Wastewater
toluene	108-88-3	Experimental Photolysis		Photolytic half-life (in air)	5.2 days (t 1/2)	

12.3 : Bioaccumulative potential

Material	Cas No.	Test type	Duration	Study Type	Test result	Protocol
bis-[4-(2,3-epoxypropoxy)phenyl]propane	1675-54-3	Experimental Bioconcentration		Log Kow	3.242	OECD 117 log Kow HPLC method
Oxide glass chemicals	65997-17-3	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Silica, vitreous	60676-86-0	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Rxn mass: 2-(\{[1-chloro-3-(\{4-[methoxy(oxiran-2-yl)methyl]cyclohexyl\}methoxy)propan-2-yl]oxy\}methyl)oxirane & 2,2'-[cis-cyclohexane-1,4-diylbis(methyleneoxymethylene)]bisoxirane & 2,2'-[trans-cyclohexane-1,4-diylbis(methyleneoxymethylene)]bisoxirane	946-427-4	Experimental Bioconcentration		Log Kow	2.05	
Acrylate Polymer	Trade Secret	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Silicon dioxide	7631-86-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	2530-83-8	Experimental Bioconcentration		Log Kow	0.5	Episuite™
Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Carbon black	1333-86-4	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
toluene	108-88-3	Experimental BCF - Other	72 hours	Bioaccumulation factor	90	
toluene	108-88-3	Experimental Bioconcentration		Log Kow	2.73	

12.4. Mobility in soil

Material	Cas No.	Test type	Study Type	Test result	Protocol
bis-[4-(2,3-epoxypropoxy)phenyl]propane	1675-54-3	Modeled Mobility in Soil	Koc	450 l/kg	Episuite™
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	2530-83-8	Modeled Mobility in Soil	Koc	10 l/kg	Episuite™
toluene	108-88-3	Experimental Mobility in Soil	Koc	37-160 l/kg	

12.5. Results of the PBT and vPvB assessment

This material does not contain any substances that are assessed to be a PBT or vPvB

12.6. Endocrine disrupting properties

This material does not contain any substances that are assessed to be an endocrine disruptor for environmental effects

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Combustion products will include halogen acid (HCl/HF/HBr). Facility must be capable of handling halogenated materials. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

EU waste code (product as sold)

08 04 09* Waste adhesives and sealants containing organic solvents or other dangerous substances

SECTION 14: Transportation information

	Ground Transport (ADR)	Air Transport (IATA)	Marine Transport (IMDG)
14.1 UN number or ID number	UN3082	UN3082	UN3082
14.2 UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.(EPOXY RESIN)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.(EPOXY RESIN)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.(EPOXY RESIN)
14.3 Transport hazard class(es)	9	9	9
14.4 Packing group	III	III	III
14.5 Environmental hazards	Environmentally Hazardous	Not applicable	Marine Pollutant

14.6 Special precautions for user	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.
14.7 Marine Transport in bulk according to IMO instruments	No data available.	No data available.	No data available.
Control Temperature	No data available.	No data available.	No data available.
Emergency Temperature	No data available.	No data available.	No data available.
ADR Classification Code	M6	Not applicable.	Not applicable.
IMDG Segregation Code	Not applicable.	Not applicable.	NONE

Please contact the address or phone number listed on the first page of the SDS for additional information on the transport/shipment of the material by rail (RID) or inland waterways (ADN).

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Carcinogenicity

<u>Ingredient</u>	<u>CAS Nbr</u>	<u>Classification</u>	<u>Regulation</u>
bis-[4-(2,3-epoxipropoxy)phenyl]propane	1675-54-3	Gr. 3: Not classifiable	International Agency for Research on Cancer
Carbon black	1333-86-4	Grp. 2B: Possible human carc.	International Agency for Research on Cancer
Silicon dioxide	7631-86-9	Gr. 3: Not classifiable	International Agency for Research on Cancer
toluene	108-88-3	Gr. 3: Not classifiable	International Agency for Research on Cancer

Restrictions on the manufacture, placing on the market and use:

The following substance(s) contained in this product is/are subject through Annex XVII of REACH regulation to restrictions on the manufacture, placing on the market and use when present in certain dangerous substances, mixtures and articles. Users of this product are required to comply with the restrictions placed upon it by the aforementioned provision.

<u>Ingredient</u>	<u>CAS Nbr</u>
bis-[4-(2,3-epoxipropoxy)phenyl]propane	1675-54-3
toluene	108-88-3

Restriction status: listed in REACH Annex XVII

Restricted uses: See Annex XVII to Regulation (EC) No 1907/2006 for Conditions of Restriction

Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The

components of this material are in compliance with the provisions of Japan Chemical Substance Control Law. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Japan Industrial Safety and Health Law. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

DIRECTIVE 2012/18/EU

Seveso hazard categories, Annex 1, Part 1

Hazard Categories	Qualifying quantity (tonnes) for the application of	
	Lower-tier requirements	Upper-tier requirements
E2 Hazardous to the Aquatic environment	200	500

Seveso named dangerous substances, Annex 1, Part 2

Dangerous Substances	Identifier(s)	Qualifying quantity (tonnes) for the application of	
		Lower-tier requirements	Upper-tier requirements
toluene	108-88-3	10	50

Regulation (EU) No 649/2012

No chemicals listed

15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out for this mixture. Chemical safety assessments for the contained substances may have been carried out by the registrants of the substances in accordance with Regulation (EC) No 1907/2006, as amended.

SECTION 16: Other information

List of relevant H statements

- H225 Highly flammable liquid and vapour.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.
- H341 Suspected of causing genetic defects.
- H361d Suspected of damaging the unborn child.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H411 Toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.

Revision information:

- Formulation: Section 16: Annex information was added.
- Industrial Use of Adhesives: Section 16: Annex information was added.
- Professional Use of Adhesives: Section 16: Annex information was added.
- Section 3: Composition/ Information of ingredients table information was modified.

Section 8: 8.2. Exposure controls information information was added.
 Section 8: 8.2.3. Environmental exposure controls information information was added.
 Section 8: DNEL table row information was added.
 Section 8: PNEC table row information was added.
 Section 09: Particle Characteristics N/A information was added.
 Section 12: Component ecotoxicity information information was modified.
 Section 12: Persistence and Degradability information information was modified.
 Section 12: Bioaccumulative potential information information was modified.
 Annex: Prediction of exposure statement information was added.

Annex

1. Title	
Substance identification	bis-[4-(2,3-epoxipropoxy)phenyl]propane; EC No. 216-823-5; CAS Nbr 1675-54-3;
Exposure Scenario Name	Formulation
Lifecycle Stage	Formulation or re-packing
Contributing activities	PROC 09 -Transfer of substance or mixture into small containers (dedicated filling line, including weighing) ERC 02 -Formulation into mixture
Processes, tasks and activities covered	Batch manufacture of a chemical substance or formulation (including polymerisation reactions).
2. Operational conditions and risk management measures	
Operating Conditions	Physical state: Liquid. General operating conditions: Duration of use: 8 hours/day; Emission days per year: <= 225 days per year;
Risk management measures	Under the operational conditions described above the following risk management measures apply: General risk management measures: Human health: Protective Gloves - Chemical resistant. Refer to Section 8 of the SDS for specific glove material.; Environmental: Waste Water treatment - Incineration;
Waste management measures	Do not apply industrial sludge to natural soils; Prevent leaks and prevent soil / water pollution caused by leaks;
3. Prediction of exposure	
Prediction of exposure	Human and environmental exposures are not expected to exceed the DNELs and PNECs when the identified risk management measures are adopted.

1. Title	
Substance identification	bis-[4-(2,3-epoxipropoxy)phenyl]propane; EC No. 216-823-5; CAS Nbr 1675-54-3;
Exposure Scenario Name	Industrial Use of Adhesives
Lifecycle Stage	Use at industrial sites
Contributing activities	PROC 08a -Transfer of substance or mixture (charging and discharging) at non-dedicated facilities PROC 13 -Treatment of articles by dipping and pouring

	ERC 05 -Use at industrial site leading to inclusion into/onto article
Processes, tasks and activities covered	Application of product with a roller or brush. Application of product with applicator gun. Application with a wipe. Transfers without dedicated controls, including loading, filling, dumping, bagging.
2. Operational conditions and risk management measures	
Operating Conditions	Physical state: Liquid. General operating conditions: Duration of use: 8 hours/day; Emission days per year: 220 days/year; Frequency of exposure at workplace [for one worker]: 5 days/week;
Risk management measures	Under the operational conditions described above the following risk management measures apply: General risk management measures: Human health: Protective Gloves - Chemical resistant. Refer to Section 8 of the SDS for specific glove material.; Environmental: None needed;
Waste management measures	Do not apply industrial sludge to natural soils; Prevent discharge of undissolved substance to or recover from wastewater;
3. Prediction of exposure	
Prediction of exposure	Human and environmental exposures are not expected to exceed the DNELs and PNECs when the identified risk management measures are adopted.

1. Title	
Substance identification	bis-[4-(2,3-epoxipropoxy)phenyl]propane; EC No. 216-823-5; CAS Nbr 1675-54-3;
Exposure Scenario Name	Professional Use of Adhesives
Lifecycle Stage	Widespread use by professional workers
Contributing activities	PROC 13 -Treatment of articles by dipping and pouring ERC 08c -Widespread use leading to inclusion into/onto article (indoor) ERC 08f -Widespread use leading to inclusion into/onto article (outdoor)
Processes, tasks and activities covered	Application of product with applicator gun.
2. Operational conditions and risk management measures	
Operating Conditions	Physical state: Liquid. General operating conditions: Application Temperature: ≤ 40 degree Celsius; Duration of use: 8 hours/day; Indoors with good general ventilation;
Risk management measures	Under the operational conditions described above the following risk management measures apply: General risk management measures: Human health: Goggles - Chemical resistant; Protective Gloves - Chemical resistant. Refer to Section 8 of the SDS for specific glove material.; Environmental: Industrial Sewage Treatment Plant;
Waste management measures	No use-specific waste management measures are required for this product. Refer to Section 13 of main SDS for disposal instructions:
3. Prediction of exposure	

Prediction of exposure	Human and environmental exposures are not expected to exceed the DNELs and PNECs when the identified risk management measures are adopted.
-------------------------------	--

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into the European Union, you are responsible for all regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration.

3M Ireland MSDSs are available at www.3M.com