



Safety Data Sheet

Copyright,2023, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	29-4794-3	Version number:	14.00
Revision date:	31/01/2023	Supersedes date:	10/01/2023
Transportation version number:			

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

51002 DMS General Purpose Body Filler

Product Identification Numbers

UU-0016-3825-1

7100050738

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Automotive.

1.3. Details of the supplier of the safety data sheet

Address: 3M Ireland Limited, The Iveagh Building, The Park, Carrickmines, Dublin 18.
Telephone: +353 1 280 3555
E Mail: tox.uk@mmm.com

Website: www.3M.com

1.4. Emergency telephone number

Emergency medical information: 8am-10pm (seven days) contact National Poisons Information Centre, Beaumont Hospital, Dublin 9 DOV2NO, Ireland. Telephone Number: +353 (0)1 809 2166

This product is a kit or a multipart product which consists of multiple, independently packaged components. A Safety Data Sheet for each of these components is included. Please do not separate the component Safety Data Sheets from this cover page. The document numbers of the MSDSs for components of this product are:

29-5075-6, 29-2292-0

TRANSPORTATION INFORMATION

Refer to section 14 of the kit components for transport information.

KIT LABEL

2.1. Classification of the substance or mixture CLP REGULATION (EC) No 1272/2008

CLASSIFICATION:

Flammable Liquid, Category 3 - Flam. Liq. 3; H226
Organic Peroxide, Type E - Org. Perox. E; H242
Skin Corrosion/Irritation, Category 2 - Skin Irrit. 2; H315
Serious Eye Damage/Eye Irritation, Category 2 - Eye Irrit. 2; H319
Skin Sensitization, Category 1 - Skin Sens. 1; H317
Reproductive Toxicity, Category 2 - Repr. 2; H361d
Specific Target Organ Toxicity-Repeated Exposure, Category 1 - STOT RE 1; H372
Aspiration Hazard, Category 1 - Asp. Tox. 1; H304
Hazardous to the Aquatic Environment (Acute), Category 1 - Aquatic Acute 1; H400
Hazardous to the Aquatic Environment (Chronic), Category 1 - Aquatic Chronic 1; H410

For full text of H phrases, see Section 16.

2.2. Label elements CLP REGULATION (EC) No 1272/2008

SIGNAL WORD
DANGER.

Symbols

GHS02 (Flame) | GHS07 (Exclamation mark) | GHS08 (Health Hazard) | GHS09 (Environment) |

Pictograms



Contains:

styrene.; N,N'-ETHYLENEBIS-12-HYDROXYSTEARAMIDE; ethanediol; dibenzoyl peroxide

HAZARD STATEMENTS:

H226	Flammable liquid and vapour.
H242	Heating may cause a fire.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H317	May cause an allergic skin reaction.
H361d	Suspected of damaging the unborn child.
H304	May be fatal if swallowed and enters airways.

sensory organs |
kidney/urinary tract |

H410 Very toxic to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENTS

Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P234 Keep only in original packaging.
P273 Avoid release to the environment.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTRE or doctor/physician.
P331 Do NOT induce vomiting.

Storage:

P411 Store at temperatures not exceeding 32 °C.

For containers not exceeding 125 ml the following Hazard and Precautionary statements may be used:

<=125 ml Hazard statements

H317 May cause an allergic skin reaction.
H361d Suspected of damaging the unborn child.
H304 May be fatal if swallowed and enters airways.

H372 Causes damage to organs through prolonged or repeated exposure: sensory organs.

<=125 ml Precautionary statements

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTRE or doctor/physician.
P331 Do NOT induce vomiting.

SUPPLEMENTAL INFORMATION:

Supplemental Hazard Statements:

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Refer to Safety Data Sheet for component % unknown values (www.3M.com/msds).

EU VOC Directive (2004/42/EC) labelling: 2004/42/EC IIB(b)(250) 100 g/l

Revision information:

Label: CLP Ingredients - kit components information was modified.



Safety Data Sheet

Copyright, 2023, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	29-2292-0	Version number:	10.04
Revision date:	23/08/2023	Supersedes date:	31/01/2023

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Filler bulk material for 3M 51002

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Automotive.

1.3. Details of the supplier of the safety data sheet

Address: 3M Ireland Limited, The Iveagh Building, The Park, Carrickmines, Dublin 18.
Telephone: +353 1 280 3555
E Mail: tox.uk@mmm.com
Website: www.3M.com

1.4. Emergency telephone number

Emergency medical information: 8am-10pm (seven days) contact National Poisons Information Centre, Beaumont Hospital, Dublin 9 DOV2NO, Ireland. Telephone Number: +353 (0)1 809 2166

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

CLP REGULATION (EC) No 1272/2008

The health and environmental classifications of this material have been derived using the calculation method, except in cases where test data are available or the physical form impacts classification. Classification(s) based on test data or physical form are noted below, if applicable.

The carcinogenicity classification for titanium dioxide is not applicable based on physical form (material is not a powder).

CLASSIFICATION:

Flammable Liquid, Category 3 - Flam. Liq. 3; H226
 Skin Corrosion/Irritation, Category 2 - Skin Irrit. 2; H315
 Serious Eye Damage/Eye Irritation, Category 2 - Eye Irrit. 2; H319
 Reproductive Toxicity, Category 2 - Repr. 2; H361d
 Specific Target Organ Toxicity-Repeated Exposure, Category 1 - STOT RE 1; H372
 Aspiration Hazard, Category 1 - Asp. Tox. 1; H304

For full text of H phrases, see Section 16.

2.2. Label elements

CLP REGULATION (EC) No 1272/2008

SIGNAL WORD

DANGER.

Symbols

GHS02 (Flame) |GHS07 (Exclamation mark) |GHS08 (Health Hazard) |

Pictograms



Ingredients:

Ingredient	CAS Nbr	EC No.	% by Wt
styrene	100-42-5	202-851-5	10 - 30

HAZARD STATEMENTS:

H226	Flammable liquid and vapour.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H361d	Suspected of damaging the unborn child.
H304	May be fatal if swallowed and enters airways.
H372	Causes damage to organs through prolonged or repeated exposure: sensory organs.

PRECAUTIONARY STATEMENTS

Prevention:

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260A	Do not breathe vapours.
P280E	Wear protective gloves.

Response:

P301 + P310	IF SWALLOWED: Immediately call a POISON CENTRE or doctor/physician.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P331	Do NOT induce vomiting.

For containers not exceeding 125 ml the following Hazard and Precautionary statements may be used:

<=125 ml Hazard statements

H361d	Suspected of damaging the unborn child.
H304	May be fatal if swallowed and enters airways.
H372	Causes damage to organs through prolonged or repeated exposure: sensory organs.

<=125 ml Precautionary statements

Prevention:

P260A Do not breathe vapours.
 P280E Wear protective gloves.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTRE or doctor/physician.
 P331 Do NOT induce vomiting.

SUPPLEMENTAL INFORMATION:

Supplemental Hazard Statements:

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
 EUH208 Contains N,N'-ETHYLENEBIS-12-HYDROXYSTEARAMIDE. May produce an allergic reaction.

51% of the mixture consists of components of unknown acute oral toxicity.

51% of the mixture consists of components of unknown acute inhalation toxicity.
 Contains 51% of components with unknown hazards to the aquatic environment.

2.3. Other hazards

None known.
 This material does not contain any substances that are assessed to be a PBT or vPvB

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Ingredient	Identifier(s)	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Talc	(CAS-No.) 14807-96-6 (EC-No.) 238-877-9	30 - 60	Substance with a national occupational exposure limit
styrene	(CAS-No.) 100-42-5 (EC-No.) 202-851-5	10 - 30	Flam. Liq. 3, H226 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Repr. 2, H361d STOT RE 1, H372 Nota D Aquatic Chronic 3, H412 Asp. Tox. 1, H304 STOT SE 3, H335
Titanium dioxide	(CAS-No.) 13463-67-7 (EC-No.) 236-675-5	5 - 10	Carc. 2, H351 (inhalation)
N,N'-ETHYLENEBIS-12-HYDROXYSTEARAMIDE	(CAS-No.) 123-26-2 (EC-No.) 204-613-6	< 0.5	Skin Sens. 1, H317
Oxide glass chemicals	(CAS-No.) 65997-17-3	1 - 5	Substance with a national occupational

	(EC-No.) 266-046-0		exposure limit
Magnesite	(CAS-No.) 13717-00-5	< 3	Substance not classified as hazardous
Dolomite	(CAS-No.) 16389-88-1 (EC-No.) 240-440-2	< 3	Substance with a national occupational exposure limit

Please see section 16 for the full text of any H statements referred to in this section

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye contact

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

If swallowed

Do not induce vomiting. Get immediate medical attention.

4.2. Most important symptoms and effects, both acute and delayed

The most important symptoms and effects based on the CLP classification include:

Irritation to the skin (localized redness, swelling, itching, and dryness). Serious irritation to the eyes (significant redness, swelling, pain, tearing, and impaired vision). Aspiration pneumonitis (coughing, gasping, choking, burning of the mouth, and difficulty breathing). Target organ effects. See Section 11 for additional details.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products

Substance

Carbon monoxide
Carbon dioxide.

Condition

During combustion.
During combustion.

5.3. Advice for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and

prevent explosive rupture. Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapours in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Cover spill area with a fire-extinguishing foam. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible.

6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Vapours may travel long distances along the ground or floor to an ignition source and flash back. Keep out of reach of children. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.) Wear low static or properly grounded shoes. Use personal protective equipment (eg. gloves, respirators...) as required. To minimize the risk of ignition, determine applicable electrical classifications for the process using this product and select specific local exhaust ventilation equipment to avoid flammable vapour accumulation. Ground/bond container and receiving equipment if there is potential for static electricity accumulation during transfer.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep cool. Keep container tightly closed. Protect from sunlight. Store away from heat. Store away from acids. Store away from oxidising agents.

7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
styrene	100-42-5	Ireland OELs	TWA(8 hours):85 mg/m ³ (20 ppm);STEL(15 minutes):170 mg/m ³ (40 ppm)	
Titanium dioxide	13463-67-7	Ireland OELs	TWA(Total inhalable dust)(8 hours):10 mg/m ³ ;TWA(as respirable dust)(8 hours):4 mg/m ³	
Talc	14807-96-6	Ireland OELs	TWA(Total inhalable dust)(8 hours):10 mg/m ³ ;TWA(as respirable dust)(8 hours):0.8 mg/m ³	
DUST, INERT OR NUISANCE	16389-88-1	Ireland OELs	TWA(Total inhalable dust)(8 hours):10 mg/m ³ ;TWA(as respirable dust)(8 hours):4 mg/m ³	
Mineral wool, with the exception of those specified elsewhere in this Annex	65997-17-3	Ireland OELs	TWA(8 hours):5 mg/m ³ (2 fiber/cc)	
Oxide glass chemicals	65997-17-3	Manufacturer determined	TWA(as non-fibrous, respirable)(8 hours):3 mg/m ³ ;TWA(as non-fibrous, inhalable fraction)(8 hours):10 mg/m ³	

Ireland OELs : Ireland. OELs
 TWA: Time-Weighted-Average
 STEL: Short Term Exposure Limit
 CEIL: Ceiling

Biological limit values

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

Recommended monitoring procedures:Information on recommended monitoring procedures can be obtained from Indust. Inspect./Ministry (IE)

8.2. Exposure controls

8.2.1. Engineering controls

Provide appropriate local exhaust ventilation for cutting, grinding, sanding or machining. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect vented goggles.

Applicable Norms/Standards

Use eye protection conforming to EN 166

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended:

Material	Thickness (mm)	Breakthrough Time
Polymer laminate	>.3	=>8 hours

The glove data presented are based on the substance driving dermal toxicity and the conditions present at the time of testing. Breakthrough time may be altered when the glove is subjected to use conditions that place additional stress on the glove.

Applicable Norms/Standards

Use gloves tested to EN 374

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

Applicable Norms/Standards

Use a respirator conforming to EN 140 or EN 136: filter types A & P

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid.
Specific Physical Form:	Paste
Colour	White
Odor	Styrene
Odour threshold	<i>No data available.</i>
Melting point/freezing point	<i>Not applicable.</i>
Boiling point/boiling range	145 °C [<i>Details:lit. value of styrene</i>]
Flammability (solid, gas)	Not applicable.
Flammable Limits(LEL)	<i>No data available.</i>
Flammable Limits(UEL)	<i>No data available.</i>
Flash point	31 °C [<i>Test Method:Closed Cup</i>] [<i>Details:lit. value of styrene</i>]
Autoignition temperature	<i>No data available.</i>
Decomposition temperature	<i>No data available.</i>
pH	<i>substance/mixture is non-soluble (in water)</i>
Kinematic Viscosity	<i>No data available.</i>
Water solubility	240 mg/l [<i>Details:lit. value of styrene</i>]
Solubility- non-water	<i>No data available.</i>
Partition coefficient: n-octanol/water	3.05 [<i>Details:Log value</i>]
Vapour pressure	<i>No data available.</i>
Density	1.3 g/cm3

Relative density	1.3 [Ref Std:WATER=1]
Relative Vapour Density	3.6 [Details:lit. value of styrene]

9.2. Other information

9.2.2 Other safety characteristics

EU Volatile Organic Compounds	245 g/l
Evaporation rate	12.4 [Details:lit. value of styrene]
Percent volatile	17.8 % weight [Details:reactive thinner]

SECTION 10: Stability and reactivity

10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

Heat.
Sparks and/or flames.

10.5 Incompatible materials

Combustibles.
Strong acids.
Strong oxidising agents.

10.6 Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
Toxic Vapour/Gas	Heat.

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from internal hazard assessments.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

May be harmful if inhaled. Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. Dust from cutting, grinding, sanding or machining may cause irritation of the respiratory system: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, nose and throat pain. May cause additional health effects (see below).

Skin contact

Mild Skin Irritation: Signs/symptoms may include localised redness, swelling, itching, and dryness. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye contact

Moderate eye irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision. Dust created by cutting, grinding, sanding, or machining may cause eye irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Ingestion

May be harmful if swallowed.

Chemical (aspiration) pneumonitis: Signs/symptoms may include coughing, gasping, choking, burning of the mouth, difficulty breathing, bluish coloured skin (cyanosis), and may be fatal. Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea. May cause additional health effects (see below).

Additional Health Effects:

Single exposure may cause target organ effects:

Auditory effects: Signs/symptoms may include hearing impairment, balance dysfunction and ringing in the ears.

Prolonged or repeated exposure may cause target organ effects:

Auditory effects: Signs/symptoms may include hearing impairment, balance dysfunction and ringing in the ears. Liver effects: Signs/symptoms may include loss of appetite, weight loss, fatigue, weakness, abdominal tenderness and jaundice.

Prolonged or repeated exposure by inhalation may cause:

Pneumoconiosis: Sign/symptoms may include persistent cough, breathlessness, chest pain, increased amounts of sputum, and changes in lung function tests. Ocular effects: Signs/symptoms may include blurred or significantly impaired vision.

Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation-Vapour(4 hr)		No data available; calculated ATE >20 - =50 mg/l
Overall product	Ingestion		No data available; calculated ATE >2,000 - =5,000 mg/kg
Talc	Dermal		LD50 estimated to be > 5,000 mg/kg
Talc	Ingestion		LD50 estimated to be > 5,000 mg/kg
styrene	Dermal	Rat	LD50 > 2,000 mg/kg
styrene	Inhalation-Vapour (4 hours)	Rat	LC50 11.8 mg/l
styrene	Ingestion	Rat	LD50 5,000 mg/kg
Titanium dioxide	Dermal	Rabbit	LD50 > 10,000 mg/kg
Titanium dioxide	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 6.82 mg/l
Titanium dioxide	Ingestion	Rat	LD50 > 10,000 mg/kg
Oxide glass chemicals	Dermal		LD50 estimated to be > 5,000 mg/kg

Filler bulk material for 3M 51002

Oxide glass chemicals	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
Dolomite	Dermal		LD50 estimated to be 2,000 - 5,000 mg/kg
Magnesite	Dermal	Professional judgement	LD50 estimated to be 2,000 - 5,000 mg/kg
Dolomite	Ingestion	Rat	LD50 > 2,000 mg/kg
Magnesite	Ingestion	Rat	LD50 > 2,000 mg/kg
N,N'-ETHYLENEBIS-12-HYDROXYSTEARAMIDE	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 5.05 mg/l
N,N'-ETHYLENEBIS-12-HYDROXYSTEARAMIDE	Ingestion	Rat	LD50 > 2,000 mg/kg
N,N'-ETHYLENEBIS-12-HYDROXYSTEARAMIDE	Dermal	similar health hazards	LD50 Not available

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Talc	Rabbit	No significant irritation
styrene	Professional judgement	Mild irritant
Titanium dioxide	Rabbit	No significant irritation
Oxide glass chemicals	Professional judgement	No significant irritation
Dolomite	Professional judgement	No significant irritation
Magnesite	In vitro data	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
Talc	Rabbit	No significant irritation
styrene	Professional judgement	Moderate irritant
Titanium dioxide	Rabbit	No significant irritation
Oxide glass chemicals	Professional judgement	No significant irritation
Dolomite	Professional judgement	No significant irritation
Magnesite	Rabbit	Mild irritant

Skin Sensitisation

Name	Species	Value
styrene	Guinea pig	Not classified
Titanium dioxide	Human and	Not classified

	animal	
N,N'-ETHYLENEBIS-12-HYDROXYSTEARAMIDE	Guinea pig	Sensitising

Respiratory Sensitisation

Name	Species	Value
Talc	Human	Not classified

Germ Cell Mutagenicity

Name	Route	Value
Talc	In Vitro	Not mutagenic
Talc	In vivo	Not mutagenic
styrene	In Vitro	Some positive data exist, but the data are not sufficient for classification
styrene	In vivo	Some positive data exist, but the data are not sufficient for classification
Titanium dioxide	In Vitro	Not mutagenic
Titanium dioxide	In vivo	Not mutagenic
Oxide glass chemicals	In Vitro	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

Name	Route	Species	Value
Talc	Inhalation	Rat	Some positive data exist, but the data are not sufficient for classification
styrene	Ingestion	Mouse	Carcinogenic.
styrene	Inhalation	Human and animal	Carcinogenic.
Titanium dioxide	Ingestion	Multiple animal species	Not carcinogenic
Titanium dioxide	Inhalation	Rat	Carcinogenic.
Oxide glass chemicals	Inhalation	Multiple animal species	Some positive data exist, but the data are not sufficient for classification

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
Talc	Ingestion	Not classified for development	Rat	NOAEL 1,600 mg/kg	during organogenesis
styrene	Ingestion	Not classified for female reproduction	Rat	NOAEL 21 mg/kg/day	3 generation
styrene	Inhalation	Not classified for female reproduction	Rat	NOAEL 2.1 mg/l	2 generation
styrene	Inhalation	Not classified for male reproduction	Rat	NOAEL 2.1 mg/l	2 generation
styrene	Ingestion	Not classified for male reproduction	Rat	NOAEL 400 mg/kg/day	60 days
styrene	Ingestion	Not classified for development	Rat	NOAEL 400 mg/kg/day	during gestation
styrene	Inhalation	Not classified for development	Multiple animal species	NOAEL 2.1 mg/l	during gestation

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
styrene	Inhalation	auditory system	Causes damage to organs	Multiple animal species	LOAEL 4.3 mg/l	not available
styrene	Inhalation	liver	Causes damage to organs	Mouse	LOAEL 2.1 mg/l	not available
styrene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	occupational exposure
styrene	Inhalation	respiratory irritation	May cause respiratory irritation	Human and animal	NOAEL Not available	
styrene	Inhalation	endocrine system	Not classified	Rat	NOAEL Not available	not available
styrene	Inhalation	kidney and/or bladder	Not classified	Multiple animal species	NOAEL 2.1 mg/l	not available

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Talc	Inhalation	pneumoconiosis	Repeated and prolonged exposure to large amounts of talc dust can cause lung injury	Human	NOAEL Not available	occupational exposure
Talc	Inhalation	pulmonary fibrosis respiratory system	Not classified	Rat	NOAEL 18 mg/m ³	113 weeks
styrene	Inhalation	auditory system	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL not available	occupational exposure
styrene	Inhalation	eyes	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure
styrene	Inhalation	liver	May cause damage to organs though prolonged or repeated exposure	Mouse	LOAEL 0.85 mg/l	13 weeks
styrene	Inhalation	nervous system	Some positive data exist, but the data are not sufficient for classification	Multiple animal species	LOAEL 1.1 mg/l	not available
styrene	Inhalation	hematopoietic system	Not classified	Rat	NOAEL 0.85 mg/l	7 days
styrene	Inhalation	endocrine system	Not classified	Rat	NOAEL 0.6 mg/l	10 days
styrene	Inhalation	respiratory system	Not classified	Multiple animal species	LOAEL 0.09 mg/l	not available
styrene	Inhalation	heart gastrointestinal tract bone, teeth, nails, and/or hair muscles kidney and/or bladder	Not classified	Multiple animal species	NOAEL 4.3 mg/l	2 years
styrene	Ingestion	nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 500 mg/kg/day	8 weeks
styrene	Ingestion	immune system	Some positive data exist, but the data are not sufficient for classification	Multiple animal species	NOAEL Not available	not available
styrene	Ingestion	liver kidney and/or bladder	Not classified	Rat	NOAEL 677 mg/kg/day	6 months
styrene	Ingestion	hematopoietic system	Not classified	Dog	NOAEL 600 mg/kg/day	470 days
styrene	Ingestion	heart respiratory system	Not classified	Rat	NOAEL 35 mg/kg/day	105 weeks
Titanium dioxide	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 0.01 mg/l	2 years
Titanium dioxide	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not available	occupational exposure
Oxide glass chemicals	Inhalation	respiratory system	Not classified	Human	NOAEL not	occupational

Filler bulk material for 3M 51002

					available	exposure
--	--	--	--	--	-----------	----------

Aspiration Hazard

Name	Value
styrene	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

11.2. Information on other hazards

This material does not contain any substances that are assessed to be an endocrine disruptor for human health.

SECTION 12: Ecological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

12.1. Toxicity

No product test data available.

Material	CAS #	Organism	Type	Exposure	Test endpoint	Test result
Talc	14807-96-6	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
styrene	100-42-5	Activated sludge	Experimental	30 minutes	EC50	500 mg/l
styrene	100-42-5	Fathead minnow	Experimental	96 hours	LC50	4.02 mg/l
styrene	100-42-5	Green algae	Experimental	72 hours	EC50	4.9 mg/l
styrene	100-42-5	Water flea	Experimental	48 hours	EC50	4.7 mg/l
styrene	100-42-5	Green algae	Experimental	96 hours	EC10	0.28 mg/l
styrene	100-42-5	Water flea	Experimental	21 days	NOEC	1.01 mg/l
Titanium dioxide	13463-67-7	Activated sludge	Experimental	3 hours	NOEC	>=1,000 mg/l
Titanium dioxide	13463-67-7	Diatom	Experimental	72 hours	EC50	>10,000 mg/l
Titanium dioxide	13463-67-7	Fathead minnow	Experimental	96 hours	LC50	>100 mg/l
Titanium dioxide	13463-67-7	Water flea	Experimental	48 hours	EC50	>100 mg/l
Titanium dioxide	13463-67-7	Diatom	Experimental	72 hours	NOEC	5,600 mg/l
N,N'-ETHYLENEBIS-12-HYDROXYSTEARA MIDE	123-26-2	Green algae	Estimated	72 hours	No tox obs at lmt of water sol	>100 mg/l
N,N'-ETHYLENEBIS-12-HYDROXYSTEARA MIDE	123-26-2	Rainbow trout	Estimated	96 hours	No tox obs at lmt of water sol	>100 mg/l
N,N'-ETHYLENEBIS-12-HYDROXYSTEARA MIDE	123-26-2	Water flea	Estimated	48 hours	No tox obs at lmt of water sol	>100 mg/l

Filler bulk material for 3M 51002

N,N'-ETHYLENEBIS-12-HYDROXYSTEARAMIDE	123-26-2	Green algae	Estimated	72 hours	No tox obs at lmt of water sol	100 mg/l
Oxide glass chemicals	65997-17-3	Green algae	Experimental	72 hours	EC50	>1,000 mg/l
Oxide glass chemicals	65997-17-3	Water flea	Experimental	72 hours	EC50	>1,000 mg/l
Oxide glass chemicals	65997-17-3	Zebra Fish	Experimental	96 hours	LC50	>1,000 mg/l
Oxide glass chemicals	65997-17-3	Green algae	Experimental	72 hours	NOEC	>=1,000 mg/l
Dolomite	16389-88-1	Water flea	Estimated	48 hours	EC50	190 mg/l
Dolomite	16389-88-1	Western Mosquitofish	Estimated	96 hours	LC50	>100 mg/l
Dolomite	16389-88-1	Rainbow trout	Estimated	21 days	NOEC	>100 mg/l
Magnesite	13717-00-5	Fathead minnow	Estimated	96 hours	LC50	1,877 mg/l
Magnesite	13717-00-5	Green algae	Estimated	72 hours	ErC50	>41 mg/l
Magnesite	13717-00-5	Water flea	Estimated	48 hours	LC50	486 mg/l
Magnesite	13717-00-5	Green algae	Estimated	72 hours	NOEC	41 mg/l
Magnesite	13717-00-5	Water flea	Estimated	21 days	EC10	284 mg/l
Magnesite	13717-00-5	Activated sludge	Estimated	3 hours	EC50	>373 mg/l

12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Talc	14807-96-6	Data not availbl-insufficient	N/A	N/A	N/A	N/A
styrene	100-42-5	Experimental Biodegradation	28 days	BOD	70.9 %BOD/ThOD	
styrene	100-42-5	Experimental Photolysis		Photolytic half-life (in air)	6.64 hours (t 1/2)	
Titanium dioxide	13463-67-7	Data not availbl-insufficient	N/A	N/A	N/A	N/A
N,N'-ETHYLENEBIS-12-HYDROXYSTEARAMIDE	123-26-2	Estimated Biodegradation	28 days	Dissolv. Organic Carbon Deplet	22 %removal of DOC	OECD 301D - Closed bottle test
Oxide glass chemicals	65997-17-3	Data not availbl-insufficient	N/A	N/A	N/A	N/A
Dolomite	16389-88-1	Data not availbl-insufficient	N/A	N/A	N/A	N/A
Magnesite	13717-00-5	Data not availbl-insufficient	N/A	N/A	N/A	N/A

12.3 : Bioaccumulative potential

Material	Cas No.	Test type	Duration	Study Type	Test result	Protocol
Talc	14807-96-6	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
styrene	100-42-5	Experimental Bioconcentration		Log Kow	2.96	
Titanium dioxide	13463-67-7	Experimental BCF - Fish	42 days	Bioaccumulation factor	9.6	
N,N'-ETHYLENEBIS-12-HYDROXYSTEARAMIDE	123-26-2	Estimated Bioconcentration		Bioaccumulation factor	7.4	
Oxide glass chemicals	65997-17-3	Data not available	N/A	N/A	N/A	N/A

Filler bulk material for 3M 51002

		or insufficient for classification				
Dolomite	16389-88-1	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Magnesite	13717-00-5	Data not available or insufficient for classification	N/A	N/A	N/A	N/A

12.4. Mobility in soil

No test data available.

12.5. Results of the PBT and vPvB assessment

This material does not contain any substances that are assessed to be a PBT or vPvB

12.6. Endocrine disrupting properties

This material does not contain any substances that are assessed to be an endocrine disruptor for environmental effects

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations**13.1 Waste treatment methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate uncured product in a permitted waste incineration facility. Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

EU waste code (product as sold)

08 04 09* Waste adhesives and sealants containing organic solvents or other dangerous substances

SECTION 14: Transportation information

	Ground Transport (ADR)	Air Transport (IATA)	Marine Transport (IMDG)
14.1 UN number or ID number	UN1866	UN1866	UN1866
14.2 UN proper shipping name	RESIN SOLUTION	RESIN SOLUTION	RESIN SOLUTION

14.3 Transport hazard class(es)	3	3	3
14.4 Packing group	III	III	III
14.5 Environmental hazards	Not Environmentally Hazardous	Not applicable	Not a Marine Pollutant
14.6 Special precautions for user	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.
14.7 Marine Transport in bulk according to IMO instruments	No data available.	No data available.	No data available.
Control Temperature	No data available.	No data available.	No data available.
Emergency Temperature	No data available.	No data available.	No data available.
ADR Classification Code	F1	Not applicable.	Not applicable.
IMDG Segregation Code	Not applicable.	Not applicable.	NONE

Please contact the address or phone number listed on the first page of the SDS for additional information on the transport/shipment of the material by rail (RID) or inland waterways (ADN).

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Carcinogenicity

<u>Ingredient</u>	<u>CAS Nbr</u>	<u>Classification</u>	<u>Regulation</u>
styrene	100-42-5	Grp. 2A: Probable human carc.	International Agency for Research on Cancer
Titanium dioxide	13463-67-7	Grp. 2B: Possible human carc.	International Agency for Research on Cancer

Global inventory status

Contact 3M for more information. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory.

DIRECTIVE 2012/18/EU

Seveso hazard categories, Annex 1, Part 1

Hazard Categories	Qualifying quantity (tonnes) for the application of
-------------------	---

	Lower-tier requirements	Upper-tier requirements
P5c FLAMMABLE LIQUIDS*	5000	50000

*If maintained at a temperature above its boiling point or if particular processing conditions, such as high pressure or high temperature, may create major-accident hazards, P5a or P5b FLAMMABLE LIQUIDS may apply

Seveso named dangerous substances, Annex 1, Part 2

Dangerous Substances	Identifier(s)	Qualifying quantity (tonnes) for the application of	
		Lower-tier requirements	Upper-tier requirements
styrene	100-42-5	10	50

Regulation (EU) No 649/2012

No chemicals listed

15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out for this substance/mixture in accordance with Regulation (EC) No 1907/2006, as amended.

SECTION 16: Other information

List of relevant H statements

- H226 Flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H351i Suspected of causing cancer by inhalation.
- H361d Suspected of damaging the unborn child.
- H372 Causes damage to organs through prolonged or repeated exposure.
- H372 Causes damage to organs through prolonged or repeated exposure: sensory organs.
- H412 Harmful to aquatic life with long lasting effects.

Revision information:

- Section 13: EU waste code (product as sold) information information was modified.
- Section 14 Classification Code – Regulation Data information was modified.
- Section 14 Hazard Class + Sub Risk – Regulation Data information was modified.
- Section 14 Hazardous/Not Hazardous for Transportation information was modified.
- Section 14 Other Dangerous Goods – Regulation Data information was modified.
- Section 14 Packing Group – Regulation Data information was modified.
- Section 14 Proper Shipping Name information was modified.
- Section 14 Segregation – Regulation Data information was modified.
- Section 14 UN Number Column data information was modified.
- Section 14: Transportation classification information was deleted.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into the European Union, you are responsible for all regulatory requirements, including, but not limited to, product registrations/notifications, substance

volume tracking, and potential substance registration.

3M Ireland MSDSs are available at www.3M.com



Safety Data Sheet

Copyright, 2023, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	29-5075-6	Version number:	19.02
Revision date:	14/12/2023	Supersedes date:	31/01/2023

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

3M Blue Cream Hardener for DMS

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Automotive.

1.3. Details of the supplier of the safety data sheet

Address: 3M Ireland Limited, The Iveagh Building, The Park, Carrickmines, Dublin 18.
Telephone: +353 1 280 3555
E Mail: tox.uk@mmm.com
Website: www.3M.com

1.4. Emergency telephone number

Emergency medical information: 8am-10pm (seven days) contact National Poisons Information Centre, Beaumont Hospital, Dublin 9 DOV2NO, Ireland. Telephone Number: +353 (0)1 809 2166

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

CLP REGULATION (EC) No 1272/2008

The health and environmental classifications of this material have been derived using the calculation method, except in cases where test data are available or the physical form impacts classification. Classification(s) based on test data or physical form are noted below, if applicable.

CLASSIFICATION:

Organic Peroxide, Type E - Org. Perox. E; H242
Serious Eye Damage/Eye Irritation, Category 2 - Eye Irrit. 2; H319
Skin Sensitization, Category 1 - Skin Sens. 1; H317
Specific Target Organ Toxicity-Repeated Exposure, Category 2 - STOT RE 2; H373
Hazardous to the Aquatic Environment (Acute), Category 1 - Aquatic Acute 1; H400
Hazardous to the Aquatic Environment (Chronic), Category 1 - Aquatic Chronic 1; H410

For full text of H phrases, see Section 16.

2.2. Label elements**CLP REGULATION (EC) No 1272/2008****SIGNAL WORD**

WARNING.

Symbols

GHS02 (Flame) |GHS07 (Exclamation mark) |GHS08 (Health Hazard) |GHS09 (Environment) |

Pictograms**Ingredients:**

Ingredient	CAS Nbr	EC No.	% by Wt
dibenzoyl peroxide	94-36-0	202-327-6	30 - 60
ethanediol	107-21-1	203-473-3	3 - 15

HAZARD STATEMENTS:

H242	Heating may cause a fire.
H319	Causes serious eye irritation.
H317	May cause an allergic skin reaction.
H373	May cause damage to organs through prolonged or repeated exposure: kidney/urinary tract.
H410	Very toxic to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENTS**Prevention:**

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P234	Keep only in original packaging.
P273	Avoid release to the environment.

Response:

P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
-------------	--

Storage:

P403	Store in a well-ventilated place.
P411	Store at temperatures not exceeding 32 °C.

For containers not exceeding 125 ml the following Hazard and Precautionary statements may be used:**<=125 ml Hazard statements**

H317	May cause an allergic skin reaction.
------	--------------------------------------

<=125 ml Precautionary statements**Response:**

P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
-------------	--

Contains 20% of components with unknown hazards to the aquatic environment.

2.3. Other hazards

None known.

This material does not contain any substances that are assessed to be a PBT or vPvB

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Ingredient	Identifier(s)	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
dibenzoyl peroxide	(CAS-No.) 94-36-0 (EC-No.) 202-327-6	30 - 60	Org. Perox. B, H241 Eye Irrit. 2, H319 Skin Sens. 1B, H317 Aquatic Acute 1, H400,M=10 Aquatic Chronic 1, H410,M=10
Water	(CAS-No.) 7732-18-5 (EC-No.) 231-791-2	10 - 30	Substance not classified as hazardous
Isodecyl benzoate	(CAS-No.) 131298-44-7 (EC-No.) ELINCS 421-090-1	10 - 30	Substance not classified as hazardous
ethanediol	(CAS-No.) 107-21-1 (EC-No.) 203-473-3 (REACH-No.) 01-2119456816-28	3 - 15	Acute Tox. 4, H302 STOT RE 2, H373
Zinc Stearate	(CAS-No.) 557-05-1 (EC-No.) 209-151-9	1 - 5	Substance with a national occupational exposure limit
Calcium sulphate	(CAS-No.) 7778-18-9 (EC-No.) 231-900-3	1 - 5	Substance with a national occupational exposure limit

Please see section 16 for the full text of any H statements referred to in this section

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms

develop, get medical attention.

Eye contact

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

The most important symptoms and effects based on the CLP classification include:

Allergic skin reaction (redness, swelling, blistering, and itching). Serious irritation to the eyes (significant redness, swelling, pain, tearing, and impaired vision). Target organ effects. See Section 11 for additional details.

4.3. Indication of any immediate medical attention and special treatment required

This product contains ethylene glycol. If there is reasonable suspicion of ethylene glycol poisoning, intravenous (IV) administration with either fomepizole (preferred) or ethanol (if fomepizole is unavailable) should be considered as part of the medical management.

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish. Use a fire fighting agent suitable for the surrounding fire.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode. Part of the oxygen for combustion is supplied by the peroxide itself.

5.3. Advice for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapours in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Contain spill. Collect as much of the spilled material as possible using non-sparking tools. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible.

6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

SECTION 7: Handling and storage

7.1. Precautions for safe handling

For industrial/occupational use only. Not for consumer sale or use. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage including any incompatibilities

Protect from sunlight. Store away from heat. Store at temperatures not exceeding 32C/90F. Keep cool. Keep only in original container. Store away from acids. Store away from other materials. Keep/store away from clothing and other combustible materials. Store away from amines.

7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

SECTION 8: Exposure controls/personal protection**8.1 Control parameters****Occupational exposure limits**

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
ethanediol	107-21-1	Ireland OELs	TWA(8 hours):52 mg/m3(20 ppm);TWA(8 hours):20 ppm(52 mg/m3);STEL(15 minutes):104 mg/m3(40 ppm);STEL(15 minutes):40 ppm(104 mg/m3)	SKIN
Zinc Stearate	557-05-1	Ireland OELs	TWA(Total inhalable dust)(8 hours):10 mg/m3;TWA(as respirable dust)(8 hours):4 mg/m3;STEL(Total inhalable dust)(15 minutes):20 mg/m3	
Calcium sulphate	7778-18-9	Ireland OELs	TWA(8 hours):10 mg/m3	
dibenzoyl peroxide	94-36-0	Ireland OELs	TWA(8 hours):5 mg/m3	

Ireland OELs : Ireland. OELs
TWA: Time-Weighted-Average
STEL: Short Term Exposure Limit
CEIL: Ceiling

Biological limit values

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

Recommended monitoring procedures:Information on recommended monitoring procedures can be obtained from Indust. Inspect./Ministry (IE)

8.2. Exposure controls**8.2.1. Engineering controls**

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)**Eye/face protection**

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect vented goggles.

Applicable Norms/Standards

Use eye protection conforming to EN 166

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended:

Material	Thickness (mm)	Breakthrough Time
Polymer laminate	No data available	No data available

Applicable Norms/Standards

Use gloves tested to EN 374

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

Applicable Norms/Standards

Use a respirator conforming to EN 140 or EN 136: filter types A & P

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Solid. Thick Paste
Specific Physical Form:	Paste
Colour	Blue
Odor	Characteristic Odour
Odour threshold	<i>No data available.</i>
Melting point/freezing point	<i>No data available.</i>
Boiling point/boiling range	<i>No data available.</i>
Flammability (solid, gas)	Organic Peroxide: Type E.
Flammable Limits(LEL)	<i>No data available.</i>
Flammable Limits(UEL)	<i>No data available.</i>
Flash point	No flash point
Autoignition temperature	50 °C [Details:SADT]
Decomposition temperature	<i>No data available.</i>
pH	<i>substance/mixture is non-soluble (in water)</i>

Kinematic Viscosity	80,645 mm ² /sec
Water solubility	Nil
Solubility- non-water	<i>No data available.</i>
Partition coefficient: n-octanol/water	<i>No data available.</i>
Vapour pressure	100 Pa [@ 20 °C]
Density	1.16 - 1.24 g/ml [@ 20 °C]
Relative density	1.16 - 1.24 [Ref Std:WATER=1]
Relative Vapour Density	<i>No data available.</i>

9.2. Other information

9.2.2 Other safety characteristics

EU Volatile Organic Compounds	<i>No data available.</i>
Evaporation rate	<i>No data available.</i>
Percent volatile	11 - 30 % weight

SECTION 10: Stability and reactivity

10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

Heat.
Sparks and/or flames.

10.5 Incompatible materials

Accelerators
Alkali and alkaline earth metals.
Amines.
Reducing agents.
Strong acids.

10.6 Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
Carbon monoxide	Not specified.
Carbon dioxide.	Not specified.

SECTION 11: Toxicological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from internal hazard assessments.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

Vapours released during curing may cause irritation of the respiratory system: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Skin contact

May be harmful in contact with skin. Contact with the skin during product use is not expected to result in significant irritation. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye contact

Severe eye irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea. May cause additional health effects (see below).

Additional Health Effects:

Single exposure may cause target organ effects:

Cardiac effects: Signs/symptoms may include irregular heartbeat (arrhythmia), changes in heart rate, damage to heart muscle, heart attack, and may be fatal. Neurological effects: Signs/symptoms may include personality changes, lack of coordination, sensory loss, tingling or numbness of the extremities, weakness, tremors, and changes in blood pressure and heart rate.

Respiratory effects: Signs/symptoms may include cough, shortness of breath, chest tightness, wheezing, increased heart rate, bluish coloured skin (cyanosis), sputum production, changes in lung function tests, and respiratory failure. Kidney/Bladder

effects: Signs/symptoms may include changes in urine production, abdominal or lower back pain, increased protein in urine, increased blood urea nitrogen (BUN), blood in urine, and painful urination.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >2,000 - =5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
dibenzoyl peroxide	Dermal		LD50 estimated to be 2,000 - 5,000 mg/kg
dibenzoyl peroxide	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 24.3 mg/l
dibenzoyl peroxide	Ingestion	Rat	LD50 > 5,000 mg/kg
Isodecyl benzoate	Dermal	Rabbit	LD50 > 2,000 mg/kg
Isodecyl benzoate	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 5 mg/l
Isodecyl benzoate	Ingestion	Rat	LD50 > 5,000 mg/kg
ethanediol	Ingestion	Human	LD50 1,600 mg/kg
ethanediol	Inhalation-Dust/Mist (4 hours)	Other	LC50 estimated to be 5 - 12.5 mg/l
ethanediol	Dermal	Rabbit	9,530 mg/kg
Calcium sulphate	Dermal	Professional judgement	LD50 estimated to be > 5,000 mg/kg
Zinc Stearate	Dermal	Rabbit	LD50 > 2,000 mg/kg

3M Blue Cream Hardener for DMS

Calcium sulphate	Ingestion	Rat	LD50 > 5,000 mg/kg
Zinc Stearate	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 50 mg/l
Zinc Stearate	Ingestion	Rat	LD50 > 2,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
dibenzoyl peroxide	Rabbit	Minimal irritation
ethanediol	Rabbit	Minimal irritation
Zinc Stearate	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
dibenzoyl peroxide	Rabbit	Severe irritant
ethanediol	Rabbit	Mild irritant
Zinc Stearate	Rabbit	No significant irritation

Skin Sensitisation

Name	Species	Value
dibenzoyl peroxide	Guinea pig	Sensitising
ethanediol	Human	Not classified
Zinc Stearate	Human	Not classified

Respiratory Sensitisation

For the component/components, either no data is currently available or the data is not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
dibenzoyl peroxide	In Vitro	Not mutagenic
dibenzoyl peroxide	In vivo	Not mutagenic
ethanediol	In Vitro	Not mutagenic
ethanediol	In vivo	Not mutagenic
Zinc Stearate	In Vitro	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
dibenzoyl peroxide	Ingestion	Multiple animal species	Not carcinogenic
dibenzoyl peroxide	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
ethanediol	Ingestion	Multiple animal species	Not carcinogenic

Reproductive Toxicity**Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test result	Exposure Duration
dibenzoyl peroxide	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	prematuring & during gestation

3M Blue Cream Hardener for DMS

dibenzoyl peroxide	Ingestion	Not classified for male reproduction	Rat	NOAEL 500 mg/kg/day	premating & during gestation
dibenzoyl peroxide	Ingestion	Not classified for development	Rat	NOAEL 500 mg/kg/day	premating & during gestation
ethanediol	Dermal	Not classified for development	Mouse	NOAEL 3,549 mg/kg/day	during organogenesis
ethanediol	Ingestion	Not classified for development	Mouse	LOAEL 750 mg/kg/day	during organogenesis
ethanediol	Inhalation	Not classified for development	Mouse	NOAEL 1,000 mg/kg/day	during organogenesis

Target Organ(s)
Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
ethanediol	Ingestion	heart nervous system kidney and/or bladder respiratory system	Causes damage to organs	Human	NOAEL Not available	poisoning and/or abuse
ethanediol	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse
ethanediol	Ingestion	liver	Not classified	Human	NOAEL Not available	poisoning and/or abuse

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
ethanediol	Ingestion	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 200 mg/kg/day	2 years
ethanediol	Ingestion	vascular system	Not classified	Rat	NOAEL 200 mg/kg/day	2 years
ethanediol	Ingestion	heart hematopoietic system liver immune system muscles	Not classified	Rat	NOAEL 1,000 mg/kg/day	2 years
ethanediol	Ingestion	respiratory system	Not classified	Mouse	NOAEL 12,000 mg/kg/day	2 years
ethanediol	Ingestion	skin endocrine system bone, teeth, nails, and/or hair nervous system eyes	Not classified	Multiple animal species	NOAEL 1,000 mg/kg/day	2 years
Zinc Stearate	Ingestion	heart endocrine system gastrointestinal tract hematopoietic system liver immune system nervous system eyes kidney and/or bladder respiratory system	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days

Aspiration Hazard

For the component/components, either no data is currently available or the data is not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information

on this material and/or its components.

11.2. Information on other hazards

This material does not contain any substances that are assessed to be an endocrine disruptor for human health.

SECTION 12: Ecological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

12.1. Toxicity

No product test data available.

Material	CAS #	Organism	Type	Exposure	Test endpoint	Test result
dibenzoyl peroxide	94-36-0	Green algae	Experimental	72 hours	EC50	0.071 mg/l
dibenzoyl peroxide	94-36-0	Rainbow trout	Experimental	96 hours	LC50	0.06 mg/l
dibenzoyl peroxide	94-36-0	Water flea	Experimental	48 hours	EC50	0.11 mg/l
dibenzoyl peroxide	94-36-0	Green algae	Experimental	72 hours	NOEC	0.02 mg/l
dibenzoyl peroxide	94-36-0	Water flea	Experimental	21 days	EC10	0.001 mg/l
dibenzoyl peroxide	94-36-0	Activated sludge	Experimental	30 minutes	EC50	35 mg/l
dibenzoyl peroxide	94-36-0	Redworm	Experimental	14 days	LC50	>1,000 mg/kg (Dry Weight)
dibenzoyl peroxide	94-36-0	Soil microbes	Experimental	28 days	EC50	2,300 mg/kg (Dry Weight)
Isodecyl benzoate	131298-44-7	Green algae	Experimental	96 hours	No tox obs at lmt of water sol	>100 mg/l
Isodecyl benzoate	131298-44-7	Rainbow trout	Experimental	96 hours	No tox obs at lmt of water sol	>100 mg/l
Isodecyl benzoate	131298-44-7	Water flea	Experimental	48 hours	No tox obs at lmt of water sol	>100 mg/l
Isodecyl benzoate	131298-44-7	Fathead minnow	Experimental	33 days	No tox obs at lmt of water sol	>100 mg/l
Isodecyl benzoate	131298-44-7	Green algae	Experimental	96 hours	No tox obs at lmt of water sol	>100 mg/l
Isodecyl benzoate	131298-44-7	Midge	Experimental	28 days	NOEC	64.7 mg/kg (Dry Weight)
Isodecyl benzoate	131298-44-7	Water flea	Experimental	21 days	No tox obs at lmt of water sol	>100 mg/l
Isodecyl benzoate	131298-44-7	Activated sludge	Experimental	3 hours	EC50	>100 mg/l
ethanediol	107-21-1	Bacteria	Experimental	16 hours	EC50	10,000 mg/l
ethanediol	107-21-1	Fathead minnow	Experimental	96 hours	LC50	8,050 mg/l
ethanediol	107-21-1	Green algae	Experimental	72 hours	EC50	>1,000 mg/l
ethanediol	107-21-1	Water flea	Experimental	48 hours	EC50	>1,100 mg/l
ethanediol	107-21-1	Green algae	Experimental	72 hours	NOEC	1,000 mg/l
ethanediol	107-21-1	Water flea	Experimental	21 days	NOEC	100 mg/l

3M Blue Cream Hardener for DMS

Calcium sulphate	7778-18-9	Activated sludge	Estimated	3 hours	NOEC	1,000 mg/l
Calcium sulphate	7778-18-9	Algae or other aquatic plants	Experimental	96 hours	EC50	3,200 mg/l
Calcium sulphate	7778-18-9	Bluegill	Experimental	96 hours	LC50	>2,980 mg/l
Calcium sulphate	7778-18-9	Water flea	Experimental	48 hours	LC50	>1,970 mg/l
Calcium sulphate	7778-18-9	Water flea	Estimated	21 days	NOEC	1,270 mg/l
Zinc Stearate	557-05-1	Water flea	Experimental	48 hours	EC50	>100 mg/l
Zinc Stearate	557-05-1	Zebra Fish	Experimental	96 hours	No tox obs at lmt of water sol	>100 mg/l

12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
dibenzoyl peroxide	94-36-0	Experimental Biodegradation	28 days	BOD	71 %BOD/ThOD	OECD 301D - Closed bottle test
dibenzoyl peroxide	94-36-0	Experimental Hydrolysis		Hydrolytic half-life	5.2 hours (t _{1/2})	OECD 111 Hydrolysis func of pH
Isodecyl benzoate	131298-44-7	Experimental Biodegradation	28 days	BOD	77.7 %BOD/ThOD	OECD 301F - Manometric respirometry
ethanediol	107-21-1	Experimental Biodegradation	14 days	BOD	90 %BOD/ThOD	OECD 301C - MITI test (I)
Calcium sulphate	7778-18-9	Data not availbl-insufficient	N/A	N/A	N/A	N/A
Zinc Stearate	557-05-1	Experimental Biodegradation	28 days	BOD	14.6 %BOD/ThOD	OECD 301D - Closed bottle test

12.3 : Bioaccumulative potential

Material	Cas No.	Test type	Duration	Study Type	Test result	Protocol
dibenzoyl peroxide	94-36-0	Experimental Bioconcentration		Log Kow	3.2	OECD 117 log Kow HPLC method
Isodecyl benzoate	131298-44-7	Modeled Bioconcentration		Bioaccumulation factor	288	Catalogic™
Isodecyl benzoate	131298-44-7	Experimental Bioconcentration		Log Kow	4.61	EC A.8 Partition Coefficient
ethanediol	107-21-1	Experimental Bioconcentration		Log Kow	-1.36	
Calcium sulphate	7778-18-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Zinc Stearate	557-05-1	Experimental Bioconcentration		Log Kow	4.64	OECD 117 log Kow HPLC method

12.4. Mobility in soil

Material	Cas No.	Test type	Study Type	Test result	Protocol
dibenzoyl peroxide	94-36-0	Experimental Mobility in Soil	Koc	6,310 l/kg	OECD 121 Estim. of Koc by HPLC
Isodecyl benzoate	131298-44-7	Modeled Mobility in Soil	Koc	2,600 l/kg	Episuite™
Zinc Stearate	557-05-1	Experimental Mobility in Soil	Koc	1,510 l/kg	OECD 121 Estim. of Koc by HPLC

12.5. Results of the PBT and vPvB assessment

This material does not contain any substances that are assessed to be a PBT or vPvB

12.6. Endocrine disrupting properties

This material does not contain any substances that are assessed to be an endocrine disruptor for environmental effects

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

EU waste code (product as sold)

08 04 09* Waste adhesives and sealants containing organic solvents or other dangerous substances

SECTION 14: Transportation information

	Ground Transport (ADR)	Air Transport (IATA)	Marine Transport (IMDG)
14.1 UN number or ID number	UN3108	UN3108	UN3108
14.2 UN proper shipping name	ORGANIC PEROXIDE TYPE E, SOLID(DIBENZOYL PEROXIDE (AS A PASTE), <= 52%)	ORGANIC PEROXIDE TYPE E, SOLID(DIBENZOYL PEROXIDE (AS A PASTE), <= 52%)	ORGANIC PEROXIDE TYPE E, SOLID(DIBENZOYL PEROXIDE (AS A PASTE), <= 52%; BENZOYL PEROXIDE)
14.3 Transport hazard class(es)	5.2	5.2	5.2
14.4 Packing group	Not applicable.	Not applicable.	Not applicable.
14.5 Environmental hazards	Environmentally Hazardous	Not applicable	Marine Pollutant
14.6 Special precautions for user	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.

14.7 Marine Transport in bulk according to IMO instruments	No data available.	No data available.	No data available.
Control Temperature	No data available.	No data available.	No data available.
Emergency Temperature	No data available.	No data available.	No data available.
ADR Classification Code	P1	Not applicable.	Not applicable.
IMDG Segregation Code	Not applicable.	Not applicable.	NONE

Please contact the address or phone number listed on the first page of the SDS for additional information on the transport/shipment of the material by rail (RID) or inland waterways (ADN).

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Carcinogenicity

Ingredient

dibenzoyl peroxide

CAS Nbr

94-36-0

Classification

Gr. 3: Not classifiable

Regulation

International Agency for Research on Cancer

Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Japan Chemical Substance Control Law. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

DIRECTIVE 2012/18/EU

Seveso hazard categories, Annex 1, Part 1

None

Seveso named dangerous substances, Annex 1, Part 2

Dangerous Substances	Identifier(s)	Qualifying quantity (tonnes) for the application of	
		Lower-tier requirements	Upper-tier requirements
dibenzoyl peroxide	94-36-0	10	50

Regulation (EU) No 649/2012

No chemicals listed

15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out for this mixture. Chemical safety assessments for the contained substances may have been carried out by the registrants of the substances in accordance with Regulation (EC) No 1907/2006, as amended.

SECTION 16: Other information

List of relevant H statements

H241	Heating may cause a fire or explosion.
H242	Heating may cause a fire.
H302	Harmful if swallowed.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H373	May cause damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure: kidney/urinary tract.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

Revision information:

Section 12: Component ecotoxicity information information was modified.
Section 12: Mobility in soil information information was modified.
Section 12: Persistence and Degradability information information was modified.
Section 12: Bioaccumulative potential information information was modified.
Section 14 Other Dangerous Goods – Regulation Data information was modified.
Section 14 Proper Shipping Name information was modified.
Section 14: Transportation classification information was deleted.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into the European Union, you are responsible for all regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration.

3M Ireland MSDSs are available at www.3M.com